

Table of Contents

1 Accounts-account-email-domain-alaises:GET.	1
2 GET /accounts/{account}/email/{domain}/aliases.	2
2.1 Contents.....	2
2.2 Request.....	2
2.3 Response.....	2
2.4 Examples.....	2
2.5 See also.....	3
3 Accounts-account-email-domain-blackwhitelist-address:DELETE.....	4
4 DELETE /accounts/{account}/email/{domain}/blackwhitelist/{address}.	5
4.1 Contents.....	5
4.2 Request.....	5
4.3 Response.....	5
4.4 Examples.....	5
5 Accounts-account-email-domain-blackwhitelist-address:GET.....	6
6 GET /accounts/{account}/email/{domain}/blackwhitelist/{address}.	7
6.1 Contents.....	7
6.2 Request.....	7
6.3 Response.....	7
6.4 Examples.....	7
7 Accounts-account-email-domain-blackwhitelist:GET.....	9
8 GET /accounts/{account}/email/{domain}/blackwhitelist.	10
8.1 Contents.....	10
8.2 Request.....	10
8.3 Response.....	10
8.4 Examples.....	11
9 Accounts-account-email-domain-blackwhitelist:PUT.....	13
10 PUT /accounts/{account}/email/{domain}/blackwhitelist.	14
10.1 Contents.....	14
10.2 Request.....	14
10.3 Response.....	14
10.4 Examples.....	14
11 Accounts-account-email-domain-cleanmailplus:GET.....	16
12 GET accounts/{account}/email/{domain}/cleanmailplus.	17
12.1 Contents.....	17
12.2 Request.....	17
12.3 Response.....	17
12.4 Examples.....	18
13 Accounts-account-email-domain-cleanmailplus:PUT.....	20
14 PUT accounts/{account}/email/{domain}/cleanmailplus.	21
14.1 Contents.....	21
14.2 Request.....	21
14.3 Response.....	21
14.4 Examples.....	21
15 Accounts-account-email-domain-contacts-contact:DELETE.....	24
16 DELETE /accounts/{account}/email/{domain}/contacts/{contact}.	25
16.1 Contents.....	25
16.2 Request.....	25
16.3 Response.....	25
16.4 Examples.....	25
16.5 See also.....	25
17 Accounts-account-email-domain-contacts-contact:GET.....	26
18 GET /accounts/{account}/email/{domain}/contacts/{contact}.	27
18.1 Contents.....	27
18.2 Request.....	27
18.3 Examples.....	28
18.4 See also.....	29
19 Accounts-account-email-domain-contacts-contact:PUT.....	30
20 PUT /accounts/{account}/email/{domain}/contacts/{contact}.	31
20.1 Contents.....	31
20.2 Request.....	31
20.3 Response.....	32
20.4 Examples.....	32
20.5 See also.....	33

Table of Contents

21 Accounts-account-email-domain-contacts:GET.....	34
22 GET /accounts/{account}/email/{domain}/contacts?filter{FieldName}={FieldValue}[&filter{FieldName}={FieldValue}].....	35
23 GET /accounts/{account}/email/{domain}/contacts?search{FieldName}={FieldValue}[&search{FieldName}={FieldValue}].....	36
23.1 Contents.....	36
23.2 Request.....	36
23.3 Examples.....	37
23.4 See also.....	39
24 Accounts-account-email-domain-contacts:POST.....	40
25 POST /accounts/{account}/email/{domain}/contacts.....	41
25.1 Contents.....	41
25.2 Request.....	41
25.3 Response.....	42
25.4 Examples.....	42
25.5 See also.....	43
26 Accounts-account-email-domain-infostore:GET.....	44
27 GET /accounts/{account}/email/{domain}/infostore.....	45
27.1 Contents.....	45
27.2 Request.....	45
27.3 Response.....	45
27.4 Examples.....	45
28 Accounts-account-email-domain-infostore:PUT.....	47
28.1 Contents.....	47
28.2 Request.....	47
28.3 Response.....	47
28.4 Examples.....	47
28.5 See also.....	48
29 Accounts-account-email-domain-statistics-mailboxTypeCount:GET.....	49
30 GET /accounts/{account}/email/{domain}/statistics/mailboxTypeCount.....	50
30.1 Contents.....	50
30.2 Request.....	50
30.3 Response.....	50
30.4 Examples.....	50
30.5 See also.....	51
31 Accounts-account-email-domain-usernames-mailboxName-autoreader:GET.....	52
32 GET accounts/{account}/email/{domain}/usernames/{mailbox}/autoreader.....	53
32.1 Contents.....	53
32.2 Request.....	53
32.3 Response.....	53
32.4 Examples.....	53
33 Accounts-account-email-domain-usernames-mailboxName-autoreader:PUT.....	55
34 PUT accounts/{account}/email/{domain}/usernames/{mailbox}/autoreader.....	56
34.1 Contents.....	56
34.2 Request.....	56
34.3 Response.....	56
34.4 Examples.....	56
35 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist-address:DELETE.....	58
36 DELETE /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}.....	59
36.1 Contents.....	59
36.2 Request.....	59
36.3 Response.....	59
36.4 Examples.....	59
37 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist-address:GET.....	60
38 GET /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}.....	61
38.1 Contents.....	61
38.2 Request.....	61
38.3 Response.....	61
38.4 Examples.....	61
39 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist:GET.....	63
40 GET /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist.....	64
40.1 Contents.....	64
40.2 Request.....	64
40.3 Response.....	64
40.4 Examples.....	65

Table of Contents

41 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist:PUT.....	67
42 PUT /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist.....	68
42.1 Contents.....	68
42.2 Request.....	68
42.3 Response.....	68
42.4 Examples.....	68
43 Accounts-account-email-domain-usernames-mailboxName-cleanmailplus:GET.....	70
44 GET accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus.....	71
44.1 Contents.....	71
44.2 Request.....	71
44.3 Response.....	71
44.4 Examples.....	72
45 Accounts-account-email-domain-usernames-mailboxName-cleanmailplus:PUT.....	74
46 PUT accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus.....	75
46.1 Contents.....	75
46.2 Request.....	75
46.3 Response.....	75
46.4 Examples.....	75
47 Accounts-account-email-domain-usernames-mailboxName-exchange-action:POST.....	78
48 POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/action.....	79
48.1 Contents.....	79
48.2 Request.....	79
48.3 Response.....	80
48.4 Examples.....	80
48.5 See also.....	80
49 Accounts-account-email-domain-usernames-mailboxName-exchange-messagestats:GET.....	81
50 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats.....	82
50.1 Contents.....	82
50.2 Request.....	82
50.3 Response.....	82
50.4 Examples.....	83
50.5 See also.....	83
51 Accounts-account-email-domain-usernames-mailboxName-exchange:DELETE.....	84
52 DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange.....	85
52.1 Contents.....	85
52.2 Request.....	85
52.3 Response.....	85
52.4 Examples.....	85
53 Accounts-account-email-domain-usernames-mailboxName-exchange:GET.....	86
54 GET accounts/{account}/email/{domain}/usernames/{mailbox}/exchange.....	87
54.1 Contents.....	87
54.2 Request.....	87
54.3 Response.....	87
54.4 Examples.....	90
55 Accounts-account-email-domain-usernames-mailboxName-exchange:PUT.....	92
56 PUT accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange.....	93
56.1 Request.....	93
56.2 Response.....	94
56.3 Examples.....	94
57 Accounts-account-email-domain-usernames-mailboxName-forwards-fwdmailbox:DELETE.....	97
58 DELETE accounts/{account}/email/{domain}/usernames/{mailbox}/forwards/{fwd-mailbox}.....	98
58.1 Contents.....	98
58.2 Request.....	98
58.3 Response.....	98
58.4 Examples.....	98
58.5 See also.....	98
59 Accounts-account-email-domain-usernames-mailboxName-forwards:GET.....	99
60 GET accounts/{account}/email/{domain}/usernames/{mailbox}/forwards.....	100
60.1 Contents.....	100
60.2 Request.....	100
60.3 Response.....	100
60.4 Examples.....	100
60.5 See also.....	101

Table of Contents

61 Accounts-account-email-domain-usernames-mailboxName-forwards:POST.....	102
62 POST accounts/{account}/email/{domain}/usernames/{mailbox}/forwards.....	103
62.1 Contents.....	103
62.2 Request.....	103
62.3 Response.....	103
62.4 Examples.....	104
62.5 See also.....	106
63 Accounts-account-email-domain-usernames-mailboxName-mailbox-action:POST.....	107
64 POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/action.....	108
64.1 Contents.....	108
64.2 Request.....	108
64.3 Response.....	109
64.4 Examples.....	109
64.5 See also.....	109
65 Accounts-account-email-domain-usernames-mailboxName-mailbox:DELETE.....	110
66 DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox.....	111
66.1 Contents.....	111
66.2 Request.....	111
66.3 Response.....	111
66.4 Examples.....	111
67 Accounts-account-email-domain-usernames-mailboxName-mailbox:GET.....	112
68 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox.....	113
68.1 Contents.....	113
68.2 Request.....	113
68.3 Response.....	113
68.4 Examples.....	114
69 Accounts-account-email-domain-usernames-mailboxName-mailbox:PUT.....	115
70 PUT accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox.....	116
70.1 Contents.....	116
70.2 Request.....	116
70.3 Response.....	117
70.4 Examples.....	117
70.5 See also.....	119
71 Accounts-account-email-domain-usernames-mailboxName-messagestats:GET.....	120
72 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats.....	121
72.1 Contents.....	121
72.2 Request.....	121
72.3 Response.....	121
72.4 Examples.....	122
72.5 See also.....	122
73 Accounts-account-email-domain-usernames-mailboxName-migration:POST.....	123
74 POST accounts/{account}/email/{domain}/usernames/{mailboxName}/migration.....	124
74.1 Contents.....	124
74.2 Request.....	124
74.3 Response.....	124
74.4 Examples.....	124
74.5 See also.....	125
75 Accounts-account-email-domain-usernames-mailboxName-secrets:GET.....	126
76 GET /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets.....	127
76.1 Contents.....	127
76.2 Request.....	127
76.3 Response.....	127
76.4 Examples.....	127
76.5 See also.....	128
77 Accounts-account-email-domain-usernames-mailboxName-secrets:PUT.....	129
78 PUT /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets.....	130
78.1 Contents.....	130
78.2 Request.....	130
78.3 Response.....	130
78.4 Examples.....	130
78.5 See also.....	131
79 Accounts-account-email-domain-usernames-mailboxName-webmail:GET.....	132
80 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail.....	133
80.1 Contents.....	133
80.2 Request.....	133
80.3 Response.....	133

Table of Contents

80 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail	134
80.4 Examples.....	134
81 Accounts-account-email-domain-usernames-mailboxName-webmail:POST.....	135
82 POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail.....	136
82.1 Contents.....	136
82.2 Request.....	136
82.3 Response.....	136
82.4 Examples.....	137
83 Accounts-account-email-domain-usernames-mailboxName-webmail:PUT.....	138
84 PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail.....	139
84.1 Contents.....	139
84.2 Request.....	139
84.3 Response.....	140
84.4 Examples.....	140
85 Accounts-account-email-domain-usernames-mailboxName:GET.....	142
86 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}.....	143
86.1 Contents.....	143
86.2 Request.....	143
86.3 Response.....	143
86.4 Examples.....	144
86.5 See also.....	144
87 Accounts-account-email-domain-usernames:GET.....	145
88 GET /accounts/{account}/email/{domain}/usernames.....	146
88.1 Contents.....	146
88.2 Request.....	146
88.3 Response.....	146
88.4 Examples.....	147
88.5 See also.....	148
89 Accounts-account-email-domain-webmail:GET.....	149
90 GET /accounts/{account}/email/{domain}/webmail.....	150
90.1 Contents.....	150
90.2 Request.....	150
90.3 Response.....	150
90.4 Examples.....	151
91 Accounts-account-email-domain-webmail:PUT.....	152
92 PUT /accounts/{account}/email/{domain}/webmail.....	153
92.1 Contents.....	153
92.2 Request.....	153
92.3 Response.....	153
92.4 Examples.....	153
93 Accounts-account-email-domain-webmailLimits:GET.....	155
94 GET /accounts/{account}/email/{domain}/webmailLimits.....	156
94.1 Contents.....	156
94.2 Request.....	156
94.3 Response.....	156
94.4 See also.....	156
95 Accounts-account-email-domain-webmailNames:GET.....	157
96 GET /accounts/{account}/email/{domain}/webmailNames.....	158
96.1 Contents.....	158
96.2 Request.....	158
96.3 Response.....	158
96.4 See also.....	158
97 Accounts-account-email-domain-webmailUpgrade:GET.....	159
98 GET /accounts/{account}/email/{domain}/webmailUpgrade.....	160
98.1 Contents.....	160
98.2 Request.....	160
98.3 Response.....	160
98.4 See also.....	160
99 Accounts-account-email-domain:GET.....	161
100 GET /accounts/{account}/email/{domain}.....	162
100.1 Contents.....	162
100.2 Request.....	162
100.3 Response.....	162
100.4 Examples.....	162

Table of Contents

101 Email API.....	164
101.1 Mailboxes.....	164
101.2 Exchange.....	164
101.3 Aliases.....	164
101.4 Forwards.....	164
101.5 Autoresponder.....	164
101.6 CleanMailPlus.....	164
101.7 Webmail.....	164
101.8 Webmail Names.....	164
101.9 Black/White List.....	164
101.10 InfoStore.....	164
101.11 Mailbox domain statistics.....	164
101.12 Mailbox migration failure.....	164
101.13 Mailbox Message Count.....	164
101.14 Exchange Message Count.....	165
101.15 Email Domain.....	165
101.16 Domain Black/White List.....	165
101.17 Domain CleanMailPlus.....	165
101.18 Secret Questions.....	165
101.19 Secret Question Settings.....	165
101.20 Supported Secret Questions.....	165
101.21 Antivirus Antispam.....	165
102 Email-domain-usernames-mailboxName-exchange-action:POST.....	166
103 POST /email/{domain}/usernames/{mailboxName}/exchange/action.....	167
103.1 Contents.....	167
103.2 Request.....	167
103.3 Response.....	168
103.4 Examples.....	168
103.5 See also.....	168
104 Email-domain-usernames-mailboxName-mailbox-action:POST.....	169
105 POST /email/{domain}/usernames/{mailboxName}/mailbox/action.....	170
105.1 Contents.....	170
105.2 Request.....	170
105.3 Response.....	171
105.4 Examples.....	171
105.5 See also.....	171
106 Email-domain-usernames-mailboxName-secrets:GET.....	172
107 GET /email/{domain}/usernames/{mailboxName}/secrets.....	173
107.1 Contents.....	173
107.2 Request.....	173
107.3 Response.....	173
107.4 Examples.....	173
107.5 See also.....	174
108 Email-domain-usernames-mailboxName-secrets:PUT.....	175
109 PUT /email/{domain}/usernames/{mailboxName}/secrets.....	176
109.1 Contents.....	176
109.2 Request.....	176
109.3 Response.....	176
109.4 Examples.....	176
109.5 See also.....	177
110 Email-domain-usernames-mailboxName-webmail:GET.....	178
111 GET /email/{domain}/usernames/{mailboxName}/webmail.....	179
111.1 Contents.....	179
111.2 Request.....	179
111.3 Response.....	179
111.4 Examples.....	179
112 Email-domain-usernames-mailboxName-webmail:POST.....	181
113 POST /email/{domain}/usernames/{mailboxName}/webmail.....	182
113.1 Contents.....	182
113.2 Request.....	182
113.3 Response.....	182
113.4 Examples.....	183
114 Email-domain-usernames-mailboxName-webmail:PUT.....	184
115 PUT /email/{domain}/usernames/{mailboxName}/webmail.....	185
115.1 Contents.....	185
115.2 Request.....	185
115.3 Response.....	185
115.4 Examples.....	186

Table of Contents

116 Email-secretQuestions:GET.....	188
117 GET /email/secretQuestions.....	189
117.1 Contents.....	189
117.2 Request.....	189
117.3 Response.....	189
117.4 Examples.....	189
118 Email-secretQuestionSettings:GET.....	191
119 GET /email/secretQuestionSettings.....	192
119.1 Contents.....	192
119.2 Request.....	192
119.3 Response.....	192
119.4 Examples.....	192
120 Template:ResetPassword.....	193
121 POST {{base}}/email/{domain}/usernames/{mailboxName}/{{{resource}}}/action.....	194
121.1 Contents.....	194
121.2 Request.....	194
121.3 Response.....	195
121.4 Examples.....	195
121.5 See also.....	195

1 Accounts-account-email-domain-alaises:GET

2 GET /accounts/{account}/email/{domain}/aliases

Retrieves a list of aliases for a specific account and domain

2.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/aliases
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◆ 1.4 See also

2.2 Request

GET /accounts/{account}/email/{domain}/aliases

2.2.1 Request Parameters

account - *string*
The user account owning the domain and the mailboxes
domain - *string*
The specific domain for which the call will retrieve the list

2.3 Response

2.3.1 Status Code

200 OK
Success
401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.
404 Not Found
The domain name or account does not exist.

2.3.2 Response Body

```
{  
    "list": [  
        "{alias}"  
    ],  
    "links": [  
        {  
            "href": "{href}",  
            "rel": "{rel}"  
        }  
    ]  
}
```

2.3.2.1 Parameters

alias - *string*
Domain name alias
href - *string*
Link to other resources relevant to the mailboxes lists
rel - *string*
Type of relation to the resource for the provided link

2.4 Examples

2.4.1 Success scenario

Request

GET accounts/test-account123/email/test.com/aliases

Response

```
{
```

```
        "list": [
            "test-alias.com", "test-alias-2.com"
        ],
        "links": [
            {
                "href": "https://api.hostway.com/accounts/test-account123/email/test.com/aliases/",
                "rel": "self"
            }
        ]
    }
```

2.5 See also

- [Email API](#)

Please enable JavaScript to view the comments powered by Disqus. [blog comments powered by Disqus](#)

3 Accounts-account-email-domain-blackwhitelist-address:DELETE

4 DELETE /accounts/{account}/email/{domain}/blackwhitelist/{address}

Remove black/white listed address

4.1 Contents

- 1 DELETE
/accounts/{account}/email/{domain}/blackwhitelist/{address}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Delete address from black/white list

4.2 Request

```
DELETE /accounts/{account}/email/{domain}/blackwhitelist/{address}
```

4.2.1 URI Parameters

account - *string*
domain - *string*
address - *string*

4.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

4.3 Response

4.3.1 Status Code

204 No Content
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or address does not exist.

4.4 Examples

4.4.1 Delete address from black/white list

Request

```
DELETE /accounts/account-number/email/test.com/blackwhitelist/mb1-white20150114-0113@somedomain.com
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

5 Accounts-account-email-domain-blackwhitelist-address:GET

6 GET /accounts/{account}/email/{domain}/blackwhitelist/{address}

Get black/white listed address details

6.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/blackwhitelist/{address}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Get address details

6.2 Request

GET /accounts/{account}/email/{domain}/blackwhitelist/{address}

6.2.1 URI Parameters

account - *string*
domain - *string*
address - *string*

6.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

6.3 Response

6.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

6.3.2 Response Body

```
{  
  "type": "{type}",  
  "address": "{address}",  
  "links": {links}  
}
```

6.3.2.1 Parameters

type - *string*
Type of address included in black/white list. Possible values are "W" or "B". "W" means the mailbox is included in "whitelist", "B" - included in "blacklist".

address - *string*
The address of the black/whitelisted mailbox or domain.

links - *list*
Hypermedia to the get black/whitelisted address

6.4 Examples

6.4.1 Get address details

Request

GET /accounts/account-number/email/test.com/blackwhitelist/mbl-white20150114-0113@somedomain.com

Response

200 OK

```
{  
  "type": "W",
```

```
        "address": "mb1-white20150114-0113@somedomain.com",
        "links": [
            {
                "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist/mb1-white20150114-0113@somedomain.com/",
                "rel": "self"
            }
        ]
    }
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

7 Accounts-account-email-domain-blackwhitelist:GET

8 GET /accounts/{account}/email/{domain}/blackwhitelist

Retrieves a list of all addresses included in black/white list for a specific domain

8.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/blackwhitelist
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Get all addresses included in black/white list
 - ◊ 1.3.2 Get filtered list by address
 - ◊ 1.3.3 Get filtered list by type
 - ◊ 1.3.4 Paginated request
 - ◊ 1.3.5 Sorted request

8.2 Request

GET /accounts/{account}/email/{domain}/blackwhitelist

8.2.1 URI Parameters

account - *string*
domain - *string*

8.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

8.3 Response

8.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

8.3.2 Response Body

```
{  
    "totalCount": {totalCount},  
    "list": [  
        {  
            "type": "{type}",  
            "address": "{address}"  
        }  
    ],  
    "links": [  
        {  
            "href": "{href}",  
            "rel": "{rel}"  
        }  
    ]  
}
```

8.3.2.1 Parameters

totalCount - *int*
The total count of addresses included in black/white list

type - *string*
Type of address included in black/white list. Possible values are "W" or "B". "W" means the mailbox is included in "whitelist", "B" - included in "blacklist".

address - *string*
The address of the black/whitelisted mailbox or domain.

links - *list*
Hypermedia to the get black/whitelisted addresses

8.4 Examples

8.4.1 Get all addresses included in black/white list

Request

```
GET /accounts/account-number/email/test.com/blackwhitelist
```

Response

200 OK

```
{  
    "totalCount": 4,  
    "list": [  
        {  
            "type": "W",  
            "address": "mb1-white@somedomain.com"  
        },  
        {  
            "type": "B",  
            "address": "mb2-black@domain.com"  
        },  
        {  
            "type": "B",  
            "address": "mb3-black@somedomain.com"  
        },  
        {  
            "type": "B",  
            "address": "@sometestdomain.com"  
        }  
    ],  
    "links": [  
        {  
            "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist",  
            "rel": "self"  
        }  
    ]  
}
```

8.4.2 Get filtered list by address

Request

```
GET /accounts/account-number/email/test.com/blackwhitelist?filterAddress=*somedomain.com*
```

Response

200 OK

```
{  
    "totalCount": 2,  
    "list": [  
        {  
            "type": "W",  
            "address": "mb1-white@somedomain.com"  
        },  
        {  
            "type": "B",  
            "address": "mb3-black@somedomain.com"  
        }  
    ],  
    "links": [  
        {  
            "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist?filterAddress=*somedomain.com*",  
            "rel": "self"  
        }  
    ]  
}
```

8.4.3 Get filtered list by type

Request

```
GET /accounts/account-number/email/test.com/blackwhitelist?filterType=W
```

Response

200 OK

```
{  
    "totalCount": 1,  
    "list": [  
        {  
            "type": "W",  
            "address": "mb1-white@somedomain.com"  
        }  
    ],  
    "links": [  
        {  
            "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist?filterType=W",  
            "rel": "self"  
        }  
    ]  
}
```

```
    ]  
}
```

8.4.4 Paginated request

Request

```
GET /accounts/account-number/email/test.com/blackwhitelist?pageSize=2&page=1
```

Response

```
200 OK
```

```
{  
  "totalCount": 2,  
  "list": [  
    {  
      "type": "W",  
      "address": "mb1-white@somedomain.com"  
    },  
    {  
      "type": "B",  
      "address": "mb2-white@domain.com"  
    }  
  ],  
  "links": [  
    {  
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist?pageSize=2&page=2",  
      "rel": "next"  
    },  
    {  
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist?pageSize=2&page=2",  
      "rel": "last"  
    }  
  ]  
}
```

8.4.5 Sorted request

Request

```
GET /accounts/account-number/email/test.com/blackwhitelist?sortField=address&sortOrder=desc
```

Response

```
200 OK
```

```
{  
  "totalCount": 4,  
  "list": [  
    {  
      "type": "B",  
      "address": "mb3-black@somedomain.com"  
    },  
    {  
      "type": "B",  
      "address": "mb2-black@domain.com"  
    },  
    {  
      "type": "W",  
      "address": "mb1-white@somedomain.com"  
    },  
    {  
      "type": "B",  
      "address": "@sometestdomain.com"  
    }  
  ],  
  "links": [  
    {  
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/blackwhitelist?sortField=address&sortOrder=desc",  
      "rel": "self"  
    }  
  ]  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

9 Accounts-account-email-domain-blackwhitelist:PUT

10 PUT /accounts/{account}/email/{domain}/blackwhitelist

Adding/updating addresses to black/white list for a specific domain

10.1 Contents

- 1 PUT
/accounts/{account}/email/{domain}/blackwhitelist
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure adding address with missing required parameter
 - ◊ 1.3.2 Failure adding address with not valid address and type
 - ◊ 1.3.3 Success adding email addresses to blackwhitelist
 - ◊ 1.3.4 Success adding domain addresses to blackwhitelist

10.2 Request

PUT /accounts/{account}/email/{domain}/blackwhitelist

10.2.1 URI Parameters

account - *string*
domain - *string*

10.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

10.2.3 Request Body

```
{  
    "list": [  
        {  
            "address": "{address}",  
            "type": "{type}"  
        }  
    ]  
}
```

10.2.3.1 Parameters

address - *string*
Must be a valid email or domain address. Required.

type - *string*
One of W, B. Required.

10.3 Response

10.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the address does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

10.4 Examples

10.4.1 Failure adding address with missing required parameter

Request

```
PUT /accounts/account-number/email/test.com/blackwhitelist
{"list": [{"address": "mbl-white@somedomain.com"}]}
```

Response

400 Bad Request

```
{
  "badRequest": {
    "message": "POST data error",
    "code": 400,
    "details": {
      "list.0.type": "Required"
    }
  }
}
```

10.4.2 Failure adding address with not valid address and type

Request

```
PUT /accounts/account-number/email/test.com/blackwhitelist
{"list": [{"address": "somedomain.com", "type": "A"}]}
```

Response

400 Bad Request

```
{
  "badRequest": {
    "message": "POST data error",
    "code": 400,
    "details": {
      "list.0.type": "\"A\" is not one of B, W",
      "list.0.address": "Invalid address format: somedomain.com"
    }
  }
}
```

10.4.3 Success adding email addresses to blackwhitelist

Request

```
PUT /accounts/account-number/email/test.com/blackwhitelist
{"list": [{"address": "mbl-white20150114-0113@somedomain.com", "type": "W"}, {"address": "mb2-white20150114-0113@somedomain.com", "type": "W"}]}
```

Response

204 No Content

10.4.4 Success adding domain addresses to blackwhitelist

Request

```
PUT /accounts/account-number/email/test.com/blackwhitelist
{
  "list": [
    {
      "type": "W",
      "address": "@domainaddr1.com"
    },
    {
      "type": "B",
      "address": "@someotherdomain.com"
    }
  ]
}
```

Please enable JavaScript to view the [comments powered by Disqus.](#) blog comments powered by Disqus

11 Accounts-account-email-domain-cleanmailplus:GET

12 GET accounts/{account}/email/{domain}/cleanmailplus

Gets domain's CleanMailPlus info.

12.1 Contents

- 1 GET accounts/{account}/email/{domain}/cleanmailplus
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure getting CleanMailPlus info for a non-existent domain
 - ◊ 1.3.2 Success getting CleanMailPlus info

12.2 Request

GET accounts/{account}/email/{domain}/cleanmailplus

12.2.1 URI Parameters

account - *string*
domain - *string*

12.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

12.3 Response

12.3.1 Status Code

200 OK
Success
401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.
404 Not Found
The domain name does not exist.

12.3.2 Response Body

```
[  
  {  
    "selected": "{selected_option_value}",  
    "fieldName": "{field_name}",  
    "description": "{description}",  
    "options": [  
      {  
        "name": "{option_name}",  
        "value": "{option_value}"  
      }  
    ]  
  }  
]
```

12.3.2.1 Parameters

selected_option_value - *string*
Currently selected option value.
field_name - *string*
Field name.
description - *string*
Descriptive option info.
options - *list*
List of options.
options.name - *string*
Option's name.
options.value - *string*
Option's value.

12.4 Examples

12.4.1 Failure getting CleanMailPlus info for a non-existent domain

Request

```
GET accounts/test-account123/email/non-existent-domain.com/cleanmailplus
```

Response

```
404 Not Found
```

12.4.2 Success getting CleanMailPlus info

Request

```
GET accounts/test-account123/email/test.com/cleanmailplus
```

Response

```
200 OK
```

```
[{"field": {"selected": "6", "fieldName": "SPAM_LEVEL", "description": "SPAM Tag Level", "options": [{"name": "Least Aggressive", "value": "6"}, {"name": "Less Aggressive", "value": "5"}, {"name": "Normal", "value": "4"}, {"name": "More Aggressive", "value": "3"}, {"name": "Most Aggressive", "value": "2"}, {"name": "Ultra Aggressive", "value": "1"}]}, {"field": {"selected": "2", "fieldName": "SPAM_ACTION", "description": "SPAM Detected Action", "options": [{"name": "None", "value": "0"}, {"name": "Tag Subject", "value": "2"}, {"name": "Move to SPAM Folder", "value": "1"}, {"name": "Delete", "value": "3"}]}, {"field": {"selected": "1", "fieldName": "ATTACHMENT_CONTROL", "description": "Attachment Control", "options": [{"name": "Enable", "value": "1"}, {"name": "Disable", "value": "0"}]}, {"field": {"selected": "1", "fieldName": "VIRUS_ACTION", "description": "Virus Detected Action", "options": [{"name": "No Virus Filter", "value": "0"}]}}]
```

```

        },
        {
            "name": "Delete Automatically",
            "value": "1"
        }
    ],
},
{
    "selected": "0",
    "fieldName": "SPAM_LEARNING",
    "description": "SPAM Learning Status",
    "options": []
},
{
    "selected": "20",
    "fieldName": "SPAM_DISCARD_LEVEL",
    "description": "SPAM Discard Level",
    "options": []
},
{
    "selected": "0",
    "fieldName": "PHISHING_CHECKS",
    "description": "Phishing Checks",
    "options": [
        {
            "name": "Enabled",
            "value": "1"
        },
        {
            "name": "Disabled",
            "value": "0"
        }
    ]
},
{
    "selected": "0",
    "fieldName": "CLEANMAIL_PLUS",
    "description": "CleanMail Plus Enable",
    "options": [
        {
            "name": "Enable",
            "value": "1"
        },
        {
            "name": "Disable",
            "value": "0"
        }
    ]
},
{
    "selected": "1",
    "fieldName": "SPAM_CHECK",
    "description": "SPAM Check Option",
    "options": [
        {
            "name": "Enable",
            "value": "1"
        },
        {
            "name": "Disable",
            "value": "0"
        }
    ]
}
]

```

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

13 Accounts-account-email-domain-cleanmailplus:PUT

14 PUT accounts/{account}/email/{domain}/cleanmailplus

Updates domain's CleanMailPlus info.

14.1 Contents

- 1 PUT accounts/{account}/email/{domain}/cleanmailplus
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure updating the CleanMailPlus filter attributes for a non-existent domain
 - ◊ 1.3.2 Failure updating the CleanMailPlus filter attributes by providing bad request body
 - ◊ 1.3.3 Failure updating the cleanmailplus filter attribute by providing a non-existent attribute name
 - ◊ 1.3.4 Failure updating the cleanmailplus filter attribute by providing a non-valid attribute value
 - ◊ 1.3.5 Success updating the CleanMailPlus filter attributes

14.2 Request

PUT accounts/{account}/email/{domain}/cleanmailplus

14.2.1 URI Parameters

account - *string*
domain - *string*

14.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

14.2.3 Request Body

```
{  
    "attributes": [  
        {  
            "attributeName": "{attribute_name}",  
            "attributeValue": "{attribute_value}"  
        }  
    ]  
}
```

14.2.3.1 Parameters

attributeName - *string*
Attribute's name.
attributeValue - *string*
New attribute's value.

14.3 Response

14.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

14.4 Examples

14.4.1 Failure updating the CleanMailPlus filter attributes for a non-existent domain

Request

PUT accounts/{account}/email/non-existent-domain.com/cleanmailplus

```
{
  "attributes": [
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "1"
    }
  ]
}
```

Response

```
404 Not Found
{
  "itemNotFound": {
    "message": "Resource not found",
    "code": 404,
    "details": {
      "message": "Domain not found"
    }
  }
}
```

14.4.2 Failure updating the CleanMailPlus filter attributes by providing bad request body

Request

```
PUT accounts/{account}/email/test.com/cleanmailplus
{
  "badBody": "badBodyValue"
}
```

Response

```
400 Bad Request
{
  "attributes": "Required"
}
```

14.4.3 Failure updating the cleanmailplus filter attribute by providing a non-existent attribute name

Request

```
PUT accounts/{account}/email/test.com/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "NON_EXISTENT_ATTRIBUTE_NAME",
      "attributeValue": "1"
    }
  ]
}
```

Response

```
400 Bad Request
{
  "attributes.0": "NON_EXISTENT_ATTRIBUTE_NAME is not valid filter attribute name"
}
```

14.4.4 Failure updating the cleanmailplus filter attribute by providing a non-valid attribute value

Request

```
PUT accounts/{account}/email/test.com/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "val01"
    }
  ]
}
```

Response

```
400 Bad Request
{
  "attributes.0": "val01 is not valid attribute option for SPAM_LEVEL filter attribute"
}
```

14.4.5 Success updating the CleanMailPlus filter attributes

Request

```
PUT accounts/{account}/email/test.com/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "1"
    },
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "1"
    }
  ]
}
```

```
        "attributeName": "SPAM_ACTION",
        "attributeValue": "1"
    ]
}
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

15 Accounts-account-email-domain-contacts-contact:DELETE

16 DELETE /accounts/{account}/email/{domain}/contacts/{contact}

Deletes domain's global address book contact.

16.1 Contents

- 1 DELETE
/accounts/{account}/email/{domain}/contacts/{contact}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success deleting domain's global address book contact
 - ◆ 1.4 See also

16.2 Request

DELETE /accounts/{account}/email/{domain}/contacts/{contact}

16.2.1 URI Parameters

account - *string*
domain - *string*
contact - *string*

16.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

16.3 Response

16.3.1 Status Code

204 No Content
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain or contact does not exist.

16.4 Examples

16.4.1 Success deleting domain's global address book contact

Request

DELETE https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact

Response

204 No Content

16.5 See also

- [Global Address Book Public API](#)

17 Accounts-account-email-domain-contacts-contact:GET

18 GET /accounts/{account}/email/{domain}/contacts/{contact}

Gets domain's global address book contact information

18.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/contacts/{contact}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Status Code
 - ◊ 1.1.4 Response Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Examples
 - ◊ 1.2.1 Error getting global address book contact info
 - ◊ 1.2.2 Success getting global address book contact info
 - ◆ 1.3 See also

18.2 Request

GET /accounts/{account}/email/{domain}/contacts/{contact}

18.2.1 URI Parameters

account - *string*
domain - *string*
contact - *string*

18.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

18.2.3 Status Code

200 Ok
Success

400 Bad Request
The format of the request body is invalid or the parameters don't meet the requirements.

404 Not Found
The domain name or contact does not exist.

18.2.4 Response Body

```
{  
    "name": "{name}",  
    "email": "{email}",  
    "firstName": "{firstName}",  
    "lastName": "{lastName}",  
    "displayName": "{displayName}"  
    "title": "{title}",  
    "homePhone": "{homePhone}",  
    "mobilePhone": "{mobilePhone}",  
    "businessPhone": "{businessPhone}",  
    "businessFax": "{businessFax}",  
    "isdnNumber": "{isdnNumber}",  
    "pager": "{pager}",  
    "telexNumber": "{telexNumber}",  
    "company": "{company}",  
    "department": "{department}",  
    "roomNumber": "{roomNumber}",  
    "streetAddress": "{streetAddress}",  
    "postalCode": "{postalCode}",  
    "city": "{city}",  
    "state": "{state}",  
    "country": "{country}",  
    "links": [{"href": "{APIBaseURL}/accounts/{account}/email/{domain}/contacts/{name}", "rel": "self"}]  
}
```

18.2.4.1 Parameters

name - *string*
The name of global address book contact.

email - *string*
The email of global address book contact.

firstName - *string*
The first name of global address book contact.

`lastName - string`
The last name of global address book contact.

`displayName - string`
The display name of global address book contact.

`title - string`
The title of global address book contact person.

`homePhone - string`
The home phone of global address book contact.

`mobilePhone - string`
The home phone of global address book contact.

`businessPhone - string`
The business phone of global address book contact.

`businessFax - string`
The business fax of global address book contact.

`isdnNumber - string`
The isdn number of global address book contact.

`pager - string`
The pager of global address book contact.

`telexNumber - string`
The telex number of global address book contact.

`company - string`
The company name of global address book contact.

`department - string`
The department name of global address book contact.

`roomNumber - string`
The room number of global address book contact.

`streetAddress - string`
The street address of global address book contact.

`postalCode - string`
The postal code of global address book contact.

`city - string`
The city name of global address book contact.

`state - string`
The state name of global address book contact.

`country - string`
The country name of global address book contact.

18.3 Examples

18.3.1 Error getting global address book contact info

Request

```
GET https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/non-existent-contact
```

Response

404 Not Found

18.3.2 Success getting global address book contact info

Request

```
GET https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact
```

Response

200 Ok

```
{  
    "city": "",  
    "businessPhone": "",  
    "displayName": "Display Name",  
    "mobilePhone": "",  
    "firstName": "First",  
    "title": "",  
    "roomNumber": "",  
    "lastName": "Last",  
    "company": ""  
}
```

```
"pager": "",  
"state": "",  
"department": "",  
"streetAddress": "",  
"isdnNumber": "",  
"postalCode": "",  
"country": "",  
"telexNumber": "",  
"businessFax": "",  
"email": "test@test.com",  
"homePhone": "",  
"links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact", "rel": "self"}]  
}
```

18.4 See also

- [Global Address Book Public API](#)

19 Accounts-account-email-domain-contacts-contact:PUT

20 PUT /accounts/{account}/email/{domain}/contacts/{contact}

Updates domain's global address book contact info

20.1 Contents

- 1 PUT /accounts/{account}/email/{domain}/contacts/{contact}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure updating global address book contact because of erroneous data
 - ◊ 1.3.2 Success updating global address book contact
 - ◆ 1.4 See also

20.2 Request

PUT /accounts/{account}/email/{domain}/contacts/{contact}

20.2.1 URI Parameters

account - *string*
domain - *string*
contact - *string*

20.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

20.2.3 Request Body

```
{  
    "email": "{email}",  
    "firstName": "{firstName}",  
    "lastName": "{lastName}",  
    "displayName": "{displayName}"  
    "title": "{title}",  
    "homePhone": "{homePhone}",  
    "mobilePhone": "{mobilePhone}",  
    "businessPhone": "{businessPhone}",  
    "businessFax": "{businessFax}",  
    "isdnNumber": "{isdnNumber}",  
    "pager": "{pager}",  
    "telexNumber": "{telexNumber}",  
    "company": "(company)",  
    "department": "(department)",  
    "roomNumber": "(roomNumber)",  
    "streetAddress": "(streetAddress)",  
    "postalCode": "(postalCode)",  
    "city": "(city)",  
    "state": "(state)",  
    "country": "(country)"  
}
```

20.2.3.1 Parameters

email - *string*
The email of global address book contact.

firstName - *string*
The first name of global address book contact.

lastName - *string*
The last name of global address book contact.

displayName - *string*
The display name of global address book contact.

title - *string*
The title of global address book contact person.

homePhone - *string*
The home phone of global address book contact.

mobilePhone - *string*
The home phone of global address book contact.

businessPhone - *string*
 The business phone of global address book contact.

businessFax - *string*
 The business fax of global address book contact.

isdnNumber - *string*
 The isdn number of global address book contact.

pager - *string*
 The pager of global address book contact.

telexNumber - *string*
 The telex number of global address book contact.

company - *string*
 The company name of global address book contact.

department - *string*
 The department name of global address book contact.

roomNumber - *string*
 The room number of global address book contact.

streetAddress - *string*
 The street address of global address book contact.

postalCode - *string*
 The postal code of global address book contact.

city - *string*
 The city name of global address book contact.

state - *string*
 The state name of global address book contact.

country - *string*
 The country name of global address book contact.

20.3 Response

20.3.1 Status Code

204 No Content
 Success

400 Bad Request
 The format of the request body is invalid or the parameters don't meet the requirements.

401 Unauthorized
 The supplied credentials are invalid or do not provide permissions for this operation.

20.4 Examples

20.4.1 Failure updating global address book contact because of erroneous data

Request

```
PUT https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact
{
  "email": "updated-email",
  "displayName": "Display Name Updated"
}
```

Response

```
400 Bad Request
{
  "email": "Invalid email address"
}
```

20.4.2 Success updating global address book contact

Request

```
PUT https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact
{
  "email": "new@test.com",
  "mobilePhone": "123456789"
}
```

Response

```
204 No Content
```

20.5 See also

- [Global Address Book Public API](#)

21 Accounts-account-email-domain-contacts:GET

22 GET

/accounts/{account}/email/{domain}/contacts?filter{FieldName}={FieldValue}[&filter{Fi}

Filter domain's global address book contacts list

23 GET /accounts/{account}/email/{domain}/contacts?search{FieldName}={FieldValue}[&search{FieldName}={FieldValue}]

Search domain's global address book contacts list

23.1 Contents

- 1 GET /accounts/{account}/email/{domain}/contacts?filter{FieldName}={FieldValue}[&filter{FieldName}={FieldValue}]
- 2 GET /accounts/{account}/email/{domain}/contacts?search{FieldName}={FieldValue}[&search{FieldName}={FieldValue}]
 - ◆ 2.1 Request
 - ◊ 2.1.1 URI Parameters
 - ◊ 2.1.2 Request Headers
 - ◊ 2.1.3 Status Code
 - ◊ 2.1.4 Response Body
 - 2.1.4.1 Parameters
 - ◆ 2.2 Examples
 - ◊ 2.2.1 Success filtering global address book contacts with filterName and filterEmail parameters
 - ◊ 2.2.2 Success filtering global address book contacts with only filterEmail parameter
 - ◊ 2.2.3 Success searching global address book contacts with only searchName parameter
 - ◊ 2.2.4 Success filtering global address book contacts with non-existent filterName parameter
 - ◊ 2.2.5 Success searching global address book contacts with non-existent searchName parameter
 - ◆ 2.3 See also

23.2 Request

GET /accounts/{account}/email/{domain}/contacts?filter{FieldName}={FieldValue}[&filter{FieldName}={FieldValue}]

GET /accounts/{account}/email/{domain}/contacts?search{FieldName}={FieldValue}[&search{FieldName}={FieldValue}]

23.2.1 URI Parameters

account - string
domain - string
filter{FieldName} - string
 Specifies fields to filter by, i.e. filterName, filterEmail, etc...
search{FieldName} - string
 Specifies fields to search by, i.e. searchName, searchEmail, etc...

23.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
 The **Authentication** credentials of the client application.

Content-Type
 Required. Set this header to application/json; charset=UTF-8

23.2.3 Status Code

200 Ok

 Success

404 Not Found

 The domain name does not exist.

23.2.4 Response Body

```
{  
    "count": {count},  
    "list": [  
        {  
            "name": "{name}",  
            "email": "{email}",  
            "firstName": "{firstName}",  
            "lastName": "{lastName}",  
            "displayName": "{displayName}"  
            "title": "{title}",  
            "homePhone": "{homePhone}",  
            "mobilePhone": "{mobilePhone}",  
            "businessPhone": "{businessPhone}",  
            "businessFax": "{businessFax}",  
            "isdnNumber": "{isdnNumber}",  
            "pager": "{pager}",  
            "telexNumber": "{telexNumber}",  
            "company": "{company}",  
            "department": "{department}",  
            "roomNumber": "{roomNumber}",  
            "streetAddress": "{streetAddress}",  
            "postalCode": "{postalCode}",  
            "city": "{city}",  
            "state": "{state}",  
            "country": "{country}",  
            "links": [{"href": "{APIBaseUrl}/accounts/{account}/email/{domain}/contacts/{name}", "rel": "self"}],  
        },  
        {  
            "links": [{"href": "{APIBaseUrl}/accounts/{account}/email/{domain}/contacts", "rel": "self"}],  
        }  
    ]  
}
```

}

23.2.4.1 Parameters

count - *int*
The count of global address book contacts matching the search/filter condition.

name - *string*
The name of global address book contact.

email - *string*
The email of global address book contact.

firstName - *string*
The first name of global address book contact.

lastName - *string*
The last name of global address book contact.

displayName - *string*
The display name of global address book contact.

title - *string*
The title of global address book contact person.

homePhone - *string*
The home phone of global address book contact.

mobilePhone - *string*
The home phone of global address book contact.

businessPhone - *string*
The business phone of global address book contact.

businessFax - *string*
The business fax of global address book contact.

isdnNumber - *string*
The isdn number of global address book contact.

pager - *string*
The pager of global address book contact.

telexNumber - *string*
The telex number of global address book contact.

company - *string*
The company name of global address book contact.

department - *string*
The department name of global address book contact.

roomNumber - *string*
The room number of global address book contact.

streetAddress - *string*
The street address of global address book contact.

postalCode - *string*
The postal code of global address book contact.

city - *string*
The city name of global address book contact.

state - *string*
The state name of global address book contact.

country - *string*
The country name of global address book contact.

23.3 Examples

23.3.1 Success filtering global address book contacts with filterName and filterEmail parameters

Request

```
GET https://api.hostway.com/accounts/account007/email/test-domain.com/contacts?filterName=search-contact&filterEmail=new@test.com
```

Response

200 Ok

```
{
  "count": 1,
  "list": [
    {
      "city": "",
      "businessPhone": ""
```

```

        "displayName": "Display Name",
        "mobilePhone": "",
        "firstName": "First",
        "title": "",
        "roomNumber": "",
        "lastName": "Last",
        "company": "",
        "pager": "",
        "state": "",
        "state": "",
        "department": "",
        "streetAddress": "",
        "isdnNumber": "",
        "postalCode": "",
        "country": "",
        "telexNumber": "",
        "businessFax": "",
        "email": "new@test.com",
        "homePhone": "",
        "name": "search-contact",
        "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/search-contact", "rel": "self"}],
    },
    "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts", "rel": "self"}],
}

```

23.3.2 Success filtering global address book contacts with only filterEmail parameter

Request

GET <https://api.hostway.com/accounts/account007/email/test-domain.com/contacts?filterEmail=new@test.com>

Response

200 Ok

```
{
    "count": 2,
    "list": [
        {
            "city": "",
            "businessPhone": "",
            "displayName": "Display Name",
            "mobilePhone": "",
            "firstName": "First",
            "title": "",
            "roomNumber": "",
            "lastName": "Last",
            "company": "",
            "pager": "",
            "state": "",
            "state": "",
            "department": "",
            "streetAddress": "",
            "isdnNumber": "",
            "postalCode": "",
            "country": "",
            "telexNumber": "",
            "businessFax": "",
            "email": "new@test.com",
            "homePhone": "",
            "name": "search-contact",
            "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/search-contact", "rel": "self"}],
        },
        {
            "city": "",
            "businessPhone": "",
            "displayName": "Display Name",
            "mobilePhone": "123456789",
            "firstName": "First",
            "title": "",
            "roomNumber": "",
            "lastName": "Last",
            "company": "",
            "pager": "",
            "state": "",
            "state": "",
            "department": "",
            "streetAddress": "",
            "isdnNumber": "",
            "postalCode": "",
            "country": "",
            "telexNumber": "",
            "businessFax": "",
            "email": "new@test.com",
            "homePhone": "",
            "name": "test-contact",
            "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact", "rel": "self"}],
        }
    ],
    "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts", "rel": "self"}],
}
```

23.3.3 Success searching global address book contacts with only searchName parameter

Request

GET <https://api.hostway.com/accounts/account007/email/test-domain.com/contacts?searchName=contact>

Response

200 Ok

```
{
  "count": 2,
  "list": [
    {
      "city": "",
      "businessPhone": "",
      "displayName": "Display Name",
      "mobilePhone": "",
      "firstName": "First",
      "title": "",
      "roomNumber": "",
      "lastName": "Last",
      "company": "",
      "pager": "",
      "state": "",
      "department": "",
      "streetAddress": "",
      "isdnNumber": "",
      "postalCode": "",
      "country": "",
      "telexNumber": "",
      "businessFax": "",
      "email": "new@test.com",
      "homePhone": "",
      "name": "search-contact",
      "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/search-contact", "rel": "self"}],
    },
    {
      "city": "",
      "businessPhone": "",
      "displayName": "Display Name",
      "mobilePhone": "123456789",
      "firstName": "First",
      "title": "",
      "roomNumber": "",
      "lastName": "Last",
      "company": "",
      "pager": "",
      "state": "",
      "department": "",
      "streetAddress": "",
      "isdnNumber": "",
      "postalCode": "",
      "country": "",
      "telexNumber": "",
      "businessFax": "",
      "email": "new@test.com",
      "homePhone": "",
      "name": "test-contact",
      "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts/test-contact", "rel": "self"}],
    }
  ],
  "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts", "rel": "self"}],
}
```

23.3.4 Success filtering global address book contacts with non-existent filterName parameter

Request

GET <https://api.hostway.com/accounts/account007/email/test-domain.com/contacts?filterName=notexisting>

Response

200 Ok

```
{
  "count": 0,
  "list": [],
  "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts", "rel": "self"}],
}
```

23.3.5 Success searching global address book contacts with non-existent searchName parameter

Request

GET <https://api.hostway.com/accounts/account007/email/test-domain.com/contacts?searchName=notexisting>

Response

200 Ok

```
{
  "count": 0,
  "list": [],
  "links": [{"href": "https://api.hostway.com/accounts/account007/email/test-domain.com/contacts", "rel": "self"}],
}
```

23.4 See also

- [Global Address Book Public API](#)

24 Accounts-account-email-domain-contacts:POST

25 POST /accounts/{account}/email/{domain}/contacts

Creates global address book contact for domain

25.1 Contents

- 1 POST /accounts/{account}/email/{domain}/contacts
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure creating global address book contact because of missing data
 - ◊ 1.3.2 Failure creating global address book contact because of erroneous data
 - ◊ 1.3.3 Success creating global address book contact
 - ◊ 1.3.4 Failure creating contact because contact with the same name already exists
 - ◆ 1.4 See also

25.2 Request

POST /accounts/{account}/email/{domain}/contacts

25.2.1 URI Parameters

account - string
domain - string

25.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

25.2.3 Request Body

```
{  
    "name": "{name}",  
    "email": "{email}",  
    "firstName": "{firstName}",  
    "lastName": "{lastName}",  
    "displayName": "{displayName}"  
    "title": "{title}",  
    "homePhone": "{homePhone}",  
    "mobilePhone": "{mobilePhone}",  
    "businessPhone": "{businessPhone}",  
    "businessFax": "{businessFax}",  
    "isdnNumber": "{isdnNumber}",  
    "pager": "{pager}",  
    "telexNumber": "{telexNumber}",  
    "company": "{company}",  
    "department": "{department}",  
    "roomNumber": "{roomNumber}",  
    "streetAddress": "{streetAddress}",  
    "postalCode": "{postalCode}",  
    "city": "{city}",  
    "state": "{state}",  
    "country": "{country}"  
}
```

25.2.3.1 Parameters

name - string
The name of global address book contact. Required.

email - string
The email of global address book contact. Required.

firstName - string
The first name of global address book contact.

lastName - string
The last name of global address book contact.

displayName - string
The display name of global address book contact. Required.

title - string
The title of global address book contact person.

homePhone - *string*
The home phone of global address book contact.

mobilePhone - *string*
The home phone of global address book contact.

businessPhone - *string*
The business phone of global address book contact.

businessFax - *string*
The business fax of global address book contact.

isdnNumber - *string*
The isdn number of global address book contact.

pager - *string*
The pager of global address book contact.

telexNumber - *string*
The telex number of global address book contact.

company - *string*
The company name of global address book contact.

department - *string*
The department name of global address book contact.

roomNumber - *string*
The room number of global address book contact.

streetAddress - *string*
The street address of global address book contact.

postalCode - *string*
The postal code of global address book contact.

city - *string*
The city name of global address book contact.

state - *string*
The state name of global address book contact.

country - *string*
The country name of global address book contact.

25.3 Response

25.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the parameters don't meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

409 Conflict
The global address book contact already exists.

25.4 Examples

25.4.1 Failure creating global address book contact because of missing data

Request

```
POST https://api.hostway.com/accounts/account007/email/test-domain.com/contacts
{}
```

Response

400 Bad Request

```
{
  "displayName": "Required",
  "name": "Required",
  "email": "Required"
}
```

25.4.2 Failure creating global address book contact because of erroneous data

Request

```
POST https://api.hostway.com/accounts/account007/email/test-domain.com/contacts
{
  "name": "test-contact",
```

```
"email": "test",
"displayName": "Display Name"
}
```

Response

400 Bad Request

```
{
  "email": "Invalid email address"
}
```

25.4.3 Success creating global address book contact

Request

POST https://api.hostway.com/accounts/account007/email/test-domain.com/contacts

```
{
  "name": "test-contact",
  "email": "test@test.com",
  "firstName": "First",
  "lastName": "Last",
  "displayName": "Display Name"
}
```

Response

204 No Content

25.4.4 Failure creating contact because contact with the same name already exists

Request

POST https://api.hostway.com/accounts/account007/email/test-domain.com/contacts

```
{
  "name": "test-contact",
  "email": "test@test.com",
  "firstName": "First",
  "lastName": "Last",
  "displayName": "Display Name"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "guid": "af4f4c85-4c8f-4c63-95d1-f3fb8cb8c479",
    "code": 409,
    "message": "Data conflict",
    "details": ""
  }
}
```

25.5 See also

- [Global Address Book Public API](#)

26 Accounts-account-email-domain-infostore:GET

27 GET /accounts/{account}/email/{domain}/infostore

Gets InfoStore usage.

27.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/infostore
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting account type

27.2 Request

GET /accounts/{account}/email/{domain}/infostore

27.2.1 URI Parameters

account - *string*
domain - *string*

27.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

27.3 Response

27.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

27.3.2 Response Body

```
{  
    "infoStore": {  
        "usage": 0,  
        "quota": 20  
    },  
    "links": [  
        {  
            "location": "{APIBaseURL}/accounts/{account}/email/{domain}/infostore/",  
            "rel": "self"  
        }  
    ]  
}
```

27.3.2.1 Parameters

usage - *int*
InfoStore usage in MB.

quota - *int*
InfoStore quota in MB.

27.4 Examples

27.4.1 Success getting account type

Request

GET /accounts/test/email/test.com/infostore

Response

200 OK

```
{"infoStore": {"usage": 0, "quota": 20}, "links": [{"href": "{APIBaseURL}/accounts/test/email/test.com/infostore/", "rel": "self"}]}
```

Please enable JavaScript to view the [comments powered by Disqus](#).

28 Accounts-account-email-domain-infostore:PUT

= PUT /accounts/{account}/email/{domain}/infostore Change InfoStore quota.

28.1 Contents

- 1 Request
 - ◆ 1.1 URI Parameters
 - ◆ 1.2 Request Headers
 - ◆ 1.3 Request Body
 - ◊ 1.3.1 Parameters
- 2 Response
 - ◆ 2.1 Status Code
- 3 Examples
 - ◆ 3.1 Failure setting new InfoStore quota with missing required parameter
 - ◆ 3.2 Failure changing the storage with invalid quota value
 - ◆ 3.3 Failure when trying to change the quota to a value that is less than the current usage
 - ◆ 3.4 Success setting new InfoStore quota
- 4 See also

28.2 Request

PUT /accounts/{account}/email/{domain}/infostore

28.2.1 URI Parameters

account - *string*
domain - *string*

28.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

28.2.3 Request Body

```
{  
    "quota": {newQuotaSize}  
}
```

28.2.3.1 Parameters

quota- *Integer*
The new quota size.

28.3 Response

28.3.1 Status Code

200 Ok
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

28.4 Examples

28.4.1 Failure setting new InfoStore quota with missing required parameter

Request

```
PUT /accounts/{account}/email/test.com/infostore  
{  
    "foo": "bar"  
}
```

Response

400 Bad Request

```
{"badRequest": {"message": "POST data error", "code": 400, "details": {"quota": "Required"}}}
```

28.4.2 Failure changing the storage with invalid quota value

Request

```
PUT /accounts/{account}/email/test.com/infostore
{
    "quota": -1
}
```

Response

```
400 Bad Request
{"badRequest": {"message": "POST data error", "code": 400, "details": {"quota": "-1 is less than minimum value 0"}}}
```

28.4.3 Failure when trying to change the quota to a value that is less than the current usage

Request

```
PUT /accounts/{account}/email/test.com/infostore
{
    "quota": 100
}
```

Response

```
400 Bad Request
{"badRequest": {"message": "POST data error", "code": 400, "details": {"message": "Used storage exceeds the quota value"}}}
```

28.4.4 Success setting setting new InfoStore quota

Request

```
PUT /accounts/{account}/email/test.com/infostore
{"quota": 50}
```

Response

```
204 No Content
```

28.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

29 Accounts-account-email-domain-statistics-mailboxTypeCount:GET

30 GET /accounts/{account}/email/{domain}/statistics/mailboxTypeCount

Retrieves per domain statistics about webmail usage

30.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/statistics/mailboxTypeCount
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◆ 1.4 See also

30.2 Request

GET /accounts/{account}/email/{domain}/statistics/mailboxTypeCount

30.2.1 Request Parameters

account - *string*
The user account owning the domain and the mailboxes
domain - *string*
The specific domain for which the call will retrieve the list

30.3 Response

30.3.1 Status Code

200 OK
Success
401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.
404 Not Found
The domain name or account does not exist.

30.3.2 Response Body

```
{  
    "numStandard": {numStandard},  
    "numActiveSync": {numActiveSync},  
    "numPremium": {numPremium},  
    "numExchange2013Standard": {numExchange2013Standard},  
    "numExchange2013Premium": {numExchange2013Premium}  
    "links": [  
        {  
            "href": "{href}",  
            "rel": "{rel}"  
        }  
    ]  
}
```

30.3.2.1 Parameters

numStandard - *integer*
Number of mailboxes for the domain with standard webmail access
numActiveSync - *integer*
Number of mailboxes for the domain with activesync webmail access
numPremium - *integer*
Number of mailboxes for the domain with premium webmail access
numExchange2013Standard - *integer*
Number of mailboxes for the domain with standard exchange access
numExchange2013Premium - *integer*
Number of mailboxes for the domain with premium exchange access
href - *string*
Link to other resources relevant to the mailboxes lists
rel - *string*
Type of relation to the resource for the provided link

30.4 Examples

30.4.1 Success scenario

Request

GET accounts/test-account123/email/test.com/statistics/mailboxTypeCount

Response

```
{  
    "numStandard": 1,  
    "numActiveSync": 0,  
    "numPremium": 0,  
    "numExchange2013Standard": 5,  
    "numExchange2013Premium": 2  
    "links": [  
        {  
            "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/statistics/mailboxTypeCount/",  
            "rel": "self"  
        }  
    ]  
}
```

30.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#).

31 Accounts-account-email-domain-usernames-mailboxName-autoresponder:GET

32 GET accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder

Gets the autoresponder info.

32.1 Contents

- 1 GET
accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting the autoresponder info

32.2 Request

GET accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder

32.2.1 URI Parameters

account - string
domain - string
mailbox - string

32.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

32.3 Response

32.3.1 Status Code

200 Ok
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

32.3.2 Response Body

```
{  
    "autoresponder": {  
        "body": "{body}",  
        "active": {active},  
        "subject": "{subject}"  
    },  
    "links": [  
        {  
            "location": "{APIBaseURL}/accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder/",  
            "rel": "self"  
        }  
    ]  
}
```

32.3.2.1 Parameters

body - string
The body of auto-responder.

active - boolean
The status of auto-responder.

subject- string
The subject of auto-responder.

32.4 Examples

32.4.1 Success getting the autoresponder info

Request

GET accounts/test-account123/email/test.com/usernames/test/autoresponder

Response

200 OK

```
{  
    "body": "AutoRespond",  
    "active": true,  
    "links": [  
        {  
            "href": "http://coreapi01.ote.chicago.hostway:8095/accounts/test-account123/email/test.com/usernames/test/autoresponder",  
            "rel": "self"  
        }  
    ],  
    "subject": "Subject"  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

33 Accounts-account-email-domain-usernames-mailboxName-autoresponder:PUT

34 PUT accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder

Activates/deactivates the autoresponder for specified mailbox, domain and account.

34.1 Contents

- 1 PUT
accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure setting the autoresponder with missing required parameter
 - ◊ 1.3.2 Success setting the auto-responder
 - ◊ 1.3.3 Success deactivating the auto-responder

34.2 Request

PUT accounts/{account}/email/{domain}/usernames/{mailbox}/autoresponder

34.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

34.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

34.2.3 Request Body

```
{  
    "subject": "{subject}",  
    "body": "{body}",  
    "active": {active}  
}
```

34.2.3.1 Parameters

subject - *string*
The subject of auto-responder.

body - *string*
The body of auto-responder. Required.

active - *boolean*
Sets the status of auto-responder. Required.

34.3 Response

34.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

34.4 Examples

34.4.1 Failure setting the autoresponder with missing required parameter

Request

PUT accounts/test-account123/email/test.com/usernames/test/autoresponder

```
{"subject": "Subject", "active": true}
```

Response

400 Bad Request

```
{"body": "Required"}
```

34.4.2 Success setting the auto-responder

Request

PUT accounts/test-account123/email/test.com/usernames/test/autoresponder

```
{"subject": "Subject", "body": "AutoRespond", "active": true}
```

Response

204 No Content

34.4.3 Success deactivating the auto-responder

Request

PUT accounts/test-account123/email/test.com/usernames/test/autoresponder

```
{"body": "AutoRespond", "active": false}
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

5 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist-address:DELETE

36 DELETE /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}

Remove black/white listed address

36.1 Contents

- 1 DELETE
/accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Delete address from black/white list

36.2 Request

```
DELETE /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}
```

36.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*
address - *string*

36.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

36.3 Response

36.3.1 Status Code

204 No Content
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain, mailbox or address does not exist.

36.4 Examples

36.4.1 Delete address from black/white list

Request

```
DELETE /accounts/account-number/email/test.com/usernames/test/blackwhitelist/mb1-white20150114-0113@somedomain.com
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

37 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist-address:GET

38 GET /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}

Get black/white listed address details

38.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Get address details

38.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist/{address}

38.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*
address - *string*

38.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

38.3 Response

38.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or the mailbox does not exist.

38.3.2 Response Body

```
{  
    "type": "{type}",  
    "address": "{address}",  
    "links": {links}  
}
```

38.3.2.1 Parameters

type - *string*
Type of address included in black/white list. Possible values are "W" or "B". "W" means the mailbox is included in "whitelist", "B" - included in "blacklist".

address - *string*
The address of the black/whitelisted mailbox or domain.

links - *list*
[Hypermedia](#) to the get black/whitelisted address

38.4 Examples

38.4.1 Get address details

Request

GET /accounts/account-number/email/test.com/usernames/test/blackwhitelist/mbl-white20150114-0113@somedomain.com

Response

200 OK

```
{  
  "type": "W",  
  "address": "mb1-white20150114-0113@somedomain.com",  
  "links": [  
    {"  
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist/mb1-white20150114-0113@somedomain.com/",  
      "rel": "self"  
    }]  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

39 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist:GET

40 GET /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist

Retrieves a list of all addresses included in black/white list for a specific mailbox

40.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Get all addresses included in black/white list
 - ◊ 1.3.2 Get filtered list by address
 - ◊ 1.3.3 Get filtered list by type
 - ◊ 1.3.4 Paginated request
 - ◊ 1.3.5 Sorted request

40.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist

40.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

40.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

40.3 Response

40.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or the mailbox does not exist.

40.3.2 Response Body

```
{  
    "totalCount": {totalCount},  
    "list": [  
        {  
            "type": "{type}",  
            "address": "{address}"  
        }  
    ],  
    "links": [  
        {  
            "href": "{href}",  
            "rel": "{rel}"  
        }  
    ]  
}
```

40.3.2.1 Parameters

totalCount - *int*
The total count of addresses included in black/white list

type - *string*
Type of address included in black/white list. Possible values are "W" or "B". "W" means the address is included in "whitelist", "B" - included in "blacklist".

address - *string*
The address of the black/whitelisted mailbox or domain.

links - *list*

Hypermedia to the get black/whitelisted addresses

40.4 Examples

40.4.1 Get all addresses included in black/white list

Request

```
GET /accounts/account-number/email/test.com/usernames/test/blackwhitelist
```

Response

200 OK

```
{
  "totalCount": 4,
  "list": [
    {
      "type": "W",
      "address": "mb1-white@somedomain.com"
    },
    {
      "type": "B",
      "address": "mb2-black@domain.com"
    },
    {
      "type": "B",
      "address": "mb3-black@somedomain.com"
    },
    {
      "type": "B",
      "address": "@sometestdomain.com"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist",
      "rel": "self"
    }
  ]
}
```

40.4.2 Get filtered list by address

Request

```
GET /accounts/account-number/email/test.com/usernames/test/blackwhitelist?filterAddress=*somedomain.com*
```

Response

200 OK

```
{
  "totalCount": 2,
  "list": [
    {
      "type": "W",
      "address": "mb1-white@somedomain.com"
    },
    {
      "type": "B",
      "address": "mb3-black@somedomain.com"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist?filterAddress=*somedomain.com*",
      "rel": "self"
    }
  ]
}
```

40.4.3 Get filtered list by type

Request

```
GET /accounts/account-number/email/test.com/usernames/test/blackwhitelist?filterType=W
```

Response

200 OK

```
{
  "totalCount": 1,
  "list": [
    {
      "type": "W",
      "address": "mb1-white@somedomain.com"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist?filterType=W",
      "rel": "self"
    }
  ]
}
```

}

40.4.4 Paginated request

Request

```
GET /accounts/account-number/email/test.com/usernames/test/blackwhitelist?pageSize=2&page=1
```

Response

200 OK

```
{
  "totalCount": 2,
  "list": [
    {
      "type": "W",
      "address": "mb1-white@somedomain.com"
    },
    {
      "type": "B",
      "address": "mb2-white@domain.com"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist?pageSize=2&page=2",
      "rel": "next"
    },
    {
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist?pageSize=2&page=2",
      "rel": "last"
    }
  ]
}
```

40.4.5 Sorted request

Request

```
GET /accounts/account-number/email/test.com/usernames/test/blackwhitelist?sortField=address&sortOrder=desc
```

Response

200 OK

```
{
  "totalCount": 4,
  "list": [
    {
      "type": "B",
      "address": "mb3-black@somedomain.com"
    },
    {
      "type": "B",
      "address": "mb2-black@domain.com"
    },
    {
      "type": "W",
      "address": "mb1-white@somedomain.com"
    },
    {
      "type": "B",
      "address": "@sometestdomain.com"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/account-number/email/test.com/usernames/test/blackwhitelist?sortField=address&sortOrder=desc",
      "rel": "self"
    }
  ]
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

41 Accounts-account-email-domain-usernames-mailboxName-blackwhitelist:PUT

42 PUT /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist

Adding/updating addresses to black/white list for a specific mailbox

42.1 Contents

- 1 PUT
/accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure adding address with missing required parameter
 - ◊ 1.3.2 Failure adding address with not valid address and type
 - ◊ 1.3.3 Success adding mailbox addresses to blackwhitelist
 - ◊ 1.3.4 Success adding domain addresses to blackwhitelist

42.2 Request

PUT /accounts/{account}/email/{domain}/usernames/{mailbox}/blackwhitelist

42.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

42.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

42.2.3 Request Body

```
{  
  "list": [  
    {  
      "address": "{address}",  
      "type": "{type}"  
    }  
  ]  
}
```

42.2.3.1 Parameters

address - *string*
Must be a valid email or domain address. Required.

type - *string*
One of W, B. Required.

42.3 Response

42.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the address does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or the mailbox does not exist.

42.4 Examples

42.4.1 Failure adding address with missing required parameter

Request

```
PUT /accounts/account-number/email/test.com/usernames/test/blackwhitelist
{"list": [{"address": "mb1-white@somedomain.com"}]}
```

Response

400 Bad Request

```
{
  "badRequest": {
    "message": "POST data error",
    "code": 400,
    "details": {
      "list.0.type": "Required"
    }
  }
}
```

42.4.2 Failure adding address with not valid address and type

Request

```
PUT /accounts/account-number/email/test.com/usernames/test/blackwhitelist
{"list": [{"address": "somedomain.com", "type": "A"}]}
```

Response

400 Bad Request

```
{
  "badRequest": {
    "message": "POST data error",
    "code": 400,
    "details": {
      "list.0.type": "\"A\" is not one of B, W",
      "list.0.address": "Invalid address format: somedomain.com"
    }
  }
}
```

42.4.3 Success adding mailbox addresses to blackwhitelist

Request

```
PUT /accounts/account-number/email/test.com/usernames/test/blackwhitelist
{
  "list": [
    {
      "address": "mb1-white@somedomain.com",
      "type": "W"
    },
    {
      "address": "mb2-white@somedomain.com",
      "type": "W"
    }
  ]
}
```

Response

204 No Content

42.4.4 Success adding domain addresses to blackwhitelist

Request

```
PUT /accounts/account-number/email/test.com/usernames/test/blackwhitelist
{
  "list": [
    {
      "type": "W",
      "address": "@domainaddr1.com"
    },
    {
      "type": "B",
      "address": "@someotherdomain.com"
    }
  ]
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

43 Accounts-account-email-domain-usernames-mailboxName-cleanmailplus:GET

44 GET accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus

Gets mailbox's CleanMailPlus info.

44.1 Contents

- 1 GET
 - accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure getting CleanMailPlus info for a non-existent domain
 - ◊ 1.3.2 Success getting CleanMailPlus info

44.2 Request

GET accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus

44.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

44.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

44.3 Response

44.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or mailbox does not exist.

44.3.2 Response Body

```
[  
  {  
    "selected": "{selected_option_value}",  
    "fieldName": "{field_name}",  
    "description": "{description}",  
    "options": [  
      {  
        "name": "{option_name}",  
        "value": "{option_value}"  
      }  
    ]  
  }  
]
```

44.3.2.1 Parameters

selected_option_value - *string*
Currently selected option value.
field_name - *string*
Field name.
description - *string*
Descriptive option info.
options - *list*
List of options.
options.name - *string*
Option's name.
options.value - *string*
Option's value.

44.4 Examples

44.4.1 Failure getting CleanMailPlus info for a non-existent domain

Request

```
GET accounts/test-account123/email/non-existent-domain.com/usernames/test/cleanmailplus
```

Response

```
404 Not Found
```

44.4.2 Success getting CleanMailPlus info

Request

```
GET accounts/test-account123/email/test.com/usernames/test/cleanmailplus
```

Response

```
200 OK
```

```
[{"field": {"selected": "6", "fieldName": "SPAM_LEVEL", "description": "SPAM Tag Level", "options": [{"name": "Least Aggressive", "value": "6"}, {"name": "Less Aggressive", "value": "5"}, {"name": "Normal", "value": "4"}, {"name": "More Aggressive", "value": "3"}, {"name": "Most Aggressive", "value": "2"}, {"name": "Ultra Aggressive", "value": "1"}]}, {"field": {"selected": "2", "fieldName": "SPAM_ACTION", "description": "SPAM Detected Action", "options": [{"name": "None", "value": "0"}, {"name": "Tag Subject", "value": "2"}, {"name": "Move to SPAM Folder", "value": "1"}, {"name": "Delete", "value": "3"}]}, {"field": {"selected": "1", "fieldName": "ATTACHMENT_CONTROL", "description": "Attachment Control", "options": [{"name": "Enable", "value": "1"}, {"name": "Disable", "value": "0"}]}, {"field": {"selected": "1", "fieldName": "VIRUS_ACTION", "description": "Virus Detected Action", "options": [{"name": "No Virus Filter", "value": "0"}]}}]
```

```

        },
        {
            "name": "Delete Automatically",
            "value": "1"
        }
    ],
},
{
    "selected": "0",
    "fieldName": "SPAM_LEARNING",
    "description": "SPAM Learning Status",
    "options": []
},
{
    "selected": "20",
    "fieldName": "SPAM_DISCARD_LEVEL",
    "description": "SPAM Discard Level",
    "options": []
},
{
    "selected": "0",
    "fieldName": "PHISHING_CHECKS",
    "description": "Phishing Checks",
    "options": [
        {
            "name": "Enabled",
            "value": "1"
        },
        {
            "name": "Disabled",
            "value": "0"
        }
    ]
},
{
    "selected": "0",
    "fieldName": "CLEANMAIL_PLUS",
    "description": "CleanMail Plus Enable",
    "options": [
        {
            "name": "Enable",
            "value": "1"
        },
        {
            "name": "Disable",
            "value": "0"
        }
    ]
},
{
    "selected": "1",
    "fieldName": "SPAM_CHECK",
    "description": "SPAM Check Option",
    "options": [
        {
            "name": "Enable",
            "value": "1"
        },
        {
            "name": "Disable",
            "value": "0"
        }
    ]
}
]

```

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

45 Accounts-account-email-domain-usernames-mailboxName-cleanmailplus:PUT

46 PUT accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus

Updates mailbox's CleanMailPlus info.

46.1 Contents

- 1 PUT accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure updating the CleanMailPlus filter attributes for a non-existent domain
 - ◊ 1.3.2 Failure updating the CleanMailPlus filter attributes by providing bad request body
 - ◊ 1.3.3 Failure updating the cleanmailplus filter attribute by providing a non-existent attribute name
 - ◊ 1.3.4 Failure updating the cleanmailplus filter attribute by providing a non-valid attribute value
 - ◊ 1.3.5 Success updating the CleanMailPlus filter attributes

46.2 Request

PUT accounts/{account}/email/{domain}/usernames/{mailbox}/cleanmailplus

46.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

46.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

46.2.3 Request Body

```
{  
  "attributes": [  
    {  
      "attributeName": "{attribute_name}",  
      "attributeValue": "{attribute_value}"  
    }  
  ]  
}
```

46.2.3.1 Parameters

attributeName - *string*
Attribute's name.
attributeValue - *string*
New attribute's value.

46.3 Response

46.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or mailbox does not exist.

46.4 Examples

46.4.1 Failure updating the CleanMailPlus filter attributes for a non-existent domain

Request

```

PUT accounts/{account}/email/non-existent-domain.com/usernames/mailbox-cleanmailplus/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "1"
    }
  ]
}

```

Response

```

404 Not Found
{
  "itemNotFound": {
    "message": "Resource not found",
    "code": 404,
    "details": {
      "message": "Domain not found"
    }
  }
}

```

46.4.2 Failure updating the CleanMailPlus filter attributes by providing bad request body

Request

```

PUT accounts/{account}/email/test.com/usernames/mailbox-cleanmailplus/cleanmailplus
{
  "badBody": "badBodyValue"
}

```

Response

```

400 Bad Request
{
  "attributes": "Required"
}

```

46.4.3 Failure updating the cleanmailplus filter attribute by providing a non-existent attribute name

Request

```

PUT accounts/{account}/email/test.com/usernames/mailbox-cleanmailplus/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "NON_EXISTENT_ATTRIBUTE_NAME",
      "attributeValue": "1"
    }
  ]
}

```

Response

```

400 Bad Request
{
  "attributes.0": "NON_EXISTENT_ATTRIBUTE_NAME is not valid filter attribute name"
}

```

46.4.4 Failure updating the cleanmailplus filter attribute by providing a non-valid attribute value

Request

```

PUT accounts/{account}/email/test.com/usernames/mailbox-cleanmailplus/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "val01"
    }
  ]
}

```

Response

```

400 Bad Request
{
  "attributes.0": "val01 is not valid attribute option for SPAM_LEVEL filter attribute"
}

```

46.4.5 Success updating the CleanMailPlus filter attributes

Request

```

PUT accounts/{account}/email/test.com/usernames/test/cleanmailplus
{
  "attributes": [
    {
      "attributeName": "SPAM_LEVEL",
      "attributeValue": "1"
    },
  ]
}

```

```
{  
    "attributeName": "SPAM_ACTION",  
    "attributeValue": "1"  
}  
]  
}
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

47 Accounts-account-email-domain-usernames-mailboxName-exchange-action:POST

48 POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/action

Apply an action on exchange mailbox e.g. **reset password**

48.1 Contents

- 1 POST
`/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/action`
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - ◆ 1.2 Response
 - ◊ 1.2.1 Expected Response Codes
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Request password reset of exchange mailbox
 - ◊ 1.3.2 Request password reset of exchange mailbox with wrong answer
 - ◆ 1.4 See also

48.2 Request

POST `/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/action`

48.2.1 Request Parameters

account - *string*
The user account owning the domain and the exchange mailboxes
domain - *string*
The specific domain for which the call will retrieve the list
maiboxName - *string*
The name of the exchange mailbox.

48.2.2 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

48.2.3 Request Body

```
{  
  "action": "resetPassword",  
  "actionData": {  
    "secretQuestionsAnswers": {"{tk)": "{answer}"},  
    "password": "{password}"  
  }  
}
```

action - *string*
The action that should be performed. Allowed values are:
resetPassword - Reset the password of exchange mailbox.

actionData - *dictionary* (*Required*)
Data to be send with the action.

secretQuestionsAnswers - *dictionary* (*Required*)
Dictionary of key/value pairs, each of which represents **secret question text key/answer** pair.

tk - *string* (*Required*)
The text key for the secret question. There should be no duplicate text keys per exchange mailbox.

answer - *string* (*Required*)
The answer in plain-text - must be at least two characters.

password - *string* (*Required*)
The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.

Password validation rules:

- >Password must not be used more than once
- Minimum length 8
- Maximum length 128
- Should have at least one digit
- Should have at least one capital letter
- Should have at least one lower case letter
- Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)
- Should not start with the phrase 'pass' case-insensitively
- Should not start with 'abc' case-insensitively
- Should not start with 123

Must not contain second-level domain, username or start with the first 3 letters from the username

48.3 Response

48.3.1 Expected Response Codes

204 No Content
Success

400 Bad Request
The supplied action or the supplied data is invalid.

404 Not Found
The resource does not exist.

409 Conflict
Validation of the secret answer failed.

48.4 Examples

48.4.1 Request password reset of exchange mailbox

Request

```
POST /accounts/account123/email/test.com/usernames/mailbox123/exchange/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswers": {"tk1": "answer123"},
    "password": "pWord123$"
}
```

Response

204 No Content

48.4.2 Request password reset of exchange mailbox with wrong answer

Request

```
POST /accounts/account123/email/test.com/usernames/mailbox123/exchange/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswersList": {"tk1": "wrongAnswer"},
    "password": "pWord123$"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "message": "Invalid secret questions and answers provided",
    "code": 409,
  }
}
```

48.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

50 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats

Retrieves exchange message count for INBOX, SENT and SPAM folders

50.1 Contents

- 1 GET
`/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats`
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success
 - ◆ 1.4 See also

50.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats

50.2.1 URI Parameters

account - *string*
domain - *string*
mailboxName - *string*

50.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

50.3 Response

50.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or the mailbox does not exist.
Unable to get message count for virtual mailboxes.

500 Internal Server Error
Missing Domain or Installation records

502 Bad Gateway
Unable to get message count. No IMAP connection
Unable to get message count. IMAP search operation failed.
Unable to get message count. IMAP folder selection failed.

50.3.2 Response Body

```
{  
  "messageCount" : {  
    "inbox" : {  
      "allMessages" : {inbox_all_messages_count},  
      "unreadMessages" : {inbox_unread_messages_count}  
    },  
    "sent" : {  
      "allMessages" : {sent_all_messages_count},  
      "unreadMessages" : {sent_unread_messages_count}  
    },  
    "spam" : {  
      "allMessages" : {spam_all_messages_count},  
      "unreadMessages" : {sent_unread_messages_count}  
    }  
  },  
  "links": [{"href": "https://api.hostway.com/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats/", "rel": "self"}]
```

50.3.2.1 Parameters

inbox_all_messages_count- *integer*
All messages for INBOX folder

inbox_unread_messages_count- *integer*
Unread messages for INBOX folder

```
sent_all_messages_count- integer  
    All messages for SENT folder  
sent_unread_messages_count- integer  
    Unread messages for SENT folder  
spam_all_messages_count- integer  
    All messages for SPAM folder  
spam_unread_messages_count- integer  
    Unread messages for SPAM folder
```

50.4 Examples

50.4.1 Success

Request

```
GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats
```

Response

200 OK

```
{  
    "messageCount" : {  
        "inbox" : {  
            "allMessages" : 3,  
            "unreadMessages" : 3  
        },  
        "sent" : {  
            "allMessages" : 0,  
            "unreadMessages" : 0  
        },  
        "spam" : {  
            "allMessages" : 0,  
            "unreadMessages" : 0  
        }  
    },  
    "links": [{"href": "https://api.hostway.com/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/messagestats/", "rel": "self"}]
```

50.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

51 Accounts-account-email-domain-usernames-mailboxName-exchange:DELETE

52 DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange

Deletes exchange mailbox.

52.1 Contents

- 1 DELETE
/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success deleting exchange

52.2 Request

```
DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange
```

52.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

52.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

52.3 Response

52.3.1 Status Code

204 No Content
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or mailbox do not exist.

409 Conflict
The domain is disabled.

52.4 Examples

52.4.1 Success deleting exchange

Request

```
DELETE /accounts/test-account/email/test.com/usernames/test/exchange
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

53 Accounts-account-email-domain-usernames-mailboxName-exchange:GET

54 GET accounts/{account}/email/{domain}/usernames/{mailbox}/exchange

Gets Exchange mailbox detailed info.

54.1 Contents

- 1 GET
 - accounts/{account}/email/{domain}/usernames/{mailbox}/exchange
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure getting Exchange mailbox info for a non-existent domain
 - ◊ 1.3.2 Success getting Exchange mailbox info

54.2 Request

GET accounts/{account}/email/{domain}/usernames/{mailbox}/exchange

54.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

The exchange mailbox name. String should meet the regexp [a-zA-Z0-9._-]+ ,max 64 characters

54.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]

The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

54.3 Response

54.3.1 Status Code

200 OK

Success

401 Unauthorized

The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found

The domain name or mailbox does not exist.

54.3.2 Response Body

```
{  
    "maxReceiveSize": "{maxReceiveSize}",  
    "maxSendSize": "{maxSendSize}",  
    "primarySmtpAddress": "{primarySmtpAddress}",  
    "quota": "{quota}",  
    "recipientLimits": "{recipientLimits}",  
    "rejectMessagesFromSendersOrMembers": "{rejectMessagesFromSendersOrMembers}",  
    "requireSenderAuthenticationEnabled": false,  
    "totalItemSize": "{totalItemSize}",  
    "activeSyncAllowedDeviceIDs": [""],  
    "activeSyncBlockedDeviceIDs": [""],  
    "activeSyncEnabled": true,  
    "activeSyncMailboxPolicy": "Default",  
    "hasActiveSyncDevicePartnership": false,  
    "imapEnabled": true,  
    "mapiEnabled": true,  
    "owaEnabled": true,  
    "popEnabled": true,  
    "serverName": "{serverName}",  
    "whenChanged": "{whenChanged}",  
    "whenCreated": "{whenCreated}",  
    "city": "{city}",  
    "company": "{company}",  
    "country": "{country}",  
    "department": "{department}",  
    "emailAddress": "{emailAddress}",  
    "fax": "{fax}",  
    "homePhone": "{homePhone}",  
    "manager": "{manager}",  
    "mobilePhone": "{mobilePhone}",  
    "notes": "{notes}",  
    "office": "{office}",  
    "postalCode": "{postalCode}",  
    "recipientType": "{recipientType}",
```

```

"resourceType": "{resourceType}",
"type": "{type}",
"state": "{state}",
"street": "{street}",
"title": "{title}",
"webPage": "{webPage}",
"workPhone": "{workPhone}",
"displayName": "{displayName}",
"firstName": "{firstName}",
"lastName": "{lastName}",
"username": "{username}",
"domain": "{domain}",
"alias": "{alias}",
"acceptMessagesOnlyFromSendersOrMembers": "{acceptMessagesOnlyFromSendersOrMembers}",
"archiveDatabase": "{archiveDatabase}",
"archiveQuota": "{archiveQuota}",
"database": "{database}",
"deliverToMailboxAndForward": false,
"emailAddresses": [
    {
        "address": "{address}",
        "header": "smtp"
    },
    {
        "address": "{address}",
        "header": "SMTP"
    }
],
"forwardingSmtpAddress": "{forwardingSmtpAddress}",
"hiddenFromAddressListsEnabled": {hiddenFromAddressListsEnabled},
"itemCount": "{itemCount}",
"links": [
    {
        "href": "{{APIBaseURL}}/accounts/{account}/email/{domain}/usernames/{mailbox}/exchange/",
        "rel": "self"
    },
    {
        "href": "{{APIBaseURL}}/accounts/{account}/email/{domain}/usernames/{mailbox}/secrets",
        "rel": "related"
    }
]
}
}

```

54.3.2.1 Parameters

maxReceiveSize - string
The MaxReceiveSize parameter specifies the maximum size of messages that this mailbox can receive. You must specify either an integer or unlimited.

maxSendSize - string
The MaxSendSize parameter specifies the maximum size of messages that this mailbox can send. You must specify either an integer or unlimited.

primarySmtpAddress - string
primary SMTP address

quota - string
Quota

recipientLimits - string
The RecipientLimits parameter specifies the maximum number of recipients per message to which this mailbox can send. You must specify either an integer or unlimited.

rejectMessagesFromSendersOrMembers - list
The RejectMessagesFromSendersOrMembers parameter specifies the identity of recipients from whom messages are rejected.

requireSenderAuthenticationEnabled - boolean
The RequireSenderAuthenticationEnabled parameter specifies whether senders must be authenticated. The two possible values for this parameter are true or false.

totalItemSize - string
total mailbox usage

activeSyncAllowedDeviceIDs - list
Active Sync allowed devices.

activeSyncBlockedDeviceIDs - list
blocked active sync devices.

activeSyncEnabled - boolean
allow mailbox access through active sync.

activeSyncMailboxPolicy - string
active sync mailbox policy name

hasActiveSyncDevicePartnership - boolean
return active sync device partnership exists of not

imapEnabled - boolean
allow mailbox access though imap.

mapiEnabled - boolean
allow mailbox access though mapi (Outlook).

owaEnabled - boolean
allow mailbox access though owa (Web mail).

popEnabled - boolean
allow mailbox access though pop3.

serverName - string
server name where user mailbox is located.

whenChanged - string
mailbox changed date.

whenCreated - string
mailbox created date.

city - string
City Name

company - string
Company Name

country - string

Country Name
 department - *string*
 Department Name
 emailAddress - *string*
 Email address, this is not actually SMTP proxy address.
 fax - *string*
 FAX number
 homePhone - *string*
 Home phone number
 manager - *string*
 manager
 mobilePhone - *string*
 Mobile phone number
 notes - *string*
 Notes
 office - *string*
 Office Name
 postalCode - *string*
 Zip code
 recipientType - *string*
 resourceType - *string*
 The resourceType parameter specifies the type of recipients returned. Recipient types are divided into recipient types and subtypes. Each recipient type contains all common properties for all subtypes. For example, the type UserMailbox represents a user account in Active Directory that has an associated mailbox. Because there are several mailbox types, each mailbox type is identified by the recipientTypeDetails parameter. For example, a conference room mailbox has RecipientTypeDetails set to RoomMailbox, whereas a user mailbox has RecipientTypeDetails set to UserMailbox.

This parameter returns the following values

- RoomMailbox
- EquipmentMailbox
- LegacyMailbox
- LinkedMailbox
- UserMailbox
- DiscoveryMailbox
- SharedMailbox

type - *string*
 the Exchange account type.

This parameter returns the following values

- standard
- premium

state - *string*
 State / Province
 street - *string*
 Street name
 title - *string*
 Title
 webPage - *string*
 web URL
 workPhone - *string*
 work phone number
 displayName - *string*
 Display Name
 firstName - *string*
 First name
 lastName - *string*
 Last name
 username - *string*
 Username
 domain - *string*
 Domain Name which mailbox belong to
 alias - *string*
 Alias, actually this is equal to username.
 acceptMessagesOnlyFromSendersOrMembers - *string*
 The AcceptMessagesOnlyFromSendersOrMembers parameter specifies the recipients who can send e-mail messages to this mailbox. You can specify users, contacts, or distribution groups. If you specify a distribution group, messages are accepted from all recipients that are members of that distribution group. You can also specify Exchange as a valid recipient for this parameter. If you configure a distribution group to accept messages only from the Exchange recipient, the distribution group only receives system-generated messages
 archiveDatabase - *string*
 Archive Database name
 archiveQuota - *string*
 Archive Quota
 database - *string*
 Mailbox database name
 deliverToMailboxAndForward - *boolean*
 The DeliverToMailboxAndForward parameter specifies whether messages sent to this mailbox are forwarded to another address. If the DeliverToMailboxAndForward parameter is set to true, messages are delivered to the mailbox and to the forwarding address. If set to false, messages are delivered only to the forwarding address.
 emailAddresses - *list*
 all SMTP proxy address.
 address - *string*
 SMTP proxy address
 header - *string*
 protocol. if HEAD is capital like SMTP, it is primary SMTP address. smtp is secondary address.

forwardingSmtpAddress - *string*

The ForwardingSmtpAddress parameter specifies a forwarding SMTP address.
hiddenFromAddressListsEnabled - boolean
The HiddenFromAddressListsEnabled parameter specifies whether this mailbox is hidden from other address lists. The two possible values for this parameter are true or false.
itemCount - string
Count of mailbox items
links - list
[Hypermedia](#) to the get exchange mailbox details resources

54.4 Examples

54.4.1 Failure getting Exchange mailbox info for a non-existent domain

Request

```
GET accounts/test-account-id/email/non-existent-domain.com/usernames/test-mailbox/exchange
```

Response

```
404 Not Found
```

54.4.2 Success getting Exchange mailbox info

Request

```
GET accounts/test-account-id/email/test.com/usernames/test-mb/exchange
```

Response

```
200 OK
```

```
{
  "maxReceiveSize": "50 MB (52,428,800 bytes)",
  "maxSendSize": "50 MB (52,428,800 bytes)",
  "primarySmtpAddress": "test-mb@test.com",
  "quota": "1000 MB (1,048,576,000 bytes)",
  "recipientLimits": "100",
  "rejectMessagesFromSendersOrMembers": "",
  "requireSenderAuthenticationEnabled": false,
  "totalItemSize": "0",
  "activeSyncAllowedDeviceIDs": [],
  "activeSyncBlockedDeviceIDs": [],
  "activeSyncEnabled": true,
  "activeSyncMailboxPolicy": "Default",
  "hasActiveSyncDevicePartnership": false,
  "imapEnabled": true,
  "mapEnabled": true,
  "owaEnabled": true,
  "popEnabled": true,
  "serverName": "uc4-exmbx01",
  "whenChanged": "10/11/2013 9:43:48 AM",
  "whenCreated": "10/11/2013 9:43:39 AM",
  "city": "My City",
  "company": "My Company",
  "country": "Canada",
  "department": "HR",
  "emailAddress": "test-mb@test.com",
  "fax": "111-111-1111",
  "homePhone": "222-222-2222",
  "manager": "",
  "mobilePhone": "333-333-3333",
  "notes": "Hello Notes",
  "office": "My Office",
  "postalCode": "V6C 3T3",
  "recipientType": "UserMailbox",
  "resourceType": "user",
  "type": "standard",
  "state": "BC",
  "street": "Burrard",
  "title": "Title",
  "webPage": "www.test.com",
  "workPhone": "222-222-2222",
  "displayName": "My DisplayName",
  "firstName": "My FirstName",
  "lastName": "My LastName",
  "username": "test-mb",
  "domain": "test.com",
  "alias": "test-mb-alias",
  "acceptMessagesOnlyFromSendersOrMembers": "",
  "archiveDatabase": "",
  "archiveQuota": "50 GB (53,687,091,200 bytes)",
  "database": "DAG01-DB01",
  "deliverToMailboxAndForward": false,
  "emailAddresses": [
    {
      "address": "test-mb@test.com",
      "header": "SMTP"
    },
    {
      "address": "test-mb@second.test.com",
      "header": "smtp"
    }
  ],
  "forwardingSmtpAddress": "smtp:test@google.com",
  "hiddenFromAddressListsEnabled": false,
  "itemCount": "0",
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account-id/email/test.com/usernames/test-mb/exchange/",
      "rel": "self"
    }
  ]
}
```

```
},
{
  "href": "{{APIBaseURL}}/accounts/test-account-id/email/test.com/usernames/test-mb/secrets",
  "rel": "related"
}
]
```

55 Accounts-account-email-domain-usernames-mailboxName-exchange:PUT

56 PUT accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange

Creates or updates an exchange mailbox for specified account and domain.

56.1 Request

PUT accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange

56.1.1 URI Parameters

account - string

domain - string

mailboxName - string

The exchange mailbox. String should meet the regexp [a-zA-Z0-9._-]+ ,max 64 characters

56.1.2 Request Headers

Authorization - *HTTP Authorization header* [1]

The **Authentication** credentials of the client application.

Content-Type

Required. Set this header to application/json; charset=UTF-8

56.1.3 Request Body

```
{  
    "password": "{password}",  
    "resetPassword": {resetPassword},  
    "displayName": "{displayName}",  
    "type": {type},  
    "resourceType": "{resourceType}",  
    "firstName": {firstName},  
    "lastName": {lastName},  
    "city": {city},  
    "company": {company},  
    "country": {country},  
    "department": {department},  
    "fax": {fax},  
    "homePhone": {homePhone},  
    "mobilePhone": {mobilePhone},  
    "postalCode": {postalCode},  
    "state": {state},  
    "street": {street},  
    "title": {title},  
}
```

56.1.3.1 Parameters

password - string (Required when creating mailbox)

The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.

Password validation rules:

 Password must not be used more than once

 Minimum length 8

 Maximum length 128

 Should start with a letter

 Should have at least one digit

 Should have at least one capital letter

 Should have at least one lower case letter

 Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)

 Should not start with the phrase 'pass' case-insensitively

 Should not start with 'abc' case-insensitively

 Should not start with 123

 Must not contain second-level domain, username or start with the first 3 letters from the username

resetPassword - boolean (Optional)

The resetPassword flag is set for "exchange" mailbox, forcing the user to change his password on next logon.

displayName - string (Required when creating mailbox)

Display Name(256 characters), The displayName parameter specifies the user's display name.

type - string - one of "standard" or "premium"

Exchange account type. Valid values are standard, premium. If not provided - standard is default.

resourceType - string - one of "user", "equipment" or "room"

Exchange resource type. If not provided - user is default. Passing this parameter when updating mailbox will result in 400 Bad Request error

firstName

First name(64 characters), The firstName parameter specifies the user's given name.

lastName

Last name(64 characters), The lastName parameter specifies the user's surname

city City Name(128 characters), The city parameter specifies the user's city.
company Company Name(64 characters), The company parameter specifies the user's company.
country Country Name(128 characters), The country parameter specifies the user's country or region.
department Department Name(64 characters), The department parameter specifies the user's department.
fax FAX number(64 characters), The fax parameter specifies the user's fax number.
homePhone Home phone number(64 characters), The homePhone parameter specifies the user's home telephone number.
mobilePhone Mobile phone number(64 characters), The mobilePhone parameter specifies the user's mobile phone number.
postalCode Zip code(40 characters), The postalCode parameter specifies the user's zip code or postal code.
state State / Province(128 characters), The state parameter specifies the user's state or province.
street Street name(1024 characters), The street parameter specifies the user's physical address.
title Title(128 characters), The Title parameter specifies the user's title.

56.2 Response

56.2.1 Status Code

201 Created
 Success
 204 No Content
 Success
 400 Bad Request
 The format of the request body is invalid or the username does not meet the requirements.
 401 Unauthorized
 The supplied credentials are invalid or do not provide permissions for this operation.
 404 Not Found
 The domain name does not exist.
 409 Conflict
 The mailbox already exists(on create) or domain is disabled(on update).

56.3 Examples

56.3.1 Trying to create exchange mailbox without a password

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"displayName": "John"}
```

Response

```
400 Bad Request
{"password": "Required"}
```

56.3.2 Trying to create exchange mailbox without a displayName

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"password": "pWord123$"}
```

Response

```
400 Bad Request
{"displayName": "Required"}
```

56.3.3 Trying to create exchange mailbox with a not valid password

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"password": "abc1234", "displayName": "John"}
```

Response

```
400 Bad Request
{"password": "Password should not start with 'abc' case-insensitively"}
```

56.3.4 Create exchange mailbox

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"password": "pWord123$", "displayName": "John"}
```

Response

```
201 Created
```

56.3.5 Create premium exchange mailbox

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"password": "pWord123$", "displayName": "John", "type": "premium"}
```

Response

```
201 Created
```

56.3.6 Update exchange mailbox password

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"password": "!q2w3e4R"}
```

Response

```
204 No Content
```

56.3.7 Create exchange room

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith.room/exchange
{"password": "pWord123$", "displayName": "John", "resourceType": "room"}
```

Response

```
201 Created
```

56.3.8 Trying to update exchange resource type

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith.rooh/exchange
{"resourceType": "equipment"}
```

Response

```
400 Bad Request
resourceType cannot be updated
```

56.3.9 Update exchange mailbox, forcing the user to reset his password on next logon

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/exchange
{"resetPassword": true}
```

Response

204 No Content

Please enable JavaScript to view the [comments powered by Disqus.](#) blog comments powered by Disqus

58 DELETE accounts/{account}/email/{domain}/usernames/{mailbox}/forwards/{fwd-mailbox}

Deletes forwarding for specified mailbox, domain and account.

58.1 Contents

- 1 DELETE
accounts/{account}/email/{domain}/usernames/{mailbox}/forwards/{fwd-mailbox}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success deleting mailbox forwarding
 - ◆ 1.4 See also

58.2 Request

```
DELETE accounts/{account}/email/{domain}/usernames/{mailbox}/forwards/{fwd-mailbox}
```

58.2.1 URI Parameters

account - string
domain - string
mailbox - string
fwd-mailbox - string

Target mailbox forwarding to be deleted.

58.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

58.3 Response

58.3.1 Status Code

204 No Content
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

58.4 Examples

58.4.1 Success deleting mailbox forwarding

Request

```
DELETE accounts/{account}/email/test.com/usernames/test/forwards/test-fwd-mailbox
```

Response

204 No Content

58.5 See also

- Email API

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

59 Accounts-account-email-domain-usernames-mailboxName-forwards:GET

60 GET accounts/{account}/email/{domain}/usernames/{mailbox}/forwards

Gets forwarding for specified mailbox, domain and account.

60.1 Contents

- 1 GET
 - accounts/{account}/email/{domain}/usernames/{mailbox}/forwards
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting forwarding info
 - ◆ 1.4 See also

60.2 Request

GET accounts/{account}/email/{domain}/usernames/{mailbox}/forwards

60.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

60.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

60.3 Response

60.3.1 Status Code

200 Ok
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

60.3.2 Response Body

```
{  
  "targets": [  
    {  
      "target": "{target_mailbox}"  
    },  
    {  
      "target": "{target_mailbox}"  
    }  
  ],  
  "links": [  
    {  
      "location": "{APIBaseURL}/accounts/{account}/email/{domain}/usernames/{mailbox}/forwards/",  
      "rel": "self"  
    }  
  ]  
}
```

60.3.2.1 Parameters

target_mailbox - *string*
The returned forward target mailbox.

60.4 Examples

60.4.1 Success getting forwarding info

Request

GET accounts/{account}/email/test.com/usernames/test/forwards

Response

200 OK

```
<nowiki>
{
  "targets": [
    {
      "target": "mb1@test.com"
    },
    {
      "target": "test@test-forward.com"
    }
  ],
  "links": [
    {
      "location": "{APIBaseURL}/accounts/{account}/email/{domain}/usernames/{mailbox}/forwards/",
      "rel": "self"
    }
  ]
}
</nowiki>
```

60.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

61 Accounts-account-email-domain-usernames-mailboxName-forwards:POST

62 POST accounts/{account}/email/{domain}/usernames/{mailbox}/forwards

Sets forwarding for specified mailbox, domain and account.

62.1 Contents

- 1 POST accounts/{account}/email/{domain}/usernames/{mailbox}/forwards
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure when creating a forwarding with missing required parameter
 - ◊ 1.3.2 Failure when creating a forwarding with an empty list of targets
 - ◊ 1.3.3 Success when creating a forwarding
 - ◊ 1.3.4 Success setting multiple forwarding targets (distribution list)
 - ◊ 1.3.5 Creating local forwarding or distribution list that contains mailboxes in the source domain
 - ◊ 1.3.6 Failure when creating forwarding to the same mailbox (avoids forwarding loops)
 - ◊ 1.3.7 Failure when creating forwarding to same mailbox on a domain alias
 - ◊ 1.3.8 Failure when creating local forwarding to non-existing mailbox
 - ◊ 1.3.9 Failure when creating a distribution list with a missing local target mailbox
 - ◊ 1.3.10 Success creating forwarding to an external mailbox
 - ◊ 1.3.11 Success creating forwarding to multiple external mailboxes (distribution list)
 - ◆ 1.4 See also

62.2 Request

POST accounts/{account}/email/{domain}/usernames/{mailbox}/forwards

62.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

62.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

62.2.3 Request Body

```
{  
    "targets": [  
        {"target": "{target-email}"},  
        {"target": "{target-email1}"}  
    ]  
}
```

62.2.3.1 Parameters

targets - *list*
List of target objects.

target - *string*
The target mailbox to forward to.

62.3 Response

62.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized

The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found

The domain name does not exist.

409 Conflict

Create of the forwarder would produce an impossible to delivery loops namely:

1. the usernames on the forward source and target are the same, **and**:
1. the domains on the source is an alias of the target's domain name, **or**
2. the domains on the target is an alias of the source's domain name

62.4 Examples

62.4.1 Failure when creating a forwarding with missing required parameter

Request

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{empty request body}
```

Response

```
400 Bad Request
{"targets": "Required"}
```

62.4.2 Failure when creating a forwarding with an empty list of targets

Request

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{"targets": []}
```

Response

```
400 Bad Request
{"targets": "Shorter than minimum length 1"}
```

62.4.3 Success when creating a forwarding

Request

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "test-fwd@example.com"}
  ]
}
```

Response

```
204 No Content
```

62.4.4 Success setting multiple forwarding targets (distribution list)

Request

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "test-fwd@test.com"},
    {"target": "test-fwd1@example.com"}
  ]
}
```

Response

```
204 No Content
```

62.4.5 Creating local forwarding or distribution list that contains mailboxes in the source domain

Local forwarding is created when some or all of the target mailboxes are in the same domain as the source mailbox. In case there are such mailboxes certain validation rules are applied that verify the target mailbox existence and that the target mailbox is different than the source.

It is important to note that **none** of the targets will be created if the validation fails for **any** of the mailboxes in the list.

That is: a single non-existent local target mailbox in the list will prevent all of the targets from being added regardless of the invalid target position in the list.

62.4.6 Failure when creating forwarding to the same mailbox (avoids forwarding loops)

Request

```
POST accounts/source_account/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "test@test.com"}
  ]
}
```

Response

```
400 Bad Request
{"test@test.com": "Is the same as current mailbox"}
```

62.4.7 Failure when creating forwarding to same mailbox on a domain alias

Request

```
POST accounts/source_account/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "test@test-com-alias.com"}
  ]
}
```

Response

```
409 Conflict
{
  "conflict": {
    "message": "Circular target test@test-com-alias.com",
    "code": 409,
    "details": ""
  }
}
```

62.4.8 Failure when creating local forwarding to non-existing mailbox

Request

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "not-existing-mailbox@test.com"}
  ]
}
```

Response

```
400 Bad Request
{"not-existing-mailbox@test.com": "Target not found"}
```

62.4.9 Failure when creating a distribution list with a missing local target mailbox

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "existing-mailbox@test.com"},
    {"target": "not-existing-mailbox@test.com"}
  ]
}
```

Response

```
400 Bad Request
{"not-existing-mailbox@test.com": "Target not found"}
```

62.4.10 Success creating forwarding to an external mailbox

Notice the **different_domain.com** in the request is external (different than **test.com**).
Request

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "test-fwd@different-domain.com"}
  ]
}
```

Response

```
204 No Content
```

62.4.11 Success creating forwarding to multiple external mailboxes (distribution list)

Request

Notice that **different_domain_1.com** and **different_domain_2.com** are both different than **test.com**.

```
POST accounts/{account}/email/test.com/usernames/test/forwards
{
  "targets": [
    {"target": "test-fwd@different-domain_1.com"},
    {"target": "test-fwd1@different-domain_2.com"}
  ]
}
```

Response

204 No Content

62.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

63 Accounts-account-email-domain-usernames-mailboxName-mailbox-action:POST

64 POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/action

Apply an action on a mailbox e.g. **reset password**

64.1 Contents

- 1 POST
`/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/action`
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - ◆ 1.2 Response
 - ◊ 1.2.1 Expected Response Codes
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Request password reset of a mailbox
 - ◊ 1.3.2 Request password reset of a mailbox with wrong answer
 - ◆ 1.4 See also

64.2 Request

`POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/action`

64.2.1 Request Parameters

`account` - *string*
The user account owning the domain and the mailboxes
`domain` - *string*
The specific domain for which the call will retrieve the list
`mailboxName` - *string*
The name of the mailbox.

64.2.2 Request Headers

`Content-Type`
Required. Set this header to `application/json; charset=UTF-8`

64.2.3 Request Body

```
{  
    "action": "resetPassword",  
    "actionData": {  
        "secretQuestionsAnswers": {"{tk)": "{answer}"},  
        "password": "{password}"  
    }  
}
```

`action` - *string*
The action that should be performed. Allowed values are:
resetPassword - Reset the password of a mailbox.

`actionData` - *dictionary (Required)*
Data to be send with the action.

`secretQuestionsAnswers` - *dictionary (Required)*
Dictionary of key/value pairs, each of which represents **secret question text key/answer** pair.

`tk` - *string (Required)*
The text key for the secret question. There should be no duplicate text keys per mailbox.

`answer` - *string (Required)*
The answer in plain-text - must be at least two characters.

`password` - *string (Required)*
The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.

Password validation rules:

- >Password must not be used more than once
- Minimum length 8
- Maximum length 128
- Should have at least one digit
- Should have at least one capital letter
- Should have at least one lower case letter
- Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)
- Should not start with the phrase 'pass' case-insensitively
- Should not start with 'abc' case-insensitively
- Should not start with 123
- Must not contain second-level domain, username or start with the first 3 letters from the username

64.3 Response

64.3.1 Expected Response Codes

204 No Content
Success

400 Bad Request
The supplied action or the supplied data is invalid.

404 Not Found
The resource does not exist.

409 Conflict
Validation of the secret answer failed.

64.4 Examples

64.4.1 Request password reset of a mailbox

Request

```
POST /accounts/account123/email/test.com/usernames/mailbox123/mailbox/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswers": {"tk1": "answer123"},
    "password": "pWord123$"
}
```

Response

204 No Content

64.4.2 Request password reset of a mailbox with wrong answer

Request

```
POST /accounts/account123/email/test.com/usernames/mailbox123/mailbox/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswersList": {"tk1": "wrongAnswer"},
    "password": "pWord123$"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "message": "Invalid secret questions and answers provided",
    "code": 409,
  }
}
```

64.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

65 Accounts-account-email-domain-usernames-mailboxName-mailbox:DELETE

66 DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox

Deletes mailbox.

66.1 Contents

- 1 [DELETE](#)
/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success deleting mailbox

66.2 Request

DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox

66.2.1 URI Parameters

account - *string*
domain - *string*
mailbox - *string*

66.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

66.3 Response

66.3.1 Status Code

204 No Content
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name or mailbox do not exist.

66.4 Examples

66.4.1 Success deleting mailbox

Request

DELETE /accounts/test-account/email/test.com/usernames/test/mailbox

Response

204 No Content

Please enable JavaScript to view the comments powered by Disqus. blog comments powered by Disqus

67 Accounts-account-email-domain-usernames-mailboxName-mailbox:GET

68 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox

Get mailbox details.

68.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting mailbox details

68.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox

68.2.1 URI Parameters

account - *string*
domain - *string*
mailboxName - *string*

68.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

68.3 Response

68.3.1 Status Code

200 OK
Success
401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.
404 Not Found
The domain name does not exist.

68.3.2 Response Body

```
{  
    "username": "{username}",  
    "master": {master},  
    "quota": {quota},  
    "usage": {usage},  
    "authToken": {authToken},  
    "links": [  
        {  
            "location": "{APIBaseURL}/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/",  
            "rel": "self"  
        }  
    ]  
    "sitemail_urls":  
    [  
        {  
            "url": "http://sitemaildev7.test",  
            "version": "7"  
        },  
        {  
            "url": "http://sitemaildev8.test",  
            "version": "8"  
        }  
    ]  
}
```

68.3.2.1 Parameters

username - *string*
The mailbox username.

authToken - *string*
Authorization string for logging into OpenXchange
Returned only if long URL, starting with "/accounts" is used

master - *boolean*
Describes if this is a master account.

quota - *integer*
Mailbox quota in MB.

usage - *integer*
Mailbox usage in MB.

sitemail_urls - *list*
List containing maps of SiteMail URLs and their versions

68.4 Examples

68.4.1 Success getting mailbox details

Request

```
GET /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
```

Response

200 OK

```
{
  "username": "test",
  "authToken": "NGA8mH65N63ZpakAIYCWZodYRRbsOQ/Uj9TcnWWWaUYuHZliHZbmT2eDFQW2zV71PYmmMhUK1Tx/5UMYkG4hv2ycGb0p7C2i4U8Vh1mK4/OrQQjQHLej27zfTMR+",
  "master": true,
  "quota": 10,
  "usage": 10,
  "links": [
    {
      "href": "{APIBaseURL}/accounts/test-account123/email/test.com/usernames/john.smith/mailbox/", "rel": "self"
    }
  ],
  "sitemail_urls": [
    {
      "url": "http://sitemaildev7.test",
      "version": "7"
    },
    {
      "url": "http://sitemaildev8.test",
      "version": "8"
    }
  ]
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

69 Accounts-account-email-domain-usernames-mailboxName-mailbox:PUT

70 PUT accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox

Creates or updates a mailbox for specified account and domain. The mailbox quota is determined by the E-mail domain product specification.

70.1 Contents

- 1 PUT
accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Trying to create mailbox without a password
 - ◊ 1.3.2 Trying to create mailbox with a not valid password
 - ◊ 1.3.3 Trying to create mailbox with invalid quota value(less or equal to 0)
 - ◊ 1.3.4 Trying to create mailbox when mailbox qty for OX type is exceeded
 - ◊ 1.3.5 Create mailbox
 - ◊ 1.3.6 Update mailbox password
 - ◊ 1.3.7 Trying to update mailbox password with already used one
 - ◊ 1.3.8 Update mailbox name
 - ◊ 1.3.9 Update mailbox using an existing name
 - ◊ 1.3.10 Create mailbox with specified quota
 - ◊ 1.3.11 Update existing mailbox quota
 - ◆ 1.4 See also

70.2 Request

PUT accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox

70.2.1 URI Parameters

account - string
domain - string
mailboxName - string
The mailbox. String should meet the regexp [a-zA-Z0-9._]+

70.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The Authentication credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

70.2.3 Request Body

```
{  
    "password": "{password}",  
    "master": {master},  
    "quota": {quota},  
    "type": {type},  
    "username": {username}  
}
```

70.2.3.1 Parameters

password - string (Required)

The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.

Password validation rules:

- Password must not be used more than once
- Minimum length 8
- Maximum length 128
- Should have at least one digit
- Should have at least one capital letter
- Should have at least one lower case letter
- Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)
- Should not start with the phrase 'pass' case-insensitively
- Should not start with 'abc' case-insensitively
- Should not start with 123
- Must not contain second-level domain, username or start with the first 3 letters from the username

master - *boolean*
 Describes if this is a master account.

quota - *int*
 Quota value in MB. If not provided default quota for OpenXchange type is set

type - *string*
 OpenXchange account type. Supported values can be obtained from the [webmailNames API endpoint](#). If not provided - standard is default.
 If current mailbox qty is more than the allowed value for specific OpenXchange account type, the response will be *400 Bad Request*

username - *string*
 The mailbox. String should meet the regexp [a-zA-Z0-9._]+
 Should be used when updating mailbox only

70.3 Response

70.3.1 Status Code

201 Created
 Success

204 No Content
 Success

400 Bad Request
 The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
 The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
 The domain name does not exist.

409 Conflict
 Mailbox already exists.

70.4 Examples

70.4.1 Trying to create mailbox without a password

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"master": false}
```

Response

```
400 Bad Request
{"password": "Required"}
```

70.4.2 Trying to create mailbox with a not valid password

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"password": "abc1234", "master": true}
```

Response

```
400 Bad Request
{"password": "Required"}
```

70.4.3 Trying to create mailbox with invalid quota value(less or equal to 0)

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"password": "test_password1", "quota": 0}
```

Response

```
400 Bad Request
{"computeFault": "Quota must be greater than 0"}
```

70.4.4 Trying to create mailbox when mailbox qty for OX type is exceeded

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"password": "test_password1", "type": "activesync"}
```

Response

```
400 Bad Request
{"computeFault":"Number of mailboxes exceeded"}
```

70.4.5 Create mailbox

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"password": "pWord123$", "master": true}
```

Response

```
201 Created
```

70.4.6 Update mailbox password

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"password": "!q2w3e4R"}
```

Response

```
204 No Content
```

70.4.7 Trying to update mailbox password with already used one

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith2/mailbox
{"password": "pWord123$"}
```

Response

```
400 Bad Request
```

70.4.8 Update mailbox name

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"username": "john.smith2"}
```

Response

```
204 No Content
```

70.4.9 Update mailbox using an existing name

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith/mailbox
{"username": "jack.smith"}
```

Response

```
400 Bad Request
```

70.4.10 Create mailbox with specified quota

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith2/mailbox
{"password": "pword1234", "quota": 70}
```

Response

201 Created

70.4.11 Update existing mailbox quota

Request

```
PUT /accounts/test-account123/email/test.com/usernames/john.smith2/mailbox
{"quota": 85}
```

Response

204 No Content

70.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

71 Accounts-account-email-domain-usernames-mailboxName-messagestats:GET

72 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats

Retrieves mailbox message count for INBOX, SENT and SPAM folders

72.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success
 - ◆ 1.4 See also

72.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats

72.2.1 URI Parameters

account - *string*
domain - *string*
mailboxName - *string*

72.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

72.3 Response

72.3.1 Status Code

200 OK

Success

401 Unauthorized

The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found

The domain name or the mailbox does not exist.
Unable to get message count for virtual mailboxes.

500 Internal Server Error

Missing Domain or Installation records

502 Bad Gateway

Unable to get message count. No IMAP connection
Unable to get message count. IMAP search operation failed.
Unable to get message count. IMAP folder selection failed.

72.3.2 Response Body

```
{  
  "messageCount" : {  
    "inbox" : {  
      "allMessages" : {inbox_all_messages_count},  
      "unreadMessages" : {inbox_unread_messages_count}  
    },  
    "sent" : {  
      "allMessages" : {sent_all_messages_count},  
      "unreadMessages" : {sent_unread_messages_count}  
    },  
    "spam" : {  
      "allMessages" : {spam_all_messages_count},  
      "unreadMessages" : {sent_unread_messages_count}  
    }  
  },  
  "links": [{"href": "https://api.hostway.com/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats/", "rel": "self"}]
```

72.3.2.1 Parameters

inbox_all_messages_count- *integer*
All messages for INBOX folder

inbox_unread_messages_count- *integer*
Unread messages for INBOX folder

```
sent_all_messages_count- integer  
    All messages for SENT folder  
sent_unread_messages_count- integer  
    Unread messages for SENT folder  
spam_all_messages_count- integer  
    All messages for SPAM folder  
spam_unread_messages_count- integer  
    Unread messages for SPAM folder
```

72.4 Examples

72.4.1 Success

Request

```
GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats
```

Response

200 OK

```
{  
  "messageCount" : {  
    "inbox" : {  
      "allMessages" : 3,  
      "unreadMessages" : 3  
    },  
    "sent" : {  
      "allMessages" : 0,  
      "unreadMessages" : 0  
    },  
    "spam" : {  
      "allMessages" : 0,  
      "unreadMessages" : 0  
    }  
  },  
  "links": [{"href": "https://api.hostway.com/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats/", "rel": "self"}]
```

72.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

73 Accounts-account-email-domain-usernames-mailboxName-migration:POST

74 POST accounts/{account}/email/{domain}/usernames/{mailboxName}/migration

Creates a support ticket for failed mailbox migration

74.1 Contents

- 1 POST accounts/{account}/email/{domain}/usernames/{mailboxName}/migration
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success creating a support ticket
 - ◆ 1.4 See also

74.2 Request

POST accounts/{account}/email/{domain}/usernames/{mailboxName}/migration

74.2.1 URI Parameters

account - *string*
domain - *string*
mailboxName - *string*

74.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

74.2.3 Request Body

```
{  
    "subject": "{subject}",  
    "body": "{body}"  
}
```

74.2.3.1 Parameters

subject - *string*
Subject of the support ticket

body - *string*
Body of the support ticket

74.3 Response

74.3.1 Status Code

201 Created
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

74.4 Examples

74.4.1 Success creating a support ticket

Request

POST accounts/test-account123/email/test.com/usernames/john.smith/migration

```
{  
    "subject": "subject"  
    "body": "body",  
}
```

Response

201 Created

74.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

75 Accounts-account-email-domain-usernames-mailboxName-secrets:GET

76 GET /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets

Retrieves a list of text keys for all mailbox(alias) secret questions.

76.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◆ 1.4 See also

76.2 Request

GET /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets

76.2.1 Request Parameters

account - *string*
The user account owning the domain and the mailboxes
domain - *string*
The specific domain for which the call will retrieve the list
maiboxName - *string*
The name of the mailbox

76.2.2 Request Headers

Content-Type
Required. Set this header to application/json; charset=UTF-8

76.3 Response

76.3.1 Status Code

200 OK
Success

404 Not Found
The domain name, mailbox or account does not exist.

76.3.2 Response Body

```
{  
    "list": [ "{tk}", "{tk}", "{tk}" ],  
    "links": [  
        {  
            "href": "https://api.hostway.com/accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets",  
            "rel": "self"  
        }  
    ]  
}
```

76.3.2.1 Parameters

list - 'list'
A list of secret questions of the account
tk - *string* (Unique)
Unique secret question text key.

links - 'list'
[Hypermedia](#) to the account secret questions resource

76.4 Examples

76.4.1 Success scenario

Request

GET /accounts/test-account123/email/test.com/usernames/test-mailbox/secrets

Response

```
{  
    "list": [ "tk1", "tk2", "tk3" ],  
    "links": [  
        {  
            "href": "https://api.hostway.com/accounts/test-account123/email/test.com/usernames/test-mailbox/secrets",  
            "rel": "self"  
        }  
    ]  
}
```

]
}

76.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

77 Accounts-account-email-domain-usernames-mailboxName-secrets:PUT

78 PUT /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets

Set or update all secret questions and answers for mailbox(alias).

78.1 Contents

- 1 PUT /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Body
 - 1.1.2.1 Parameters
 - ◊ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◊ 1.3.2 Set only two secret questions and answers, when the minimum required is three
 - ◆ 1.4 See also

78.2 Request

PUT /accounts/{account}/email/{domain}/usernames/{maiboxName}/secrets

78.2.1 Request Parameters

account - *string*
The user account owning the domain and the mailboxes
domain - *string*
The specific mailbox domain
maiboxName - *string*
The name of the mailbox

78.2.2 Request Body

```
{  
    "{tk)": "{answer}",  
    "{tk)": "{answer}",  
    ...  
}
```

78.2.2.1 Parameters

tk - *string* (Required)
The text key for the secret question. There should be no duplicate text keys per mailbox.

answer - *string* (Required)
The answer in plain-text - must be at least two characters.

78.2.3 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

78.3 Response

78.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the number of the secret questions and answers pairs in the request is lower then the **required minimum**.

401 Unauthorized
The supplied credentials are invalid.

403 Forbidden
The authorized user does not have permissions for this operation.

404 Not Found
The domain name, mailbox or account does not exist.

78.4 Examples

78.4.1 Success scenario

Request

PUT /accounts/test-account123/email/test.com/usernames/test-mailbox/secrets

```
{  
    "tk1": "answer1",  
    "tk2": "answer2",  
    "tk3": "answer3"  
}
```

Response

204 No Content

78.4.2 Set only two secret questions and answers, when the minimum required is three

Request

PUT /accounts/test-account123/email/test.com/usernames/test-mailbox/secrets

```
{  
    "tk1": "answer1",  
    "tk2": "answer2"  
}
```

Response

400 Bad Request

"details": { """: "Shorter than minimum length 3"}

78.5 See also

- [Email API](#)

Please enable JavaScript to view the comments powered by Disqus. [blog comments powered by Disqus](#)

79 Accounts-account-email-domain-usernames-mailboxName-webmail:GET

80 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail

Gets OpenXchange account type.

80.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting account type

80.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail

80.2.1 URI Parameters

account - *string*
domain - *string*
mailboxName - *string*

80.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

80.3 Response

80.3.1 Status Code

200 OK
Success
401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.
404 Not Found
The domain name does not exist.

80.3.2 Response Body

```
{  
  "authToken": "{authenticationToken}",  
  "type": "{type}",  
  "allowUpgrade": {allowUpgrade},  
  "resetPassword": {resetPassword},  
  "theme": "{theme}",  
  "language": "{language}",  
  "timezone": "{timezone}",  
  "links": [  
    {  
      "location": "{APIBaseURL}/accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail/",  
      "rel": "self"  
    }  
  ]  
}
```

80.3.2.1 Parameters

authenticationToken - *string*
Authentication token value
allowUpgrade - *boolean*
OpenXchange allowUpgrade option
type - *string*
OpenXchange account type. Supported values can be obtained from the **webmailNames API endpoint**.
resetPassword - *boolean*
Returns if customer will be forced to reset mailbox password the next time he logs in to his OX account
theme - *string*
Theme identifier for setting a specific theme when creating an OX account
language - *string*
OpenXchange account locale of type 'en_US'.
timezone - *string*
OpenXchange account timezone of type 'America/Chicago'.

80.4 Examples

80.4.1 Success getting account type

Request

```
GET /accounts/test/email/test.com/usernames/john.smith/webmail
```

Response

200 OK

```
{  
    "authToken": "PoiC9iyBehe13ZHWhfa2eArKUJy+RJ5WpyN0eCBs2+N8SIdvhgto9zWLdnGZWlgTV9MuJ1F+//XnoKZWxjaRr2qh++437fChyxZmaHwe7g==",  
    "type": "standard",  
    "allowUpgrade": true,  
    "resetPassword": false,  
    "theme": "test_theme",  
    "language": "en_US",  
    "timezone": "America/Chicago",  
    "links": [  
        {  
            "href": "{APIBaseURL}/accounts/test/email/test.com/usernames/john.smith/webmail/",  
            "rel": "self"  
        }  
    ]  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

81 Accounts-account-email-domain-usernames-mailboxName-webmail:POST

82 POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail

Creates OpenXchange account.

82.1 Contents

- 1 POST
/accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure creating account with not-valid parameter
 - ◊ 1.3.2 Failure creating account when mailbox qty for OX type is exceeded
 - ◊ 1.3.3 Success creating account

82.2 Request

POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail

82.2.1 URI Parameters

account - *string*
domain - *string*
mailboxName - *string*

82.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

82.2.3 Request Body

```
{  
    "type": "{type}",  
    "allowUpgrade": {allowUpgrade},  
    "theme": "{theme}",  
    "language": "{language}",  
    "timezone": "{timezone}"  
}
```

82.2.3.1 Parameters

allowUpgrade - *boolean*
OpenXchange allowUpgrade option value. The default value is true.
type - *string*
OpenXchange account type. Supported values can be obtained from the [webmailNames API endpoint](#). If not provided - standard is default.
If current mailbox qty is more than allowed for specific OpenXchange account type - the response is 400 Bad Request
theme - *string*
Theme identifier for setting a specific theme when creating an OX account. If not provided, default theme is set.
language - *string*
OpenXchange account locale of type 'en_US'.
timezone - *string*
OpenXchange account timezone of type 'America/Chicago'.

82.3 Response

82.3.1 Status Code

201 Created
Success

400 Bad Request
The format of the request body is invalid or the OpenXchange account type does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

409 Conflict
OpenXchange account already exists.

404 Not Found

The domain name or mailbox do not exist.

82.4 Examples

82.4.1 Failure creating account with not-valid parameter

Request

```
POST /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "non-valid"}
```

Response

```
400 Bad Request
{"type": "\"non-existing\" is not one of standard, activesync, premium"}
```

82.4.2 Failure creating account when mailbox qty for OX type is exceeded

Request

```
POST /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "activesync"}
```

Response

```
400 Bad Request
{"computeFault": "Number of mailboxes exceeded"}
```

82.4.3 Success creating account

Request

```
POST /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "standard", "allowUpgrade": false, "language": "en_US", "timezone": "America/Chicago"}
```

Response

```
201 Created
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

83 Accounts-account-email-domain-usernames-mailboxName-webmail:PUT

84 PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail

Upgrades/downgrades OpenXchange account type.

84.1 Contents

- 1 PUT
/accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure updating account type with missing required parameter
 - ◊ 1.3.2 Failure updating account type with invalid parameter
 - ◊ 1.3.3 Failure using inconsistent combination of allowUpgrade and type
 - ◊ 1.3.4 Failure changing the allowUpgrade option for activesync or premium accounts
 - ◊ 1.3.5 Failure upgrading account while allowUpgrade is set to false
 - ◊ 1.3.6 Failure upgrading account when mailbox qty for OX type is exceeded
 - ◊ 1.3.7 Success updating account type
 - ◊ 1.3.8 Failure downgrading account due to current usage greater than new quota
 - ◊ 1.3.9 Success updating resetPassword flag
 - ◊ 1.3.10 Success updating timezone, language and theme

84.2 Request

PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail

84.2.1 URI Parameters

account - string
domain - string
mailboxName - string

84.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

84.2.3 Request Body

```
{  
    "type": "{oxtype}",  
    "allowUpgrade": {allowUpgrade},  
    "resetPassword": {resetPassword},  
    "theme": "{theme}",  
    "language": "{language}",  
    "timezone": "{timezone}"  
}
```

84.2.3.1 Parameters

allowUpgrade - boolean
OpenXchange allowUpgrade option value. If upgrades are disabled by the product, it cannot be set to true.

type - string (Required)
OpenXchange account type. Supported values can be obtained from the **webmailNames API endpoint**.
The account owner(with admin-user credentials) can make changes between account types regardless of the allowUpgrade settings.
If the call is made with the end-user credentials and allowUpgrade is set to *false* providing a type different than standard results in a *400 Bad Request* response.
If the call is made with the end-user credentials and type is already different than standard and allowUpgrade is set to *false* the response is *400 Bad Request*.
If current usage is more than new type quota the response is *400 Bad Request*.
If current mailbox qty is more than allowed for specific OpenXchange account type the response is *400 Bad Request*.
If upgrades are disabled by the product, it can only be set to the current type.

resetPassword - boolean
Forces customer to reset his password the next time he logs in to his OX account.

theme - string
Theme identifier for setting a specific theme when creating an OX account.

```
language - string  
          OpenXchange account locale of type 'en_US'.  
timezone - string  
          OpenXchange account timezone of type 'America/Chicago'.
```

84.3 Response

84.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

84.4 Examples

84.4.1 Failure updating account type with missing required parameter

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail  
{"type": ""}
```

Response

```
400 Bad Request  
{"type": "Required"}
```

84.4.2 Failure updating account type with invalid parameter

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail  
{"type": "invalid-type"}
```

Response

```
400 Bad Request  
{"type": "\"invalid-type\" is not one of standard, activesync, premium"}
```

84.4.3 Failure using inconsistent combination of allowUpgrade and type

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail  
{"type": "premium", "allowUpgrade": false}
```

Response

```
400 Bad Request  
{"message": "The allowUpgrade option is inconsistent with the provided type"}
```

84.4.4 Failure changing the allowUpgrade option for activesync or premium accounts

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail  
{"allowUpgrade": false}
```

Response

```
400 Bad Request  
{"message": "The account is already upgraded. Please downgrade it to standard first."}
```

84.4.5 Failure upgrading account while allowUpgrade is set to false

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "premium"}
```

Response

```
400 Bad Request
{"message": "This account is not allowed to be upgraded"}
```

84.4.6 Failure upgrading account when mailbox qty for OX type is exceeded

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "activesync"}
```

Response

```
400 Bad Request
{"computeFault": "Number of mailboxes exceeded"}
```

84.4.7 Success updating account type

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "premium"}
```

Response

```
204 No Content
```

84.4.8 Failure downgrading account due to current usage greater than new quota

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "standard"}
```

Response

```
400 Bad Request
{"message": "Current mailbox usage is larger than the new quota value"}
```

84.4.9 Success updating resetPassword flag

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"resetPassword": true}
```

Response

```
204 No Content
```

84.4.10 Success updating timezone, language and theme

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"theme": "new_theme", "language": "en_US", "timezone": "America/Chicago"}
```

Response

```
204 No Content
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

85 Accounts-account-email-domain-usernames-mailboxName:GET

86 GET /accounts/{account}/email/{domain}/usernames/{mailboxName}

Details about a username

86.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames/{mailboxName}
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Exchange scenario
 - ◊ 1.3.2 MFG2 scenario
 - ◆ 1.4 See also

86.2 Request

GET /accounts/{account}/email/{domain}/usernames/{mailboxName}

86.2.1 Request Parameters

account - *string*
The user account owning the domain and the username
domain - *string*
The domain on which the username resides
mailboxName - *string*
Username for which to display the details

86.3 Response

86.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name, account or username does not exist.

86.3.2 Response Body

```
{  
    "exchange": [  
        {  
            "href": "{{APIBaseURL}}/accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/",  
            "rel": "related"  
        }  
    ],  
    "mailbox": [  
        {  
            "href": "{{APIBaseURL}}/accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/",  
            "rel": "related"  
        }  
    ],  
    "secrets": [  
        {  
            "href": "{{APIBaseURL}}/accounts/{account}/email/{domain}/usernames/{mailboxName}/secrets/",  
            "rel": "related"  
        }  
    ],  
    "links": [  
        {  
            "href": "{{APIBaseURL}}/accounts/{account}/email/{domain}/usernames/{mailboxName}/",  
            "rel": "self"  
        }  
    ]  
}
```

86.3.2.1 Parameters

exchange - *string*
(OPTIONAL)
[Hypermedia](#) to the exchange details for the username. Will only show if the username is hosted exchange

mailbox - *string*
(OPTIONAL)
[Hypermedia](#) to the regular mailbox details for the username. Will only show if the username is a MFG2 mailbox

secrets - *string*
[Hypermedia](#) to the secret questions for the username. Will be available for both hosted exchange and MFG2

links - *string*
[Hypermedia](#) for this resource. Links to self

86.4 Examples

86.4.1 Exchange scenario

Request

```
GET /accounts/test-account123/email/test.com/usernames/exchange-mbox
```

Response

```
{
  "exchange": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/exchange-mbox/exchange/",
      "rel": "related"
    }
  ],
  "secrets": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/exchange-mbox/secrets/",
      "rel": "related"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/exchange-mbox/",
      "rel": "self"
    }
  ]
}
```

86.4.2 MFG2 scenario

Request

```
GET /accounts/test-account123/email/test.com/usernames/mfg-mbox
```

Response

```
{
  "mailbox": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/mfg-mbox/mailbox/",
      "rel": "related"
    }
  ],
  "secrets": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/mfg-mbox/secrets/",
      "rel": "related"
    }
  ],
  "links": [
    {
      "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/mfg-mbox/",
      "rel": "self"
    }
  ]
}
```

86.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

87 Accounts-account-email-domain-usernames:GET

88 GET /accounts/{account}/email/{domain}/usernames

Retrieves a list of mailboxes for a specific account and domain

88.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/usernames
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 URI Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◊ 1.3.2 Request with webmailAccess
 - ◊ 1.3.3 Paginated request with sort order
 - ◆ 1.4 See also

88.2 Request

GET /accounts/{account}/email/{domain}/usernames

88.2.1 Request Parameters

account - *string*
The user account owning the domain and the mailboxes
domain - *string*
The specific domain for which the call will retrieve the list

88.2.2 URI Parameters

filterUsername - *string*
Only mailboxes with username matching the value of the parameter will be returned. The values used could be specified as a partial match with a wildcard(*)
page - *integer*
Specifies which page should be displayed. Requires a pageSize parameter to also be provided
pageSize - *integer*
Specifies the number of entries to be displayed on a page. Requires a page parameter to also be provided
sortField - *string*
Specifies if the resulting list is to be sorted by a given field. Allowed values are **username** and **quota**
sortOrder - *string*
The order in which the sorting is to be done. Allowed values are **asc** and **desc**
details - *integer*
If set to 1 the type of mailbox users will be displayed for each mailbox

88.3 Response

88.3.1 Status Code

200 OK
Success
401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.
404 Not Found
The domain name or account does not exist.

88.3.2 Response Body

```
{  
    "totalCount": "{count}",  
    "list": [  
        {  
            "username": "{username}",  
            "webmailAccess": "{webmailAccess}",  
            "links": [  
                {  
                    "href": "{href}",  
                    "rel": "{rel}"  
                }  
            ],  
            "type": {type},  
            "quota": {quota},  
            "master": {master},  
            "trialType": "{trialType}"  
        }  
    ]  
}
```

```

        "trialExpiration": "{trialExpiration}",
        "allowUpgrade": {allowUpgrade}
    },
]

}

88.3.2.1 Parameters

total count - integer  

The total number of mailboxes under the domain

username - string  

The username of an individual mailbox

master - integer  

Allowed values are 0 or 1

quota - integer  

The quota of the mailbox in Megabytes

webmailAccess - string  

(OPTIONAL)  

The type of webmail of the mailbox. Allowed values can be obtained from the webmailNames API endpoint. Will only be displayed if the user passed the details URI parameter

trialType - string  

Trial account type set for a given period of time. Supported values can be obtained from the webmailNames API endpoint.
```

trialExpiration - *date* - YYYY-mm-dd
Expiration date of trial period formatted as YYYY-mm-dd.

href - *string*
Link to other resources relevant to the mailboxes lists

rel - *string*
Type of relation to the resource for the provided link

88.4 Examples

88.4.1 Success scenario

Request

GET accounts/test-account123/email/test.com/usernames

Response

```
{
    "totalCount": 1,
    "list": [
        {
            "username": "test",
            "links": [
                {
                    "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/test/mailbox/",
                    "rel": "self"
                }
            ],
            "type": "imap",
            "quota": 10,
            "master": false,
            "trialType": "premium",
            "trialExpiration": "2018-10-28",
            "allowUpgrade": true
        }
    ]
}
```

88.4.2 Request with webmailAccess

Request

GET accounts/test-account123/email/test.com/usernames?details=1

Response

```
{
    "totalCount": 1,
    "list": [
        {
            "username": "test",
            "webmailAccess": "standard",
            "links": [
                {
                    "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/test/mailbox/",
                    "rel": "self"
                }
            ],
            "type": "imap",
            "quota": 10,
            "master": false,
            "trialType": "premium",
            "allowUpgrade": true
        }
    ]
}
```

```

        "trialExpiration": "2018-10-28",
        "allowUpgrade": true
    }
]
}

```

88.4.3 Paginated request with sort order

Request

GET accounts/test-account123/email/test.com/usernames?page=2&pageSize=2&sortField=username&sortOrder=desc

Response

```
{
    "totalCount": 6,
    "list": [
        {
            "username": "test2",
            "links": [
                {
                    "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/test2/mailbox/",
                    "rel": "self"
                }
            ],
            "type": "imap",
            "quota": 10,
            "master": true,
            "trialType": "premium",
            "trialExpiration": "2018-10-28",
            "allowUpgrade": true
        },
        {
            "username": "test1",
            "links": [
                {
                    "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames/test1/mailbox/",
                    "rel": "self"
                }
            ],
            "type": "imap",
            "quota": 10,
            "master": false,
            "trialType": "premium",
            "trialExpiration": "2018-10-28",
            "allowUpgrade": true
        }
    ],
    "links": [
        {
            "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames?page=1&pageSize=2",
            "rel": "first"
        },
        {
            "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames?page=1&pageSize=2",
            "rel": "previous"
        },
        {
            "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames?page=3&pageSize=2",
            "rel": "next"
        },
        {
            "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames?page=3&pageSize=2",
            "rel": "last"
        },
        {
            "href": "{{APIBaseURL}}/accounts/test-account123/email/test.com/usernames?page=2&pageSize=2",
            "rel": "self"
        }
    ]
}
```

88.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

89 Accounts-account-email-domain-webmail:GET

90 GET /accounts/{account}/email/{domain}/webmail

Gets OpenXchange account type for the domain.

90.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting account type

90.2 Request

GET /accounts/{account}/email/{domain}/webmail

90.2.1 URI Parameters

account - *string*
domain - *string*

90.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

90.3 Response

90.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

90.3.2 Response Body

```
{  
    "type": "{type}",  
    "allowUpgrade": {allowUpgrade},  
    "trialType": "{trialType}",  
    "trialExpiration": "{trialExpiration}",  
    "links": [  
        {  
            "location": "{APIBaseURL}/accounts/{account}/email/{domain}/webmail/",  
            "rel": "self"  
        }  
    ]  
}
```

90.3.2.1 Parameters

type - *string*
Webmail account type. Supported values can be obtained from the [webmailNames API endpoint](#).

allowUpgrade - *boolean*
Webmail allowUpgrade option value.

trialType - *string* - Can be null
Trial account type. Null if not set. Supported values can be obtained from the [webmailNames API endpoint](#).

trialExpiration - *date*
Expiration date of trial period formatted as YYYY-mm-dd. Null if not set.

90.4 Examples

90.4.1 Success getting account type

Request

```
GET /accounts/test/email/test.com/webmail
```

Response

200 OK

```
{  
    "type": "standard",  
    "allowUpgrade": true,  
    "trialType": "premium",  
    "trialExpiration": "2018-10-28",  
    "links": [  
        {  
            "location": "{APIBaseURL}/accounts/{account}/email/{domain}/webmail/",  
            "rel": "self"  
        }  
    ]  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

91 Accounts-account-email-domain-webmail:PUT

92 PUT /accounts/{account}/email/{domain}/webmail

Change the OpenXchange allowUpgrade option.

92.1 Contents

- 1 PUT /accounts/{account}/email/{domain}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure updating the domain settings without any options
 - ◊ 1.3.2 Success updating the allowUpgrade value

92.2 Request

PUT /accounts/{account}/email/{domain}/webmail

92.2.1 URI Parameters

account - *string*
domain - *string*

92.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

92.2.3 Request Body

```
{  
    "allowUpgrade": {allowUpgrade}  
}
```

92.2.3.1 Parameters

allowUpgrade - *boolean*
OpenXchange allowUpgrade option value.

92.3 Response

92.3.1 Status Code

204 No Content

400 Bad Request
The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

409 Conflict
Upgrade is disabled at the product level and cannot be turned on

92.4 Examples

92.4.1 Failure updating the domain settings without any options

Request

PUT /accounts/test/email/test.com/webmail

```
{ }
```

Response

400 Bad Request

```
{"allowUpgrade": "Required"}
```

92.4.2 Success updating the allowUpgrade value

Request

```
PUT /accounts/test/email/test.com/webmail  
{"allowUpgrade": true}
```

Response

```
204 No Content
```

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

93 Accounts-account-email-domain-webmailLimits:GET

94 GET /accounts/{account}/email/{domain}/webmailLimits

Getting maximum allowed number of mailboxes for each type

Note: /email/{domain}/webmailLimits is a shortcut equivalent of this resource

94.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/webmailLimits
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 See also

94.2 Request

GET /accounts/{account}/email/{domain}/webmailLimits

94.2.1 URI Parameters

account - *string*
Account number for the owner of the email domain entity.
domain - *string*
Target domain name of the email domain resource.

94.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

94.3 Response

Returns dictionary which contains the webmail upgrade settings for the target domain as a key-value pairs.

94.3.1 Status Code

200 OK
Success

94.3.2 Response Body

```
{  
    "webmailLimits": {  
        "activesync": 2,  
        "premium": -1,  
        "starter": -1,  
        "standard": -1  
    },  
    "links": [  
        {  
            "href": "https://api.hostway.com/accounts/accNum123/email/example.com/webmailLimits/",  
            "rel": "self"  
        }  
    ]  
}
```

94.3.2.1 Parameters

webmailLimits - *dictionary*
Specifies a limit for each available webmail type. Negative values and zero mean that there is no limit for the type

links - *list*
Hypermedia for the resource.

94.4 See also

- Email API
- Common Features

Please enable JavaScript to view the comments powered by Disqus. blog comments powered by Disqus

95 Accounts-account-email-domain-webmailNames:GET

96 GET /accounts/{account}/email/{domain}/webmailNames

Retrieves mapping of the allowed OX types with WebMail plan names for the target email domain resource. The result can be tied to a specific plan configuration on the product level.

Note: /email/{domain}/webmailNames is a shortcut equivalent of this resource

96.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/webmailNames
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 See also

96.2 Request

GET /accounts/{account}/email/{domain}/webmailNames

96.2.1 URI Parameters

account - *string*
Account number for the owner of the email domain entity.
domain - *string*
Target domain name of the email domain resource.

96.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

96.3 Response

Returns dictionary which contains the mapping of supported OpenXchange types by text key and WebMail plan names for the specific email domain resource.

96.3.1 Status Code

200 OK
Success

96.3.2 Response Body

```
{  
  "webmailNames": {  
    "activesync": "SMX Sync Advanced",  
    "premium": "SMA Collaborate Premium",  
    "standard": "SMX Mail Basic"  
  },  
  "links": [  
    {  
      "href": "https://api.hostway.com/accounts/accNum123/email/example.com/webmailNames/",  
      "rel": "self"  
    }  
  ]  
}
```

96.3.2.1 Parameters

webmailNames - *dictionary*
Dictionary containing the supported OX types by text key and the WebMail plan names.

links - *list*
[Hypermedia](#) for the resource.

96.4 See also

- [Email API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

97 Accounts-account-email-domain-webmailUpgrade:GET

98 GET /accounts/{account}/email/{domain}/webmailUpgrade

Retrieves the product level upgrade configuration

Note: /email/{domain}/webmailUpgrade is a shortcut equivalent of this resource

98.1 Contents

- 1 GET
/accounts/{account}/email/{domain}/webmailUpgrade
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 See also

98.2 Request

```
GET /accounts/{account}/email/{domain}/webmailUpgrade
```

98.2.1 URI Parameters

account - *string*
Account number for the owner of the email domain entity.
domain - *string*
Target domain name of the email domain resource.

98.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

98.3 Response

Returns dictionary which contains the webmail upgrade settings for the target domain as a key-value pairs.

98.3.1 Status Code

200 OK
Success

98.3.2 Response Body

```
{  
    "allowed": false,  
    "links": [  
        {  
            "href": "https://api.hostway.com/accounts/accNum123/email/example.com/webmailUpgrade/",  
            "rel": "self"  
        }  
    ]  
}
```

98.3.2.1 Parameters

allowed - *boolean*
Whether upgrades are enabled or disabled by the product
links - *list*
[Hypermedia](#) for the resource.

98.4 See also

- [Email API](#)
- [Common Features](#)

Please enable JavaScript to view the comments powered by Disqus. blog comments powered by Disqus

99 Accounts-account-email-domain:GET

100 GET /accounts/{account}/email/{domain}

Gets email domain's info.

100.1 Contents

- 1 GET
/accounts/{account}/email/{domain}
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting domain info

100.2 Request

GET /accounts/{account}/email/{domain}

100.2.1 URI Parameters

account - *string*
domain - *string*

100.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]
The [Authentication](#) credentials of the client application.

Content-Type
Optional. Set this header to `application/json; charset=UTF-8`

100.3 Response

100.3.1 Status Code

200 OK
Success

401 Unauthorized
The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found
The domain name does not exist.

100.3.2 Response Body

```
{  
    "quota": 19320,  
    "links": [  
        {  
            "location": "{APIBaseURL}/accounts/{account}/email/{domain}",  
            "rel": "self"  
        }  
    ]  
}
```

100.3.2.1 Parameters

quota - *int*
Domain quota in MB(sum of all domain's mailboxes quota).

100.4 Examples

100.4.1 Success getting domain info

Request

GET /accounts/test-account/email/test.com

Response

200 OK

```
{  
    "quota": 19320,  
    "links": [  
        {  
            "href": "{APIBaseURL}/accounts/test-account/email/test.com/",  
            "rel": "self"  
        }  
    ]  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

101 Email API

101.1 Mailboxes

- `GET /accounts/{account}/email/{domain}/usernames` - Retrieves a list of mailboxes
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}` - Details about a username
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox` - Gets mailbox details
- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox` - Create or update mailbox data
- `DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox` - Deletes a mailbox
- `POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/action` - Apply action on a mailbox, e.g. reset password

101.2 Exchange

- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange` - Create or update exchange mailbox
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange` - Get exchange mailbox info
- `DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange` - Delete exchange mailbox
- `POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/exchange/action` - Apply action on exchange mailbox, e.g. reset password

101.3 Aliases

- `GET /accounts/{account}/email/{domain}/aliases` - Retrieves a list of domain aliases

101.4 Forwards

- `POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/forwards` - Sets mailbox forwarding
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/forwards` - Gets mailbox forwarding info
- `DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/forwards/{fwd-mailbox}` - Deletes mailbox forwarding

101.5 Autoresponder

- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/autoresponder` - Sets an auto-responder
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/autoresponder` - Gets auto-responder info

101.6 CleanMailPlus

- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/cleanmailplus` - Gets mailbox's CleanMailPlus info
- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/cleanmailplus` - Updates mailbox's CleanMailPlus info

101.7 Webmail

- `GET /accounts/{account}/email/{domain}/webmail` - Getting OX allowUpgrade option for the domain
- `PUT /accounts/{account}/email/{domain}/webmail` - Change the OX allowUpgrade option for the domain
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail` - Getting OX account
- `GET /email/{domain}/usernames/{mailboxName}/webmail` - Getting OX account
- `POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail` - Create OX account
- `POST /email/{domain}/usernames/{mailboxName}/webmail` - Create OX account
- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/webmail` - Update OX account
- `PUT /email/{domain}/usernames/{mailboxName}/webmail` - Update OX account
- `GET /accounts/{account}/email/{domain}/webmailLimits` - Getting maximum allowed number of mailboxes for each type
- `GET /accounts/{account}/email/{domain}/webmailUpgrade` - Getting OX allowUpgrade option for the product
- `GET /email/{domain}/webmailUpgrade` - Getting OX allowUpgrade option for the product

101.8 Webmail Names

- `GET /accounts/{account}/email/{domain}/webmailNames` - Returns mapping of allowed OX types with webmail names for the domain
- `GET /email/{domain}/webmailNames` - Returns mapping of allowed OX types with webmail names for the domain

101.9 Black/White List

- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/blackwhitelist` - Retrieves black/whitelisted addresses
- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/blackwhitelist` - Adds address(es) to black/white list
- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/blackwhitelist/{address}` - Get particular address info
- `DELETE /accounts/{account}/email/{domain}/usernames/{mailboxName}/blackwhitelist/{address}` - Deletes an address from black/white list

101.10 InfoStore

- `GET /accounts/{account}/email/{domain}/infostore` - Getting InfoStore usage
- `PUT /accounts/{account}/email/{domain}/infostore` - Change InfoStore quota

101.11 Mailbox domain statistics

- `GET /accounts/{account}/email/{domain}/statistics/mailboxTypeCount` - Retrieves per domain statistics about webmail usage

101.12 Mailbox migration failure

- `POST /accounts/{account}/email/{domain}/usernames/{mailboxName}/migration` - Creating support ticket for failed mailbox migration

101.13 Mailbox Message Count

- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/messagestats` - Get mailbox message count for INBOX, SENT and SPAM folders

101.14 Exchange Message Count

- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/mailbox/exchange/messagestats` - Get exchange message count for INBOX, SENT and SPAM folders

101.15 Email Domain

- `GET /accounts/{account}/email/{domain}` - Gets specific email domain's info

101.16 Domain Black/White List

- `GET /accounts/{account}/email/{domain}/blackwhitelist` - Retrieves black/whitelisted addresses for domain
- `PUT /accounts/{account}/email/{domain}/blackwhitelist` - Adds address(es) to black/white list for domain
- `GET /accounts/{account}/email/{domain}/blackwhitelist/{address}` - Get particular address info
- `DELETE /accounts/{account}/email/{domain}/blackwhitelist/{address}` - Deletes an address from black/white list

101.17 Domain CleanMailPlus

- `GET /accounts/{account}/email/{domain}/cleanmailplus` - Gets domain's CleanMailPlus info
- `PUT /accounts/{account}/email/{domain}/cleanmailplus` - Updates domain's CleanMailPlus info

101.18 Secret Questions

- `GET /accounts/{account}/email/{domain}/usernames/{mailboxName}/secrets` - Retrieves a list of mailbox(alias) secret questions
- `PUT /accounts/{account}/email/{domain}/usernames/{mailboxName}/secrets` - Set or update all secret questions and answers for mailbox(alias)

101.19 Secret Question Settings

- `GET /email/secretQuestionSettings` - Get franchise specific secret question settings (e.g. **minimum** required number of secret questions, etc.)

101.20 Supported Secret Questions

- `GET /email/secretQuestions` - Get dictionary of supported secret questions with text keys

101.21 Antivirus Antispam

- `GET /accounts/{accountId}/avas/{domain}/SSOLink` - Returns a SSO Link for antispam control panel

101.21.1 Templates

- `resetPassword`

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

102 Email-domain-usernames-mailboxName-exchange-action:POST

103 POST /email/{domain}/usernames/{mailboxName}/exchange/action

Apply an action on exchange mailbox e.g. **reset password**

103.1 Contents

- 1 POST
/email/{domain}/usernames/{mailboxName}/exchange/action
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - ◆ 1.2 Response
 - ◊ 1.2.1 Expected Response Codes
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Request password reset of exchange mailbox
 - ◊ 1.3.2 Request password reset of exchange mailbox with wrong answer
 - ◆ 1.4 See also

103.2 Request

POST /email/{domain}/usernames/{mailboxName}/exchange/action

103.2.1 Request Parameters

account - *string*
The user account owning the domain and the exchange mailboxes
domain - *string*
The specific domain for which the call will retrieve the list
maiboxName - *string*
The name of the exchange mailbox.

103.2.2 Request Headers

Content-Type
Required. Set this header to application/json; charset=UTF-8

103.2.3 Request Body

```
{  
  "action": "resetPassword",  
  "actionData": [  
    "secretQuestionsAnswers": {"tk": "{answer}"},  
    "password": "{password}"  
  ]  
}
```

action - *string*
The action that should be performed. Allowed values are:
resetPassword - Reset the password of exchange mailbox.

actionData - *dictionary* (*Required*)
Data to be send with the action.

secretQuestionsAnswers - *dictionary* (*Required*)
Dictionary of key/value pairs, each of which represents **secret question text key/answer** pair.

tk - *string* (*Required*)
The text key for the secret question. There should be no duplicate text keys per exchange mailbox.

answer - *string* (*Required*)
The answer in plain-text - must be at least two characters.

password - *string* (*Required*)
The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.

Password validation rules:

- Password must not be used more than once
- Minimum length 8
- Maximum length 128
- Should have at least one digit
- Should have at least one capital letter
- Should have at least one lower case letter
- Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)
- Should not start with the phrase 'pass' case-insensitively
- Should not start with 'abc' case-insensitively
- Should not start with 123
- Must not contain second-level domain, username or start with the first 3 letters from the username

103.3 Response

103.3.1 Expected Response Codes

204 No Content
Success

400 Bad Request
The supplied action or the supplied data is invalid.

404 Not Found
The resource does not exist.

409 Conflict
Validation of the secret answer failed.

103.4 Examples

103.4.1 Request password reset of exchange mailbox

Request

```
POST /email/test.com/usernames/mailbox123/exchange/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswers": {"tk1": "answer123"},
    "password": "pWord123$"
}
```

Response

204 No Content

103.4.2 Request password reset of exchange mailbox with wrong answer

Request

```
POST /email/test.com/usernames/mailbox123/exchange/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswersList": {"tk1": "wrongAnswer"},
    "password": "pWord123$"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "message": "Invalid secret questions and answers provided",
    "code": 409,
  }
}
```

103.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

104 Email-domain-usernames-mailboxName-mailbox-action:POST

105 POST /email/{domain}/usernames/{mailboxName}/mailbox/action

Apply an action on a mailbox e.g. **reset password**

105.1 Contents

- 1 POST
/email/{domain}/usernames/{mailboxName}/mailbox/action
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - ◆ 1.2 Response
 - ◊ 1.2.1 Expected Response Codes
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Request password reset of a mailbox
 - ◊ 1.3.2 Request password reset of a mailbox with wrong answer
 - ◆ 1.4 See also

105.2 Request

POST /email/{domain}/usernames/{mailboxName}/mailbox/action

105.2.1 Request Parameters

account - *string*
The user account owning the domain and the mailboxes
domain - *string*
The specific domain for which the call will retrieve the list
maiboxName - *string*
The name of the mailbox.

105.2.2 Request Headers

Content-Type
Required. Set this header to application/json; charset=UTF-8

105.2.3 Request Body

```
{  
    "action": "resetPassword",  
    "actionData": {  
        "secretQuestionsAnswers": {"{tk)": "{answer}"},  
        "password": "{password}"  
    }  
}
```

action - *string*
The action that should be performed. Allowed values are:
resetPassword - Reset the password of a mailbox.

actionData - *dictionary* (*Required*)
Data to be send with the action.

secretQuestionsAnswers - *dictionary* (*Required*)
Dictionary of key/value pairs, each of which represents **secret question text key/answer** pair.

tk - *string* (*Required*)
The text key for the secret question. There should be no duplicate text keys per mailbox.

answer - *string* (*Required*)
The answer in plain-text - must be at least two characters.

password - *string* (*Required*)
The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.
Password validation rules:

 Password must not be used more than once
 Minimum length 8
 Maximum length 128
 Should have at least one digit
 Should have at least one capital letter
 Should have at least one lower case letter
 Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)
 Should not start with the phrase 'pass' case-insensitively
 Should not start with 'abc' case-insensitively
 Should not start with 123
 Must not contain second-level domain, username or start with the first 3 letters from the username

105.3 Response

105.3.1 Expected Response Codes

204 No Content
Success

400 Bad Request
The supplied action or the supplied data is invalid.

404 Not Found
The resource does not exist.

409 Conflict
Validation of the secret answer failed.

105.4 Examples

105.4.1 Request password reset of a mailbox

Request

```
POST /email/test.com/usernames/mailbox123/mailbox/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswers": {"tk1": "answer123"},
    "password": "pWord123$"
}
```

Response

204 No Content

105.4.2 Request password reset of a mailbox with wrong answer

Request

```
POST /email/test.com/usernames/mailbox123/mailbox/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswersList": {"tk1": "wrongAnswer"},
    "password": "pWord123$"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "message": "Invalid secret questions and answers provided",
    "code": 409,
  }
}
```

105.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

106 Email-domain-usernames-mailboxName-secrets:GET

107 GET /email/{domain}/usernames/{mailboxName}/secrets

Retrieves a list of text keys for all mailbox(alias) secret questions.

107.1 Contents

- 1 GET /email/{domain}/usernames/{mailboxName}/secrets
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◆ 1.4 See also

107.2 Request

GET /email/{domain}/usernames/{mailboxName}/secrets

107.2.1 Request Parameters

domain - *string*
The specific domain for which the call will retrieve the list
mailboxName - *string*
The name of the mailbox

107.2.2 Request Headers

Content-Type
Required. Set this header to application/json; charset=UTF-8

107.3 Response

107.3.1 Status Code

200 OK
Success

404 Not Found
The domain name or mailbox does not exist.

107.3.2 Response Body

```
{  
    "list": [ "{tk}", "{tk}", "{tk}" ],  
    "links": [  
        {  
            "href": "https://api.hostway.com/email/{domain}/usernames/{mailboxName}/secrets",  
            "rel": "self"  
        }  
    ]  
}
```

107.3.2.1 Parameters

list - 'list'
A list of secret questions of the account
tk - *string* (Unique)
Unique secret question text key.

links - 'list'
[Hypermedia](#) to the account secret questions resource

107.4 Examples

107.4.1 Success scenario

Request

GET /email/test.com/usernames/test-mailbox/secrets

Response

```
{  
    "list": [ "tk1", "tk2", "tk3" ],  
    "links": [  
        {  
            "href": "https://api.hostway.com/email/test.com/usernames/test-mailbox/secrets",  
            "rel": "self"  
        }  
    ]  
}
```

}

107.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

108 Email-domain-usernames-mailboxName-secrets:PUT

109 PUT /email/{domain}/usernames/{mailboxName}/secrets

Set or update all secret questions and answers for mailbox(alias).

109.1 Contents

- 1 PUT /email/{domain}/usernames/{mailboxName}/secrets
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Body
 - 1.1.2.1 Parameters
 - ◊ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success scenario
 - ◊ 1.3.2 Set only two secret questions and answers, when the required minimum is three
 - ◆ 1.4 See also

109.2 Request

PUT /email/{domain}/usernames/{mailboxName}/secrets

109.2.1 Request Parameters

domain - *string*
The specific mailbox domain
mailboxName - *string*
The name of the mailbox

109.2.2 Request Body

```
{  
    "{tk)": "{answer}",  
    "{tk)": "{answer}",  
    ...  
}
```

109.2.2.1 Parameters

tk - *string* (Required)
The text key for the secret question. There should be no duplicate text keys per mailbox.

answer - *string* (Required)
The answer in plain-text - must be at least two characters.

109.2.3 Request Headers

Authorization - *HTTP Authorization header* [1]
The **Authentication** credentials of the client application.

Content-Type
Required. Set this header to application/json; charset=UTF-8

109.3 Response

109.3.1 Status Code

204 No Content
Success

400 Bad Request
The format of the request body is invalid or the number of the secret questions and answers pairs in the request is lower than the required minimum.

401 Unauthorized
The supplied credentials are invalid.

403 Forbidden
The authorized user does not have permissions for this operation.

404 Not Found
The domain name, mailbox or account does not exist.

109.4 Examples

109.4.1 Success scenario

Request

PUT /email/test.com/usernames/test-mailbox/secrets

```
{  
    "tk1": "answer1",  
    "tk2": "answer2",  
}
```

```
        "tk3": "answer3"
    }
```

Response

204 No Content

109.4.2 Set only two secret questions and answers, when the required minimum is three

Request

```
PUT /email/test.com/usernames/test-mailbox/secrets
```

```
{
    "tk1": "answer1",
    "tk2": "answer2"
}
```

Response

400 Bad Request

```
"details": {"": "Shorter than minimum length 3"}
```

109.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

110 Email-domain-usernames-mailboxName-webmail:GET

111 GET /email/{domain}/usernames/{mailboxName}/webmail

Gets OpenXchange account type.

111.1 Contents

- 1 GET
 - /email/{domain}/usernames/{mailboxName}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting account type

111.2 Request

GET /email/{domain}/usernames/{mailboxName}/webmail

111.2.1 URI Parameters

domain - string

mailboxName - string

111.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]

Use the mailbox owner credentials for the specific mailbox, e.g. username: email@domain.com, password: secret

Content-Type

Required. Set this header to application/json; charset=UTF-8

111.3 Response

111.3.1 Status Code

200 OK

Success

401 Unauthorized

The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found

The domain name does not exist.

111.3.2 Response Body

```
{  
    "type": "{type}",  
    "allowUpgrade": {allowUpgrade},  
    "theme": "{theme}",  
    "language": "{language}",  
    "timezone": "{timezone}",  
    "links": [  
        {  
            "location": "{APIBaseURL}/email/{domain}/usernames/{mailboxName}/webmail/",  
            "rel": "self"  
        }  
    ]  
}
```

111.3.2.1 Parameters

allowUpgrade - boolean

OpenXchange allowUpgrade option value.

type - string - one of "standard", "activesync" or "premium"

OpenXchange account type.

theme - string

Theme identifier for setting a specific theme when creating an OX account

language - string

OpenXchange account locale of type 'en_US'.

timezone - string

OpenXchange account timezone of type 'America/Chicago'.

111.4 Examples

111.4.1 Success getting account type

Request

GET /email/test.com/usernames/test/webmail

Response

200 OK

```
{"type": "standard", "allowUpgrade": true, "theme": "test_theme", "language": "en_US", "timezone": "America/Chicago", "links": [{"href": "(AP)"}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

112 Email-domain-usernames-mailboxName-webmail:POST

113 POST /email/{domain}/usernames/{mailboxName}/webmail

Creates OpenXchange account.

113.1 Contents

- 1 POST /email/{domain}/usernames/{mailboxName}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure creating account with not-valid parameter
 - ◊ 1.3.2 Failure creating account when mailbox qty for OX type is exceeded
 - ◊ 1.3.3 Success creating account

113.2 Request

POST /email/{domain}/usernames/{mailboxName}/webmail

113.2.1 URI Parameters

domain - *string*

mailboxName - *string*

113.2.2 Request Headers

Authorization - *HTTP Authorization header* [1]

Use the mailbox owner credentials for the specific mailbox, e.g. username: email@domain.com, password: secret

Content-Type

Required. Set this header to application/json; charset=UTF-8

113.2.3 Request Body

```
{  
    "type": "{oxtype}",  
    "allowUpgrade": {allowUpgrade},  
    "theme": "{theme}",  
    "language": "{language}",  
    "timezone": "{timezone}"  
}
```

113.2.3.1 Parameters

allowUpgrade - *boolean*

OpenXchange allowUpgrade option value. The default value is true.

type - *string*

OpenXchange account type. Supported values can be obtained from the [webmailNames API endpoint](#). If not provided - standard is default.
If current mailbox qty is more than allowed for specific OpenXchange account type the response is 400 Bad Request

theme - *string*

Theme identifier for setting a specific theme when creating an OX account. If not provided , default theme is set.

language - *string*

OpenXchange account locale of type 'en_US'.

timezone - *string*

OpenXchange account timezone of type 'America/Chicago'.

113.3 Response

113.3.1 Status Code

201 Created

Success

400 Bad Request

The format of the request body is invalid or the OpenXchange account type does not meet the requirements.

401 Unauthorized

The supplied credentials are invalid or do not provide permissions for this operation.

409 Conflict

OpenXchange account already exists.

404 Not Found

The domain name or mailbox do not exist.

113.4 Examples

113.4.1 Failure creating account with not-valid parameter

Request

```
POST /email/test.com/usernames/john.smith/webmail
{"type": "non-valid"}
```

Response

```
400 Bad Request
{"type": "\"non-existing\" is not one of standard, activesync, premium"}
```

113.4.2 Failure creating account when mailbox qty for OX type is exceeded

Request

```
POST /email/test.com/usernames/john.smith/webmail
{"type": "activesync"}
```

Response

```
400 Bad Request
{"computeFault":"Number of mailboxes exceeded"}
```

113.4.3 Success creating account

Request

```
POST /email/test.com/usernames/john.smith/webmail
{"type": "activesync", "allowUpgrade": false, "language": "en_US", "timezone": "America/Chicago"}
```

Response

```
201 Created
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

114 Email-domain-usernames-mailboxName-webmail:PUT

115 PUT /email/{domain}/usernames/{mailboxName}/webmail

Upgrades/downgrades OpenXchange account type.

115.1 Contents

- 1 PUT /email/{domain}/usernames/{mailboxName}/webmail
 - ◆ 1.1 Request
 - ◊ 1.1.1 URI Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Failure updating account type with empty type
 - ◊ 1.3.2 Failure updating account type with invalid type
 - ◊ 1.3.3 Failure using inconsistent combination of allowUpgrade and type
 - ◊ 1.3.4 Failure changing the allowUpgrade option for activesync or premium accounts
 - ◊ 1.3.5 Failure upgrading account while allowUpgrade is set to false
 - ◊ 1.3.6 Failure upgrading account when mailbox qty for OX type is exceeded
 - ◊ 1.3.7 Success updating account type
 - ◊ 1.3.8 Failure downgrading account due to current usage greater than new quota
 - ◊ 1.3.9 Success updating timezone, language and theme

115.2 Request

PUT /email/{domain}/usernames/{mailboxName} /webmail

115.2.1 URI Parameters

domain - string

mailboxName - string

115.2.2 Request Headers

Authorization - *HTTP Authorization header [1]*

Use the mailbox owner credentials for the specific mailbox, e.g. username: email@domain.com, password: secret

Content-Type

Required. Set this header to application/json; charset=UTF-8

115.2.3 Request Body

```
{  
    "type": "{type}",  
    "allowUpgrade": {allowUpgrade},  
    "theme": "{theme}",  
    "language": "{language}",  
    "timezone": "{timezone}"  
}
```

115.2.3.1 Parameters

allowUpgrade - boolean

OpenXchange allowUpgrade option value. If upgrades are disabled by the product, it cannot be set to true.

type - string (Required)

OpenXchange account type. Supported values can be obtained from the [webmailNames API endpoint](#).

The account owner(with admin-user credentials) can make changes between account types regardless of the allowUpgrade settings.

If the call is made with the end-user credentials and allowUpgrade is set to *false* providing a type different than standard results in a *400 Bad Request* response

If the call is made with the end-user credentials and type is already different than standard and allowUpgrade is set to *false* the response is *400 Bad Request*

If current usage is more than new type quota the response is *400 Bad Request*

If current mailbox qty is more than allowed for specific OpenXchange account type the response is *400 Bad Request*

If upgrades are disabled by the product, it can only be set to the current type

resetPassword - boolean

Forces customer to reset his password the next time he logs in to his OX account.

theme - string

Theme identifier for setting a specific theme when creating an OX account.

language - string

OpenXchange account locale of type 'en_US'.

timezone - string

OpenXchange account timezone of type 'America/Chicago'.

115.3 Response

115.3.1 Status Code

204 No Content
Success

400 Bad Request

The format of the request body is invalid or the username does not meet the requirements.

401 Unauthorized

The supplied credentials are invalid or do not provide permissions for this operation.

404 Not Found

The domain name does not exist.

115.4 Examples

115.4.1 Failure updating account type with empty type

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"type": ""}
```

Response

400 Bad Request
{"type": "Required"}

115.4.2 Failure updating account type with invalid type

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"type": "invalid-type"}
```

Response

400 Bad Request
{"type": "\"invalid-type\" is not one of standard, activesync, premium"}

115.4.3 Failure using inconsistent combination of allowUpgrade and type

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"type": "premium", "allowUpgrade": false}
```

Response

400 Bad Request
{"message": "The allowUpgrade option is inconsistent with the provided type"}

115.4.4 Failure changing the allowUpgrade option for activesync or premium accounts

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"allowUpgrade": false}
```

Response

400 Bad Request
{"message": "The account is already upgraded. Please downgrade it to standard first."}

115.4.5 Failure upgrading account while allowUpgrade is set to false

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"type": "premium"}
```

Response

400 Bad Request
{"message": "This account is not allowed to be upgraded"}

115.4.6 Failure upgrading account when mailbox qty for OX type is exceeded

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"type": "activesync"}
```

Response

```
400 Bad Request
{"computeFault": "Number of mailboxes exceeded"}
```

115.4.7 Success updating account type

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"type": "premium"}
```

Response

```
204 No Content
```

115.4.8 Failure downgrading account due to current usage greater than new quota

Request

```
PUT /accounts/test/email/test.com/usernames/john.smith/webmail
{"type": "standard"}
```

Response

```
400 Bad Request
{"message": "Current mailbox usage is larger than the new quota value"}
```

115.4.9 Success updating timezone, language and theme

Request

```
PUT /email/test.com/usernames/john.smith/webmail
{"theme": "new_theme", "language": "en_US", "timezone": "America/Chicago"}
```

Response

```
204 No Content
```

Please enable JavaScript to view the comments powered by Disqus. blog comments powered by Disqus

116 Email-secretQuestions:GET

117 GET /email/secretQuestions

Get dictionary of supported secret questions with text keys.

117.1 Contents

- 1 GET /email/secretQuestions
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Headers
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting supported secret questions with text keys
 - ◊ 1.3.2 No secret questions supported

117.2 Request

```
GET /email/secretQuestions
```

117.2.1 Request Headers

Content-Type
Required. Set this header to application/json; charset=UTF-8

117.3 Response

117.3.1 Status Code

200 OK
Success

117.3.2 Response Body

Retrieves dictionary of secret questions with text keys.

```
{
  "questions": [
    {
      "{tk)": "{question}",
      "{tk)": "{question}",
      ...
    },
    "links": [
      {
        "location": "https://api.hostway.com/email/secretQuestions/",
        "rel": "self"
      }
    ]
}
```

117.3.2.1 Parameters

questions - *dictionary*
A dictionary of secret questions text-key with their relevant explanation in plain-text
tk - *string*
Secret question text key.
question - *string*
The question in plain-text.

links - *list*
[Hypermedia](#) to the secret questions resource

117.4 Examples

117.4.1 Success getting supported secret questions with text keys

Request

```
GET /email/secretQuestions
```

Response

200 OK

```
{
  "questions": [
    {
      "tk1": "What is question one?",
      "tk2": "What is question two?",
      "tk3": "What is question three?"
    },
    "links": [
      {
        "location": "https://api.hostway.com/email/secretQuestions/"
      }
    ]
}
```

```
        "rel": "self"
    }
}
```

117.4.2 No secret questions supported

Request

```
GET /email/secretQuestions
```

Response

```
200 OK
```

```
{
  "questions": {},
  "links": [
    {
      "location": "https://api.hostway.com/email/secretQuestions/",
      "rel": "self"
    }
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

118 Email-secretQuestionSettings:GET

119 GET /email/secretQuestionSettings

Get franchise specific secret question settings (e.g. **minimum** required number of secret questions, etc.)

119.1 Contents

- 1 GET /email/secretQuestionSettings
 - ◆ 1.1 Request
 - ◆ 1.2 Response
 - ◊ 1.2.1 Status Code
 - ◊ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Success getting secret question settings

119.2 Request

GET /email/secretQuestionSettings

119.3 Response

119.3.1 Status Code

200 OK
Success

119.3.2 Response Body

Retrieves dictionary of secret question settings.

```
{  
  "minimum": 1,  
  "links": [  
    {  
      "location": "https://api.hostway.com/email/secretQuestionSettings",  
      "rel": "self"  
    }  
  ]  
}
```

119.3.2.1 Parameters

minimum - *integer*
A minimum number of secret questions/answers pairs required to be on file for each email account.
The minimum value for this parameter is one.

links - *list*
[Hypermedia](#) to the secret question settings resource

119.4 Examples

119.4.1 Success getting secret question settings

Request

GET /email/secretQuestionSettings

Response

200 OK

```
{  
  "minimum": 3,  
  "links": [  
    {  
      "location": "https://api.hostway.com/email/secretQuestionSettings",  
      "rel": "self"  
    }  
  ]  
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). blog comments powered by Disqus

120 Template:ResetPassword

121 POST

`{{{base}}}/email/{{domain}}/usernames/{{mailboxName}}/{{resource}}/action`

Apply an action on {{2}}{{1}} mailbox e.g. **reset password**

121.1 Contents

- 1 POST
`{{{base}}}/email/{{domain}}/usernames/{{mailboxName}}/{{resource}}/action`
 - ◆ 1.1 Request
 - ◊ 1.1.1 Request Parameters
 - ◊ 1.1.2 Request Headers
 - ◊ 1.1.3 Request Body
 - ◆ 1.2 Response
 - ◊ 1.2.1 Expected Response Codes
 - ◆ 1.3 Examples
 - ◊ 1.3.1 Request password reset of {{2}}{{1}} mailbox
 - ◊ 1.3.2 Request password reset of {{2}}{{1}} mailbox with wrong answer
 - ◆ 1.4 See also

121.2 Request

POST `{{{base}}}/email/{{domain}}/usernames/{{mailboxName}}/{{resource}}/action`

121.2.1 Request Parameters

account - *string*
The user account owning the domain and the {{1}} mailboxes
domain - *string*
The specific domain for which the call will retrieve the list
mailboxName - *string*
The name of the {{1}} mailbox.

121.2.2 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

121.2.3 Request Body

```
{  
    "action": "resetPassword",  
    "actionData": {  
        "secretQuestionsAnswers": {"tk": "{answer}"},  
        "password": "{password}"  
    }  
}
```

action - *string*
The action that should be performed. Allowed values are:
resetPassword - Reset the password of {{2}}{{1}} mailbox.

actionData - *dictionary* (*Required*)
Data to be send with the action.

secretQuestionsAnswers - *dictionary* (*Required*)
Dictionary of key/value pairs, each of which represents **secret question text key/answer** pair.

tk - *string* (*Required*)
The text key for the secret question. There should be no duplicate text keys per {{1}} mailbox.

answer - *string* (*Required*)
The answer in plain-text - must be at least two characters.

password - *string* (*Required*)
The password. The password should be at least 8 characters long, a mix of numbers, symbols and mixed-case letters. It should not begin with "pass", "123", "abc", should not contain the second-level domain name of the service, should not contain the username of the mailbox or start with its first 3 characters. There is a restriction using the same password more than once.
Password validation rules:

- >Password must not be used more than once
- Minimum length 8
- Maximum length 128
- Should have at least one digit
- Should have at least one capital letter
- Should have at least one lower case letter
- Should contain at least one special character (any character other than lower or uppercase letters, digits and underscore "_" is considered special character)
- Should not start with the phrase 'pass' case-insensitively
- Should not start with 'abc' case-insensitively
- Should not start with 123
- Must not contain second-level domain, username or start with the first 3 letters from the username

121.3 Response

121.3.1 Expected Response Codes

204 No Content
Success

400 Bad Request
The supplied action or the supplied data is invalid.

404 Not Found
The resource does not exist.

409 Conflict
Validation of the secret answer failed.

121.4 Examples

121.4.1 Request password reset of{{2}}/{{1}} mailbox

Request

```
POST {{base_example}}/email/test.com/usernames/mailbox123/{{resource}}/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswers": {"tk1": "answer123"},
    "password": "pWord123$"
}
```

Response

204 No Content

121.4.2 Request password reset of{{2}}/{{1}} mailbox with wrong answer

Request

```
POST {{base_example}}/email/test.com/usernames/mailbox123/{{resource}}/action
Content-Type: application/json; Charset=UTF-8
```

```
{
  "action": "resetPassword",
  "actionData": {
    "secretQuestionsAnswersList": {"tk1": "wrongAnswer"},
    "password": "pWord123$"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "message": "Invalid secret questions and answers provided",
    "code": 409,
  }
}
```

121.5 See also

- [Email API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)