

Table of Contents

1 Orders:POST.....	1
2 POST /orders.....	2
2.1 Contents.....	2
2.2 Request.....	2
2.3 Response.....	2
2.4 Example.....	3
2.5 See also.....	4
3 Orders-orderId:GET.....	5
4 GET /orders/{orderId}.....	6
4.1 Contents.....	6
4.2 Request.....	6
4.3 Response.....	6
4.4 Example.....	7
4.5 OPTIONS /orders/{order_id}.....	8
4.6 See also.....	8
5 Orders-orderId:DELETE.....	9
6 DELETE /orders/{orderId}.....	10
6.1 Contents.....	10
6.2 Request.....	10
6.3 Response.....	10
6.4 Example.....	10
6.5 See also.....	11
7 Orders-orderId-action:POST.....	12
8 POST /orders/{orderId}/action.....	13
8.1 Contents.....	13
8.2 Request.....	13
8.3 Response.....	14
8.4 Examples.....	14
8.5 OPTIONS /orders/{orderId}/action.....	16
8.6 See also.....	17
9 Order Shorthand.....	18
10 /order.....	19
10.1 Contents.....	19
10.2 Request Headers.....	19
10.3 Order Shorthand.....	19
10.4 Available Methods and Child Resources.....	19
10.5 Implicit Order Creation.....	19
10.6 Response Headers.....	19
10.7 Additional Status Code.....	19
10.8 OwnerId cookie.....	19
10.9 Examples.....	20
10.10 See also.....	21
11 Orders-orderId-attributes:PUT.....	22
12 PUT /orders/{orderId}/attributes.....	23
12.1 Contents.....	23
12.2 Request.....	23
12.3 Response.....	24
12.4 Example.....	24
12.5 See also.....	25
13 Orders-orderId-attributes:GET.....	26
14 GET /orders/{orderId}/attributes.....	27
14.1 Contents.....	27
14.2 Request.....	27
14.3 Response.....	27
14.4 Example.....	28
14.5 See also.....	29
15 Orders-orderId-account:PUT.....	30
16 PUT /orders/{orderId}/account.....	31
16.1 Contents.....	31
16.2 Request.....	31
16.3 Response.....	32
16.4 Example.....	32
16.5 See also.....	34
17 Orders-orderId-account:GET.....	35
18 GET /orders/{orderId}/account.....	36
18.1 Contents.....	36
18.2 Request.....	36
18.3 Response.....	36

Table of Contents

18 GET /orders/{orderId}/account	
18.4 Example.....	37
18.5 See also.....	38
19 Orders-orderId-account-attributes:PUT.....	39
20 PUT /orders/{orderId}/account/attributes.....	40
20.1 Contents.....	40
20.2 Request.....	40
20.3 Response.....	41
20.4 Example.....	41
20.5 See also.....	43
21 Orders-orderId-account-attributes:GET.....	44
22 GET /orders/{orderId}/account/attributes.....	45
22.1 Contents.....	45
22.2 Request.....	45
22.3 Response.....	45
22.4 Example.....	46
22.5 See also.....	47
23 Orders-orderId-account-attributes:DELETE.....	48
24 DELETE /orders/{orderId}/account/attributes.....	49
24.1 Contents.....	49
24.2 Request.....	49
24.3 Response.....	49
24.4 Example.....	49
24.5 See also.....	50
25 Orders-orderId-account-contactInfo-contactType:PUT.....	51
26 PUT /orders/{orderId}/account/contactInfo/{contactType}.....	52
26.1 Contents.....	52
26.2 Request.....	52
26.3 Response.....	53
26.4 Example.....	54
26.5 See also.....	56
27 Orders-orderId-account-contactInfo-contactType:GET.....	57
28 GET /orders/{orderId}/account/contactInfo/{contactType}.....	58
28.1 Contents.....	58
28.2 Request.....	58
28.3 Response.....	58
28.4 Example.....	59
28.5 See also.....	60
29 Orders-orderId-account-contactInfo:GET.....	61
30 GET /orders/{orderId}/account/contactInfo.....	62
30.1 Contents.....	62
30.2 Request.....	62
30.3 Response.....	62
30.4 Example.....	63
30.5 See also.....	64
31 Orders-orderId-account-contactInfo-contactType:DELETE.....	65
32 DELETE /orders/{orderId}/account/contactInfo/{contactType}.....	66
32.1 Contents.....	66
32.2 Request.....	66
32.3 Response.....	66
32.4 Example.....	66
32.5 See also.....	67
33 Orders-orderId-account-paymentInfo:PUT.....	69
34 PUT /orders/{orderId}/account/paymentInfo.....	70
34.1 Contents.....	70
34.2 Request.....	70
34.3 Response.....	71
34.4 Example.....	71
34.5 See also.....	75
35 Orders-orderId-account-paymentInfo:GET.....	76
36 GET /orders/{orderId}/account/paymentInfo.....	77
36.1 Contents.....	77
36.2 Request.....	77
36.3 Response.....	77
36.4 Example.....	78
36.5 See also.....	79

Table of Contents

37 Orders-orderId-account-user:PUT.....	80
38 PUT /orders/{orderId}/account/user.....	81
38.1 Contents.....	81
38.2 Request.....	81
38.3 Response.....	82
38.4 Example.....	82
38.5 See also.....	84
39 Orders-orderId-account-user:GET.....	85
40 GET /orders/{orderId}/account/user.....	86
40.1 Contents.....	86
40.2 Request.....	86
40.3 Response.....	86
40.4 Example.....	87
40.5 See also.....	88
41 Orders-orderId-account-products:POST.....	89
42 POST /orders/{orderId}/account/products.....	90
42.1 Contents.....	90
42.2 Request.....	90
42.3 Response.....	91
42.4 See also.....	93
43 Orders-orderId-account-products:GET.....	94
44 GET /orders/{orderId}/account/products.....	95
44.1 Contents.....	95
44.2 Request.....	95
44.3 Response.....	95
44.4 See also.....	96
45 Orders-orderId-account-products-productId:GET.....	97
46 GET /orders/{orderId}/account/products/{productId}.....	98
46.1 Contents.....	98
46.2 Request.....	98
46.3 Response.....	98
46.4 See also.....	99
47 Orders-orderId-account-products-productId:PUT.....	100
48 PUT /orders/{orderId}/account/products/{productId}.....	101
48.1 Contents.....	101
48.2 Request.....	101
48.3 Response.....	101
48.4 See also.....	103
49 Orders-orderId-account-products-productId:DELETE.....	104
50 DELETE /orders/{orderId}/account/products/{productId}.....	105
50.1 Contents.....	105
50.2 Request.....	105
50.3 Response.....	105
50.4 See also.....	106
51 Orders-orderId-account-products-productId-services:POST.....	107
52 POST /orders/{orderId}/account/products/{productId}/services.....	108
52.1 Contents.....	108
52.2 Request.....	108
52.3 Response.....	109
52.4 Examples.....	112
52.5 See also.....	113
53 Orders-orderId-account-products-productId-services:GET.....	114
54 GET /orders/{orderId}/account/products/{productId}/services.....	115
54.1 Contents.....	115
54.2 Request.....	115
54.3 Response.....	115
54.4 See also.....	116
55 Orders-orderId-account-products-productId-services-serviceId:GET.....	117
56 GET /orders/{orderId}/account/products/{productId}/services/{serviceId}.....	118
56.1 Contents.....	118
56.2 Request.....	118
56.3 Response.....	118
56.4 See also.....	119

Table of Contents

57 Orders-orderId-account-products-productId-services-serviceld:PUT.....	120
58 PUT /orders/{orderId}/account/products/{productId}/services/{serviceld}.....	121
58.1 Contents.....	121
58.2 Request.....	121
58.3 Response.....	121
58.4 See also.....	122
59 Orders-orderId-account-products-productId-services-serviceld:DELETE.....	123
60 DELETE /orders/{orderId}/account/products/{productId}/services/{serviceld}.....	124
60.1 Contents.....	124
60.2 Request.....	124
60.3 Response.....	124
60.4 See also.....	125
61 Orders-orderId-account-products-productId-services-serviceld-attributes:PUT.....	126
62 PUT /orders/{orderId}/account/products/{productId}/services/{serviceld}/attributes.....	127
62.1 Contents.....	127
62.2 Request.....	127
62.3 Response.....	127
62.4 See also.....	128
63 Orders-orderId-account-products-productId-services-serviceld-attributes:GET.....	130
64 GET /orders/{orderId}/account/products/{productId}/services/{serviceld}/attributes.....	131
64.1 Contents.....	131
64.2 Request.....	131
64.3 Response.....	131
64.4 See also.....	132
65 Orders-orderId-account-products-productId-services-serviceld-attributes:OPTIONS.....	133
66 OPTIONS /orders/{orderId}/account/products/{productId}/services/{serviceld}/attributes.....	134
66.1 Contents.....	134
66.2 Request.....	134
66.3 Response.....	134
66.4 See also.....	134
67 ServiceAttributesStructure.....	135
67.1 See also.....	135
68 Orders-orderId-account-products-productId-services-serviceld-notes:POST.....	136
69 POST /orders/{orderId}/account/products/{productId}/services/{serviceld}/notes.....	137
69.1 Contents.....	137
69.2 Request.....	137
69.3 Response.....	137
69.4 See also.....	138
70 Orders-orderId-account-products-productId-services-serviceld-notes:PUT.....	139
71 PUT /orders/{orderId}/account/products/{productId}/services/{serviceld}/notes.....	140
71.1 Contents.....	140
71.2 Request.....	140
71.3 Response.....	140
71.4 See also.....	141
72 Orders-orderId-account-products-productId-services-serviceld-notes:GET.....	142
73 GET /orders/{orderId}/account/products/{productId}/services/{serviceld}/notes.....	143
73.1 Contents.....	143
73.2 Request.....	143
73.3 Response.....	143
73.4 See also.....	144
74 Orders-orderId-account-products-productId-services-serviceld-notes:DELETE.....	145
75 DELETE /orders/{orderId}/account/products/{productId}/services/{serviceld}/notes.....	146
75.1 Contents.....	146
75.2 Request.....	146
75.3 Response.....	146
75.4 See also.....	147
76 Orders-orderId-account-products-productId-services-serviceld-notes:OPTIONS.....	148
77 OPTIONS /orders/{orderId}/account/products/{productId}/services/{serviceld}/notes.....	149
77.1 Contents.....	149
77.2 Request.....	149
77.3 Response.....	149
77.4 See also.....	149

Table of Contents

78 Orders-orderId-account-products-productId-promotion:PUT.....	150
79 PUT /orders/{orderId}/account/products/{productId}/promotion.....	151
79.1 Contents.....	151
79.2 Request.....	151
79.3 Response.....	151
79.4 Example.....	151
79.5 See also.....	153
80 Orders-orderId-account-products-productId-promotion:DELETE.....	154
81 DELETE /orders/{orderId}/account/products/{productId}/promotion.....	155
81.1 Contents.....	155
81.2 Request.....	155
81.3 Response.....	155
81.4 Example.....	155
81.5 See also.....	156
82 Orders-orderId-account-products-productId-services-serviceId-promotion:PUT.....	157
83 PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion.....	158
83.1 Contents.....	158
83.2 Request.....	158
83.3 Response.....	158
83.4 Example.....	158
83.5 See also.....	159
84 Orders-orderId-account-products-productId-services-serviceId-promotion:DELETE.....	161
85 DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion.....	162
85.1 Contents.....	162
85.2 Request.....	162
85.3 Response.....	162
85.4 Example.....	162
85.5 See also.....	163
86 Orders-orderId-discounts:PUT.....	164
87 PUT /orders/{orderId}/discounts.....	165
87.1 Contents.....	165
87.2 Request.....	165
87.3 Response.....	166
87.4 Example.....	166
87.5 See also.....	169
88 Orders-orderId-discounts:GET.....	170
89 GET /orders/{orderId}/discounts.....	171
89.1 Contents.....	171
89.2 Request.....	171
89.3 Response.....	171
89.4 Example.....	172
89.5 See also.....	173
90 Orders-orderId-discounts:DELETE.....	174
91 DELETE /orders/{orderId}/discounts.....	175
91.1 Contents.....	175
91.2 Request.....	175
91.3 Response.....	175
91.4 Example.....	175
91.5 See also.....	176
92 Orders-orderId-account-products-productId-discounts:PUT.....	177
93 PUT /orders/{orderId}/account/products/{productId}/discounts.....	178
93.1 Contents.....	178
93.2 Request.....	178
93.3 Response.....	179
93.4 Example.....	179
93.5 See also.....	182
94 Orders-orderId-account-products-productId-discounts:GET.....	183
95 GET /orders/{orderId}/account/products/{productId}/discounts.....	184
95.1 Contents.....	184
95.2 Request.....	184
95.3 Response.....	184
95.4 Example.....	185
95.5 See also.....	186
96 Orders-orderId-account-products-productId-discounts:DELETE.....	187

Table of Contents

97 DELETE /orders/{orderId}/account/products/{productId}/discounts.....	188
97.1 Contents.....	188
97.2 Request.....	188
97.3 Response.....	188
97.4 Example.....	188
97.5 See also.....	189
98 Orders-orderId-account-products-productId-services-serviceld-discounts:PUT.....	190
99 PUT /orders/{orderId}/account/products/{productId}/services/{serviceld}/discounts.....	191
99.1 Contents.....	191
99.2 Request.....	191
99.3 Response.....	192
99.4 Example.....	192
99.5 See also.....	196
100 Orders-orderId-account-products-productId-services-serviceld-discounts:GET.....	197
101 GET /orders/{orderId}/account/products/{productId}/services/{serviceld}/discounts.....	198
101.1 Contents.....	198
101.2 Request.....	198
101.3 Response.....	198
101.4 Example.....	199
101.5 See also.....	200
102 Orders-orderId-account-products-productId-services-serviceld-discounts:DELETE.....	201
103 DELETE /orders/{orderId}/account/products/{productId}/services/{serviceld}/discounts.....	202
103.1 Contents.....	202
103.2 Request.....	202
103.3 Response.....	202
103.4 Example.....	202
103.5 See also.....	204
104 Orders-orderId-quote:GET.....	205
105 GET /orders/{orderId}/quote.....	206
105.1 Contents.....	206
105.2 Request.....	206
105.3 Response.....	206
105.4 Example.....	208
105.5 See also.....	210
106 Common Features.....	211
107 Order-Products-Account.....	212
108 Set account on a later step when ordering products and services.....	213
108.1 Create a new order.....	213
108.2 Add a product.....	213
108.3 Add a service to the product with no attributes.....	213
108.4 Create a new account for the order.....	213
108.5 Set an existing account for the order.....	214
108.6 Submit the order.....	214
109 Order-Products-Account-Modify.....	215
110 Set and modify an account on a later step when ordering products and services.....	216
110.1 Create a new order.....	216
110.2 Add a product.....	216
110.3 Add a service to the product with no attributes.....	216
110.4 Set an existing account for the order.....	216
110.5 Set some account attributes.....	217
110.6 Set modified regular contact.....	217
110.7 Set account payment info.....	217
110.8 Submit the order.....	218
111 Order-Email-Domain.....	219
112 Order a new email domain.....	220
112.1 Create a new order.....	220
112.2 Create a new account for the order.....	220
112.3 Add the email domain product.....	220
112.4 Add the email service to the new product.....	220
112.5 Add service attributes.....	221
112.6 Submit the order.....	221
113 Order-Domain-Alias.....	222
114 Order a new email domain alias.....	223
114.1 Create a new order.....	223
114.2 Create a new account for the order.....	223
114.3 Add an email domain product.....	223
114.4 Add an email service to the new product.....	223
114.5 Add service attributes.....	224

Table of Contents

114 Order a new email domain alias	224
114.6 Add an email domain alias service to the new product.....	224
114.7 Add the domain alias service attributes.....	224
114.8 Submit the order.....	224
115 Order-Exchange	226
115.1 Order a new Exchange domain.....	226
115.2 Create a new order.....	226
115.3 Create a new account for the order.....	226
115.4 Add an Exchange product to the order.....	226
115.5 Add an Exchange service to the new product.....	226
115.6 Obtain a quote.....	227
115.7 Submit the order.....	227
115.8 Check for status.....	227
116 Order-Exchange-mailbox-free	229
116.1 Order a new, free Exchange mailbox.....	229
116.2 Create the mailbox.....	229
116.3 Check for status.....	229
117 Order-Exchange-mailbox-paid	230
117.1 Order a new, paid Exchange mailbox.....	230
117.2 Create the mailbox.....	230
117.3 Submit the order.....	230
117.4 Check for status.....	230
118 Order-Exchange-otherproduct	232
118.1 Ordering Other Exchange Products.....	232
118.2 Create Encryption for a domain.....	232
118.3 Obtain a quote.....	232
118.4 Submit the order.....	232
118.5 Check for status.....	232
119 Order-cloud-drive	234
120 Order a new cloud drive	235
120.1 Request.....	235
120.2 Create a new account for the order.....	235
120.3 Add "Linux Web Start" product to the order.....	235
120.4 Add the cloud drive service to the new product.....	235
120.5 Submit the order.....	236
121 Order-cloud-backup	237
122 Order a new cloud backup	238
122.1 Request.....	238
122.2 Create a new account for the order.....	238
122.3 Add "Linux Web Start" product to the order.....	238
122.4 Add the cloud backup service to the new product.....	238
122.5 Submit the order.....	239
123 Order-webs-planet	240
123.1 Order a new WebsPlanet.....	240
123.2 Create a new order.....	240
123.3 Create a new account for the order.....	240
123.4 Add a Websplanet product to the order.....	240
123.5 Add a Webhosting service to the new product.....	240
123.6 Add the Webhosting service attributes.....	241
123.7 Add a Websplanet service to the new product.....	241
123.8 Add the WebsPlanet service attributes.....	241
124 Order-vps-virtuozzo	242
124.1 Order VPS Virtuozzo products and services.....	242
124.2 Create a new order.....	242
124.3 Create a new account or add an existing one to the order.....	242
124.4 Add a VPS Virtuozzo product to the order.....	242
124.5 Add a Virtuozzo Server service to the new product.....	242
124.6 Add VPS Virtuozzo services to the new product.....	243
124.7 Submit the order.....	244
125 Order-Domain	246
126 Order a new domain	247
126.1 Create a new order.....	247
126.2 Add product to the order.....	247
126.3 Add a service to the product.....	247
126.4 Add attributes to the service.....	247
126.5 Create a new account for the order.....	248
126.6 Add user info.....	249
126.7 Add billing contact.....	249
126.8 Add regular contact.....	249
126.9 Add payment info to the order.....	249
126.10 Validate the order.....	250
126.11 Get a quote.....	250
126.12 Submit the order.....	252

Table of Contents

127 Order-Domain-Shortcut.....	253
128 Order a new domain.....	254
128.1 Create a new domain registration order.....	254

1 Orders:POST

2 POST /orders

Creates a new order and returns the unique order URI.

2.1 Contents

- 1 POST /orders
 - ◆ 1.1 Request
 - ◇ 1.1.1 URI Parameters
 - ◇ 1.1.2 Request Headers
 - ◇ 1.1.3 Request Body
 - 1.1.3.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - 1.2.3.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Create Order successfully
 - ◇ 1.3.2 Create without permission to pass client IP
 - ◇ 1.3.3 An open order already exists
 - ◆ 1.4 See also

2.2 Request

POST /orders

2.2.1 URI Parameters

None.

2.2.2 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

Optional. A cookie named **OwnerId** may be specified to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to a previous request for this resource (in the **Set-Cookie** response header).

2.2.3 Request Body

```
{
  "clientId": {client_ip_address}
}
```

2.2.3.1 Parameters

clientId - *string*

Optional. The IP address of the client that submitted the order. If not provided, the IP address of the client that called the API will be used. The IP address may be used to check the order for possible fraud. This parameter may be useful in cases where the API client accepts and relays orders from a 3rd-party customer (such as a shopping cart application). This parameter requires elevated permissions.

2.3 Response

2.3.1 Status Code

Status Code	Error Message	Description
201 Created	-	The new order was created.
400 Bad Request	User cannot specify the client IP address	The client attempted to pass the client IP address and is not allowed. Use of this parameter requires elevated permissions.
409 Conflict	A new order has already been created for this ownerId	The client already has an open order. If the OwnerId cookie was passed in the request headers, a 409 will be returned if there's already an open (unsubmitted) order for the same client.

2.3.2 Response Headers

Location

Returned with successful response. Contains the order URI. The client must use this URI for all subsequent operations with the order.

Set-Cookie

Returned with successful response. Contains an **OwnerId** value which must be submitted with all subsequent requests for this order. The **OwnerId** identifies the client and prohibits it from having more than one open (unsubmitted) orders.

2.3.3 Response Body

```
{
  "orderId": "{orderId}",
  "links": [
    {"href": "https://api.hostway.com/orders/", "rel": "self"},
    {"href": "https://api.hostway.com/orders/{orderId}", "rel": "item"}
  ]
}
```

2.3.3.1 Parameters

orderId - *string*
The Id of the new order

links - *list*
[Hypermedia](#) for this resource. Links to self and the newly created order.

2.4 Example

2.4.1 Create Order successfully

Request

```
POST /orders
Content-Type: application/json; charset=UTF-8
```

```
{}
```

Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf
Set-Cookie : OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "orderId": "0000013ad6dd95746a399f90000a71384bf242cf",
  "links": [
    {"href": "https://api.hostway.com/orders/", "rel": "self"},
    {"href": "https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf", "rel": "item"}
  ]
}
```

2.4.2 Create without permission to pass client IP

Request

```
POST /orders
Content-Type: application/json; charset=UTF-8
Authorization: Basic AuthString
{
  "clientId": "1.2.3.4"
}
```

Response

```
400 Bad Request
Content-Type: application/json; charset=UTF-8

{
  "computeFault": {
    "guid": "143336cd-1763-4fe9-b3e3-c1e172b14fae",
    "message": "User cannot specify the client IP address",
    "code": 400, "details": ""
  }
}
```

2.4.3 An open order already exists

Request

```
POST /orders
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=0b3fc7bd-6905-4de7-bddb-43d2c7365e7a

{}
```

Response

```
409 Conflict
Content-Type: application/json; charset=UTF-8

{
  "conflict": {
    "guid": "e250bf7e-688d-45ba-8308-58374529be58",
    "message": "A new order has already been created for this ownerId",
    "code": 409,
    "details": ""
  }
}
```

2.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

3 Orders-orderId:GET

4 GET /orders/{orderId}

Returns the content of an order specified by the URI.

4.1 Contents

- 1 GET /orders/{orderId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Get order information
 - ◇ 1.3.2 Get info with wrong OwnerId
 - ◇ 1.3.3 Unassociated user without cookie
 - ◇ 1.3.4 Unexisting order
 - ◆ 1.4 OPTIONS /orders/{order_id}
 - ◇ 1.4.1 Parameters
 - ◇ 1.4.2 Request Headers
 - ◇ 1.4.3 Response Status Code
 - ◇ 1.4.4 Response Headers
 - ◆ 1.5 See also

4.2 Request

GET /orders/{orderId}

4.2.1 Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the **POST /orders** call.

4.2.2 URI Parameters

None.

4.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

Authorization
Optional. Specify the **Authorization** header when requesting details for an order that was already submitted. Follow the instructions for API **Authentication**.

4.3 Response

4.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	Success.
401 Unauthorized	-	

The **OwnerId** cookie or the **Authorization** header are not specified or do not permit access to the specified order.

403 Forbidden Unauthorized: Order failed permission check

Access an associated order as an authenticated user, not associated with the order.

404 Not Found Resource not found

The specified order does not exist.

4.3.2 Response Body

The response body may contain additional information beyond what is specified in the documentation. Such information should be ignored or treated as volatile, since it may change in the future.

```
{
  "order": {
    "Status": "{orderStatus}",
    "Account": "{accountUrl}"
  },
  "links": {
    "self": {"href": "https://api.hostway.com/orders/{orderId}/", "rel": "self"}
  }
}
```

4.3.2.1 Parameters

orderStatus - *string*

The status of the order.

accountUrl - *string (optional)*

[Hypermedia](#) for the account of this order. Link to the account.

links - *list*

[Hypermedia](#) for this resource. Link to the order.

4.4 Example

4.4.1 Get order information

Request

```
GET /orders/0000013ca61880fbfc068b33000a02c9d8ef861c
Cookie: OwnerId=948ce0d4-7cf0-43b6-88a5-2b3f1331b689; Path=/
```

Response

```
200 OK
Content-Type: application/json; charset=UTF-8

{
  "order": {
    "Status": "new",
    "Account": "http://accounts/acc20130821"
  },
  "links": [ {
    "href": "https://api.hostway.com/orders/0000013ca61880fbfc068b33000a02c9d8ef861c/",
    "rel": "self"
  } ]
}
```

4.4.2 Get info with wrong OwnerId

Request

```
GET /orders/000001483b9336c4be0a0c89000a19010d347ea1
Cookie: OwnerId={wrong_order_id}; Path=/
```

Response

```
401 Unauthorized
Content-Type: text/plain; charset=UTF-8
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

4.4.3 Unassociated user without cookie

Request

```
GET /orders/000001483b9336c4be0a0c89000a19010d347ea2
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden": {
    "guid": "4dle97e2-1497-48d5-b7a3-b3726656c4b5",
    "message": "Unauthorized: Order failed permission check",
    "code": 403,
    "details": ""
  }
}
```

4.4.4 Unexisting order

Request

```
GET /orders/000001483b9336c4be0a0c89000a19010d347ea2
Cookie: OwnerId=0b3fc7bd-6905-4de7-bddb-43d2c7365e7a; Path=/
```

Response

```
404 Not Found
Content-Type: application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "286aab08-7a2b-41a7-81fa-6530f14ed728",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

4.5 OPTIONS /orders/{order_id}

In addition to the GET method the API supports the OPTIONS method for direct browser access to the API. The format of the request is:

```
OPTIONS /orders/{order_id}
```

4.5.1 Parameters

`order_id` - *string*
The unique order Id. The full URI of each order is returned by the [POST /orders](#) call.

4.5.2 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

4.5.3 Response Status Code

200 OK
Success.

404 Not Found
The specified order does not exist.

4.5.4 Response Headers

Access-Control-Allow-Methods
A comma-separated list of request methods supported on this URI.

Access-Control-Allow-Origin
All origins are allowed. This header has value `*`.

4.6 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

5 Orders-orderId:DELETE

6 DELETE /orders/{orderId}

Deletes an order. Only new orders that were not submitted can be deleted.

6.1 Contents

- 1 DELETE /orders/{orderId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 No permission
 - ◇ 1.3.3 Unassociated user without cookie
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Order has already been submitted
 - ◆ 1.4 See also

6.2 Request

DELETE /orders/{orderId}

6.2.1 Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

6.2.2 URI Parameters

None.

6.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

6.3 Response

6.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	Order was successfully deleted.
401 Unauthorized	-	The OwnerId cookie or the Authorization header are not specified or do not permit deletion of the specified order.
403 Forbidden	Unauthorized: Order failed permission check	Access an associated order as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist or it was previously deleted.
405 Method Not Allowed	Method not allowed	The order was submitted and cannot be deleted.

6.4 Example

6.4.1 Success

Request

```
DELETE /orders/0000013ca61880fbfc068b33000a02c9d8ef861c
Cookie: OwnerId=948ce0d4-7cf0-43b6-88a5-2b3f1331b689; Path=/
```

Response

204 No Content

6.4.2 No permission

Request

```
DELETE /orders/000001483b9336c4be0a0c89000a19010d347ea2
Cookie: OwnerId=wrong_owner_id; Path=/
```

Response

```
401 Unauthorized
Content-Type: text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

6.4.3 Unassociated user without cookie

Request

```
DELETE /orders/000001483b9336c4be0a0c89000a19010d347ea2
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8
```

```
{
  "forbidden" : {
    "guid" : "bb99d8e5-cb4a-4c87-9c03-57743ef06ac7",
    "message" : "Unauthorized: Order failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

6.4.4 Order does not exist

Request

```
DELETE /orders/000001483b9336c4be0a0c89000a19010d347ea2
Cookie: OwnerId=0b3fc7bd-6905-4de7-bddb-43d2c7365e7a; Path=/
```

Response

```
404 Not Found
Content-Type: application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "3d9b09b4-9737-473b-91a5-6a8d2d212581",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

6.4.5 Order has already been submitted

Request

```
DELETE /orders/0000013ca61880fbfc068b33000a02c9d8ef861c
Cookie: OwnerId=948ce0d4-7cf0-43b6-88a5-2b3f1331b689; Path=/
```

Response

```
405 Method Not Allowed
Content-Type: application/json; charset=UTF-8
```

```
{
  "badMethod": {
    "guid": "93343aac-1451-4ed1-bca8-ac143f263cbe",
    "message": "Method not allowed",
    "code": 405,
    "details": ""
  }
}
```

6.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

7 Orders-orderId-action:POST

8 POST /orders/{orderId}/action

Performs an action like validating or submitting an order.

8.1 Contents

- 1 POST /orders/{orderId}/action
 - ◆ 1.1 Request
 - ◇ 1.1.1 Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◇ 1.1.5 Notes
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Error Response
 - ◆ 1.3 Examples
 - ◇ 1.3.1 Submit an order
 - ◇ 1.3.2 Validate an order
 - ◇ 1.3.3 Submit an order with invalid quote
 - ◇ 1.3.4 Order without contact info
 - ◇ 1.3.5 Submit an order before a service is added
 - ◇ 1.3.6 Order without domain attribute
 - ◇ 1.3.7 Unassociated user without cookie
 - ◇ 1.3.8 Order containing a domain with blacklisted word
 - ◇ 1.3.9 Domain associated with another account
 - ◆ 1.4 OPTIONS /orders/{orderId}/action
 - ◇ 1.4.1 Parameters
 - ◇ 1.4.2 Request Headers
 - ◇ 1.4.3 Response Status Code
 - ◇ 1.4.4 Response Headers
 - ◆ 1.5 See also

8.2 Request

POST /orders/{orderId}/action

8.2.1 Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

8.2.2 URI Parameters

None.

8.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

8.2.4 Request Body

```
{
  "action": "{action}",
  "actionData": {actionData}
  "quoteHash": {quoteId}
}
```

8.2.4.1 Parameters

action - *string*
The action that should be performed. Allowed values are:
validate - checks the integrity of the order.
submit - submits the order for processing.

actionData - *dictionary*
Optional. Reserved for data specific for the requested action.

quoteHash - *string*

Optional. Specifies the Id of the previously obtained quote to be used with the action.

8.2.5 Notes

If a sales agent authorization is provided, the submitted order will be assigned an agent.

8.3 Response

8.3.1 Status Code

Status Code	Error Message	Description
202 Accepted	-	The requested action was initiated successfully (in case of "submit" action). Check the status of the order for future updates.
204 No Content	-	The requested action was successfully completed (in case of "validate" action)
	Account has not been set	Cannot check contact info because no account (new or existing) has been set in the order.
		Cannot add test attribute because account has not been set.
400 Bad Request	No {attribute_name} attribute set.	A required account attribute has not been set.
	Contact info type {contact_type} is not set	A required contact info type has not been set.
	All plans in the order must contain at least one product.	A product does not contain any service.
	Missing plugin data for service type(s): set([u'core.www'])	Service is missing attribute domain .
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to perform actions on this order.
403 Forbidden	Unauthorized: Action failed permission check	An unassociated user cannot validate or submit order.
404 Not Found	Resource not found	The specified order does not exist.
		Domain-dependent services:
	Cannot create domain alias to the same domain name.	Duplicate domain.
	Domain {domain_name} is associated with another account	One of the domains to be ordered is already owned by another account
409 Conflict	A domain in the order contains a restricted word	One of the domains contains blacklisted word.
	Contains a blacklisted domain	One of the domains to be ordered is blacklisted.
	Transfer is already in progress for this domain	A transfer is in progress for a domain.
	Email domain alias service:	A domain alias would produce impossible to delivery loops
	Domain {domain_name} has circular forwards to alias {alias_name}	There is an email forwarder from the target domain name to a mailbox of the domain alias with the same username
		There is an email forwarder from the domain alias to a mailbox of the target domain name with the same username
502 Bad Gateway	-	Unexpected backend response. Cannot submit or validate order.

8.3.2 Response Body

Depends on the result.

8.3.2.1 Error Response

```
{
  "{errorType}": {
    "message": "{errorMessage}",
    "code": {errorCode},
    "details": "{errorDetails}"
  }
}
```

8.4 Examples

8.4.1 Submit an order

Request

```
POST /orders/0000013ca61880fbfc068b33000a02c9d8ef861c/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId=948ce0d4-7cf0-43b6-88a5-2b3f1331b689; Path=/

{
  "action": "submit"
}
```

Response

202 Accepted

8.4.2 Validate an order

Request

```
POST /orders/0000013ca61880fbfc068b33000a02c9d8ef861c/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId=948ce0d4-7cf0-43b6-88a5-2b3f1331b689; Path=/
```

```
{
  "action": "validate"
}
```

Response

204 No Content

8.4.3 Submit an order with invalid quote

Request

```
POST /orders/0000013ca61880fbfc068b33000a02c9d8ef861c/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId=948ce0d4-7cf0-43b6-88a5-2b3f1331b689; Path=/
```

```
{
  "action" : "submit",
  "quoteHash" : "invalid_quote_id"
}
```

Response

400 Bad Request

```
{
  "computeFault": {
    "message": "Account has not been set",
    "code": 400,
    "details": ""
  }
}
```

8.4.4 Order without contact info

Request

```
POST /orders/{orderId}/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId={ownerId}; Path=/
```

```
{
  "action" : "submit",
  "quoteHash" : "{quoteId}"
}
```

Response

400 Bad Request

```
{
  "computeFault": {
    "guid": "32adf6a1-e710-4362-83c7-7743c7097db9",
    "message": "Contact info type \"regular\" is not set",
    "code": 400,
    "details": ""
  }
}
```

8.4.5 Submit an order before a service is added

Request

```
POST /orders/{orderId}/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId={ownerId}; Path=/
```

```
{
  "action" : "submit",
  "quoteHash" : "{quoteId}"
}
```

Response

400 Bad Request

```
{
  "computeFault": {
    "guid": "7ef492af-3ebe-4334-9e37-5b0365977ef2",
    "message": "All plans in the order must contain at least one product.",
    "code": 400,
    "details": ""
  }
}
```

8.4.6 Order without domain attribute

Request

```
POST /orders/{orderId}/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId={ownerId}; Path=/
```

```
{
  "action" : "submit",
  "quoteHash" : "{quoteId}"
}
```

```
}
```

Response

400 Bad Request

```
{
  "computeFault": {
    "guid": "bc2e3c0c-b4da-43e2-b576-7801180bfb6e",
    "message": "Missing plugin data for service type(s): set ([u'core.www'])",
    "code": 400,
    "details": ""
  }
}
```

8.4.7 Unassociated user without cookie

Request

POST /orders/000001483b9336c4be0a0c89000a19010d347ea2/action
Authorization: {unassociated_user_authorization}
Content-Type: application/json; charset=UTF-8

```
{
  "action": "validate"
}
```

Response

403 Forbidden
Content-Type: application/json; charset=UTF-8

```
{
  "forbidden": {
    "guid": "4d1e97e2-1497-48d5-b7a3-b3726656c4b5",
    "message": "Unauthorized: Order failed permission check",
    "code": 403,
    "details": ""
  }
}
```

8.4.8 Order containing a domain with blacklisted word

Request

POST /orders/{orderId}/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId={ownerId}; Path=/

```
{
  "action" : "submit",
  "quoteHash" : "{quoteId}"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "guid": "bfb2988f-d745-4b2a-9eff-f2deed3451db",
    "message": "A domain in the order contains a restricted word",
    "code": 409,
    "details": ""
  }
}
```

8.4.9 Domain associated with another account

Request

POST /orders/{orderId}/action
Content-Type:application/json; Charset=UTF-8
Cookie: OwnerId={ownerId}; Path=/

```
{
  "action" : "submit",
  "quoteHash" : "{quoteId}"
}
```

Response

409 Conflict

```
{
  "conflict": {
    "guid": "3fcd11ec-ffb9-47be-b14e-53a74ecb7de2",
    "message": "Domain ng-test-hwus-petre-140718a.com is associated with another account",
    "code": 409,
    "details": ""
  }
}
```

8.5 OPTIONS /orders/{orderId}/action

In addition to the POST method the API supports the OPTIONS method for direct browser access to the API. The format of the request is:

OPTIONS /orders/{orderId}/action

8.5.1 Parameters

orderId - *string*

The unique order Id. The full URI of each order is returned by the [POST /orders](#) call.

8.5.2 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

8.5.3 Response Status Code

200 OK

Success

404 Not Found

The specified order does not exist.

8.5.4 Response Headers

Access-Control-Allow-Methods

A comma-separated list of request methods supported on this URI.

Access-Control-Allow-Origin

All origins are allowed. This header has value *.

8.6 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

9 Order Shorthand

10 /order

A shorthand that allows a user to access directly the current open order with the appropriate OwnerId.

10.1 Contents

- 1 /order
 - ◆ 1.1 Request Headers
 - ◆ 1.2 Order Shorthand
 - ◆ 1.3 Available Methods and Child Resources
 - ◆ 1.4 Implicit Order Creation
 - ◆ 1.5 Response Headers
 - ◆ 1.6 Additional Status Code
 - ◇ 1.6.1 Status Code
 - ◆ 1.7 OwnerId cookie
 - ◇ 1.7.1 Definition and purpose
 - ◇ 1.7.2 Order states and OwnerId cookie life cycle
 - 1.7.2.1 Fresh client session
 - 1.7.2.2 Subsequent calls to order shorthand resources/subresources
 - 1.7.2.3 Order instance deletion or submission
 - 1.7.2.4 Refreshing the OwnerId cookie after the order gets deleted or submitted
 - ◇ 1.7.3 CORS (Cross-origin resource sharing) and OwnerId cookie
 - ◆ 1.8 Examples
 - ◇ 1.8.1 Implicit Creation
 - ◇ 1.8.2 Alternate Hypermedia
 - ◇ 1.8.3 Accessing a Child Resource
 - ◆ 1.9 See also

10.2 Request Headers

Cookie
Required. Any call trying to use the shorthand notation has to have a valid **OwnerId** cookie set, with the exception of calls that will create a new order implicitly. A valid **Set-Cookie** header is returned with the response of either implicit or explicit order creation calls.

10.3 Order Shorthand

Using `/order` will try to find an order with status *new* that is associated with the **OwnerId** specified in the cookie header sent with the request. The value of the cookie may be set by either explicit or implicit order creation.

10.4 Available Methods and Child Resources

The shorthand supports all the methods that are available when using the `/orders/{orderId}` notation and all of the order's child resources are also accessible using the shorthand. A GET call to the order shorthand itself will include an *alternate* link to the explicit URL of the order in the hypermedia section. If an order is submitted using the shorthand URL, a **Location** header containing the explicit location of the order will be returned with a successful response for future reference.

10.5 Implicit Order Creation

If there is no current order associated with the active user, that is not submitted, a PUT or POST call to a child resource will implicitly create a new order for the user and will populate the data of the actual call to the new order. The final response of the implicitly created order will contain additional **Set-Cookie** header as described below. A GET or OPTIONS call to a non-existing order will not create it implicitly, but will return response with **404** status code.

10.6 Response Headers

Set-Cookie
If an order is created implicitly while accessing a child resource, the final response will include a **Set-Cookie** header containing an **OwnerId** identifier, in a similar way to explicit creation of an order using `POST /orders`. The cookie will be used to identify the end user, if no existing account is associated with the order, and to find which is the currently open order associated with the end client.

10.7 Additional Status Code

In addition to the response status codes that can be returned by various `/orders/{orderId}` calls, the order shorthand may also return:

10.7.1 Status Code

Status Code	Error Message	Description
405 Method Not Allowed	-	Trying to create a shortcut <code>/order</code> directly with PUT or POST
409 Conflict	-	There is already a new order associated with the same OwnerId and a second order cannot be created until the existing one is either submitted or deleted..

10.8 OwnerId cookie

10.8.1 Definition and purpose

The Order API defines the so called order shorthand. The Order shorthand is exposing all Order API resources and subresources, without supplying the order id. This means that at given time only one order instance is available to a client session. The Order API identifies the order instance by using

"OwnerId" cookie.

10.8.2 Order states and OwnerId cookie life cycle

10.8.2.1 Fresh client session

When client with fresh session starts using the Order API through the shorthand the order API is designed to create order instance implicitly. The created order instance is in "new" state. When the order instance is created, the Order API will return a Set-Cookie HTTP header for setting the "OwnerId" cookie into the client session.

10.8.2.2 Subsequent calls to order shorthand resources/subresources

Once the OwnerId has been set to the client session, the client should start providing the OwnerId cookie in all subsequent calls to Order API. Receiving request with OwnerId cookie will make Order API search for order instance in "new" state, identified by the OwnerId

10.8.2.3 Order instance deletion or submission

From "new" state the order instance can be deleted or submitted for provisioning. If the order is submitted its state will be changed to "placed".

10.8.2.4 Refreshing the OwnerId cookie after the order gets deleted or submitted

Subsequent calls, which identifies deleted or "placed" order instance will trigger Order API to implicitly create a new order instance and respond with Set-Cookie HTTP header with a new OwnerId value. The client session should start using the new OwnerId value when calling the Order API.

10.8.3 CORS (Cross-origin resource sharing) and OwnerId cookie

All browser based clients should abide the security policies enforced by the browsers itself. One such policy is the same origin security policy. To overcome the same origin security policy the browsers are providing the so called CORS (Cross-origin resource sharing) mechanism - http://en.wikipedia.org/wiki/Cross-origin_resource_sharing.

Basically the CORS mechanism makes the browsers to "disallow" requests which are originating from domain that does not match one of the Access-Control-Allow-Origin response header values. Ideally the Public API should allow calls, originated from all domains, by setting the Access-Control-Allow-Origin response header to * (Asterisk). Unfortunately when the requests are containing cookies the CORS mechanism dictates that the Access-Control-Allow-Origin should be very specific to the allowed domains(https://developer.mozilla.org/en-US/docs/HTTP/Access_control_CORS?redirectlocale=en-US&redirectslug=HTTP_access_control#Requests_with_credentials) meaning that your domain should be set into the Public API allowed domains. If your domain is not set to the Public API allowed domains, then please contact your sales or technical person and ask them to do that for you.

10.9 Examples

10.9.1 Implicit Creation

Request

```
PUT /order/account
Content-Type: application/json; charset=UTF-8
Authorization: {Base64-encoded username & password string}
```

```
{
  "currency": "USD",
  "language": "en-US"
}
```

Response

```
200 OK
Set-Cookie: OwnerId=4d84cd13-bbb3-46ba-a40c-8988351e3681; Path=/order
Set-Cookie: OwnerId=4d84cd13-bbb3-46ba-a40c-8988351e3681; Path=/orders
```

10.9.2 Alternate Hypermedia

Request

```
GET /order
Authorization: {Base64-encoded username & password string}
Cookie: OwnerId=4d84cd13-bbb3-46ba-a40c-8988351e3681; Path=/order
```

Response

```
200 OK
Content-Type: application/json; charset=UTF-8
{
  "order": {
    "OwnerId": "4d84cd13-bbb3-46ba-a40c-8988351e3681"
  },
  "links": {
    "self": { "href": "https://api.hostway.com/order/", "rel": "self" },
    "alternate": { "href": "https://api.hostway.com/orders/{orderId}/", "rel": "alternate" }
  }
}
```

10.9.3 Accessing a Child Resource

Request

```
GET /order/product/{productId}
Authorization: {Base64-encoded username & password string}
Cookie: OwnerId=4d84cd13-bbb3-46ba-a40c-8988351e3681; Path=/order
```

Response

200 OK
Content-Type: application/json; charset=UTF-8

```
{
  "status": "new",
  "services": "https://api.hostway.com/order/product/{productId}/services",
  "offering": "https://api.hostway.com/productSpecifications/{productSpecId}/offerings/{offering}",
  "links": [
    { "href": "https://api.hostway.com/order/product/{productId}/", "rel": "self" }
  ]
}
```

10.10 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

11 Orders-orderId-attributes:PUT

12 PUT /orders/{orderId}/attributes

Set the list of attributes for an order.

12.1 Contents

- 1 PUT /orders/{orderId}/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Set order attributes correctly
 - ◇ 1.3.2 Set order attributes with invalid key
 - ◇ 1.3.3 Set order attributes with malformed body
 - ◇ 1.3.4 Set order attributes without authenticating
 - ◇ 1.3.5 Unassociated user without cookie
 - ◇ 1.3.6 Set order attributes of unexisting order
 - ◆ 1.4 See also

12.2 Request

PUT /orders/{orderId}/attributes

12.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

12.2.2 URI Parameters

None.

12.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

12.2.4 Request Body

```
[
  {
    "name": "{attributeName}",
    "value": "{attributeValue}"
  },
  {
    "name": "{attributeName}",
    "value": "{attributeValue}"
  }
]
```

12.2.4.1 Parameters

attributeName - *string*

The unique name of the attribute. The list of supported attribute names is specific to the franchise. The common attributes include:
AffiliateId - identifies an affiliate.

attributeValue - *string*

The value of the attribute max 200 characters. Should adhere to the rules for the attribute specified by the name.

12.3 Response

12.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The order attributes were successfully set.
400 Bad Request	POST data error Could not find MetaData Type {attribute_key} for franchise {franchise}.	The request body format is invalid. The attribute name is not supported by the franchise, the attribute value is invalid (e.g: too long, contains invalid characters, etc).
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to set order attributes.
403 Forbidden	Unauthorized: Attributes failed permission check	Set order attributes as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist.
502 Bad Gateway	-	A critical (unknown) error occurred.

12.4 Example

12.4.1 Set order attributes correctly

Request

```
PUT /orders/{orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

[ { "name": "_utma", "value": "utma_val" }, { "name": "_utmb", "value": "utmb_val" } ]
```

Response

204 No Content

12.4.2 Set order attributes with invalid key

Request

```
PUT /orders/{orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

[ { "name": "nonexistent_key", "value": "some_value" } ]
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "computeFault": {
    "guid": "5b01960d-4110-43f0-b58f-d3178db61c6d",
    "message": "Could not find MetaData Type nonexistent_key for franchise hostway_us_main",
    "code": 400, "details": ""
  }
}
```

12.4.3 Set order attributes with malformed body

Request

```
PUT /orders/{orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

[ { "_utma": "utma_val" } ]
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "badRequest": {
    "guid": "9a6b18b4-66cf-4b5e-bee6-f4f44c0b9450",
    "message": "POST data error",
    "code": 400,
    "details": {
      "0.name": "Required",
      "0.value": "Required"
    }
  }
}
```

12.4.4 Set order attributes without authenticating

Request

```
PUT /orders/{orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

[ { "name": "nonexistent_key", "value": "some_value" } ]
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```


401 Unauthorized
This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

12.4.5 Unassociated user without cookie

Request

```
PUT /orders/{orderId}/attributes
Authorization: {unassociated_user_authorization}

[ {"name": "_utma", "value": "utma_val"}, {"name": "_utmb", "value": "utmb_val"} ]
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden": {
    "guid": "4dle97e2-1497-48d5-b7a3-b3726656c4b5",
    "message": "Unauthorized: Attributes failed permission check",
    "code": 403,
    "details": ""
  }
}
```

12.4.6 Set order attributes of unexisting order

Request

```
PUT /orders/{orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

[ {"_utma": "utma_val"} ]
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "6273e2fb-6efd-4294-9281-7alea664cf11",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

12.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

13 Orders-orderId-attributes:GET

14 GET /orders/{orderId}/attributes

Get the list of attributes for an order.

14.1 Contents

- 1 GET /orders/{orderId}/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully retrieve order attributes
 - ◇ 1.3.2 Wrong authorization
 - ◇ 1.3.3 Unassociated user without cookie
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 No attributes set
 - ◆ 1.4 See also

14.2 Request

GET /orders/{orderId}/attributes

14.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

14.2.2 URI Parameters

None.

14.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

14.3 Response

14.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	Successfully retrieved order attributes.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to retrieve order attributes.
403 Forbidden	Unauthorized: Attributes failed permission check	Access order attributes as an authenticated user, not associated with the order.
404 Not Found	Resource not found MetaData is missing.	Order does not exist. Attributes have not been set.
502 Bad Gateway	Unable to get attributes	Unexpected (backend) error. Unable to retrieve order attributes.

14.3.2 Response Body

```
{
  "list": [
    {
      "name": "{attributeName}",
      "value": "{attributeValue}"
    },
    ...
  ]
}
```

```

    ],
    "links": [
      { "href": "https://api.hostway.com/orders/{orderId}/attributes/", "rel": "self" }
    ]
  }
}

```

14.3.2.1 Parameters

attributeName - *string*
The unique name of the attribute.

attributeValue - *string*
The value of the attribute.

links - *list*
[Hypermedia](#) for this resource.

14.4 Example

14.4.1 Successfully retrieve order attributes

Request

```

GET /orders/000001485a3c75c8569447b3007f000000010001/attributes
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

200 OK
Content-Type : application/json; charset=UTF-8

{
  "list" : [ {
    "name" : "_utmb",
    "value" : "utmb_val"
  }, {
    "name" : "_utma",
    "value" : "utma_val"
  } ],
  "links" : [ {
    "href" : "https://api.hostway.com/orders/000001485a3c75c8569447b3007f000000010001/attributes/",
    "rel" : "self"
  } ]
}

```

14.4.2 Wrong authorization

Request

```

GET /orders/{orderId}/attributes
Cookie: OwnerId={wrong_owner_id}; Path=/

```

Response

```

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested.
Either you supplied the wrong credentials (e.g., bad password),
or your browser does not understand how to supply the credentials required.

```

14.4.3 Unassociated user without cookie

Request

```

GET /orders/{orderId}/attributes
Authorization: {unassociated_user_authorization}

```

Response

```

403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden": {
    "guid": "4d1e97e2-1497-48d5-b7a3-b3726656c4b5",
    "message": "Unauthorized: Attributes failed permission check",
    "code": 403,
    "details": ""
  }
}

```

14.4.4 Order does not exist

Request

```

GET /orders/{wrong_orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

404 Not found

```

Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "ee20516d-011e-44ea-99d2-ae7a2b6fe99a",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

14.4.5 No attributes set

Request

GET /orders/{orderId}/attributes
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "ee20516d-011e-44ea-99d2-ae7a2b6fe99a",
    "message": "MetaData is missing.",
    "code": 404,
    "details": ""
  }
}
```

14.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

15 Orders-orderId-account:PUT

16 PUT /orders/{orderId}/account

Assign an Account to an Order.

16.1 Contents

- 1 PUT /orders/{orderId}/account
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Request Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - ◆ 1.3 Example
 - ◇ 1.3.1 The currency is not supported by the franchise
 - ◇ 1.3.2 Missing currency
 - ◇ 1.3.3 Missing currency and language
 - ◇ 1.3.4 No authorization
 - ◇ 1.3.5 Unassociated user without cookie
 - ◇ 1.3.6 A test partner agent assigns a non-test account
 - ◇ 1.3.7 Inconsistent currency
 - ◆ 1.4 See also

16.2 Request

PUT /orders/{orderId}/account

16.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

16.2.2 URI Parameters

None.

16.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

16.2.4 Request Body

Request Body for adding a new Account to the Order

```
{
  "currency": "{currency}",
  "language": "{language}"
}
```

Request Body for adding an existing Account to the Order

```
{
  "accountNumber": "{accountNumber}"
}
```

16.2.4.1 Request Parameters

currency - *string*

An ISO-4217[1] currency code assigned to the account.

language - *string*

An IETF[2] language tag (ex. en, en-CA, en-US, etc.) specifying account's language.

accountNumber - *string*

The unique account number for an existing account.

16.3 Response

16.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The account was successfully set.
400 Bad Request	POST data error Currency {unsupported_currency} not allowed for this franchise Language {unsupported_language} not allowed for this franchise	The request body format is invalid. Missing language or currency. The currency is not supported by the franchise. The language is not supported by the franchise.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to perform add account for this order.
403 Forbidden	Trying to add a non-test account with invalid credentials: test partner agents cannot add non-test accounts Unauthorized: OrderAccount failed permission check	-
409 Conflict	Trying to add an account with inconsistent currency: the order has already products with {product_currency} while the account you are adding uses {account_currency}	Attempt to set currency that is different from currencies of the products or that of the existing account.
502 Bad Gateway	-	Unexpected backend response.

16.3.2 Response Body

None.

16.4 Example

16.4.1 The currency is not supported by the franchise

Request

```
PUT /orders/{orderId}/account
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "currency": "BGN",
  "language": "en-US"
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "computeFault" : {
    "guid" : "ee39580b-8c74-4c0a-aall-4de5864d8e51",
    "message" : "Currency BGN not allowed for this franchise",
    "code" : 400,
    "details" : ""
  }
}
```

16.4.2 Missing currency

Request

```
PUT /orders/{orderId}/account
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "language": "en-US"
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "badRequest": {
    "guid": "6f96c728-e6b6-4ca3-bd97-f931d2cd326c",
    "message": "POST data error",
    "code": 400, "details": {
      "currency": "Required"
    }
  }
}
```

16.4.3 Missing currency and language

Request

```
PUT /orders/{orderId}/account
Cookie: OwnerId={owner_id}; Path=/
```

```
{ }
```

Response


```

400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "badRequest" : {
    "guid" : "f4b6f4b6-fa15-4649-9c31-ec9b7b8150db",
    "message" : "POST data error",
    "code" : 400,
    "details" : {
      "accountNumber" : "Either accountNumber or both currency AND language should be provided"
    }
  }
}

```

16.4.4 No authorization

Request

```
PUT /orders/{orderId}/account
```

```

{
  "currency": "USD",
  "language": "en-US"
}

```

Response

```

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

16.4.5 Unassociated user without cookie

Request

```

PUT /orders/{orderId}/account
Authorization: {unassociated_user_authorization}

```

```

{
  "accountNumber": "smith909090"
}

```

Response

```

403 Forbidden
Content-Type: application/json; charset=UTF-8

```

```

{
  "forbidden" : {
    "guid" : "f9583d13-1ad3-4ea9-bf26-a5315af5f234",
    "message" : "Unauthorized: OrderAccount failed permission check",
    "code" : 403,
    "details" : ""
  }
}

```

16.4.6 A test partner agent assigns a non-test account

Request

```

PUT /orders/{orderId}/account
Authorization: {test_partner_agent_authorization}
Content-Type : application/json; charset=UTF-8
Cookie: OwnerId={owner_id}; Path=/

```

```

{
  "accountNumber": "smith909090"
}

```

Response

```

403 Forbidden
Content-Type : application/json; charset=UTF-8

```

```

{
  "forbidden" : {
    "guid" : "7a7d4ce6-241c-44a2-a2e3-cefb26f33a69",
    "message" : "Trying to add a non-test account with invalid credentials: test partner agents cannot add non-test accounts",
    "code" : 403,
    "details" : ""
  }
}

```

16.4.7 Inconsistent currency

Request

```

PUT /orders/{orderId}/account
Cookie: OwnerId={owner_id}; Path=/

```

```

{
  "currency": "CAD",
  "language": "en-US"
}

```

Response

409 Conflict

Content-Type : application/json; charset=UTF-8

```
{
  "conflict" : {
    "guid" : "8ec26107-a368-4809-8590-3523d9178893",
    "message" : "Trying to add an account with inconsistent currency: the order has already products with USD while the account you are adding has products with EUR",
    "code" : 409,
    "details" : ""
  }
}
```

16.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

17 Orders-orderId-account:GET

18 GET /orders/{orderId}/account

Get details of an Account in a given Order. It must be **added** to an order before details can be retrieved.

18.1 Contents

- 1 GET /orders/{orderId}/account
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Wrong authorization
 - ◇ 1.3.2 Unassociated user without cookie
 - ◇ 1.3.3 Account has not been set
 - ◇ 1.3.4 Order does not exist
 - ◆ 1.4 See also

18.2 Request

GET /orders/{orderId}/account

18.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the **POST /orders** call.

18.2.2 URI Parameters

None.

18.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

18.3 Response

18.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to perform add account for this order.
403 Forbidden	Unauthorized: OrderAccount failed permission check	Access order account as an authenticated user, not associated with the order.
404 Not Found	Resource not found	An account has not been added to the given order. The order does not exist.

18.3.2 Response Body

```
{
  "status": "{status}",
  "paymentInfo": "https://api.hostway.com/orders/{orderId}/account/paymentInfo/",
  "links": [
    { "href": "https://api.hostway.com/orders/{orderId}/account/", "rel": "self" }
  ]
}
```

```

"language": "{language}",
"number": "{accountId}",
"currency": "{currency}",
"products": "https://api.hostway.com/orders/{orderId}/account/products/",
"user": "https://api.hostway.com/orders/{orderId}/account/user/",
"attributes": "https://api.hostway.com/orders/{orderId}/account/attributes/",
"contactInfo": "https://api.hostway.com/orders/{orderId}/account/contactInfo/",
}

```

18.3.2.1 Parameters

currency - *string*
An ISO-4217[1] currency code assigned to the account.

language - *string*
An IETF[2] language tag (ex. en, en-CA, en-US, etc.) specifying account's language.

number - *string*
The account's Id.

status - *string*
The account's current status. Accounts that have not been provisioned will have a status of "new".

attributes - *string*
A link to the account's [attributes](#).

contactInfo - *string*
A link to the account's [contact info](#).

paymentInfo - *string*
A link to the account's [payment information](#).

user - *string*
A link to the account's [user](#).

products - *string*
A link to the account's [products](#).

links - *list*
[Hypermedia](#) for this resource.

18.4 Example

18.4.1 Wrong authorization

Request

```

GET /orders/{orderId}/account
Cookie: OwnerId={wrong_owner_id}; Path=/

```

Response

```

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

18.4.2 Unassociated user without cookie

Request

```

GET /orders/{orderId}/account
Authorization: {unassociated_user_authorization}

```

Response

```

403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden" : {
    "guid" : "95646dcf-55cd-46cb-9bef-e1ef5d06f6c8",
    "message" : "Unauthorized: OrderAccount failed permission check",
    "code" : 403,
    "details" : ""
  }
}

```

18.4.3 Account has not been set

Request

```

GET /orders/{orderId}/account
Cookie: OwnerId={owner_id}; Path=/

```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "9c2bf07d-4e74-4434-9d3e-77d57408d839",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

18.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "402282af-9f53-4973-8437-469087465843",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

18.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

19 Orders-orderId-account-attributes:PUT

20 PUT /orders/{orderId}/account/attributes

Set the list of attributes for an account in a given order.

20.1 Contents

- 1 PUT /orders/{orderId}/account/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - ◆ 1.3 Example
 - ◇ 1.3.1 Set valid account attribute
 - ◇ 1.3.2 Set bad account attributes
 - ◇ 1.3.3 Set an attribute with too long value
 - ◇ 1.3.4 Set too long Partner Account ID value
 - ◇ 1.3.5 Set attributes with wrong OwnerId
 - ◇ 1.3.6 Unassociated user without cookie
 - ◇ 1.3.7 Set existing Partner Account ID
 - ◇ 1.3.8 Account has not been set
 - ◆ 1.4 See also

20.2 Request

PUT /orders/{orderId}/account/attributes

20.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

20.2.2 URI Parameters

None.

20.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

20.2.4 Request Body

```
[
  {
    "name": "{attributeName}",
    "value": "{attributeValue}"
  },
  {
    "name": "{attributeName}",
```



```

    "value": "{attributeValue}"
  }
}

```

20.2.4.1 Parameters

attributeName - *string*

The unique name of the attribute. The list of supported attribute names is specific to the franchise. The common attributes include:
partner_account_id - unique account identifier in the partner system. The value should be unique within the franchise.

attributeValue - *string*

The value of the attribute max 200 characters. Should adhere to the rules for the attribute specified by the name.

The value of the "partner_account_id" attribute is max 100 characters. Allowed characters are alphanumeric characters, underscore, dot and dash.

20.3 Response

20.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The account attributes were successfully set.
	POST data error	The request body format is invalid and all attributes must have less than 200 characters.
400 Bad Request	Not allowed or not existing MetaData Type Partner Account ID cannot exceed 100 characters	Setting some bad account attributes
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to add attributes for this account.
403 Forbidden	Unauthorized: Attributes failed permission check	Access order account attributes as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist.
409 Conflict	Account ID already in use	Attribute value for Partner Account ID, supposed to be unique, is already in use.
500 Internal Server Error	-	Account has not been set for this order.
502 Bad Gateway	-	A critical (unknown) error occurred.

20.3.2 Response Body

None.

20.4 Example

20.4.1 Set valid account attribute

Request

```

PUT /orders/{orderId}/account/attributes
Cookie: OwnerId={owner_id}; Path=/

```

```

[
  {
    "name": "partner_account_id",
    "value": "paccid_050914054136"
  }
]

```

Response

204 No Content

20.4.2 Set bad account attributes

Request

```

PUT /orders/{orderId}/account/attributes
Cookie: OwnerId={owner_id}; Path=/

```

```

[
  {
    "name": "attribute_a",
    "value": "value_a"
  },
  {
    "name": "attribute_b",
    "value": "value_b"
  }
]

```

Response

```

400 Bad Request
Content-Type : application/json; charset=UTF-8

```

```

{
  "computeFault": {
    "guid": "5268a14c-ced6-4f32-87ee-aa6709414396",
    "message": "Not allowed or not existing MetaData Type",
    "code": 400,
    "details": ""
  }
}

```



```
403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden" : {
    "guid" : "66f63a81-52e9-4ec6-a50a-42acebc021e7",
    "message" : "Unauthorized: Attributes failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

20.4.7 Set existing Partner Account ID

Request

```
PUT /orders/{orderId}/account/attributes
Cookie: OwnerId={owner_id}; Path=/

[
  {
    "name": "partner_account_id",
    "value": "ext_140213131348"
  }
]
```

Response

```
409 Conflict
Content-Type : application/json; charset=UTF-8

{
  "conflict": {
    "guid": "a8d38abe-1f68-49c5-bafe-29894671ed06",
    "message": "Account ID already in use",
    "code": 409,
    "details": ""
  }
}
```

20.4.8 Account has not been set

Request

```
PUT /orders/{orderId}/account/attributes
Cookie: OwnerId={owner_id}; Path=/

[
  {
    "name": "partner_account_id",
    "value": "paccid_050914054136"
  }
]
```

Response

```
500 Internal Server Error
Content-Type : application/json; charset=UTF-8

{
  "computeFault" : {
    "guid" : "a4eae57d-b172-45ff-ae6e-474a8b6061a0",
    "timestamp" : "2014-09-10 10:12:41",
    "code" : 500,
    "errorRefId" : "a4eae57d-b172-45ff-ae6e-474a8b6061a0"
  }
}
```

20.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

21 Orders-orderId-account-attributes:GET

22 GET /orders/{orderId}/account/attributes

Get the list of attributes for an account in a given order.

22.1 Contents

- 1 GET /orders/{orderId}/account/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Get order information
 - ◇ 1.3.2 Get attributes with wrong OwnerId
 - ◇ 1.3.3 Unassociated user without cookie
 - ◇ 1.3.4 Get attributes of unset account
 - ◆ 1.4 See also

22.2 Request

GET /orders/{orderId}/account/attributes

22.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

22.2.2 URI Parameters

None.

22.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

22.3 Response

22.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to get attributes for this account.
403 Forbidden	Unauthorized: Attributes failed permission check	Access order account attributes as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist.
	MetaData is missing. Make sure the account is set before querying attributes.	An account should be set before getting info for attributes.

22.3.2 Response Body

```
{
  "list": [
    {
      "name": "{attributeName}",
      "value": "{attributeValue}"
    }
  ]
}
```

```

    },
    ...
  ],
  "links": [
    { "href": "https://api.hostway.com/orders/{orderId}/account/attributes/", "rel": "self" }
  ]
}

```

22.3.2.1 Parameters

attributeName - *string*
The unique name of the attribute.

attributeValue - *string*
The value of the attribute.

links - *list*
[Hypermedia](#) for this resource.

22.4 Example

22.4.1 Get order information

Request

```

GET /orders/{orderId}/account/attributes
Cookie: OwnerId={ownerId}; Path=/

```

Response

```

200 OK
Content-Type: application/json; charset=UTF-8

{
  "list" : [ {
    "name" : "partner_account_id",
    "value" : "paccid_050914054136"
  } ],
  "links" : [ {
    "href" : "https://api.hostway.com/orders/{ownerId}/account/attributes/",
    "rel" : "self"
  } ]
}

```

22.4.2 Get attributes with wrong OwnerId

Request

```

GET /orders/{orderId}/account/attributes
Cookie: OwnerId={wrong_order_id}; Path=/

```

Response

```

401 Unauthorized
Content-Type: text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested.
Either you supplied the wrong credentials (e.g., bad password),
or your browser does not understand how to supply the credentials required.

```

22.4.3 Unassociated user without cookie

Request

```

GET /orders/{orderId}/account/attributes
Authorization: {unassociated_user_authorization}

```

Response

```

403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden" : {
    "guid" : "66f63a81-52e9-4ec6-a50a-42acebc021e7",
    "message" : "Unauthorized: Attributes failed permission check",
    "code" : 403,
    "details" : ""
  }
}

```

22.4.4 Get attributes of unset account

Request

```

GET /orders/{orderId}/account/attributes
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

404 Not Found
Content-Type : application/json; charset=UTF-8

```

```
{
  "itemNotFound": {
    "guid": "0068a205-0c4c-4105-9a14-dafe313bfc3a",
    "message": "MetaData is missing. Make sure the account is set before querying attributes.",
    "code": 404,
    "details": ""
  }
}
```

22.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

23 Orders-orderId-account-attributes:DELETE

24 DELETE /orders/{orderId}/account/attributes

Remove all attributes for an account in a given order.

24.1 Contents

- 1 DELETE /orders/{orderId}/account/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully delete all attributes
 - ◇ 1.3.2 Delete attributes with wrong OwnerId
 - ◇ 1.3.3 Unassociated user without cookie
 - ◆ 1.4 See also

24.2 Request

DELETE /orders/{orderId}/account/attributes

24.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

24.2.2 URI Parameters

None.

24.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

24.3 Response

24.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The account attributes were successfully deleted.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to delete attributes for this account.
403 Forbidden	Unauthorized: Attributes failed permission check	Access order account attributes as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist.

24.4 Example

24.4.1 Successfully delete all attributes

Request

```
DELETE /orders/{orderId}/account/attributes
Cookie: OwnerId={owner_id}; Path=/
```

Response

204 No Content

24.4.2 Delete attributes with wrong OwnerId

Request

```
DELETE /orders/{orderId}/account/attributes
Cookie: OwnerId={wrong_order_id}; Path=/
```

Response

```
401 Unauthorized
Content-Type: text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

24.4.3 Unassociated user without cookie

Request

```
DELETE /orders/{orderId}/account/attributes
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8
```

```
{
  "forbidden" : {
    "guid" : "66f63a81-52e9-4ec6-a50a-42acebc021e7",
    "message" : "Unauthorized: Attributes failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

24.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

25 Orders-orderId-account-contactInfo-contactType:PUT

26 PUT /orders/{orderId}/account/contactInfo/{contactType}

Set the account contact details for a given contact type in an order.

26.1 Contents

- 1 PUT
/orders/{orderId}/account/contactInfo/{contactType}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - ◆ 1.3 Example
 - ◇ 1.3.1 Set bad contact info values
 - ◇ 1.3.2 Set bad contact info values 2
 - ◇ 1.3.3 Set contact info with wrong OwnerId
 - ◇ 1.3.4 Unassociated user without cookie
 - ◇ 1.3.5 Set contact info in non-existent order
 - ◇ 1.3.6 Set contact info on an unset account
 - ◆ 1.4 See also

26.2 Request

PUT /orders/{orderId}/account/contactInfo/{contactType}

26.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

contact_type - *string*

Contact Type (regular, billing, administrator or technical)

26.2.2 URI Parameters

None.

26.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

26.2.4 Request Body

```
{
  "name": {
    "salutation": "{salutation}",
    "firstName": "{firstname}",
    "middleName": "{middleName}",
    "lastName": "{lastName}",
    "company": "{company}"
  },
  "address": {
    "street1": "{street1}",
    "street2": "{street2}",
    "city": "{city}",
    "stateOrProvince": "{stateOrProvince}",
    "postalCode": "{postalCode}",
    "countryCode": "{countryCode}"
  },
  "contactMedia": {
    "phone1": "{phone1}",
    "phone2": "{phone2}",
    "fax": "{fax}",
    "email1": "{email1}",
    "email1Format": "{html|text}",
    "email2": "{email2}",
    "email2Format": "{html|text}"
  }
}
```

26.2.4.1 Parameters

salutation - *string*
(*OPTIONAL*)
May contain one of the salutations provided by [GET /salutations](#)

firstName - *string*
Required string max 50 characters. May contain only alphanumerics, white space and the following characters: -.'

middleName - *string*
Optional string max 50 characters. May contain only alphanumerics, white space and the following characters: -.'

lastName - *string*
Required string max 50 characters. May contain only alphanumerics, white space and the following characters: -.'

company - *string*
Optional string max 200 characters. May contain only alphanumerics, white space and the following characters: -.'

street1 - *string*
Required string max 100 characters. May contain only alphanumerics, white space and the following characters: -.'

street2 - *string*
Optional string max 100 characters. May contain only alphanumerics, white space and the following characters: -.'

city - *string*
Required string max 50 characters. May contain only alphanumerics, white space and the following characters: -.'

stateOrProvince - *string*
Required string max 20 characters. May contain only alphanumerics, white space and the following characters: -.' If the selected country is United States, then this must be a valid two-letter US state abbreviation. If the selected country is Canada, then this value must be a valid two-letter Canadian province abbreviation.

postalCode - *string*
Required string max 30 characters. May contain only alphanumerics, white space and the following characters: -.' If the selected country is United States, then the postalCode must be in format "#####" or "#####-####" (where "#" represents any numeric digit). If the selected country is Canada, then the postalCode must be in format "A#A#A#" or "A#A-A#" or "A#A #A#" (where "A" represents any latin alphabet character and "#" represents any numeric digit).

country - *string*
Required string ISO 3166-1 alpha-2[1] country code.

phone1 - *string*
Required string ITU-T E.164[2] formatted phone number max 20 digits.

phone2 - *string*
Optional string ITU-T E.164[3] formatted phone number max 20 digits.

fax - *string*
Optional string ITU-T E.164[4] formatted phone number max 20 digits.

email1 - *string*
Required string valid e-mail address max 100 characters.

email1Format - *string*
Optional string ? one of *html* or *text*. The default value of *html* will be applied if omitted from the request.

email2 - *string*
Optional string valid e-mail address max 100 characters.

email2Format - *string*
Optional string ? one of *html* or *text*. The default value of *html* will be used if *email2* is supplied and *email2Format* is omitted.

26.3 Response

26.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
400 Bad Request	POST data error Field cannot have any alphabet letters; only numbers and symbols allowed.	The value of one or more contact info fields is not valid or missing.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to set contact info for this order.
403 Forbidden	Unauthorized: ContactInfo failed permission check	Set account contact info as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist.
502 Bad Gateway	-	Account has not been set. Cannot add contact info.

26.3.2 Response Body

None.

26.4 Example

26.4.1 Set bad contact info values

Request

```
PUT /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "name": {
    "firstName": "&",
    "middleName": "&",
    "lastName": "&",
    "company": "Hostway",
    "salutation": "invalid"
  },
  "address": {
    "street1": "(",
    "street2": "(",
    "city": "&",
    "stateOrProvince": "&",
    "postalCode": "asfagag",
    "countryCode": "^"
  },
  "contactMedia": {
    "phone1": "a",
    "phone2": "a",
    "fax": "a",
    "email1": "em",
    "email1Format": "test"
  }
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8
```

```
{
  "badRequest": {
    "guid": "1c9b2dc5-2feb-4599-9753-aae2c39853dd",
    "message": "POST data error",
    "code": 400,
    "details": {
      "name.lastName": "Only alphanumerics, spaces, and the following characters are allowed in lastName: -'.",
      "address.city": "Only alphanumerics, spaces, and the following characters are allowed in city: -'.",
      "address.street2": "Only alphanumerics, spaces, and the following characters are allowed in street2: -'.",
      "name.firstName": "Only alphanumerics, spaces, and the following characters are allowed in firstName: -'.",
      "address.street1": "Only alphanumerics, spaces, and the following characters are allowed in street1: -'.",
      "name.salutation": "\"invalid\" is not one of Mr., Ms., Mrs., Dr.",
      "address.stateOrProvince": "Only alphanumerics, spaces, and the following characters are allowed in stateOrProvince: -'.",
      "name.middleName": "Only alphanumerics, spaces, and the following characters are allowed in middleName: -'.",
      "contactMedia.email1": "Invalid email address in email: em",
      "address.countryCode": "Invalid Country Code",
      "contactMedia.email1Format": "\"test\" is not one of html, text"
    }
  }
}
```

26.4.2 Set bad contact info values 2

Request

```
PUT /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "name": {
    "firstName": "Billing",
    "middleName": "X",
    "lastName": "Customer",
    "company": "Hostway"
  },
  "address": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  },
  "contactMedia": {
    "phone1": "test",
    "phone2": "test",
    "fax": "test",
    "email1": "petre.popescu@hostway.com",
    "email1Format": "html",
    "email2": "gah@wev.com",
    "email2Format": "text"
  }
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8
```

```
{
  "computeFault": {
    "guid": "3fb07aa5-157e-474d-b7cc-ece0cf87f36e",
    "message": "Field cannot have any alphabet letters; only numbers and symbols allowed.",
    "code": 400,
  }
}
```

```

    "details": ""
  }
}

```

26.4.3 Set contact info with wrong OwnerId

Request

```

PUT /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={wrong_order_id}; Path=/

```

```

{
  "name": {
    "firstName": "Billing",
    "middleName": "X",
    "lastName": "Customer",
    "company": "Hostway",
    "salutation": "Mr."
  },
  "address": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  },
  "contactMedia": {
    "phone1": "312-555-2222",
    "phone2": "312-555-3333",
    "fax": "312-555-1111",
    "email1": "petre.popescu@hostway.com",
    "email1Format": "html",
    "email2": "gah@wev.com",
    "email2Format": "text"
  }
}

```

Response

```

401 Unauthorized
Content-Type: text/plain; charset=UTF-8

```

```

401 Unauthorized

```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

26.4.4 Unassociated user without cookie

Request

```

PUT /orders/{orderId}/account/contactInfo/billing
Authorization: {unassociated_user_authorization}

```

```

{
  "name": {
    "firstName": "Billing",
    "middleName": "X",
    "lastName": "Customer",
    "company": "Hostway",
    "salutation": "Mr."
  },
  "address": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  },
  "contactMedia": {
    "phone1": "312-555-2222",
    "phone2": "312-555-3333",
    "fax": "312-555-1111",
    "email1": "petre.popescu@hostway.com",
    "email1Format": "html",
    "email2": "gah@wev.com",
    "email2Format": "text"
  }
}

```

Response

```

403 Forbidden
Content-Type: application/json; charset=UTF-8

```

```

{
  "forbidden" : {
    "guid" : "53fd5c41-a4b1-48d1-8196-43fc5ba32cf2",
    "message" : "Unauthorized: ContactInfo failed permission check",
    "code" : 403,
    "details" : ""
  }
}

```

26.4.5 Set contact info in non-existent order

Request

```

PUT /orders/{non-existent_orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=/

```

```
{
  "name": {
    "firstName": "Billing",
    "middleName": "X",
    "lastName": "Customer",
    "company": "Hostway",
    "salutation": "Mr."
  },
  "address": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  },
  "contactMedia": {
    "phone1": "312-555-2222",
    "phone2": "312-555-3333",
    "fax": "312-555-1111",
    "email1": "petre.popescu@hostway.com",
    "email1Format": "html",
    "email2": "gah@wev.com",
    "email2Format": "text"
  }
}
```

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound" : {
    "guid" : "ed5f236d-6983-4576-bld3-9cd69c4255a0",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

26.4.6 Set contact info on an unset account

Request

PUT /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=

```
{
  "name": {
    "firstName": "Billing",
    "middleName": "X",
    "lastName": "Customer",
    "company": "Hostway",
    "salutation": "Mr."
  },
  "address": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  },
  "contactMedia": {
    "phone1": "312-555-2222",
    "phone2": "312-555-3333",
    "fax": "312-555-1111",
    "email1": "petre.popescu@hostway.com",
    "email1Format": "html",
    "email2": "gah@wev.com",
    "email2Format": "text"
  }
}
```

Response

502 Bad Gateway
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault" : {
    "guid" : "5db3e3c9-37ac-4a1d-8085-c931577e1c16",
    "timestamp" : "2014-09-10 12:10:12",
    "code" : 502,
    "errorRefId" : "5db3e3c9-37ac-4a1d-8085-c931577e1c16"
  }
}
```

26.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

27 Orders-orderId-account-contactInfo-contactType:GET

28 GET /orders/{orderId}/account/contactInfo/{contactType}

Get specific contact type details for an account in a given order.

28.1 Contents

- 1 GET /orders/{orderId}/account/contactInfo/{contactType}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Get contact info with wrong OwnerId
 - ◇ 1.3.2 Unassociated user without cookie
 - ◇ 1.3.3 Get contact info of unset contact type
 - ◇ 1.3.4 Account has not been set
 - ◇ 1.3.5 Order does not exist
 - ◆ 1.4 See also

28.2 Request

GET /orders/{orderId}/account/contactInfo/{contactType}

28.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

contact_type - *string*

Contact Type (regular, billing, administrative or technical)

28.2.2 URI Parameters

None.

28.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

28.3 Response

28.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to get contact type info for this order.
403 Forbidden	Unauthorized: ContactInfo failed permission check	Access account contact info as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist. An account was not set for the order.
502 Bad Gateway	-	The order does not have contact info of this type. Unexpected backend response. Cannot retrieve contact info.

28.3.2 Response Body

```
{
  "contactInfo": {
    "name": {
      "salutation": "{salutation}",
      "firstName": "{firstname}",
      "middleName": "{middleName}",
      "lastName": "{lastName}",
      "company": "{company}"
    },
    "address": {
      "street1": "{street1}",
      "street2": "{street2}",
      "city": "{city}",
      "stateOrProvince": "{stateOrProvince}",
      "postalCode": "{postalCode}",
      "countryCode": "{countryCode}"
    },
    "contactMedia": {
```

```

    "phone1": "{phone1}",
    "phone2": "{phone2}",
    "fax": "{fax}",
    "email1": "{email1}",
    "email1Format": "{html|text}",
    "email2": "{email2}",
    "email2Format": "{html|text}"
  },
  "links": [
    { "href": "https://api.hostway.com/orders/{orderId}/account/contactInfo/{contactType}/", "rel": "self" } ]
}

```

28.3.2.1 Parameters

salutation
Contact's salutation

firstName
Contact's first name.

middleName
Contact's middle name (optional).

lastName
Contact's last name.

company
Contact's company name (optional).

street1
Contact's street address.

street2
Contact's street address second line (optional).

city
Contact's city.

stateOrProvince
Contact's state or province.

postalCode
Contact's postal or ZIP code.

country
Contact's country code per ISO 3166-1 alpha-2^[1].

phone1
Contact's primary phone number in ITU-T E.164^[2] format.

phone2
Contact's secondary phone number in ITU-T E.164^[3] format (optional).

fax
Contact's fax number in ITU-T E.164^[4] format (optional).

email1
Contact's primary e-mail address.

email1Format
Primary e-mail delivery format: *html* or *text*.

email2
Contact's secondary e-mail address (optional).

email2Format
Secondary e-mail delivery format: *html* or *text* (optional).

links - list
^[1] [Hypermedia](#) for this resource.

28.4 Example

28.4.1 Get contact info with wrong OwnerId

Request

```

GET /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={wrong_order_id}; Path=/

```

Response

```

401 Unauthorized
Content-Type: text/plain; charset=UTF-8

```

```

401 Unauthorized

```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

28.4.2 Unassociated user without cookie

Request

```
GET /orders/{orderId}/account/contactInfo/billing
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8

{
  "forbidden": {
    "guid": "53fd5c41-a4b1-48d1-8196-43fc5ba32cf2",
    "message": "Unauthorized: ContactInfo failed permission check",
    "code": 403,
    "details": ""
  }
}
```

28.4.3 Get contact info of unset contact type

Request

```
GET /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "3f8d5d31-3986-4075-8a13-5fe3e20a2be4",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

28.4.4 Account has not been set

Request

```
GET /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "3f8d5d31-3986-4075-8a13-5fe3e20a2be4",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

28.4.5 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "80d5e49e-0795-4209-a929-1ee051e0f252",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

28.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

29 Orders-orderId-account-contactInfo:GET

30 GET /orders/{orderId}/account/contactInfo

Get all contact infos for an account in a given order.

30.1 Contents

- 1 GET /orders/{orderId}/account/contactInfo
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Get contact info with wrong OwnerId
 - ◇ 1.3.2 Unassociated user without cookie
 - ◇ 1.3.3 Non-existent contact info for the order
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Unset account for the order
 - ◆ 1.4 See also

30.2 Request

GET /orders/{orderId}/account/contactInfo

30.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

30.2.2 URI Parameters

None.

30.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

30.3 Response

30.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to get contact info for this order.
403 Forbidden	Unauthorized: ContactInfo failed permission check	Access account contact info as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The order does not have any contact info.
	AccountNumber is missing. Make sure the account is set before querying.	The specified order does not exist.
502 Bad Gateway	-	An account was not set for the order.
		Unexpected backend response. Cannot retrieve contact infos.

30.3.2 Response Body

```
{
  "contactInfo": {
    "regular": {...},
    "billing": {...},
    "administrator": {...},
    "technical": {...}
  },
  "links": [
    { "href": "https://api.hostway.com/orders/{orderId}/account/contactInfo/", "rel": "self" }
  ]
}
```

30.3.2.1 Parameters

contactInfo - *dictionary*
Details for all contact types specified for the account.

links - *list*
[Hypermedia](#) for this resource.

30.4 Example

30.4.1 Get contact info with wrong OwnerId

Request

```
GET /orders/{orderId}/account/contactInfo
Cookie: OwnerId={wrong_order_id}; Path=
```

Response

```
401 Unauthorized
Content-Type: text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

30.4.2 Unassociated user without cookie

Request

```
GET /orders/{orderId}/account/contactInfo
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8
```

```
{
  "forbidden" : {
    "guid" : "53fd5c41-a4b1-48d1-8196-43fc5ba32cf2",
    "message" : "Unauthorized: ContactInfo failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

30.4.3 Non-existent contact info for the order

Request

```
GET /orders/{orderId}/account/contactInfo
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "80d5e49e-0795-4209-a929-1ee051e0f252",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

30.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account/contactInfo
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "80d5e49e-0795-4209-a929-1ee051e0f252",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

30.4.5 Unset account for the order

Request

GET /orders/{orderId}/account/contactInfo
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "80d5e49e-0795-4209-a929-1ee051e0f252",
    "message": "AccountNumber is missing. Make sure the account is set before querying.",
    "code": 404,
    "details": ""
  }
}
```

30.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

31 Orders-orderId-account-contactInfo-contactType:DELETE

32 DELETE /orders/{orderId}/account/contactInfo/{contactType}

Deletes the account contact details for a given contact type in an order.

32.1 Contents

- 1 DELETE /orders/{orderId}/account/contactInfo/{contactType}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully delete contact type of an order
 - ◇ 1.3.2 Get contact info with wrong OwnerId
 - ◇ 1.3.3 Unassociated user without cookie
 - ◇ 1.3.4 Delete contact info of unset contact type
 - ◇ 1.3.5 Account has not been set
 - ◇ 1.3.6 Order does not exist
 - ◆ 1.4 See also

32.2 Request

DELETE /orders/{orderId}/account/contactInfo/{contactType}

32.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

contact_type - *string*
Contact Type (regular, billing, administrator or technical)

32.2.2 URI Parameters

None.

32.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

32.3 Response

Status Code	Error Message	Description
204 No Content	-	The contact info was successfully deleted. The specified order does not exist.
404 Not Found	Resource not found	An account has not been added to the given order. The specified contact type is not set
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to delete contact info for this order.
403 Forbidden	Unauthorized: ContactInfo failed permission check	Delete account contact info as an authenticated user, not associated with the order.
502 Bad Gateway	-	Unexpected backend response. Cannot delete contact info.

32.4 Example

32.4.1 Successfully delete contact type of an order

Request

```
DELETE /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

204 No Content

32.4.2 Get contact info with wrong OwnerId

Request

```
DELETE /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={wrong_order_id}; Path=
```

Response

```
401 Unauthorized
Content-Type: text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

32.4.3 Unassociated user without cookie

Request

```
DELETE /orders/{orderId}/account/contactInfo/billing
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8
```

```
{
  "forbidden" : {
    "guid" : "53fd5c41-a4b1-48d1-8196-43fc5ba32cf2",
    "message" : "Unauthorized: ContactInfo failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

32.4.4 Delete contact info of unset contact type

Request

```
DELETE /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "3f8d5d31-3986-4075-8a13-5fe3e20a2be4",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

32.4.5 Account has not been set

Request

```
DELETE /orders/{orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "3f8d5d31-3986-4075-8a13-5fe3e20a2be4",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

32.4.6 Order does not exist

Request

```
DELETE /orders/{non-existent_orderId}/account/contactInfo/billing
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "80d5e49e-0795-4209-a929-1ee051e0f252",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

32.5 See also

- [Orders API](#)

- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

33 Orders-orderId-account-paymentInfo:PUT

34 PUT /orders/{orderId}/account/paymentInfo

Set the account's payment information for a given order.

34.1 Contents

- 1 PUT /orders/{orderId}/account/paymentInfo
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Offline payment for supported franchises with agent access
 - ◇ 1.3.3 Invalid payment info type
 - ◇ 1.3.4 Missing attribute for paymentInfoType credit_card
 - ◇ 1.3.5 Credit card number length exceeds 16 characters
 - ◇ 1.3.6 Credit card number cannot contain hyphens
 - ◇ 1.3.7 Credit card number with wrong length
 - ◇ 1.3.8 Invalid verification number
 - ◇ 1.3.9 Invalid date format
 - ◇ 1.3.10 No authorization
 - ◇ 1.3.11 Unauthorized user
 - ◇ 1.3.12 Unset account for the order
 - ◆ 1.4 See also

34.2 Request

PUT /orders/{orderId}/account/paymentInfo

34.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

34.2.2 URI Parameters

None.

34.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

34.2.4 Request Body

The request format depends on the type of payment method that is added. The following format is required for credit cards.

```
{
  "paymentInfoType": "credit_card",
  "accountNumber": "4111111111111111",
  "cardHolderName": "John Smith",
  "creditCardType": "visa",
  "expirationDate": "2012-08",
  "verificationNumber": "123",
  "billingAddress": {
    "city": "Chicago",
    "countryCode": "US",
    "postalCode": "60606",
    "stateOrProvince": "IL",
    "street1": "100 N Riverside",
    "street2": ""
  }
}
```

34.2.4.1 Parameters

paymentInfoType - *string*

The type of payment method that will be used. Allowed value(s) are:

credit_card

offline (Available only for agents on supported franchises)

accountNumber - *string*

Credit card number. Must consist of numbers only. Required if paymentInfoType is set to **credit_card**.

cardHolderName - *string*
The owner name as it appears on the card. Required if paymentInfoType is set to **credit_card**.

creditCardType - *string*
The type of credit card - **visa**, **mastercard**, **discover**, **amex**. Required if paymentInfoType is set to **credit_card**.

expirationDate - *string*
The credit card expiration date in YYYY-MM format. Should exceed the current date. Required if paymentInfoType is set to **credit_card**.

verificationNumber - *string*
The credit card security code. This is only used to validate the credit card and will not be stored. Required if paymentInfoType is set to **credit_card**.

billingAddress - *dictionary*
Contains the credit card's billing address. Required if paymentInfoType is set to **credit_card**.

34.3 Response

34.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
	POST data error	A required attribute for the payment info type is missing.
	declined	paymentInfoType can only be credit_card.
	Invalid verificationNumber	Invalid verificationNumber
400 Bad Request	Invalid date format	Wrong expirationDate format
	invalid number or type	creditCardType can be only one of visa, mastercard, amex, discover.
		Credit card number with wrong length
		Credit card number does not comply with visa rules
		expirationDate set in past
	Incorrect padding	Hyphens or spaces in credit card number are not allowed
	Input strings must be a multiple of 16 in length	Credit card number length should be 16.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to add payment info.
403 Forbidden	Unauthorized: PaymentInfo failed permission check	An unauthorized user cannot set or get payment info.
404 Not Found	Resource not found	The specified order does not exist.
502 Bad Gateway	-	An account has not been added to the given order.
		Unexpected backend error.

34.3.2 Response Body

None.

34.4 Example

34.4.1 Success

Request

```
PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName":
    "John Jello",
  "expirationDate":
    "2015-06",
  "verificationNumber": "505",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

Response

204 No Content

34.4.2 Offline payment for supported franchises with agent access

Request

```
PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/
Authorization: Basic Auth_String

{
```

```
    "paymentInfoType": "offline"
}
```

Response

204 No Content

34.4.3 Invalid payment info type

Request

```
PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "paymentInfoType": "direct_debit",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName":
    "John Jello",
  "expirationDate":
    "2015-06",
  "verificationNumber": "505",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "badRequest": {
    "guid": "7ca8b2cc-88d5-4e5b-aab8-e4015a5b3ad8",
    "message": "POST data error",
    "code": 400,
    "details": {
      "paymentInfoType": "\"direct_debit\" is not one of credit_card, vz_payment"
    }
  }
}
```

34.4.4 Missing attribute for paymentInfoType credit_card

Request

```
PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "paymentInfoType": "credit_card",
  "accountNumber": "4111111111111111",
  "cardHolderName": "John Smith",
  "creditCardType": "visa",
  "expirationDate": "2012-08",
  "billingAddress": {
    "city": "Chicago",
    "countryCode": "US",
    "postalCode": "60606",
    "stateOrProvince": "IL",
    "street1": "100 N Riverside",
    "street2": ""
  }
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "badRequest": {
    "guid": "2829e9e2-04e1-4fe2-8e05-be738b4c467c",
    "message": "POST data error",
    "code": 400,
    "details": {
      "verificationNumber": "Required"
    }
  }
}
```

34.4.5 Credit card number length exceeds 16 characters

Request

```
PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "paymentInfoType": "credit_card",
  "accountNumber": "4111-1111-1111-1111",
  "cardHolderName": "John Smith",
  "creditCardType": "visa",
  "expirationDate": "2012-08",
  "verificationNumber": "505",

```



```

    "billingAddress": {
      "city": "Chicago",
      "countryCode": "US",
      "postalCode": "60606",
      "stateOrProvince": "IL",
      "street1": "100 N Riverside",
      "street2": ""
    }
  }
}

```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```

{
  "badRequest": {
    "guid": "f5ed5738-086d-4751-8ad5-0dfead39ea3a",
    "message": "Input strings must be a multiple of 16 in length",
    "code": 400,
    "details": ""
  }
}

```

34.4.6 Credit card number cannot contain hyphens

Request

PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=

```

{
  "paymentInfoType": "credit_card",
  "accountNumber": "4111-111-111-111",
  "cardHolderName": "John Smith",
  "creditCardType": "visa",
  "expirationDate": "2012-08",
  "verificationNumber": "505",
  "billingAddress": {
    "city": "Chicago",
    "countryCode": "US",
    "postalCode": "60606",
    "stateOrProvince": "IL",
    "street1": "100 N Riverside",
    "street2": ""
  }
}

```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```

{
  "computeFault": {
    "guid": "5a757a5a-870e-4d4f-acdf-aed95e066b3d",
    "message": "Incorrect padding",
    "code": 400,
    "details": ""
  }
}

```

34.4.7 Credit card number with wrong length

Request

PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=

```

{
  "paymentInfoType": "credit_card",
  "accountNumber": "411111111111111122",
  "cardHolderName": "John Smith",
  "creditCardType": "visa",
  "expirationDate": "2012-08",
  "verificationNumber": "505",
  "billingAddress": {
    "city": "Chicago",
    "countryCode": "US",
    "postalCode": "60606",
    "stateOrProvince": "IL",
    "street1": "100 N Riverside",
    "street2": ""
  }
}

```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```

{
  "badRequest": {
    "guid": "ced1a8a8-21dc-4a10-9d36-5a201214a5ce",
    "message": "invalid number or type",
    "code": 400,
    "details": ""
  }
}

```

34.4.8 Invalid verification number

Request

PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName": "John Jello",
  "expirationDate": "2015-06",
  "verificationNumber": "0000",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault" : {
    "guid" : "031b8bc2-8da3-41c7-860c-ca3743cef135",
    "message" : "declined",
    "code" : 400,
    "details" : ""
  }
}
```

34.4.9 Invalid date format

Request

PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/

```
{
  "paymentInfoType": "credit_card",
  "accountNumber": "4111111111111111",
  "cardHolderName": "John Smith",
  "creditCardType": "visa",
  "expirationDate": "15-06",
  "verificationNumber": "505",
  "billingAddress": {
    "city": "Chicago",
    "countryCode": "US",
    "postalCode": "60606",
    "stateOrProvince": "IL",
    "street1": "100 N Riverside",
    "street2": ""
  }
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "badRequest": {
    "guid": "30e66cfe-649c-4b1c-bfaf-c65caf47b99d",
    "message": "Invalid date format",
    "code": 400,
    "details": ""
  }
}
```

34.4.10 No authorization

Request

PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={wrong_owner_id}; Path=/

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName": "John Jello",
  "expirationDate": "2015-06",
  "verificationNumber": "505",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

34.4.11 Unauthorized user

Request

```
PUT /orders/{orderId}/account/paymentInfo
Authorization: Basic {wrong_user_authorization}
```

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName":
    "John Jello",
  "expirationDate":
    "2015-06",
  "verificationNumber": "505",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8
```

```
{
  "forbidden": {
    "guid": "5a199170-843a-44fc-bbb0-87155eb15fc6",
    "message": "Unauthorized: PaymentInfo failed permission check",
    "code": 403,
    "details": ""
  }
}
```

34.4.12 Unset account for the order

Request

```
PUT /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName":
    "John Jello",
  "expirationDate":
    "2015-06",
  "verificationNumber": "505",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

Response

```
502 Bad Gateway
Content-Type : application/json; charset=UTF-8
```

```
{
  "computeFault": {
    "guid": "a4f6b310-11d9-4263-8482-81bccf261df7",
    "timestamp": "2014-09-08 08:34:20",
    "code": 502,
    "errorRefId":
      "a4f6b310-11d9-4263-8482-81bccf261df7"
  }
}
```

34.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

35 Orders-orderId-account-paymentInfo:GET

36 GET /orders/{orderId}/account/paymentInfo

Get the payment method information for a given order. Only a minimum amount of information will be returned to recognize the payment method.

36.1 Contents

- 1 GET /orders/{orderId}/account/paymentInfo
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 No authorization
 - ◇ 1.3.3 Unauthorized user
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Account has not been set
 - ◇ 1.3.6 Payment info has not been set
 - ◆ 1.4 See also

36.2 Request

GET /orders/{orderId}/account/paymentInfo

36.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

36.2.2 URI Parameters

None.

36.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

36.3 Response

36.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to get payment info for this order.
403 Forbidden	Unauthorized: PaymentInfo failed permission check	An unauthorized user cannot set or get payment info.
404 Not Found	Resource not found	The specified order does not exist.
	-	An account was not set for the order.
	-	No payment info for the order was found.
502 Bad Gateway	-	Unexpected backend error

36.3.2 Response Body

The following is the response body for credit cards.

```
{
  "paymentInfoType": "credit_card",
  "accountNumber": "*****1111",
  "creditCardType": "visa",
  "expirationDate": "2012-08",
  "links": [
```

```

    {"href": "https://api.hostway.com/orders/{order_id}/account/paymentInfo/", "rel": "self"}
  ]
}

```

The following is the response for Verizon payment information.

```

{
  "paymentInfoType": "vz_payment",
  "paymentReference": "123432429034",
  "sessionId": "23432434244",
  "links": [
    {"href": "https://api.hostway.com/orders/{order_id}/account/paymentInfo/", "rel": "self"}
  ]
}

```

The following is the response for offline payment information.

```

{
  "paymentInfoType": "offline",
  "links": [
    {"href": "https://api.hostway.com/orders/{order_id}/account/paymentInfo/", "rel": "self"}
  ]
}

```

36.3.2.1 Parameters

paymentInfoType - *string*

The type of payment method. Possible value(s) are:

credit_card
vz_payment
offline

accountNumber - *string*

The credit card number. Only the last four digits will be revealed. Only applies for credit cards.

creditCardType - *string*

The type of credit card such as visa, mastercard, discover, etc. Only applies for credit cards.

expirationDate - *string*

The credit card expiration date in YYYY-MM format. Only applies for credit cards.

paymentReference - *string*

Verizon payment reference id. Only applies for Verizon payment type.

sessionId - *string*

Verizon payment session id. Only applies for Verizon payment type.

links - *list*

[Hypermedia](#) for this resource. Links to self.

36.4 Example

36.4.1 Success

Request

```

GET /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

200 OK
Content-Type : application/json; charset=UTF-8

{
  "links": [
    {
      "href": "https://api.hostway.com/orders/00000148546ce1ac1d12585e007f000000010001/account/paymentinfo/",
      "rel": "self"
    }
  ],
  "creditCardType": "visa",
  "expirationDate": "2015-06",
  "paymentInfoType": "credit_card",
  "accountNumber": "*****1111"
}

```

36.4.2 No authorization

Request

```

GET /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={wrong_owner_id}; Path=/

```

Response

```

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

36.4.3 Unauthorized user

Request

```
GET /orders/{orderId}/account/paymentInfo
Authorization: Basic {wrong_user_authorization}
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8
```

```
{
  "forbidden": {
    "guid": "5a199170-843a-44fc-bbb0-87155eb15fc6",
    "message": "Unauthorized: PaymentInfo failed permission check",
    "code": 403,
    "details": ""
  }
}
```

36.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

36.4.5 Account has not been set

Request

```
GET /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "9ae11205-0650-471a-9ed7-7642107011dc",
    "message": "",
    "code": 404,
    "details": ""
  }
}
```

36.4.6 Payment info has not been set

Request

```
GET /orders/{orderId}/account/paymentInfo
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "9ae11205-0650-471a-9ed7-7642107011dc",
    "message": "",
    "code": 404,
    "details": ""
  }
}
```

36.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

37 Orders-orderId-account-user:PUT

38 PUT /orders/{orderId}/account/user

Sets or updates the account user credentials in a given order.

38.1 Contents

- 1 PUT /orders/{orderId}/account/user
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully add/update user to order
 - ◇ 1.3.2 Missing username
 - ◇ 1.3.3 Invalid username
 - ◇ 1.3.4 Invalid password
 - ◇ 1.3.5 No authorization
 - ◇ 1.3.6 Unauthorized user
 - ◇ 1.3.7 Order does not exist
 - ◇ 1.3.8 Existing account in the system
 - ◇ 1.3.9 Account has not been set
 - ◆ 1.4 See also

38.2 Request

PUT /orders/{orderId}/account/user

38.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

38.2.2 URI Parameters

None.

38.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

38.2.4 Request Body

```
{
  "userName": "mytestuser1",
  "password": "Mytestpass1"
}
```

38.2.4.1 Parameters

userName - *string*
Required string max 50 characters. Only letters, digits and dot (.), dash (-), underscore (_) and at sign (@) are allowed.

password - *string*

Required string min 8, max 50 characters. Must include at least one letter and one digit. The following characters are not allowed: &`"'\<>\$.

38.3 Response

38.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
400 Bad Request	POST data error	JSON is invalid Username or password is missing. Username or password breaks its format rules.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to set user credentials.
403 Forbidden	Unauthorized: User failed permission check	Set user credentials as an authenticated user, not associated with the order.
404 Not Found	Resource not found	Order does not exist.
409 Conflict	Data conflict	The same username already exists in the system.
502 Bad Gateway	-	Account hasn't been added

38.3.2 Response Body

None.

38.4 Example

38.4.1 Successfully add/update user to order

Request

```
PUT /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=/

{
  "userName": "accountUser1",
  "password": "userPass1"
}
```

Response

204 No Content

38.4.2 Missing username

Request

```
PUT /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=/

{
  "password": "userPass1"
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "badRequest": {
    "guid": "50f051a3-8325-4064-b174-d82d78da83d9",
    "message": "POST data error",
    "code": 400,
    "details": {
      "userName": "Required"
    }
  }
}
```

38.4.3 Invalid username

Request

```
PUT /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=/

{
  "userName": "user:name"
  "password": "userPass1"
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "badRequest": {
    "guid": "50f051a3-8325-4064-b174-d82d78da83d9",
    "message": "POST data error",
    "code": 400,
    "details": {
      "userName": "Only letters, digits and dot (.), dash (-), underscore (_) and at sign (@) are allowed"
    }
  }
}
```

```
}  
}  
}
```

38.4.4 Invalid password

Request

```
PUT /orders/{orderId}/account/user  
Cookie: OwnerId={owner_id}; Path=/  

```

```
{  
  "userName": "accountUser1"  
  "password": "userPass$$$"  
}
```

Response

```
400 Bad Request  
Content-Type : application/json; charset=UTF-8
```

```
{  
  "badRequest": {  
    "guid": "9cdfae0e-ad2a-4759-a5ef-ceddd2ac14be",  
    "message": "POST data error",  
    "code": 400,  
    "details": {  
      "password": "The following characters are not allowed: &`'\\"/>  
    }  
  }  
}
```

38.4.5 No authorization

Request

```
PUT /orders/{orderId}/account/user  
Cookie: OwnerId={wrong_owner_id}; Path=/  

```

```
{  
  "userName": "accountUser1",  
  "password": "userPass1"  
}
```

Response

```
401 Unauthorized  
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

38.4.6 Unauthorized user

Request

```
PUT /orders/{orderId}/account/user  
Authorization: {unassociated_user_authorization}
```

```
{  
  "userName": "accountUser1",  
  "password": "userPass1"  
}
```

Response

```
403 Forbidden  
Content-Type: application/json; charset=UTF-8
```

```
{  
  "forbidden" : {  
    "guid" : "66f63a81-52e9-4ec6-a50a-42acebc021e7",  
    "message": "Unauthorized: User failed permission check",  
    "code" : 403,  
    "details" : ""  
  }  
}
```

38.4.7 Order does not exist

Request

```
PUT /orders/{non-existent_orderId}/account/user  
Cookie: OwnerId={owner_id}; Path=/  

```

Response

```
404 Not found  
Content-Type : application/json; charset=UTF-8
```

```
{  
  "itemNotFound": {  
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",  
    "message": "Resource not found",  
    "code": 404,  
    "details": ""  
  }  
}
```

```
}
```

38.4.8 Existing account in the system

Request

```
PUT /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "userName": "zxc01"
  "password": "Mytestpass1"
}
```

Response

```
409 Conflict
Content-Type : application/json; charset=UTF-8
```

```
{
  "conflict": {
    "guid": "5c817267-5302-4ea6-abd7-bc9b77f01082",
    "message": "Data conflict",
    "code": 409,
    "details": ""
  }
}
```

38.4.9 Account has not been set

Request

```
PUT /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "userName": "accountUser1"
  "password": "userPass1"
}
```

Response

```
502 Bad Gateway
Content-Type : application/json; charset=UTF-8
```

```
{
  "computeFault": {
    "guid": "a4f6b310-11d9-4263-8482-81bccf261df7",
    "timestamp": "2014-09-08 08:34:20",
    "code": 502,
    "errorRefId":
      "a4f6b310-11d9-4263-8482-81bccf261df7"
  }
}
```

38.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

39 Orders-orderId-account-user:GET

40 GET /orders/{orderId}/account/user

Get details of the account user for the given order. A user with auto-generated information is created by default when the account is created. The user password is excluded from the response.

40.1 Contents

- 1 GET /orders/{orderId}/account/user
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 No authorization
 - ◇ 1.3.3 Unauthorized user
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Account has not been set
 - ◆ 1.4 See also

40.2 Request

GET /orders/{orderId}/account/user

40.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

40.2.2 URI Parameters

None.

40.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

40.3 Response

40.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to set user credentials.
403 Forbidden	Unauthorized: User failed permission check	Retrieve user as an authenticated user, not associated with the order.
404 Not Found	Resource not found	The specified order does not exist. An account was not set for the order. No user data found for the account.
	-	

502 Bad Gateway

- Failed retrieving user data.

40.3.2 Response Body

```
{
  "userName": "{userName}",
  "links": [
    { "href": "https://api.hostway.com/orders/{order_id}/account/user/", "rel": "self" }
  ]
}
```

40.3.2.1 Parameters

userName - *string*

The username of the account login credentials.

links - *list*

[Hypermedia](#) for this resource. Links to self.

40.4 Example

40.4.1 Success

Request

```
GET /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=
```

Response

```
200 OK
Content-Type : application/json; charset=UTF-8
```

```
{
  "userName": "accountUser1",
  "links": [{
    "href": "https://api.hostway.com/orders/0000014854c737a28b6dffbe007f000000010001/account/user/",
    "rel": "self"
  }]
}
```

40.4.2 No authorization

Request

```
GET /orders/{orderId}/account/user
Cookie: OwnerId={wrong_owner_id}; Path=
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

40.4.3 Unauthorized user

Request

```
GET /orders/{orderId}/account/user
Authorization: {unassociated_user_authorization}
```

Response

```
403 Forbidden
Content-Type: application/json; charset=UTF-8
```

```
{
  "forbidden" : {
    "guid" : "66f63a81-52e9-4ec6-a50a-42acebc021e7",
    "message" : "Unauthorized: User failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

40.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account/user
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "b0b38b3e-b693-4021-8116-b59f7ec3fea7",
    "message": "Resource not found",
  }
}
```

```
    "code": 404,  
    "details": ""  
  }  
}
```

40.4.5 Account has not been set

Request

GET /orders/{orderId}/account/user
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not found
Content-Type : application/json; charset=UTF-8

{
 "itemNotFound": {
 "guid": "0c0c1f50-8d80-4423-b501-0a3cc5f070af",
 "message": "",
 "code": 404,
 "details": ""
 }
}

40.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

41 Orders-orderId-account-products:POST

42 POST /orders/{orderId}/account/products

Adds a new or existing Product to the Account's Order.

If, at the time the product is created, there is not yet an Account in the order, then this call will implicitly add a very rudimentary Account (containing only a default language & the currency of this product).

If there is already an Account in the order at the time this call is made, the currency of the specified product offering *must* match the currency of the Account.

42.1 Contents

- 1 POST
 /orders/{orderId}/account/products
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◇ 1.1.5 Validation Rules
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - 1.2.3.1 Successful response
 - 1.2.3.2 Error responses
 - ◆ 1.3 See also

42.2 Request

POST /orders/{orderId}/account/products

42.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

42.2.2 URI Parameters

None.

42.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

42.2.4 Request Body

There are two possible formats. To add a new product that does not already exist:

```
{
  "offering": "https://api.hostway.com/productSpecifications/{productSpecificationId}/offerings/{productOfferingId}",
  "promoCode": "{promoCode}",
  "displayName": "My custom product name",
  "partnerId": "PartnerId",
}
```

OR

To specify an existing product, use the following:

```
{
  "existingProductUrl": "https://api.hostway.com/accounts/{accountId}/products/{productId}"
}
```

}

42.2.4.1 Parameters

offering - *string*

Link to the [product catalog offering](#) specifying the new product.

promoCode - *string* (optional)

A promotion code for the new product [promotion codes](#).

displayName - *string* (optional)

A custom display name for the product.

partnerId - *string* (optional)

Partner id.

existingProductUrl - *string*

Link to [an existing product](#). Only required when adding an existing product to the order.

42.2.5 Validation Rules

1. The product specification URL (<https://api.hostway.com/productSpecifications/{productSpecificationId}>) should point to an existing product.
2. The product offering currency should match the account currency or if no account is specified should be allowed for the franchise.
3. The product offering URL (<https://api.hostway.com/productSpecifications/{productSpecificationId}/offerings/{productOfferingId}>) should point to an existing product offering.
4. The product use type (public, internal, internal view only, etc.) should be allowed for the current user.
5. The product offering should be valid according to the back-end.
6. The account product URL (<{APIBaseURL}/accounts/{accountId}/products/{productId}>) should point to an existing product that is open and belongs to the account.

42.3 Response

42.3.1 Status Code

Status Code	Error Message	Description
201 Created	-	The operation was successfully completed.
	POST data error	Trying to create a product with invalid body.
	Cannot add non-existent product "fake"	Trying to create a product by passing fake offering.
	Invalid offering URI	Trying to create a product by passing invalid offering (missing currency, monthly cycle or productSpecifications)
400 Bad Request	The requested offering is invalid	Trying to create a product with invalid monthly cycle (eg: 100)
	Trying to add inconsistent currency: product {product} with FAKE while account uses USD	Trying to create a product with currency, which does not match the account's currency
	Currency FAKE not allowed for this franchise	Trying to add a product with invalid for the franchise currency to an order for which no account has been set.
	Trying to add Internal product {product} without authorization	Trying to add product, which is internal, without the proper credentials.
	Trying to add Internal View Only product {product}	Trying to add product, which is internal view only, without the proper credentials.
	Invalid product URI	Tried to add an existing product with wrong existingProductUrl
	The account of the order and the account of the product doesn't match	Tried to add an existing product with account, which is different from the account of the order.
	Product doesn't exist.	Tried to add an existing product which does not exist
401 Unauthorized	Cannot add a product that is not open.	Tried to add an existing product that is not open.
	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The <i>OwnerId</i> cookie was not specified or is incorrect.
403 Forbidden	Unauthorized: Products failed permission check	The client does not have permissions to add products.
404 Not Found	Resource not found	The client is trying to add a product to non existing order.
502 Bad Gateway	-	Unexpected backend response.

42.3.2 Response Headers

Location

Returned with successful response. Contains the URI of the newly added product and the id of the product.

42.3.3 Response Body

42.3.3.1 Successful response

```
201 Created
{
  "productId": "00000148842a5f6448a61ce6007f000000010001",
  "url" : "https://api.hostway.com/orders/0000014884293798c68eafa5007f000000010001/account/products/00000148842a5f6448a61ce6007f000000010001/"
}
```

Note: The product Id will change once the order is provisioned.

42.3.3.2 Error responses

400 Bad Request - trying to order product, which is internal, without the proper authorization.

```
{
  "computeFault": {
    "guid": "c940c886-5343-4a49-b728-0b94cbb1a3e9",
    "message": "Trying to add Internal product {product} without authorization",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add a product, which is internal view only, such products cannot be added via the Public API.

```
{
  "computeFault": {
    "guid": "3ee2bd37-81ee-4a57-bd63-dc84705b3985",
    "message": "Trying to add Internal View Only product {product}",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add a product without supplying the required attributes in the body.

```
{
  "badRequest": {
    "guid": "0f3e0435-21ac-43e5-acfd-ac33886fbe70",
    "message": "POST data error",
    "code": 400,
    "details": {
      "offering": "Required"
    }
  }
}
```

400 Bad Request - trying to add a product that does not exist.

```
{
  "computeFault": {
    "guid": "12cf7a72-3261-4c57-a82e-1f2f1c124d50",
    "message": "Cannot add non-existent product \"fake\"",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add a product by supplying invalid offering URI (eg: "offering": "http://coreapi01.ote.chicago.hostway:8092/product")

```
{
  "computeFault": {
    "guid": "0ced627e-c9fc-4835-92da-1a4256165607",
    "message": "Invalid offering URI",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add a product with invalid currency (case when account is set and the currency provided does not match the account's currency)

```
{
  "computeFault": {
    "guid": "742e193a-4667-47fd-a5ff-ec1f7788d459",
    "message": "Trying to add inconsistent currency: product {product} with FAKE while account uses USD",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add a product with invalid for the franchise currency (case when an account is not set so the currency it is determined by the franchise)

```
{
  "computeFault": {
    "guid": "3ee2bd37-81ee-4a57-bd63-dc84705b3985",
    "message": "Currency FAKE not allowed for this franchise",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add a product with invalid month cycle (eg: 100)

```
{
  "computeFault": {
    "guid": "8165a0b2-80f5-436f-ab47-075d824144d9",
    "message": "The requested offering is invalid",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add an existing product with invalid existingProductUri

```
{
  "computeFault": {
    "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "message": "Invalid product URI",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add an existing product that belongs to account different from the account of the order.

```
{
  "computeFault": {
    "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "message": "The account of the order and the account of the product doesn't match",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to add an existing product that does not exist

```
{
  "computeFault": {
```

```

        "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
        "message": "Product doesn't exist.",
        "code": 400,
        "details": ""
    }
}

400 Bad Request - trying to add an existing product that is not open
{
    "computeFault": {
        "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
        "message": "Cannot add a product that is not open.",
        "code": 400,
        "details": ""
    }
}

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have permission to add products.
{
    "forbidden": {
        "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
        "message": "Unauthorized: Products failed permission check",
        "code": 403,
        "details": ""
    }
}

404 Not Found - the order does not exist
{
    "itemNotFound": {
        "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
        "message": "Resource not found",
        "code": 404,
        "details": ""
    }
}

502 Bad Gateway - unexpected error from the backend.
{
    "computeFault": {
        "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
        "timestamp": "2014-09-10 20:59:50",
        "code": 502,
        "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
    }
}

```

42.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

43 Orders-orderId-account-products:GET

44 GET /orders/{orderId}/account/products

Get all Product in an account.

44.1 Contents

- 1 GET /orders/{orderId}/account/products
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.1.1 Parameters
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

44.2 Request

GET /orders/{orderId}/account/products

44.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

44.2.2 URI Parameters

None.

44.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

44.3 Response

44.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The products for the order (if any) are successfully returned.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The OwnerId cookie or the Authorization header are not specified or do not permit access to the specified order.
403 Forbidden	Unauthorized: Products failed permission check	The client does not have permission to get the products.
404 Not Found	Resource not found	The client is trying to get the products for non existing order.
502 Bad Gateway	-	Unexpected backend response.

44.3.2 Response Body

44.3.2.1 Successful response

```
200 OK
{
  "list": [
    {
      "status": "open",
      "services": "https://api.hostway.com/orders/{orderId}/account/products/{orderProductId}/services",
      "offering" : "https://api.hostway.com/productSpecifications/{productSpecificationId}/offerings/{productOfferingId}",
      "displayName": "My custom product name",
      "partnerId": "PartnerId",
      "links": [
        { "href": "https://api.hostway.com/orders/{orderId}/account/products/{orderProductId}", "rel": "self" }
      ]
    }
  ]
}
```

```

    }
  ],
  "links": [
    {
      "href": "https://api.hostway.com/orders/{orderId}/account/products/",
      "rel": "self"
    }
  ]
}

```

44.3.2.1.1 Parameters

list - *list*

List of the products for the given account order. Each element of the list has the following attributes:

status - *string*

Current status of the product. Allowed values are **new**, **pending**, **open**, **suspended**, **closed** and **purged**

services - *string*

A link to the services associated with the product

displayName - *string*

A custom display name for the product.

partnerId - *string*

Partner id.

links - *list*

[Hypermedia](#) for the product resource

offering - *string*

Link to the product catalogue offering specifying the given product

links - *list*

[Hypermedia](#) for the list of product resources

44.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have permission to get the products.

```

{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Products failed permission check",
    "code": 403,
    "details": ""
  }
}

```

404 Not Found - there is no such order.

```

{
  "itemNotFound": {
    "guid": "579951da-5f2c-4db7-9169-25658bfaafdb",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

```

502 Bad Gateway - unexpected error from the backend.

```

{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}

```

44.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

45 Orders-orderId-account-products-productId:GET

46 GET /orders/{orderId}/account/products/{productId}

Get details about a specific Product in an account.

46.1 Contents

- 1 GET /orders/{orderId}/account/products/{productId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.1.1 Parameters
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

46.2 Request

GET /orders/{orderId}/account/products/{productId}

46.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
Product's unique Id.

46.2.2 URI Parameters

None.

46.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

46.3 Response

46.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The OwnerId cookie or the Authorization header are not specified or are invalid
403 Forbidden	Unauthorized: Products failed permission check	The client does not have permission to get the product.
404 Not Found	Resource not found	The client is trying to get a product for non existing order or is trying to get non existing product.
502 Bad Gateway	-	Unexpected backend response.

46.3.2 Response Body

46.3.2.1 Successful response

```
200 OK
{
  "status" : "open",
  "services" : "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services",
  "offering" : "https://api.hostway.com/productSpecifications/{productSpecificationId}/offerings/{productOfferingId}",
  "displayName": "My custom product name",
  "partnerId": "Partner Id",
  "links" : [
    { "href": "https://api.hostway.com/orders/{orderId}/account/products/{productId}", "rel": "self" }
  ]
}
```

46.3.2.1.1 Parameters

status - *string*
Current status of the product. Allowed values are **new**, **pending**, **open**, **suspended**, **closed** and **purged**

services - *string*
A link to the services associated with the product

offering - *string*
Link to the [product catalog offering](#) specifying the given product

displayName - *string*
A custom display name for the product.

partnerId - *string*
Partner id.

links - *list*
[Hypermedia](#) for the product resource

46.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have permission to get the product.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Products failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found

```
{
  "itemNotFound": {
    "guid": "579951da-5f2c-4db7-9169-25658bfaafdb",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

46.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

47 Orders-orderId-account-products-productId:PUT

48 PUT /orders/{orderId}/account/products/{productId}

Updates an existing product in order builder. Currently supports only updating the billing cycle.

48.1 Contents

- 1 PUT /orders/{orderId}/account/products/{productId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - ◇ 1.1.5 Validation Rules
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

48.2 Request

PUT /orders/{orderId}/account/products/{productId}

48.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

48.2.2 URI Parameters

None.

48.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

48.2.4 Request Body

A dictionary containing the key "billingCycle" and a value that is integer.

```
{
  "billingCycle": 12
}
```

48.2.5 Validation Rules

1. The product URL (`https://api.hostway.com/orders/{orderId}/account/products/{productId}`) should point to a valid product already added to the order.
2. The billing cycle should be a valid integer between 1 and 120 and also a valid billing cycle as defined in ServicePlex.

48.3 Response

48.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
	POST data error	Missing billing cycle value.
	POST data error	Trying to add a billing cycle less than 1.
400 Bad Request	POST data error	Trying to update the billing cycle to value > 120.
		Trying to update the billing cycle to value that is not available for the product.
	Unable to update the product 0000014ee39eee9c95fa4b5b007f000000010001	

401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The <i>OwnerId</i> cookie was not specified or is incorrect.
403 Forbidden	Unauthorized: Products failed permission check	The client does not have permissions to update the product.
404 Not Found	Resource not found	The client is trying to update the billing cycle for a non existing product or order.
502 Bad Gateway	-	Unexpected backend response.

48.3.2 Response Body

48.3.2.1 Successful response

None.

48.3.2.2 Error responses

```

400 Bad Request - empty body is passed
{
  "badRequest": {
    "guid": "bd80dfdc-5752-4472-96f2-90f590ddb3f9",
    "message": "POST data error",
    "code": 400,
    "details": {"billingCycle": "Required"}
  }
}

400 Bad Request - invalid body is passed (required field is missing)
{
  "badRequest": {
    "guid": "aae865ae-5102-49d9-b1ef-8a5419cc0ce7",
    "message": "POST data error",
    "code": 400,
    "details": {"billingCycle": "Required"}
  }
}

400 Bad Request - invalid billing cycle is passed
{
  "badRequest": {
    "guid": "fdd0b796-c690-47af-9666-0478e2bcae27",
    "message": "POST data error",
    "code": 400,
    "details": {"billingCycle": "0 is less than minimum value 1"}
  }
}

400 Bad Request - invalid billing cycle is passed
{
  "computeFault": {
    "guid": "1e98f8ea-d298-4867-a9aa-0a6486dbefb0",
    "message": "POST data error",
    "code": 400,
    "details": {"billingCycle": "122 is greater than maximum value 120"}
  }
}

400 Bad Request - billing cycle is not available for the product
{
  "computeFault": {
    "guid": "1e98f8ea-d298-4867-a9aa-0a6486dbefb0",
    "message": "Unable to update the product 0000014edfe57d8b9b2c78bf007f000000010001",
    "code": 400,
    "details": ""
  }
}

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden

{
  "forbidden": {
    "guid": "6af8e3e6-c3dc-4083-8389-1c1a038c62c0",
    "message": "Unauthorized: Products failed permission check",
    "code": 403,
    "details": ""
  }
}

404 Not Found - the order or product was not found.
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

502 Bad Gateway - unexpected error from the backend.
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}

```

```
} }
```

48.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

49 Orders-orderId-account-products-productId:DELETE

50 DELETE /orders/{orderId}/account/products/{productId}

Removes a product from the account's order.

50.1 Contents

- 1 DELETE /orders/{orderId}/account/products/{productId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

50.2 Request

DELETE /orders/{orderId}/account/products/{productId}

50.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
Product's unique Id.

50.2.2 URI Parameters

None.

50.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

50.3 Response

50.3.1 Status Code

Status Code	Error Message	Description
204	-	The product was successfully deleted.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The OwnerId cookie or the Authorization header are not specified or invalid.
403 Forbidden	Unauthorized: Products failed permission check	The client does not have permissions to delete products.
404 Not Found	Resource not found	The client is trying to delete a non existing product or the order does not exist.
502 Bad Gateway	-	Unexpected backend response.

50.3.2 Response Body

50.3.2.1 Successful response

None.

50.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have permission to delete products.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Products failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found

```
{
  "itemNotFound": {
    "guid": "579951da-5f2c-4db7-9169-25658bfaafdb",
```

```
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

502 Bad Gateway - unexpected error from the backend.
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

50.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

51 Orders-orderId-account-products-productId-services:POST

52 POST /orders/{orderId}/account/products/{productId}/services

Adds a new service to a product in the order.

52.1 Contents

- 1 POST /orders/{orderId}/account/products/{productId}/services
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◇ 1.1.5 Validation Rules
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - 1.2.3.1 Successful response
 - 1.2.3.2 Error responses
 - ◆ 1.3 Examples
 - ◇ 1.3.1 Create a service with attributes
 - ◇ 1.3.2 Create a service with attributes and make it related to an existing service
 - ◇ 1.3.3 Create a service with attributes and make it related to another new service in the same order
 - ◇ 1.3.4 Create a service with quantity but without attributes and make it related to another new service in the same order
 - ◇ 1.3.5 Create a service and make it associated to an existing service
 - ◇ 1.3.6 Create a service and make it associated to another new service in the same order
 - ◇ 1.3.7 Create a service and make it associated to two other new services in the same order
 - ◇ 1.3.8 Create a service and make it related to another new service and associate it with a second new service in the same order
 - ◆ 1.4 See also

52.2 Request

POST /orders/{orderId}/account/products/{productId}/services

52.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*

UUID specifying the product

52.2.2 URI Parameters

None.

52.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

52.2.4 Request Body

```
{
  "name": "john.smith1",
  "relatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}" ],
  "associatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}" ],
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/{serviceSpecificationId}",
  "promoCode": "{promoCode}"
  "billingCycle": 1,
  "quantity": 1,
  "attributes": {
    "{attribute-name}": "{attribute-value}",
    ....
  }
}
```

52.2.4.1 Parameters

name - *string*

The name of the new service

relatedTo - *list* (optional)

A list containing other services related in some way to the newly created service. The relatedTo may be omitted, but relationships between some types of services have to be established for the order to be validated or submitted. The list may contain links to [other new services in the order](#) and/or a link to an [existing service](#) that belongs to the same account. If a link to an existing service is specified, a parent-child relationship will be created between the existing service and the newly-added service.

serviceSpecification - *string*

Link to the [product catalog specification](#) describing the new service

billingCycle - *integer*

Billing cycle (length of billing period in months) of the service. Allowed values are from **1** to **120**

quantity - *integer* (optional)

Quantity of the service. Must be greater than **0**. It is **1** by default. Quantity greater than 1 only allowed for services configured to support multiple quantities when ordering.

attributes - *dictionary* (optional)

a dictionary of the new service's attributes values. Each (*attribute-name*, *attribute-value*) pair present the service attribute name and its relevant value to be set. The allowed attribute names depends on the *serviceSpecification* field value. See [Service Attributes Structure](#).

promoCode - *string* (optional)

A promotion code for the new service [promotion codes](#).

associatedTo - *list* (optional)

A list containing other services that are associated in some way to the newly created service. The list may contain links to [other new services in the order](#) and/or a link to an [existing service](#) that belongs to the same account and product. Adding a service to this list will not alter existing or create new parent-child relationships between the existing service and the newly-added service. In most cases the list may be empty unless otherwise stated.

52.2.5 Validation Rules

1. The service specification URL (<https://api.hostway.com/serviceSpecifications/{serviceSpecificationId}>) should point to an existing service.
2. Each service URL (<https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}>) from the related services list should point to a valid service already added to the product.
3. The related services list may contain at most one URL to an existing service (ex. <https://api.hostway.com/accounts/{accountId}/products/{productId}/services/{serviceId}>) that is open on the account.
4. The service billing cycle should be allowed for the product.
5. The product should support adding the service.
6. Each service URL from the associated services list should point to a valid service already added to the product.
7. Any associated service that already exists on the account must be open.

52.3 Response

52.3.1 Status Code

Status Code	Error Message	Description
201 Created	-	The service was successfully added to the order.
	POST data error	Trying to create a service without passing all the required attributes.
	Invalid service specification	Malformed serviceSpecification was passed or the service is not found in the backend.
	Invalid cycle	Trying to add service with wrong billingCycle.
	Invalid quantity	Trying to add service with invalid quantity input. It should be a number greater than 0.
400 Bad Request	Product does not support quantity	Trying to set quantity on service that is not configured to support multiple units.
	Invalid relatedTo service ID provided: fake.service	Trying to add a service with invalid relatedTo.
	Invalid associatedTo service ID: fake.service	Trying to add a service with invalid associatedTo.
	Product does not support this service	Trying to add service to a product, which doesn't support the service.
	Current service requires being a child service.	The service that can be added only as a child is not added as a child of another service.
	Cannot create domain alias to the same domain name.	Trying to create domain alias to the same domain name.
	Parent service doesn't exist.	Tried to add the service as a child service of an existing service that doesn't exist.
Parent service is not open.	Tried to add the service as a child service of an existing service that is not open.	
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The <i>OwnerId</i> cookie was not specified or is incorrect.
403 Forbidden	Unauthorized: Services failed permission check	The client does not have permissions to add services.
404 Not Found	Resource not found	The order or product doesn't exist.
Domain-dependent services:		
409 Conflict	Cannot create domain alias to the same domain name.	Duplicate domain.
	Email domain alias service: A domain alias would produce impossible to delivery loops	
	Domain {domain_name} has circular forwards to alias {alias_name}	There is an email forwarder from the target domain name to a mailbox of the domain alias with the same username There is an email forwarder from the domain alias to a mailbox of the target domain name with the same username
502 Bad Gateway	-	Unexpected backend response.

52.3.2 Response Headers

Location

Returned with successful response. Contains the URI of the newly added service and the id of the service.

52.3.3 Response Body

52.3.3.1 Successful response

201 Created

```
{
  "serviceId": "00000140735d43640f62c50f007f000000010001",
  "url": "https://api.hostway.com/order/account/products/00000140728b013c52e249a4007f000000010001/services/00000140735d43640f62c50f007f000000010001"
}
```

Note: The service Id will change once the order is provisioned.

52.3.3.2 Error responses

400 Bad Request - request body is missing some of the required attributes

```
{
  "badRequest": {
    "guid": "23bf964e-fb93-4bd6-816e-3dcb31b82755",
    "message": "POST data error",
    "code": 400,
    "details": {
      "serviceSpecification": "Required",
      "billingCycle": "Required"
    }
  }
}
```

400 Bad Request - malformed serviceSpecification was passed or the service is not found in the backend

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Invalid service specification",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - wrong billingCycle

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Invalid cycle",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - invalid quantity

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Invalid quantity",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - unsupported quantity

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Product does not support quantity",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - invalid service was passed as relatedTo

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Invalid relatedTo service ID provided: fake.service",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - the service is not supported by the product

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Product does not support this service",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - the service that can be added only as a child was not added as a child of another service

```
{
  "computeFault": {
    "guid": "e4443fe7-1139-4078-b407-39d868c02d26",
    "message": "Current service requires being a child service.",
    "code": 400,
    "details": ""
  }
}
```

```

400 Bad Request - request body provided incorrect attributes
{
  "badRequest": {
    "guid": "5386544b-6dbf-4d21-b22a-879979070c01",
    "message": "POST data error",
    "code": 400,
    "details": {"attributes.serverName": "Required"}
  }
}

400 Bad Request - trying to create domain alias to the same domain name
{
  "computeFault": {
    "guid": "c270f3a1-331f-4736-b420-c006cbdae689",
    "message": "Cannot create domain alias to the same domain name.",
    "code": 400,
    "details": ""
  }
}

400 Bad Request - trying to add domain alias with invalid domain name
{
  "badRequest": {
    "guid": "6321f804-285a-43fb-890a-bbdbcb1bd8db3",
    "message": "POST data error",
    "code": 400,
    "details": {"attributes.domain": "Invalid domain name in domain: invalid", "attributes.domain_alias": "Invalid domain name in domain_"}
  }
}

400 Bad Request - trying to specify a relationship to an existing service that doesn't exist
{
  "badRequest": {
    "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "message": "Parent service doesn't exist.",
    "code": 400,
    "details": ""
  }
}

400 Bad Request - trying to specify a relationship to an existing service that isn't open
{
  "badRequest": {
    "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "message": "Parent service is not open.",
    "code": 400,
    "details": ""
  }
}

400 Bad Request - trying to specify an association to an existing service that doesn't exist
{
  "badRequest": {
    "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "message": "Invalid associatedTo service ID: xxxxx",
    "code": 400,
    "details": ""
  }
}

400 Bad Request - trying to specify an association to an existing service that isn't open
{
  "badRequest": {
    "guid": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "message": "Associated service is not open",
    "code": 400,
    "details": ""
  }
}

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have access to get the information about the services.
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Services failed permission check",
    "code": 403,
    "details": ""
  }
}

404 Not Found - the order or product was not found.
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

409 Conflict
{
  "conflict": {
    "guid": "685b8586-c854-4dd8-ae9d-6233fe007a86",
    "message": "Domain ng-test-hwus-drago-140723b.com has circular forwards to alias ng-test-hwus-drago-140723b-alias140814.com",
    "code": 409,
    "details": ""
  }
}

502 Bad Gateway - unexpected error from the backend.
{

```

```

    "computeFault": {
      "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
      "timestamp": "2014-09-10 20:59:50",
      "code": 502,
      "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
    }
  }
}

```

52.4 Examples

52.4.1 Create a service with attributes

Request

```

{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedserver",
  "billingCycle": 1,
  "attributes": {
    "serverName": "sampleServerName",
    "serverLocation": "Tampa"
  }
}

```

52.4.2 Create a service with attributes and make it related to an existing service

Request

```

{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedserver",
  "billingCycle": 1,
  "attributes": {
    "serverName": "sampleServerName",
    "serverLocation": "Tampa"
  },
  "relatedTo": ["https://api.hostway.com/accounts/{accountId}/products/{productId}/services/{serviceId}"]
}

```

52.4.3 Create a service with attributes and make it related to another new service in the same order

Request

```

{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedserver",
  "billingCycle": 1,
  "attributes": {
    "serverName": "sampleServerName",
    "serverLocation": "Tampa"
  },
  "relatedTo": ["https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}"]
}

```

52.4.4 Create a service with quantity but without attributes and make it related to another new service in the same order

Request

```

{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedserver.hardware.memory",
  "billingCycle": 1,
  "quantity": 4,
  "relatedTo": ["https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}"]
}

```

52.4.5 Create a service and make it associated to an existing service

Request

```

{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedicatedserver.hardware.disk.500gb",
  "billingCycle": 1,
  "quantity": 4,
  "associatedTo": ["https://api.hostway.com/accounts/{accountId}/products/{productId}/services/{serviceId}"]
}

```

52.4.6 Create a service and make it associated to another new service in the same order

Request

```

{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedicatedserver.hardware.disk.500gb",
  "billingCycle": 1,
  "quantity": 4,
  "associatedTo": ["https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}"]
}

```


52.4.7 Create a service and make it associated to two other new services in the same order

Request

```
{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedicatedserver.hardware.diskcontroller.sataraid",
  "billingCycle": 1,
  "quantity": 4,
  "associatedTo": [
    "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{service1Id}",
    "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{service2Id}"
  ]
}
```

52.4.8 Create a service and make it related to another new service and associate it with a second new service in the same order

Request

```
{
  "name": "ng-test-hwus-test.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedicatedserver.hardware.disk.500gb",
  "billingCycle": 1,
  "quantity": 4,
  "relatedTo": ["https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{service1Id}"],
  "associatedTo": ["https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{service2Id}"]
}
```

52.5 See also

- [Orders API](#)
- [Common Features](#)
- [Service Attributes Structure](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

53 Orders-orderId-account-products-productId-services:GET

54 GET /orders/{orderId}/account/products/{productId}/services

Get all Services in a given product.

54.1 Contents

- 1 GET /orders/{orderId}/account/products/{productId}/services
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.1.1 Parameters
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

54.2 Request

GET /orders/{orderId}/account/products/{productId}/services

54.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

54.2.2 URI Parameters

None.

54.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

54.3 Response

54.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The services for the order and product (if any) are successfully returned.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The OwnerId cookie or the Authorization header are not specified or do not permit access to the specified order.
403 Forbidden	Unauthorized: Services failed permission check	The client does not have permissions to get information about the services.
404 Not Found	Resource not found	The client is trying to get the services for non existing order or non existing product.
502 Bad Gateway	-	Unexpected backend response.

54.3.2 Response Body

54.3.2.1 Successful response

```
200 OK
{
  "list": [
    {
      "status": "new",
      "name": "john.smith1",
      "links": [
        { "href": "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}/", "rel": "self" }
      ],
      "relatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}" ],
      "associatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}" ],
      "serviceSpecification": "https://api.hostway.com/serviceSpecifications/{serviceSpecificationId}",
      "billingCycle": 1,
      "quantity": 1,
      "attributes": "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes"
    }
  ],
  "links": [
    { "href": "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/", "rel": "self" }
  ]
}
```

54.3.2.1.1 Parameters

`list` - *list*
List of the services for the given product. Each element of the list has the following attributes:

`status` - *string*
Current status of the service. Allowed values are **new**, **pending**, **open**, **suspended**, **close_pending**, **closed**, **purge_pending** and **purged**

`name` - *string*
The name of the specific service

`links` - *list*
[Hypermedia](#) for the product resource

`relatedTo` - *list*
A list containing other services in the current order related in some way to the current service

`associatedTo` - *list* (optional)
A list containing other services that are associated in some way to the service. The list may contain links to [other new services in the order](#) and/or a link to an [existing service](#) that belongs to the same account and product. In most cases the list may be empty unless otherwise stated.

`serviceSpecification` - *string*
Link to the product catalogue specification describing the given service

`billingCycle` - *integer*
Billing cycle (length of billing period in months) of the service. Allowed values are from **1** to **120**

`quantity` - *integer*
Quantity (if multiple services is allowed) of the service.

`attributes` - *string*
A link to the attributes of the service

`links` - *list*
[Hypermedia](#) for the list of product resources

54.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have assess to get the information about the services.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Services failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found - the order or the product doesn't exist.

```
{
  "itemNotFound": {
    "guid": "3a422918-24c3-4c20-9bee-f1c61695e987",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

54.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

55 Orders-orderId-account-products-productId-services-serviceId:GET

56 GET /orders/{orderId}/account/products/{productId}/services/{serviceId}

Get details about a specific service in a given product.

56.1 Contents

- 1 GET /orders/{orderId}/account/products/{productId}/services/{serviceId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.1.1 Parameters
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

56.2 Request

GET /orders/{orderId}/account/products/{productId}/services/{serviceId}

56.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

56.2.2 URI Parameters

None.

56.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

56.3 Response

56.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The services for the order and product (if any) are successfully returned.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The OwnerId cookie or the Authorization header are not specified or do not permit access to the specified order.
403 Forbidden	Unauthorized: Services failed permission check	The client does not have access to get the information about the service.
404 Not Found	Resource not found	The client is trying to get the information for a service for non existing order, product or service.
502 Bad Gateway	-	Unexpected backend response.

56.3.2 Response Body

56.3.2.1 Successful response

```
{
  "status": "new",
  "name": "john.smith1",
  "links": [
    {
      "href": "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}/",
      "rel": "self"
    }
  ],
  "relatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{relatedServiceId}" ],
  "associatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}" ],
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/{serviceSpecificationId}",
  "billingCycle": 1,
  "quantity": 1,
  "attributes": "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes"
}
```

56.3.2.1.1 Parameters

- status** - *string*
Current status of the service. Allowed values are **new**, **placed**, **pending**, **open**, **suspended**, **close_pending**, **closed**, **purge_pending** and **purged**
- name** - *string*
The name of the specific service
- links** - *list*
[Hypermedia](#) for the product resource
- relatedTo** - *list*
A list containing other services related in some way to the current service
- associatedTo** - *list* (optional)
A list containing other services that are associated in some way to the service. The list may contain links to [other new services in the order](#) and/or a link to an [existing service](#) that belongs to the same account and product. In most cases the list may be empty unless otherwise stated.
- serviceSpecification** - *string*
Link to the product catalogue specification describing the given service
- billingCycle** - *integer*
Billing cycle of the service. Allowed values are from **1** to **120**
- quantity** - *integer*
Quantity (if multiple services is allowed) of the service.
- attributes** - *string*
A link to the attributes of the service

56.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have assess to get the information about the service.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Services failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found - the order, product or service doesn't exist.

```
{
  "itemNotFound": {
    "guid": "3a422918-24c3-4c20-9bee-f1c61695e987",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

56.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

57 Orders-orderId-account-products-productId-services-serviceId:PUT

58 PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}

Updates a service in order builder. Currently supports only updating the name and the billing cycle of the service.

58.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/services/{serviceId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - ◇ 1.1.5 Validation Rules
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

58.2 Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}

58.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

58.2.2 URI Parameters

None.

58.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

58.2.4 Request Body

A dictionary containing the keys "billingCycle" and "name" and their values.

```
{
  "billingCycle": 12,
  "name": "Service Name",
  "associatedTo": [ "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}", "https://api.hostway.com/ac"
}
```

58.2.5 Validation Rules

1. The service URL (`https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}`) should point to a valid service already added to the product.
2. The dictionary key/value pairs should be valid billing cycle and service name.
3. The billingCycle and name parameters are required.
4. Each service URL from the associated services list should point to a valid service already added to the product.
5. Any associated service that already exists on the account must be open.

58.3 Response

58.3.1 Status Code

Status Code	Error Message	Description
204 No Content -		The operation was successfully completed.
400 Bad Request	POST data error Unable to change service: invalid cycle	Trying to update service with empty body or with invalid body. Trying to change the billing cycle to value that is not supported by the current service.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The <i>OwnerId</i> cookie was not specified or is incorrect.

403 Forbidden Unauthorized: Service failed permission check

404 Not Found Resource not found

502 Bad Gateway -

58.3.2 Response Body

58.3.2.1 Successful response

None.

58.3.2.2 Error responses

400 Bad Request - invalid or empty body is passed (required field is missing)

```
{
  "badRequest": {
    "guid": "aae865ae-5102-49d9-b1ef-8a5419cc0ce7",
    "message": "POST data error",
    "code": 400,
    "details": {"billingCycle": "Required", "name": "Required"}
  }
}
```

400 Bad Request - missing billingCycle

```
{
  "badRequest": {
    "guid": "aae865ae-5102-49d9-b1ef-8a5419cc0ce7",
    "message": "POST data error",
    "code": 400,
    "details": {"billingCycle": "Required"}
  }
}
```

400 Bad Request - missing name

```
{
  "badRequest": {
    "guid": "aae865ae-5102-49d9-b1ef-8a5419cc0ce7",
    "message": "POST data error",
    "code": 400,
    "details": {"name": "Required"}
  }
}
```

400 Bad Request - invalid billing cycle

```
{
  "computeFault": {
    "guid": "7c72847f-5138-44e8-ad93-cc80bb5ba7bc",
    "message": "Unable to change service: invalid cycle",
    "code": 400,
    "details": ""
  }
}
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

404 Not Found - the order or product was not found.

```
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

58.4 See also

- [Orders API](#)
- [Common Features](#)

The client does not have permissions to update the service.

The client is trying to update a non existing service.

Unexpected backend response.

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

59 Orders-orderId-account-products-productId-services-serviceId:DELETE

60 DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}

Removes service from a product.

60.1 Contents

- 1 DELETE
/orders/{orderId}/account/products/{productId}/services/{serviceId}
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

60.2 Request

DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}

60.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*

Product's unique Id.

serviceId - *string*

UUID specifying the service to be deleted

60.2.2 URI Parameters

None.

60.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

60.3 Response

60.3.1 Status Code

Status Code	Error Message	Description
204	-	The operation was successfully completed.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The OwnerId cookie or the Authorization header are not specified or do not permit access to the specified order.
403 Forbidden	Unauthorized: Services failed permission check	The client does not have permissions to delete a service.
404 Not Found	Resource not found	The order, product or service is not found.
502 Bad Gateway	-	Unexpected backend response.

60.3.2 Response Body

60.3.2.1 Successful response

None.

60.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have permissions to delete a service.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: Services failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found

```
{
  "itemNotFound": {
    "guid": "579951da-5f2c-4db7-9169-25658bfaafdb",
    "message": "Resource not found",
    "code": 404,
  }
}
```

```
        "details": ""
    }
}

502 Bad Gateway - unexpected error from the backend.
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

60.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

61 Orders-orderId-account-products-productId-services-serviceId-attributes:PUT

62 PUT

/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes

Adds Attributes to the Service. Not all services support this call. Depending on the service, this call *may* return a response code of 405 (method not supported).

62.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - ◇ 1.1.5 Validation Rules
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

62.2 Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes

62.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

62.2.2 URI Parameters

None.

62.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

62.2.4 Request Body

A dictionary whose keys/values will depend on the service category of the service. See [Service Attributes Structure](#).

```
{  
  "key_one": "Value One",  
  "key_two": "Value Two",  
  ...  
}
```

62.2.5 Validation Rules

1. The service URL (<https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}>) should point to a valid service already added to the product.
2. The attribute key/value pair should be allowed for the service specification.

62.3 Response

62.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
	POST data error	Trying to create an attribute without body or with invalid body.
400 Bad Request	Invalid term supplied -1	Trying to add attributes for transfer domain request with invalid value for term (should be 1).
	No attributes defined for the provided service specification	Trying to get attributes for service with no attributes.
401 Unauthorized		

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

403 Forbidden Unauthorized: Attributes failed permission check

404 Not Found Resource not found

405 Method Not Allowed -

502 Bad Gateway -

62.3.2 Response Body

62.3.2.1 Successful response

None.

62.3.2.2 Error responses

400 Bad Request - no request body is passed

```
{
  "badRequest": {
    "guid": "bd80dfdc-5752-4472-96f2-90f590ddb3f9",
    "message": "POST data error",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - invalid body is passed (required field is missing)

```
{
  "badRequest": {
    "guid": "aae865ae-5102-49d9-blef-8a5419cc0ce7",
    "message": "POST data error",
    "code": 400,
    "details": {"serverName": "Required"}
  }
}
```

400 Bad Request - invalid attributes are passed

```
{
  "badRequest": {
    "guid": "fdd0b796-c690-47af-9666-0478e2bcae27",
    "message": "POST data error",
    "code": 400,
    "details": {"serverLocation": "String does not match expected pattern"}
  }
}
```

400 Bad Request - invalid term for transfer request is passed.

```
{
  "computeFault": {
    "guid": "1e98f8ea-d298-4867-a9aa-0a6486dbefb0",
    "message": "Invalid term supplied -1",
    "code": 400,
    "details": ""
  }
}
```

400 Bad Request - trying to get the attributes for a service that does not have attributes.

```
{
  "computeFault": {
    "guid": "756b755a-84cf-4692-b2c6-70808dc9d00d",
    "message": "No attributes defined for the provided service specification",
    "code": 400, "details": ""
  }
}
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

404 Not Found - the order or product was not found.

```
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

62.4 See also

- [Orders API](#)
- [Common Features](#)
- [Service Attributes Structure](#)

The *OwnerId* cookie was not specified or is incorrect.

The client does not have permissions to add attributes.

The client is trying to add attribute for non existing order, product or service.

The service does not support attributes.

Unexpected backend response.

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

63 Orders-orderId-account-products-productId-services-serviceId-attributes:GET

64 GET

/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes

Get the Attributes of a given Service. Not all services will have attributes; depending on the service, this call *may* return a response code of 405 (Method not supported). If attributes are supported on the service, but have not yet been set, this call will return an empty dictionary in the response body.

64.1 Contents

- 1 GET
/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful responses
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

64.2 Request

GET /orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes

64.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

64.2.2 URI Parameters

None.

64.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

64.3 Response

64.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
400 Bad Request	No attributes defined for the provided service specification	Trying to get attributes for service with no attributes.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The <i>OwnerId</i> cookie was not specified or is incorrect.
403 Forbidden	Unauthorized: Attributes failed permission check	The client does not have permissions for this operation.
404 Not Found	Resource not found	The client is trying to add attribute for non existing order, product or service.
405 Method Not Allowed	-	The service does not support attributes.
502 Bad Gateway	-	Unexpected backend response.

64.3.2 Response Body

64.3.2.1 Successful responses

Will be a dictionary whose keys/values are specific to the service category of the service. See [Service Attributes Structure](#).

64.3.2.2 Error responses

```
400 Bad Request - trying to get the attributes for a service that does not have attributes.
{
  "computeFault": {
    "guid": "756b755a-84cf-4692-b2c6-70808dc9d00d",
    "message": "No attributes defined for the provided service specification",
    "code": 400, "details": ""
  }
}
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

404 Not Found - the order, product or service was not found.

```
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

64.4 See also

- [Orders API](#)
- [Common Features](#)
- [Service Attributes Structure](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

66 OPTIONS

/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes

Get list of supported methods for this resource, plus some hints on the expected resource structure.

66.1 Contents

- 1 OPTIONS
/orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Response Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - ◆ 1.3 See also

66.2 Request

OPTIONS /orders/{orderId}/account/products/{productId}/services/{serviceId}/attributes

66.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

66.3 Response

66.3.1 Response Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The <i>OwnerId</i> cookie was not specified or is incorrect.
403 Forbidden	Unauthorized: Attributes failed permission check	The client does not have permissions for this operation.
404 Not Found	Resource not found	The client is trying to add attribute for non existing order, product or service.
502 Bad Gateway	-	Unexpected backend response.

66.3.2 Response Headers

Allow
Contains a comma-separated list of methods that are allowed on this resource. For services that do not support attributes, this will contain only the OPTIONS method.

66.3.3 Response Body

A dictionary whose keys/values are specific to the service category of the service. Rather than returning actual service data, the body will contain a dictionary that provides hints for how to build the request body for a PUT request, for example:

```
{
  "name": "String",
  "numWidgets": "Integer",
  "widgets": [
    {
      "id": "String",
      "widgetType": "String",
      "otherAttribute": "String"
    }
  ]
}
```

66.4 See also

- [Orders API](#)
- [Common Features](#)
- [Service Attributes Structure](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

67 ServiceAttributesStructure

Services supported by Hostway Public Order API:

- [Web Hosting](#)
- [Domain Name Registration](#)
- [Sub-Domain Registration](#)
- [Dedicated Server](#)
- [Dedicated Server Firewall](#)
- [Exchange2010](#)
- [WhoisProtector \(Private Registration\)](#)
- [DomainGuard](#)
- [VPS Virtuozzo Server](#)
- [WebsPlanet](#)
- [Excel Micro](#)
- [Cloud Compute](#)
- [Sharepoint](#)
- [Sharepoint 2007](#)
- [Fax Over Email - User](#)
- [Fax Over Email - Number](#)
- [Online Backup - Account](#)
- [AVAS](#)

67.1 See also

- [Orders API](#)
- [Account Management API](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

68 Orders-orderId-account-products-productId-services-serviceId-notes:POST

69 POST

/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

Adds a new note to a service in the order.

69.1 Contents

- 1 POST
/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - 1.2.3.1 Successful response
 - 1.2.3.2 Error responses
 - ◆ 1.3 See also

69.2 Request

POST /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

69.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

69.2.2 URI Parameters

None.

69.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

69.2.4 Request Body

```
{  
  "note": "xx"  
}
```

69.2.4.1 Parameters

note - *string*
The text of the note

69.3 Response

69.3.1 Status Code

Status Code	Error Message	Description
201 Created	-	The note was successfully added to the service.
400 Bad Request	POST data error	Trying to create a note without passing all the required attributes.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The request was not properly authorized.
403 Forbidden	Unauthorized: NotesView failed permission check	The client does not have permissions to add notes.
404 Not Found	Resource not found	The order or product or service doesn't exist.
405 Method not allowed	Method not allowed	Trying to add notes for placed order.
502 Bad Gateway	-	Unexpected backend response.

69.3.2 Response Headers

None.

69.3.3 Response Body

69.3.3.1 Successful response

201 Created

69.3.3.2 Error responses

400 Bad Request - request body is missing some of the required attributes

```
{
  "badRequest": {
    "guid": "23bf964e-fb93-4bd6-816e-3dcb31b82755",
    "message": "POST data error",
    "code": 400,
    "details": {
      "note": "Required"
    }
  }
}
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have access to add notes.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: NotesView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found - the order, product or the service was not found.

```
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

{
  "badMethod": {
    "guid": "3e9418e0-5a5d-4652-ae50-0e665d39571a",
    "message": "Method not allowed",
    "code": 405,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

69.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

70 Orders-orderId-account-products-productId-services-serviceId-notes:PUT

71 PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

Updates the notes for a service in the order.

71.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - 1.2.3.1 Successful response
 - 1.2.3.2 Error responses
 - ◆ 1.3 See also

71.2 Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

71.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service

71.2.2 URI Parameters

None.

71.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

71.2.4 Request Body

```
{  
  "notes": ["xx", "zz"]  
}
```

71.2.4.1 Parameters

notes - *list*
List of notes to update the existing notes for a the service

71.3 Response

71.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The notes were successfully added to the service.
400 Bad Request	POST data error	Trying to update the notes without passing all the required attributes.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The request was not properly authorized.
403 Forbidden	Unauthorized: NotesView failed permission check	The client does not have permissions to update the notes.
404 Not Found	Resource not found	The order, product or service doesn't exist.
405 Method not allowed	Method not allowed	Trying to update the notes for placed order.
502 Bad Gateway	-	Unexpected backend response.

71.3.2 Response Headers

None.

71.3.3 Response Body

71.3.3.1 Successful response

201 Created

71.3.3.2 Error responses

400 Bad Request - request body is missing some of the required attributes

```
{
  "badRequest": {
    "guid": "23bf964e-fb93-4bd6-816e-3dcb31b82755",
    "message": "POST data error",
    "code": 400,
    "details": {
      "notes": "Required"
    }
  }
}
```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have access to update the notes.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: NotesView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found - the order, product or the service was not found.

```
{
  "itemNotFound": {
    "guid": "e1792d8a-5b0a-43ef-adf5-34a0710c8fc5",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

{
  "badMethod": {
    "guid": "3e9418e0-5a5d-4652-ae50-0e665d39571a",
    "message": "Method not allowed",
    "code": 405,
    "details": ""
  }
}
```

502 Bad Gateway - unexpected error from the backend.

```
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}
```

71.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

72 Orders-orderId-account-products-productId-services-serviceId-notes:GET

73 GET /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

Get all notes for a given service.

73.1 Contents

- 1 GET
/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.1.1 Parameters
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

73.2 Request

GET /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

73.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the product

73.2.2 URI Parameters

None.

73.2.3 Request Headers

73.3 Response

73.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The notes for the service (if any) are successfully returned.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The request was not properly authorized.
403 Forbidden	Unauthorized: NotesView failed permission check	The client does not have permissions to get information about the notes.
404 Not Found	Resource not found	The client is trying to get the notes for non existing order, product or service.
502 Bad Gateway	-	Unexpected backend response.

73.3.2 Response Body

73.3.2.1 Successful response

```
200 OK
{
  "notes": ["xx", "zz"],
  "links": [
    { "href": "https://api.hostway.com/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes", "rel": "self" }
  ]
}
```

73.3.2.1.1 Parameters

notes - *list*
List of the notes for the given service.

links - *list*
[Hypermedia](#) for the list of notes resources

73.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have access to get the information about the notes for a service.

```

{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: NotesView failed permission check",
    "code": 403,
    "details": ""
  }
}

404 Not Found - the order, the product or the service doesn't exist.
{
  "itemNotFound": {
    "guid": "3a422918-24c3-4c20-9bee-f1c61695e987",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}

502 Bad Gateway - unexpected error from the backend.
{
  "computeFault": {
    "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",
    "timestamp": "2014-09-10 20:59:50",
    "code": 502,
    "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"
  }
}

```

73.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

74 Orders-orderId-account-products-productId-services-serviceId-notes:DELETE

75 DELETE

/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

Removes notes from a service.

75.1 Contents

- 1 DELETE
/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Successful response
 - 1.2.2.2 Error responses
 - ◆ 1.3 See also

75.2 Request

DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

75.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the POST /orders call.

productId - *string*
Product's unique Id.

serviceId - *string*
UUID specifying the service to be deleted

75.2.2 URI Parameters

None.

75.2.3 Request Headers

75.3 Response

75.3.1 Status Code

Status Code	Error Message	Description
204	-	The operation was successfully completed.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The request was not properly authorized.
403 Forbidden	Unauthorized: NotesView failed permission check	The client does not have permissions to delete the notes.
404 Not Found	Resource not found	The order, product or service is not found.
502 Bad Gateway	-	Unexpected backend response.

75.3.2 Response Body

75.3.2.1 Successful response

None.

75.3.2.2 Error responses

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., b

403 Forbidden - the client does not have permissions to delete the notes.

```
{
  "forbidden": {
    "guid": "d336dd8e-bc52-44f3-b672-9aa2fac7fbf4",
    "message": "Unauthorized: NotesView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

404 Not Found

```
{
  "itemNotFound": {
    "guid": "579951da-5f2c-4db7-9169-25658bfaafdb",
    "message": "Resource not found",

```

```
        "code": 404,  
        "details": ""  
    }  
}  
  
502 Bad Gateway - unexpected error from the backend.  
{  
    "computeFault": {  
        "guid": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce",  
        "timestamp": "2014-09-10 20:59:50",  
        "code": 502,  
        "errorRefId": "8ced5fe7-f6a9-4e8f-8700-cfc9fa15e6ce"  
    }  
}
```

75.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

76 Orders-orderId-account-products-productId-services-serviceId-notes:OPTIONS

77 OPTIONS

/orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

Get list of supported methods for this resource, plus some hints on the expected resource structure.

77.1 Contents

- 1 OPTIONS
 - /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Response Status Code
 - ◇ 1.2.2 Response Headers
 - ◇ 1.2.3 Response Body
 - ◆ 1.3 See also

77.2 Request

OPTIONS /orders/{orderId}/account/products/{productId}/services/{serviceId}/notes

77.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*

UUID specifying the product

serviceId - *string*

UUID specifying the service

77.3 Response

77.3.1 Response Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.	The request was not properly authorized.
403 Forbidden	Unauthorized: NotesView failed permission check	The client does not have permissions for this operation.
404 Not Found	Resource not found	The order, product or service doesn't exist.

77.3.2 Response Headers

Allow

Contains a comma-separated list of methods that are allowed on this resource. For services that do not support attributes, this will contain only the OPTIONS method.

77.3.3 Response Body

A dictionary whose keys/values are specific to the service category of the service. Rather than returning actual service data, the body will contain a dictionary that provides hints for how to build the request body for a PUT request, for example:

77.4 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

78 Orders-orderId-account-products-productId-promotion:PUT

79 PUT /orders/{orderId}/account/products/{productId}/promotion

Set promotion code for a product in an order.

79.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/promotion
 - ◆ 1.1 Request
 - ◇ 1.1.1 URI Parameters
 - ◇ 1.1.2 Query String Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Request Body Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully add a promotion code for product
 - ◇ 1.3.2 Missing promoCode field
 - ◇ 1.3.3 No authorization
 - ◇ 1.3.4 Unassociated user without cookie
 - ◇ 1.3.5 Order does not exist
 - ◆ 1.4 See also

79.2 Request

PUT /orders/{orderId}/account/products/{productId}/promotion

79.2.1 URI Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*

UUID specifying the product for which actions are to be performed

79.2.2 Query String Parameters

None.

79.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

79.2.4 Request Body

```
{
  "promoCode": "ThanksgivingPriceDrop"
}
```

79.2.4.1 Request Body Parameters

promoCode - *string*

A promotion code to be applied to the product fees when retrieving the quote.

79.3 Response

79.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
400 Bad Request	POST data error	promoCode was not provided.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to add the promotion code.
403 Forbidden	Unauthorized: PromotionView failed permission check	Set product promotion as an authenticated user, not associated with the order.
404 Not Found	Resource not found	Order does not exist. Product does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot apply promotion code.

79.4 Example

79.4.1 Successfully add a promotion code for product

Request

```
PUT /orders/{orderId}/account/products/{product_id}/promotion
Cookie: OwnerId={owner_id}; Path=/

{
  "promoCode": "ThanksgivingPriceDrop"
}
```

Response

204 No Content

79.4.2 Missing promoCode field

Request

```
PUT /orders/{orderId}/account/products/{product_id}/promotion
Cookie: OwnerId={owner_id}; Path=/

{
  "code": "ThanksgivingPriceDrop"
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "badRequest": {
    "guid": "ee20516d-011e-44ea-99d2-ae7a2b6fe99a",
    "message": "Resource not found",
    "code": 400,
    "details": {
      "promoCode": "Required"
    }
  }
}
```

79.4.3 No authorization

Request

```
PUT /orders/{orderId}/account/user
Cookie: OwnerId={wrong_owner_id}; Path=/

{
  "promoCode": "ThanksgivingPriceDrop"
}
```

Response

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

79.4.4 Unassociated user without cookie

Request

```
PUT /orders/{orderId}/account/products/{productId}/promotion
Authorization: {unassociated_user_authorization}

{
  "promoCode": "truflex600_mitko"
}
```

Response

403 Forbidden
Content-Type: application/json; charset=UTF-8

```
{
  "forbidden" : {
    "guid" : "3e6e1847-402f-4a91-b083-190ca0713b23",
    "message" : "Unauthorized: PromotionView failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

79.4.5 Order does not exist

Request

```
PUT /orders/{non-existent_orderId}/account/products/{product_id}/promotion
Cookie: OwnerId={owner_id}; Path=/

{
  "promoCode": "ThanksgivingPriceDrop"
}
```


Response

```
404 Not found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "ee20516d-011e-44ea-99d2-ae7a2b6fe99a",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

79.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

80 Orders-orderId-account-products-productId-promotion:DELETE

81 DELETE /orders/{orderId}/account/products/{productId}/promotion

Set promotion code for a product in an order.

81.1 Contents

- 1 DELETE /orders/{orderId}/account/products/{productId}/promotion
 - ◆ 1.1 Request
 - ◇ 1.1.1 URI Parameters
 - ◇ 1.1.2 Query String Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully delete a promotion code for product
 - ◇ 1.3.2 Product does not exist
 - ◆ 1.4 See also

81.2 Request

DELETE /orders/{orderId}/account/products/{productId}/promotion

81.2.1 URI Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product for which actions are to be performed

81.2.2 Query String Parameters

None.

81.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

81.3 Response

81.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
404 Not Found	Resource not found	Order does not exist. Product does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot delete promotion code.

81.4 Example

81.4.1 Successfully delete a promotion code for product

Request

DELETE /orders/{orderId}/account/products/{product_id}/promotion
Cookie: OwnerId={owner_id}; Path=/

Response

204 No Content

81.4.2 Product does not exist

Request

DELETE /orders/{order_id}/account/products/{non-existent_product_id}/promotion
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not found
Content-Type : application/json; charset=UTF-8

{
 "itemNotFound": {
 "guid": "ee20516d-011e-44ea-99d2-ae7a2b6fe99a",
 "message": "Resource not found",
 "code": 404,
 "details": ""
 }
}

```
} }
```

81.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

82 Orders-orderId-account-products-productId-services-serviceId-promotion:PUT

83 PUT

/orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion

Set promotion code for a service in an order.

83.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion
 - ◆ 1.1 Request
 - ◇ 1.1.1 URI Parameters
 - ◇ 1.1.2 Query String Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Request Body Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully add a promotion code for service
 - ◇ 1.3.2 Missing promoCode field
 - ◇ 1.3.3 No authorization
 - ◇ 1.3.4 Order does not exist
 - ◆ 1.4 See also

83.2 Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion

83.2.1 URI Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service for which actions are to be performed

83.2.2 Query String Parameters

None.

83.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

83.2.4 Request Body

```
{
  "promoCode": "{promoCode}"
}
```

83.2.4.1 Request Body Parameters

promoCode - *string* (Required)
A promotion code to be applied to the service fees when retrieving the quote.

83.3 Response

83.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
400 Bad Request	POST data error	promoCode was not provided.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to add the promotion code. Only authenticated users may access the order, and no authentication header provided for the current request.
404 Not Found	Resource not found	Order does not exist. Product or service does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot apply promotion code.

83.4 Example

83.4.1 Successfully add a promotion code for service

Request

```
PUT /orders/{orderId}/account/products/{product_id}/services/{serviceId}/promotion
Cookie: OwnerId={owner_id}; Path=/

{
  "promoCode": "ThanksgivingPriceDrop"
}
```

Response

204 No Content

83.4.2 Missing promoCode field

Request

```
PUT /orders/{orderId}/account/products/{product_id}/services/{serviceId}/promotion
Cookie: OwnerId={owner_id}; Path=/

{
  "code": "ThanksgivingPriceDrop"
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8

{
  "badRequest": {
    "guid": "{guid}",
    "message": "Resource not found",
    "code": 400,
    "details": {
      "promoCode": "Required"
    }
  }
}
```

83.4.3 No authorization

Request

```
PUT /orders/{orderId}/account/products/{product_id}/services/{serviceId}/promotion
Cookie: OwnerId={wrong_owner_id}; Path=/

{
  "promoCode": "ThanksgivingPriceDrop"
}
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested.
Either you supplied the wrong credentials (e.g., bad password),
or your browser does not understand how to supply the credentials required.
```

83.4.4 Order does not exist

Request

```
PUT /orders/{non-existing_orderId}/account/products/{product_id}/services/{serviceId}/promotion
Cookie: OwnerId={owner_id}; Path=/

{
  "promoCode": "ThanksgivingPriceDrop"
}
```

Response

```
404 Not found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "{guid}",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

83.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

84 Orders-orderId-account-products-productId-services-serviceId-promotion:DELETE

85 DELETE

/orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion

Remove promotion code for a service in an order.

85.1 Contents

- 1 DELETE
/orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion
 - ◆ 1.1 Request
 - ◇ 1.1.1 URI Parameters
 - ◇ 1.1.2 Query String Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Successfully remove a promotion code for service
 - ◇ 1.3.2 No authorization
 - ◇ 1.3.3 Service does not exist
 - ◆ 1.4 See also

85.2 Request

DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/promotion

85.2.1 URI Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product

serviceId - *string*
UUID specifying the service for which actions are to be performed

85.2.2 Query String Parameters

None.

85.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

85.3 Response

85.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to delete the promotion code. Only authenticated users may access the order, and no authentication header provided for the current request.
404 Not Found	Resource not found	Order does not exist. Product or service does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot delete promotion code.

85.4 Example

85.4.1 Successfully remove a promotion code for service

Request

DELETE /orders/{order_id}/account/products/{product_id}/services/{service_id}/promotion
Cookie: OwnerId={owner_id}; Path=

Response

204 No Content

85.4.2 No authorization

Request

DELETE /orders/{orderId}/account/products/{product_id}/services/{serviceId}/promotion
Cookie: OwnerId={wrong_owner_id}; Path=

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

85.4.3 Service does not exist

Request

```
DELETE /orders/{order_id}/account/products/{product_id}/services/{non_existing_service_id}/promotion
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "{guid}",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

85.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

86 Orders-orderId-discounts:PUT

87 PUT /orders/{orderId}/discounts

Set discounts for the entire Order. Discounts that are applied to an entire order will be applied to all of the product and services within the order. **Note:** This will replace any existing discounts that were configured at the order level.

87.1 Contents

- 1 PUT /orders/{orderId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Invalid discount amount
 - ◇ 1.3.3 Invalid discount type
 - ◇ 1.3.4 Invalid discount number of recurrences
 - ◇ 1.3.5 Missing price type
 - ◇ 1.3.6 Missing authorization
 - ◇ 1.3.7 Insufficient privileges
 - ◇ 1.3.8 Order does not exist
 - ◆ 1.4 See also

87.2 Request

PUT /orders/{orderId}/discounts

87.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

87.2.2 URI Parameters

None.

87.2.3 Request Headers

Content-Type

Required. Set this header to `application/json; charset=UTF-8`

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

87.2.4 Request Body

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": -1,
      "type": "amount",
      "value": "1.00"
    }
  ]
}
```

87.2.4.1 Parameters

discounts - *list*

A list of discounts. Each discount contains the following:

priceName - *string*

The type of price to which the discount will be applied.

Validation: Should match the fee types configured in the back-end.

Note: Only "recurring" is currently supported

recurrences - *integer*

The number of times that the discount will be applied. A value of "-1" means the discount will be applied every time the fee is charged.

Validation: Should be either a positive integer or -1.

Note: Value must be -1 if the priceName is "recurring".

type - *string*

Specifies the discount type which determines the method used to calculate the amount that is discounted. Possible values are:

amount: Discount will be treated as an exact amount

percent: Discount will be treated as a percentage

Validation: Should be set to either **amount** or **percent**.

value - *string*

The discount amount. The value will be interpreted based on the specified discount type.

Validation: Should be a positive number.

87.3 Response

87.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The discount was successfully set.
	POST data error	A required field is missing.
		Validation Error:
		Reccurences should be either a positive integer or -1.
400 Bad Request	Bad request	Price type should be reccuring .
	{value} discount amount is invalid	Discount amount should be a positive number.
	{type} discount type is unsupported	Type should be set to either amount or percent .
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot set custom discounts.

87.4 Example

87.4.1 Success

Request

```
PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

204 No Content

87.4.2 Invalid discount amount

Request

```
PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "-5.00"
  }]
}
```

```
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "c3563e61-a297-4dbe-b072-24aace7b5e44",
    "message": "-5.00 discount amount is invalid",
    "code": 400,
    "details": ""
  }
}
```

87.4.3 Invalid discount type

Request

PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "numbers",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "1a94f744-5b33-4d54-ab28-77b875934829",
    "message": "amounts discount type is unsupported",
    "code": 400,
    "details": ""
  }
}
```

87.4.4 Invalid discount number of recurrences

Request

PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-10",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "e15a6425-1cad-4154-b8f9-c10a0e46bf2c",
    "message": "Bad Request",
    "code": 400,
    "details": ""
  }
}
```

87.4.5 Missing price type

Request

PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "recurrences": "-1",
    "type": "amount",
    "value": "-5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "badRequest" : {
    "guid" : "bb3da718-f0e1-4787-acd4-8cf4215f0c44",
    "message" : "POST data error",
    "code" : 400,
    "details" : {
      "discounts.0.priceName" : "Required"
    }
  }
}
```

87.4.6 Missing authorization

Request

```
PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

87.4.7 Insufficient privileges

Request

```
PUT /orders/{orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic ZWdjUlBtZWZiWnJVQHNPdGVjb250cm9sX2hvc3R3YXlfdXNfbWVpbjBjTdnVROGlWOUFTVTc0
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8
```

```
{
  "forbidden": {
    "guid": "1912d9fa-5fbe-4e16-b0ba-00d50c9c1ec4",
    "message": "Unauthorized: DiscountsView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

87.4.8 Order does not exist

Request

```
PUT /orders/{non-existent_orderId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```


}

87.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

88 Orders-orderId-discounts:GET

89 GET /orders/{orderId}/discounts

Get discounts that were added at the Order level. Discounts that are applied to an entire order will be applied to all of the product and services within the order.

89.1 Contents

- 1 GET /orders/{orderId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Missing authorization
 - ◇ 1.3.3 Insufficient privileges
 - ◇ 1.3.4 Order does not exist
 - ◆ 1.4 See also

89.2 Request

GET /orders/{orderId}/discounts

89.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

89.2.2 URI Parameters

None.

89.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

89.3 Response

89.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The request was executed successfully.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot retrieve order discounts.

89.3.2 Response Body

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": -1,
      "type": "amount",
      "value": "1.00"
    }
  ],
  "links": [
```

```

    {
      "href": "https://api.hostway.com/orders/{orderId}/account/user/",
      "rel": "self"
    }
  ]
}

```

89.3.2.1 Parameters

discounts - *list*

A list of discounts. Each discount contains the following:

priceName - *string*

The type of price to which the discount will be applied.

recurrences - *integer*

The number of times that the discount will be applied. A value of "-1" means the discount will be applied every time the fee is charged.

type - *string*

Specifies the discount type which determines the method used to calculate the amount that is discounted. Possible values are:
amount: Discount will be treated as an exact amount.

value - *string*

The discount amount. The value will be interpreted based on the specified discount type.

links - *list*

[Hypermedia](#) for this resource. Links to self.

89.4 Example

89.4.1 Success

Request

```

GET /orders/{orderId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

200 OK
Content-Type : application/json; charset=UTF-8

{
  "discounts": [
    {
      "priceName": "recurring",
      "type": "amount",
      "value": "5.00",
      "recurrences": -1
    }
  ],
  "links": [
    {
      "href": "https://api.hostway.com/orders/000001485584ddfe2c27d60a007f000000010001/discounts/",
      "rel": "self"
    }
  ]
}

```

89.4.2 Missing authorization

Request

```

GET /orders/{orderId}/discounts
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

```

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

89.4.3 Insufficient privileges

Request

```

GET /orders/{orderId}/discounts
Authorization: Basic ZWdjUlBtZWZiWnJVQHNPdGVjb250cm9sX2hvc3R3YXlfdXNfbWVpbjBpTdnVROGlWOUFTVTc0
Cookie: OwnerId={owner_id}; Path=/

```

Response

```

403 Forbidden
Content-Type : application/json; charset=UTF-8

```

```

{

```

```
"forbidden": {
  "guid": "b5b513b8-8436-4eee-b49e-ac1d369a9d1b",
  "message": "Unauthorized: DiscountsView failed permission check",
  "code": 403,
  "details": ""
}
```

89.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound": {
    "guid": "402282af-9f53-4973-8437-469087465843",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

89.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

90 Orders-orderId-discounts:DELETE

91 DELETE /orders/{orderId}/discounts

Remove all discounts that were previously added at the Order level. This will not remove discounts that were added to specific products or services.

91.1 Contents

- 1 DELETE /orders/{orderId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Missing authorization
 - ◇ 1.3.3 Insufficient privileges
 - ◇ 1.3.4 Order does not exist
 - ◆ 1.4 See also

91.2 Request

DELETE /orders/{orderId}/discounts

91.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

91.2.2 URI Parameters

None.

91.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

91.3 Response

91.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The request was executed successfully.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot delete custom discounts.

91.4 Example

91.4.1 Success

Request

DELETE /orders/{orderId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/

Response

204 No Content

91.4.2 Missing authorization

Request

```
DELETE /orders/{orderId}/discounts
Cookie: OwnerId={owner_id}; Path=
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

91.4.3 Insufficient privileges

Request

```
DELETE /orders/{orderId}/discounts
Authorization: Basic ZWdjUlBtZWZiWnJVQHNpdGVjb250cm9sX2hvc3R3YXlfdXNfbWVpYjpTdnVROGlWOUFTVTc0
Cookie: OwnerId={owner_id}; Path=
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8
```

```
{
  "forbidden": {
    "guid": "8e235035-f8fe-465f-9b5d-85ef49829fd3",
    "message": "Unauthorized: DiscountsView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

91.4.4 Order does not exist

Request

```
DELETE /orders/{non-existent_orderId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "7f3091bd-5930-4f14-9f02-86780cd8405f",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

91.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

92 Orders-orderId-account-products-productId-discounts:PUT

93 PUT /orders/{orderId}/account/products/{productId}/discounts

Set discounts for a Product in an Order. Discounts will be applied only to the specified product. **Note: This will replace any existing discounts that were configured for the specified product.**

93.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Invalid discount amount
 - ◇ 1.3.3 Invalid discount type
 - ◇ 1.3.4 Invalid price type
 - ◇ 1.3.5 Invalid discount number of recurrences
 - ◇ 1.3.6 Missing price type
 - ◇ 1.3.7 Missing authorization
 - ◇ 1.3.8 Insufficient privileges
 - ◇ 1.3.9 Order does not exist
 - ◆ 1.4 See also

93.2 Request

PUT /orders/{orderId}/account/products/{productId}/discounts

93.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product for which actions are to be performed

93.2.2 URI Parameters

None.

93.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

93.2.4 Request Body

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": -1,
      "type": "amount",
      "value": "1.00"
    }
  ]
}
```

93.2.4.1 Parameters

discounts - *list*
A list of discounts. Each discount contains the following:

priceName - *string*
The type of price to which the discount will be applied.
Validation: Should match the fee types configured in the back-end (eg. 'recurring').

recurrences - *integer*
The number of times that the discount will be applied. A value of "-1" means the discount will be applied every time the fee is charged.
Validation: Should be either a positive integer or -1.
Note: Value must be -1 if the priceName is "recurring".

type - *string*
Specifies the discount type which determines the method used to calculate the amount that is discounted. Possible values are:
amount: Discount will be treated as an exact amount
percent: Discount will be treated as a percentage

Validation: Should be set to either **amount** or **percent**.

value - *string*

The discount amount. The value will be interpreted based on the specified discount type.
Validation: Should be a positive number.

93.3 Response

93.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The discount was successfully set.
	POST data error	Required fields are missing.
400 Bad Request	{priceName} discount fee type is invalid {value} discount amount is invalid {type} discount type is unsupported {recurrences} discount period is invalid	Validation Error: Type of price is not recognized by the system. Discount amount should be a positive number. Type should be set to either amount or percent . Number of recurrences should be either a positive integer or -1 . If priceName is recurring , it should be -1 .
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist. Product could not be found.
502 Bad Gateway	-	Unexpected backend response. Cannot set custom discounts.

93.4 Example

93.4.1 Success

Request

```
PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

204 No Content

93.4.2 Invalid discount amount

Request

```
PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "-5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "c3563e61-a297-4dbe-b072-24aace7b5e44",
    "message": "-5.00 discount amount is invalid",
    "code": 400,
    "details": ""
  }
}
```

93.4.3 Invalid discount type

Request

```
PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "numbers",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "1a94f744-5b33-4d54-ab28-77b875934829",
    "message": "numbers discount type is unsupported",
    "code": 400,
    "details": ""
  }
}
```

93.4.4 Invalid price type

Request

PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "nonrecurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault" : {
    "guid" : "62967417-b2d6-46fa-8a8d-90d9231ce844",
    "message" : "nonrecurring discount fee type is invalid",
    "code" : 400,
    "details" : ""
  }
}
```

93.4.5 Invalid discount number of recurrences

Request

PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-10",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault" : {
    "guid" : "bc360508-3392-4185-a07f-8f8cfff6884e",
    "message" : "-10 discount period is invalid",
    "code" : 400,
    "details" : ""
  }
}
```

93.4.6 Missing price type

Request

PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{,
    "recurrences": "-10",
    "type": "amount",
    "value": "5.00"
  }]
}
```

```
}
```

Response

```
400 Bad Request
Content-Type : application/json; charset=UTF-8
```

```
{
  "badRequest" : {
    "guid" : "5f2c19c5-ae18-4fee-b509-476b7ebe4b9c",
    "message" : "POST data error",
    "code" : 400,
    "details" : {
      "discounts.0.priceName" : "Required"
    }
  }
}
```

93.4.7 Missing authorization

Request

```
PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

93.4.8 Insufficient privileges

Request

```
PUT /orders/{orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic ZWdjUlBtZWZiWnJVQHNPdGVjb250cm9sX2hvc3R3YXlfdXNfbWpjbTdnVROGlWOUFTVTc0
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8
```

```
{
  "forbidden": {
    "guid": "1912d9fa-5fbe-4e16-b0ba-00d50c9c1ec4",
    "message": "Unauthorized: DiscountsView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

93.4.9 Order does not exist

Request

```
PUT /orders/{non-existent_orderId}/account/products/{productId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound": {
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

93.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

95 GET /orders/{orderId}/account/products/{productId}/discounts

Get discounts that were added at the Product level.

95.1 Contents

- 1 GET
/orders/{orderId}/account/products/{productId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Missing authorization
 - ◇ 1.3.3 Insufficient privileges
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Product could not be found
 - ◆ 1.4 See also

95.2 Request

GET /orders/{orderId}/account/products/{productId}/discounts

95.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the **POST /orders** call.

productId - *string*
UUID specifying the product for which actions are to be preformed

95.2.2 URI Parameters

None.

95.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

95.3 Response

95.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The request was executed successfully.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist. Product could not be found.
502 Bad Gateway	-	Unexpected backend response. Cannot retrieve product discounts.

95.3.2 Response Body

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": -1,
      "type": "amount",
      "value": "1.00"
    }
  ],
  "links": [
    {
      "href": "https://api.hostway.com/orders/{orderId}/account/product/{productId}/discounts",
      "rel": "self"
    }
  ]
}
```

95.3.2.1 Parameters

discounts - *list*
A list of discounts. Each discount contains the following:

priceName - *string*
The type of price to which the discount will be applied.

recurrences - *integer*

The number of times that the discount will be applied. A value of "-1" means the discount will be applied every time the fee is charged.

type - *string*

Specifies the discount type which determines the method used to calculate the amount that is discounted. Possible values are:
amount: Discount will be treated as an exact amount.

value - *string*

The discount amount. The value will be interpreted based on the specified discount type.

links - *list*

[Hypermedia](#) for this resource. Links to self.

95.4 Example

95.4.1 Success

Request

```
GET /orders/{orderId}/account/products/{productId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/
```

Response

```
200 OK
Content-Type : application/json; charset=UTF-8
```

```
{
  "discounts" : [ {
    "priceName" : "recurring",
    "type" : "amount",
    "value" : "5.00",
    "recurrences" : -1
  } ],
  "links" : [ {
    "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000148598765a3088232de007f000000010001/account/products/000001485988d9197a60",
    "rel" : "self"
  } ]
}
```

95.4.2 Missing authorization

Request

```
GET /orders/{orderId}/account/products/{productId}/discounts
Cookie: OwnerId={owner_id}; Path=/
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
```

```
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

95.4.3 Insufficient privileges

Request

```
GET /orders/{orderId}/account/products/{productId}/discounts
Authorization: Basic ZWdjUlBtZWZiWnJVQHNPdGVjb250cm9sX2hvc3R3YXlfdXNfbWpjbjPTdnVROGlWOuFTVTic0
Cookie: OwnerId={owner_id}; Path=/
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8
```

```
{
  "forbidden": {
    "guid": "b5b513b8-8436-4eee-b49e-ac1d369a9d1b",
    "message": "Unauthorized: DiscountsView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

95.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account/products/{productId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound" : {
    "guid" : "4383366c-845c-4311-97ee-9dd7d7d0045b",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

95.4.5 Product could not be found

Request

```
GET /orders/{orderId}/account/products/{non-existent_productId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8
```

```
{
  "itemNotFound" : {
    "guid" : "40caab58-6c0b-4056-97eb-2219afe92ec1",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

95.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

96 Orders-orderId-account-products-productId-discounts:DELETE

97 DELETE /orders/{orderId}/account/products/{productId}/discounts

Remove all discounts that were previously added at the Product level. This will not remove discounts that were added at the order or service level.

97.1 Contents

- 1 DELETE
/orders/{orderId}/account/products/{productId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Missing authorization
 - ◇ 1.3.3 Insufficient privileges
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Product could not be found
 - ◆ 1.4 See also

97.2 Request

DELETE /orders/{orderId}/account/products/{productId}/discounts

97.2.1 Request Parameters

orderId - *string*

The unique order Id. The URI of the order is returned by the **POST /orders** call.

productId - *string*

UUID specifying the product for which actions are to be performed

97.2.2 URI Parameters

None.

97.2.3 Request Headers

Cookie

A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

97.3 Response

97.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The request was executed successfully.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist. Product could not be found.
502 Bad Gateway	-	Unexpected backend response. Cannot delete custom product discounts.

97.4 Example

97.4.1 Success

Request

```
DELETE /orders/{orderId}/account/products/{productId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

204 No Content

97.4.2 Missing authorization

Request

```
DELETE /orders/{orderId}/account/products/{productId}/discounts
Cookie: OwnerId={owner_id}; Path=
```

Response

```
401 Unauthorized
Content-Type : text/plain; charset=UTF-8
401 Unauthorized
```

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

97.4.3 Insufficient privileges

Request

```
DELETE /orders/{orderId}/account/products/{productId}/discounts
Authorization: Basic ZWdjUlBtZWZiWnJVQHNPdGVjb250cm9sX2hvc3R3YXlfdXNfbWVpYjBpTdnVROGlWOuFTVTc0
Cookie: OwnerId={owner_id}; Path=
```

Response

```
403 Forbidden
Content-Type : application/json; charset=UTF-8

{
  "forbidden" : {
    "guid" : "a0c6a265-eea9-4187-b4eb-0b0b7b112810",
    "message" : "Unauthorized: DiscountsView failed permission check",
    "code" : 403,
    "details" : ""
  }
}
```

97.4.4 Order does not exist

Request

```
DELETE /orders/{non-existent_orderId}/account/products/{productId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound" : {
    "guid" : "8a56063d-b099-4688-b020-d31035529d45",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

97.4.5 Product could not be found

Request

```
DELETE /orders/{orderId}/account/products/{non-existent_productId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound" : {
    "guid" : "42f454f4-a534-46ea-888e-c05af56c1130",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

97.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

98 Orders-orderId-account-products-productId-services-serviceId-discounts:PUT

99 PUT

/orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts

Set discounts for the specified service. **Note: This will replace any existing discounts that were configured for the specified service.**

99.1 Contents

- 1 PUT
/orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◇ 1.1.4 Request Body
 - 1.1.4.1 Parameters
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Invalid discount amount
 - ◇ 1.3.3 Invalid discount type
 - ◇ 1.3.4 Unsupported price type
 - ◇ 1.3.5 Invalid discount number of recurrences
 - ◇ 1.3.6 Missing price type
 - ◇ 1.3.7 Missing authorization
 - ◇ 1.3.8 Insufficient privileges
 - ◇ 1.3.9 Order does not exist
 - ◇ 1.3.10 Product not found
 - ◇ 1.3.11 Service not found
 - ◆ 1.4 See also

99.2 Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts

99.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product for which actions are to be performed

serviceId - *string*
UUID specifying the service for which actions are to be performed

99.2.2 URI Parameters

None.

99.2.3 Request Headers

Content-Type
Required. Set this header to `application/json; charset=UTF-8`

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

99.2.4 Request Body

Body for adding an indefinite discount of 1 dollar for the recurring fee for the service:

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": -1,
      "type": "amount",
      "value": 1.00
    }
  ]
}
```

Body for adding a 1 dollar amount discount for the first cycle for a domain registration fee:

```
{
  "discounts": [
    {
      "priceName": "domain_registration_fee",
      "recurrences": 1,
      "type": "amount",
      "value": 1.00
    }
  ]
}
```

Body for adding a 10% discount for the first three monthly cycles for a service's recurring fee:

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": 3,
      "type": "percent",
      "value": 0.1
    }
  ]
}
```

99.2.4.1 Parameters

discounts - *list*

A list of discounts. Each discount contains the following:

priceName - *string*

The type of price to which the discount will be applied.

Validation: Should match the fee types configured in the back-end (eg. 'recurring', 'domain_registration_fee', 'setup_fee' etc.) and should be configured for the corresponding franchise.

recurrences - *integer*

The number of times that the discount will be applied. A value of "-1" means the discount will be applied every time the fee is charged.

Validation: Should be either a positive integer or -1.

Note: Value must be -1 if the priceName is "recurring".

type - *string*

Specifies the discount type which determines the method used to calculate the amount that is discounted. Possible values are:

amount: Discount will be treated as an exact amount

percent: Discount will be treated as a percentage

Validation: Should be set to either **amount** or **percent**.

value - *string*

The discount amount. The value will be interpreted based on the specified discount type.

Validation: Should be a positive number.

99.3 Response

99.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The discount was successfully set.
	POST data error	Required fields are missing. Validation Error:
400 Bad Request	{priceName} discount fee type is invalid {value} discount amount is invalid {type} discount type is unsupported {recurrences} discount period is invalid	Type of price is not recognized by the system. Discount amount should be a positive number. Type should be set to either amount or percent . Number of recurrences should be either a positive integer or -1. If price type is recurring , it should be -1.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist. Product could not be found in this order. Service could not be found for this product.
502 Bad Gateway	-	Unexpected backend response. Cannot set custom discounts.

99.4 Example

99.4.1 Success

Request

```
PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

204 No Content

99.4.2 Invalid discount amount

Request

```
PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
```


Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "-5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "c3563e61-a297-4dbe-b072-24aace7b5e44",
    "message": "-5.00 discount amount is invalid",
    "code": 400,
    "details": ""
  }
}
```

99.4.3 Invalid discount type

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "numbers",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault": {
    "guid": "1a94f744-5b33-4d54-ab28-77b875934829",
    "message": "numbers discount type is unsupported",
    "code": 400,
    "details": ""
  }
}
```

99.4.4 Unsupported price type

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring_yearly",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```
{
  "computeFault" : {
    "guid" : "43357b7a-0bba-4e40-b565-21422937b7df",
    "message" : "recurring_yearly discount fee type is invalid",
    "code" : 400,
    "details" : ""
  }
}
```

99.4.5 Invalid discount number of recurrences

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
```

```

    "recurrences": "-10",
    "type": "amount",
    "value": "5.00"
  }]
}

```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```

{
  "computeFault" : {
    "guid" : "bc360508-3392-4185-a07f-8f8cfff6884e",
    "message" : "-10 discount period is invalid",
    "code" : 400,
    "details" : ""
  }
}

```

99.4.6 Missing price type

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```

{
  "discounts": [{
    "recurrences": "-10",
    "type": "amount",
    "value": "5.00"
  }]
}

```

Response

400 Bad Request
Content-Type : application/json; charset=UTF-8

```

{
  "badRequest" : {
    "guid" : "5f2c19c5-ae18-4fee-b509-476b7ebe4b9c",
    "message" : "POST data error",
    "code" : 400,
    "details" : {
      "discounts.0.priceName" : "Required"
    }
  }
}

```

99.4.7 Missing authorization

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Cookie: OwnerId={owner_id}; Path=

```

{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}

```

Response

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested. Either you supplied the wrong credentials (e.g., bad password), or your browser does not understand how to supply the credentials required.

99.4.8 Insufficient privileges

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic ZWdjUlBtZWZiWnJVQHNpdGVjb250cm9sX2hvc3R3YXlfdXNfbWFPbjpTdnVROGlWOUFTVTIcO
Cookie: OwnerId={owner_id}; Path=

```

{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}

```

Response

403 Forbidden
Content-Type : application/json; charset=UTF-8

```
{
  "forbidden": {
    "guid": "1912d9fa-5fbe-4e16-b0ba-00d50c9c1ec4",
    "message": "Unauthorized: DiscountsView failed permission check",
    "code": 403,
    "details": ""
  }
}
```

99.4.9 Order does not exist

Request

PUT /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

99.4.10 Product not found

Request

PUT /orders/{orderId}/account/products/{non-existent_productId}/services/{serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

99.4.11 Service not found

Request

PUT /orders/{orderId}/account/products/{productId}/services/{non-existent_serviceId}/discounts
Content-Type : application/json; charset=UTF-8
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=

```
{
  "discounts": [{
    "priceName": "recurring",
    "recurrences": "-1",
    "type": "amount",
    "value": "5.00"
  }]
}
```

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "cca219c5-3e2b-481d-8e7f-7083064872ff",

```

```
    "message": "Resource not found",  
    "code": 404,  
    "details": ""  
  }  
}
```

99.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

101 GET

/orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts

Get discounts that were added at the Service level.

101.1 Contents

- 1 GET
/orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Missing authorization
 - ◇ 1.3.3 Insufficient privileges
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Product could not be found
 - ◇ 1.3.6 Service could not be found
 - ◆ 1.4 See also

101.2 Request

GET /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts

101.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product for which actions are to be preformed

serviceId - *string*
UUID specifying the service for which actions are to be performed

101.2.2 URI Parameters

None.

101.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

101.3 Response

101.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The request was executed successfully.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist. Product could not be found in this order. Service could not be found for this product.
502 Bad Gateway	-	Failed to retrieve service discount info.

101.3.2 Response Body

```
{
  "discounts": [
    {
      "priceName": "recurring",
      "recurrences": -1,
      "type": "amount",
      "value": "1.00"
    }
  ],
  "links": [
    {
      "href": "https://api.hostway.com/orders/{orderId}/account/product/{productId}/services/{serviceId}/discounts",
      "rel": "self"
    }
  ]
}
```

discounts - *list*

priceName - *string*

recurrences - *integer*

type - *string*

value - *string*

links - *list*

199

101.4.4 Order does not exist

Request

```
GET /orders/{non-existent_orderId}/account/products/{productId}/services/{serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound" : {
    "guid" : "4383366c-845c-4311-97ee-9dd7d7d0045b",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

101.4.5 Product could not be found

Request

```
GET /orders/{orderId}/account/products/{non-existent_productId}/services/{serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound" : {
    "guid" : "40caab58-6c0b-4056-97eb-2219afe92ec1",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

101.4.6 Service could not be found

Request

```
GET /orders/{orderId}/account/products/{productId}/services/{non-existent_serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

```
404 Not Found
Content-Type : application/json; charset=UTF-8

{
  "itemNotFound" : {
    "guid" : "fdbff03e-5992-4c64-a769-94cd61bbb927",
    "message" : "Resource not found",
    "code" : 404,
    "details" : ""
  }
}
```

101.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

102 Orders-orderId-account-products-productId-services-serviceId-discounts:DELETE

103 DELETE

/orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts

Remove all discounts that were previously added at the Service level. This will not remove discounts that were added at the order or product level.

103.1 Contents

- 1 DELETE
/orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◆ 1.3 Example
 - ◇ 1.3.1 Success
 - ◇ 1.3.2 Missing authorization
 - ◇ 1.3.3 Insufficient privileges
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Product could not be found
 - ◇ 1.3.6 Service could not be found
 - ◆ 1.4 See also

103.2 Request

DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts

103.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

productId - *string*
UUID specifying the product for which actions are to be performed

serviceId - *string*
UUID specifying the service for which actions are to be performed

103.2.2 URI Parameters

None.

103.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

103.3 Response

103.3.1 Status Code

Status Code	Error Message	Description
204 No Content	-	The request was executed successfully.
401 Unauthorized	-	The request was not properly authorized.
403 Forbidden	Unauthorized: DiscountsView failed permission check	The client does not have sufficient privileges.
404 Not Found	Resource not found	Order does not exist. Product could not be found in this order. Service could not be found for this product.
502 Bad Gateway	-	Custom discount could not be deleted.

103.4 Example

103.4.1 Success

Request

```
DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=
```

Response

204 No Content

103.4.2 Missing authorization

Request

```
DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
```

Cookie: OwnerId={owner_id}; Path=/

Response

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested.
Either you supplied the wrong credentials (e.g., bad password),
or your browser does not understand how to supply the credentials required.

103.4.3 Insufficient privileges

Request

DELETE /orders/{orderId}/account/products/{productId}/services/{serviceId}/discounts
Authorization: Basic ZWdjUlBtZWZiWnJVQHNPdGVjb250cm9sX2hvc3R3YXlfdXNfbWZpbnR3VROGlWOuFTVtC0
Cookie: OwnerId={owner_id}; Path=/

Response

403 Forbidden
Content-Type : application/json; charset=UTF-8

{
 "forbidden" : {
 "guid" : "a0c6a265-eaa9-4187-b4eb-0b0b7b112810",
 "message" : "Unauthorized: DiscountsView failed permission check",
 "code" : 403,
 "details" : ""
 }
}

103.4.4 Order does not exist

Request

DELETE /orders/{non-existent_orderId}/account/products/{productId}/services/{serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

{
 "itemNotFound" : {
 "guid" : "8a56063d-b099-4688-b020-d31035529d45",
 "message" : "Resource not found",
 "code" : 404,
 "details" : ""
 }
}

103.4.5 Product could not be found

Request

DELETE /orders/{orderId}/account/products/{non-existent_productId}/services/{serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

{
 "itemNotFound" : {
 "guid" : "42f454f4-a534-46ea-888e-c05af56c1130",
 "message" : "Resource not found",
 "code" : 404,
 "details" : ""
 }
}

103.4.6 Service could not be found

Request

DELETE /orders/{orderId}/account/products/{productId}/services/{non-existent_serviceId}/discounts
Authorization: Basic dGVzdC52cGxleEBjb3JwX2xkYXBfc2VydmljZV9jaGk6VHJAcXNQODch
Cookie: OwnerId={owner_id}; Path=/

Response

404 Not Found
Content-Type : application/json; charset=UTF-8

{
 "itemNotFound" : {
 "guid" : "42f454f4-a534-46ea-888e-c05af56c1130",
 "message" : "Resource not found",
 "code" : 404,
 "details" : ""
 }
}

103.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

104 Orders-orderId-quote:GET

105 GET /orders/{orderId}/quote

Get quote for a given order.

105.1 Contents

- 1 GET /orders/{orderId}/quote
 - ◆ 1.1 Request
 - ◇ 1.1.1 Request Parameters
 - ◇ 1.1.2 URI Parameters
 - ◇ 1.1.3 Request Headers
 - ◆ 1.2 Response
 - ◇ 1.2.1 Status Code
 - ◇ 1.2.2 Response Body
 - 1.2.2.1 Parameters
 - ◆ 1.3 Example
 - ◇ 1.3.1 Get empty quote info
 - ◇ 1.3.2 No authorization
 - ◇ 1.3.3 Unauthorized user
 - ◇ 1.3.4 Order does not exist
 - ◇ 1.3.5 Get quote with child product
 - ◆ 1.4 See also

105.2 Request

GET /orders/{orderId}/quote

105.2.1 Request Parameters

orderId - *string*
The unique order Id. The URI of the order is returned by the [POST /orders](#) call.

105.2.2 URI Parameters

None.

105.2.3 Request Headers

Cookie
A cookie named **OwnerId** to identify the client (for most browser clients, the browser will do this automatically, depending on the browser configuration). The value of the cookie would come from the response to the create order request in the **Set-Cookie** response header.

105.3 Response

105.3.1 Status Code

Status Code	Error Message	Description
200 OK	-	The operation was successfully completed.
401 Unauthorized	-	No owner Id specified or the specified owner is not authorized to get quote for this order.
403 Forbidden	Unauthorized: Fees failed permission check	The user does not have sufficient privilege.
404 Not Found	Resource not found	The specified order does not exist.
502 Bad Gateway	-	Unexpected backend response. Cannot retrieve order quote.

105.3.2 Response Body

```
{
  "quote": {
    "Hash": "42fc1e100808efc62dadf8ad027d424dff30d6f1",
    "Currency": "USD",
    "Products": [
      {
        "Services": [],
        "PlanNumber": "00000139b5dd73be7f14d3f8000a88fa0fa65d70",
        "PromotionCode": "promo_1234",
        "PromotionName": "Seasonal Discount 25% off all dedicated servers for 3 months",
        "ChildProduct": [],
        "Fees": [
          {
            "ProrationAllowed": "0",
            "StartDate": "2012-09-11",
            "NumCharged": "0",
            "EndDate": "2012-09-11",
            "Description": "Setup fee ",
            "BaseAmount": "100.00",
            "UnitAmount": "100.00",
            "Prorated": "0",
            "MonthlyCycle": "1",
            "Currency": "USD",
            "Amount": "100.00",
            "NumCharges": "1",
            "ProratedUnitAmount": "100.00",
            "Type": "setup_fee",
            "Quantity": "1",
            "Deferred": "0"
          },
          {
            "ProrationAllowed": "1",
            "StartDate": "2012-09-11",
            "NumCharged": "0",
            "EndDate": "2012-10-10",
            "Description": "Recurring fee",
            "BaseAmount": "239.00",
            "UnitAmount": "239.00",
            "Prorated": "0",
            "MonthlyCycle": "1",
            "Currency": "USD",
            "Amount": "239.00",
            "NumCharges": "-1",
            "ProratedUnitAmount": "239.00",
            "Type": "recurring",
            "Quantity": "1",
            "Deferred": "1"
          }
        ]
      }
    ],
    "Total": "100.00",
    "SubTotal": "100.00",
    "OneTimeFeeAmount": "100.00",
    "TaxTotal": "0",
    "DeferredSubTotals": [
      {
        "PurchasedPlanNumber": "00000139b5dd73be7f14d3f8000a88fa0fa65d70",
        "Amount": "239.00"
      }
    ],
    "DeferredTaxes": [],
    "DeferredTotals": [
      {
        "PurchasedPlanNumber": "00000139b5dd73be7f14d3f8000a88fa0fa65d70",
        "Amount": "239.00"
      }
    ]
  },
  "links": [
    {
      "href": "https://api.hostway.com/orders/{orderId}/quote/",
      "rel": "self"
    }
  ]
}
```

105.3.2.1 Parameters

quote - *dictionary*

Quote's ordered items info

Hash - *string*

Hash string of this particular order.

Currency - *string*

The currency for this particular order. Must be a ISO-4217 currency code. ex. USD, CAD, etc.

Products - *list*

List of plan products

Services - *list*

List of product services

PlanNumber - *string*

Plan number identifier

PromotionCode - *string*

Promotion code, if any (applied at the time the product was added to the order)

PromotionName - *string*

(OPTIONAL)

Name or short description of the promotion that was applied, if any

ChildProduct - *list*
List of products of the plan product

Fees - *list*
List of product fees

ProrationAllowed - *integer*
Number indicating whether fee proration is allowed

StartDate - *date*
Start date of the fee

NumCharged - *integer*
Number how many times this fee is charged

EndDate - *date*
End date the fee is applied

Description - *string*
Description info for this fee

BaseAmount - *decimal*
Base amount for this fee

UnitAmount - *decimal*
Unit amount for this fee

Prorated - *integer*
Integer indicating whether this fee is prorated

MonthlyCycle - *integer*
Billing cycle in months for this fee

Currency - *string*
The currency for this particular fee. Must be a ISO-4217 currency code. ex. USD, CAD, etc.

Amount - *decimal*
The actual fee amount

NumCharges - *integer*
Number of charges for this fee

ProratedUnitAmount - *decimal*
The prorated unit amount

Type - *string*
The type of this fee

Quantity - *integer*
The quantity for this fee

Deferred - *integer*
Indicates whether the fee is deferred

Total - *decimal*
Total sum for this quote. Does not include deferred charges.

SubTotal - *decimal*
Subtotal sum for this quote. Does not include deferred charges.

OneTimeFeeAmount - *decimal*
One time payable fee amount

TaxTotal - *decimal*
Tax total value. Does not include taxes on deferred charges.

DeferredSubTotals - *list*
A list of dictionaries, containing the sub of deferred subtotals for each PurchasedPlan in the order. If no deferred fees are found in the plan, it might not be present.

DeferredTaxes - *list*
A list of dictionaries, containing the sub of deferred taxes for each PurchasedPlan in the order. If no deferred fees are found in the plan, it might not be present.

DeferredTotals - *list*
A list of dictionaries, containing the sub of deferred totals (subtotal + tax) for each PurchasedPlan in the order. If no deferred fees are found in the plan, it might not be present.

links - *list*
[Hypermedia](#) for this resource. Links to self.

105.4 Example

105.4.1 Get empty quote info

Request

```
GET /orders/{orderId}/quote
Cookie: OwnerId={owner_id}; Path=
```


Response

200 OK
Content-Type : application/json; charset=UTF-8

```
{
  "quote": {
    "PurchasedPlan": [],
    "Hash": "26d42ebf46c38b3eaabca48a0f588d90e8f542fc",
    "Currency": "USD",
    "Total": "0",
    "SubTotal": "0",
    "OneTimeFeeAmount": "0",
    "TaxTotal": "0"
  },
  "links": {
    "self": {
      "href": "https://api.hostway.com/orders/0000014854ec1d454e9cfd3d007f000000010001/quote/",
      "rel": "self"
    }
  }
}
```

105.4.2 No authorization

Request

GET /orders/{orderId}/quote
Cookie: OwnerId={wrong_owner_id}; Path=

Response

401 Unauthorized
Content-Type : text/plain; charset=UTF-8

401 Unauthorized

This server could not verify that you are authorized to access the document you requested.
Either you supplied the wrong credentials (e.g., bad password),
or your browser does not understand how to supply the credentials required.

105.4.3 Unauthorized user

Request

GET /orders/{orderId}/quote
Authorization: Basic {wrong_user_authorization}; Path=

Response

403 Forbidden
Content-Type : application/json; charset=UTF-8

```
{
  "forbidden": {
    "guid": "ea88f675-dc71-410e-9e72-84f0944a289a",
    "message": "Unauthorized: Fees failed permission check",
    "code": 403,
    "details": ""
  }
}
```

105.4.4 Order does not exist

Request

GET /orders/{non-existent_orderId}/quote
Cookie: OwnerId={owner_id}; Path=

Response

404 Not found
Content-Type : application/json; charset=UTF-8

```
{
  "itemNotFound": {
    "guid": "92b7773f-e224-4971-a3dd-60fbd9c7129a",
    "message": "Resource not found",
    "code": 404,
    "details": ""
  }
}
```

105.4.5 Get quote with child product

Request

GET /orders/{orderId}/quote
Cookie: OwnerId={owner_id}; Path=

Response

200 OK
Content-Type : application/json; charset=UTF-8

```
{
  "quote": {
```

```

"PurchasedPlan": [
  "Product": [
    "PromotionCode":null,
    "ChildProduct": [
      {
        "PromotionCode":null,
        "ChildProduct":[],
        "Name":"ChildProductName",
        "ProductNumber":null,
        "MonthlyCycle":1,
        "ConfigType":"ptc",
        "Fees": [
          {
            "Currency":"USD",
            "Amount":"0.00",
            "NumCharges":"1",
            "ProratedUnitAmount":"0.00",
            "Type":"setup_fee",
            "Discounts":[],
            "Quantity":"1"
          },
          {
            "BaseAmount":"10.00",
            "UnitAmount":"10.00",
            "Prorated":"0",
            "MonthlyCycle":"1"
          }
        ]
      }
    ],
    "Name":"ParentProduct",
    "ProductNumber":null,
    "MonthlyCycle":1,
    "ConfigType":"parent.product",
    "Fees":[ ],
    "OrderNotes":[ ],
    "ProductGUID":"0000015100dcc330be07657a007f000000010001"
  ],
  "DisplayName":"",
  "Name":"plan_name",
  "ReferralKey":null,
  "MonthlyCycle":1,
  "PartnerId":"",
  "Plan":"test.plan",
  "Fees":[ ],
  "PlanNumber":"0000015100dcbf46c7576990007f000000010001",
  "PromotionCode":null
],
"Hash": "26d42ebf46c38b3eaabca48a0f588d90e8f542fc",
"Currency": "USD",
"DeferredSubTotals":[],
"DeferredTotals":[],
"Total": "0",
"SubTotal": "0",
"OneTimeFeeAmount": "0",
"DeferredTaxes":[],
"TaxTotal": "0"
},
"links": {
  "self": {
    "href": "https://api.hostway.com/orders/0000014854ec1d454e9cfd3d007f000000010001/quote/",
    "rel": "self"
  }
}
}
}

```

105.5 See also

- [Orders API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

106 Common Features

All Hostway APIs support common features for authentication and authorization, pagination, references to related resources, etc.

- [Authentication](#)
- [Hypermedia](#)
- [Pagination](#)
- [Server Response Codes](#)
- [Filtering](#)

[download this selection of articles as a PDF book](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

107 Order-Products-Account

108 Set account on a later step when ordering products and services

This example provides the steps to set order's account on a later step.

108.1 Create a new order

Use **POST /orders** to create a new order

108.1.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

108.1.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001
Set-Cookie : OwnerId=d0977ed2-86e7-4101-adfe-2675ba0e26ac; Path=/

{
  "orderId": "000001452259ee0103d4e652007f000000010001",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001", "rel": "item" }
  ]
}
```

108.2 Add a product

Use **POST /orders/{order_id}/account/products** to add a product

108.2.1 Request

```
POST /orders/000001452259ee0103d4e652007f000000010001/account/products
Content-Type: application/json; charset=UTF-8

{
  "offering": "https://api.hostway.com/productSpecifications/core.plangroup.dedserver.plan4/offerings/USD-1"
}
```

108.2.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001/account/products/00000145225a87f17bd8d66d007f000000010001/

{
  "url": "https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001/account/products/00000145225a87f17bd8d66d007f000000010001/"
}
```

108.3 Add a service to the product with no attributes

Use **POST /orders/{order_id}/account/products/{productId}/services** to add a product's service

108.3.1 Request

```
POST /orders/000001452259ee0103d4e652007f000000010001/account/products/00000145225a87f17bd8d66d007f000000010001/services
Content-Type: application/json; charset=UTF-8

{
  "name": "test123.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedserver",
  "billingCycle": 1
}
```

108.3.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/000001452292557b24c2acc0007f000000010001/account/products/0000014522925d3222f0ce5b007f000000010001/

{
  "url": "https://api.hostway.com/orders/000001452292557b24c2acc0007f000000010001/account/products/0000014522925d3222f0ce5b007f000000010001/se"
}
```

108.4 Create a new account for the order

Use **PUT /orders/{order_id}/account** to add a new account to the order

108.4.1 Request

```
PUT /orders/000001452292557b24c2acc0007f000000010001/account
Content-Type: application/json; charset=UTF-8
```

```
{
  "currency": "USD",
  "language": "en-US"
}
```

108.4.2 Response

204 No Content

108.5 Set an existing account for the order

Use [PUT /orders/{order_id}/account](#) to assign an existing account to the order

108.5.1 Request

```
PUT /orders/000001452292557b24c2acc0007f000000010001/account
Content-Type: application/json; charset=UTF-8
```

```
{
  "accountNumber": "test793347"
}
```

108.5.2 Response

204 No Content

108.6 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and to invoke the ordered product provisioning.

108.6.1 Request

```
POST /orders/000001452292557b24c2acc0007f000000010001/action
Content-Type: application/json; charset=UTF-8
```

```
{
  "action": "submit"
}
```

108.6.2 Response

202 Accepted

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

109 Order-Products-Account-Modify

110 Set and modify an account on a later step when ordering products and services

This example provides the steps to set order's account on a later step and modify it afterward.

110.1 Create a new order

Use [POST /orders](#) to create a new order

110.1.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

110.1.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001
Set-Cookie : OwnerId=d0977ed2-86e7-4101-adfe-2675ba0e26ac; Path=/

{
  "orderId": "000001452259ee0103d4e652007f000000010001",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001", "rel": "item" }
  ]
}
```

110.2 Add a product

Use [POST /orders/{order_id}/account/products](#) to add a product

110.2.1 Request

```
POST /orders/000001452259ee0103d4e652007f000000010001/account/products
Content-Type: application/json; charset=UTF-8

{
  "offering": "https://api.hostway.com/productSpecifications/core.plangroup.dedserver.plan4/offerings/USD-1"
}
```

110.2.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001/account/products/00000145225a87f17bd8d66d007f000000010001/

{
  "url": "https://api.hostway.com/orders/000001452259ee0103d4e652007f000000010001/account/products/00000145225a87f17bd8d66d007f000000010001/"
}
```

110.3 Add a service to the product with no attributes

Use [POST /orders/{order_id}/account/products/{productId}/services](#) to add a product's service

110.3.1 Request

```
POST /orders/000001452259ee0103d4e652007f000000010001/account/products/00000145225a87f17bd8d66d007f000000010001/services
Content-Type: application/json; charset=UTF-8

{
  "name": "test123.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.dedserver",
  "billingCycle": 1
}
```

110.3.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/000001452292557b24c2acc0007f000000010001/account/products/0000014522925d3222f0ce5b007f000000010001/

{
  "url": "https://api.hostway.com/orders/000001452292557b24c2acc0007f000000010001/account/products/0000014522925d3222f0ce5b007f000000010001/se"
}
```

110.4 Set an existing account for the order

Use [PUT /orders/{order_id}/account](#) to assign an existing account to the order

110.4.1 Request

```
PUT /orders/000001452292557b24c2acc0007f000000010001/account
Content-Type: application/json; charset=UTF-8
```

```
{
  "accountNumber": "test793347"
}
```

110.4.2 Response

204 No Content

110.5 Set some account attributes

Use [PUT /orders/{orderId}/account/attributes](#) to set the account attributes in an order.

110.5.1 Request

```
PUT /orders/0000014522fbfd383c2b1a33007f000000010001/account/attributes
Content-Type: application/json; charset=UTF-8
```

```
[
  {
    "name": "partner_account_id",
    "value": "paccid_030414051600"
  }
]
```

110.5.2 Response

204 No Content

110.6 Set modified regular contact

Use [PUT /orders/{orderId}/account/contactInfo/{contactType}](#) to set the account contact details for a given contact type in an order.

110.6.1 Request

```
PUT /orders/0000014522fbfd383c2b1a33007f000000010001/account/contactInfo/regular
Content-Type: application/json; charset=UTF-8
```

```
{
  "name":
    {
      "firstName": "Test-Regular",
      "lastName": "Contact",
      "company": "MyCompany"
    },
  "address":
    {
      "street1": "111 My Street",
      "street2": "street2",
      "city": "Chicago",
      "stateOrProvince": "IL",
      "postalCode": "60606",
      "countryCode": "US"
    },
  "contactMedia":
    {
      "phone1": "312-555-1111",
      "phone2": "312-555-222",
      "fax": "312-555-1111",
      "email1": "myemail@something.com",
      "email1Format": "html"
    }
}
```

110.7 Set account payment info

Use [PUT /orders/{orderId}/account/paymentInfo](#) to set the account's payment info.

110.7.1 Request

```
PUT /orders/0000014522fbfd383c2b1a33007f000000010001/account/paymentInfo
Content-Type: application/json; charset=UTF-8
```

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "1234567890123456",
  "cardHolderName": "John Jello",
  "expirationDate": "2015-06",
  "verificationNumber": "503",
  "billingAddress":
    {
      "street1": "My street",
      "street2": "",
      "city": "Chicago",
      "stateOrProvince": "IL",
      "postalCode": "60606",
      "countryCode": "US"
    }
}
```

110.7.2 Response

204 No Content

110.7.3 Response

204 No Content

110.8 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and to invoke the ordered product provisioning.

110.8.1 Request

```
POST /orders/000001452292557b24c2acc0007f000000010001/action
Content-Type: application/json; charset=UTF-8

{
  "action": "submit"
}
```

110.8.2 Response

202 Accepted

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

111 Order-Email-Domain

112 Order a new email domain

This example provides the steps to order a new email domain through the Hostway [Ordering API](#).

112.1 Create a new order

Use [POST /orders](#) to create a new order

112.1.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

112.1.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf
Set-Cookie : OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "orderId": "0000013ad6dd95746a399f90000a71384bf242cf",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf", "rel": "item" }
  ]
}
```

112.2 Create a new account for the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

112.2.1 Request

```
PUT /orders/0000013ad6dd95746a399f90000a71384bf242cf/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

112.2.2 Response

```
204 No Content
```

112.3 Add the email domain product

The email domain product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add a new email domain product to the order by using [POST /orders/{order_id}/account/products](#).

112.3.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.email.business/offerings/USD-12"
}
```

112.3.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf
```

112.4 Add the email service to the new product

The email service specification offerings can be determined using the Hostway [Product Catalog API](#) for the core.plan.email.business product. Then add a new email service to the order by using [POST /orders/{order_id}/account/products/{product_id}/services](#).

112.4.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "name": "test-email-domain.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.email.mfg2",
  "billingCycle": 1
}
```

112.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/
```

112.5 Add service attributes

Use the [PUT /orders/{order_id}/account/products/{product_id}/services/{service_id}/attributes](#) call to add the domain name for the email service.

112.5.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/services/0000013fe6dd95726c399e90000a71384bf242cf/attributes
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "domain": "test-email-domain.com"
}
```

112.5.2 Response

```
204 No content
```

112.6 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and invoke the email domain provisioning.

112.6.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/action
Content-Type: application/json; charset=UTF-8

{
  "action": "submit"
}
```

112.6.2 Response

```
202 Accepted
```

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

113 Order-Domain-Alias

114 Order a new email domain alias

This example provides the steps to order a new email domain through the Hostway [Ordering API](#).

114.1 Create a new order

Use [POST /orders](#) to create a new order

114.1.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

114.1.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001
Set-Cookie : OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "orderId": "00000143d407b34742ee26ae007f000000010001",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001", "rel": "item" }
  ]
}
```

114.2 Create a new account for the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

114.2.1 Request

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

114.2.2 Response

```
204 No Content
```

114.3 Add an email domain product

The email domain product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add a new email domain product to the order by using [POST /orders/{order_id}/account/products](#).

114.3.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.email.business/offerings/USD-12"
}
```

114.3.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001
```

114.4 Add an email service to the new product

The email service specification offerings can be determined using the Hostway [Product Catalog API](#) for the core.plan.email.business product. Then add a new email service to the order by using [POST /orders/{order_id}/account/products/{product_id}/services](#).

114.4.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "name": "test-email-domain.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.email.mfg2",
  "billingCycle": 1
}
```

114.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

114.5 Add service attributes

Use the [PUT /orders/{order_id}/account/products/{product_id}/services/{service_id}/attributes](#) call to add the domain name for the email service.

114.5.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services/00000143d407bea7e2b8
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "domain": "test-email-domain.com"
}
```

114.5.2 Response

```
204 No content
```

114.6 Add an email domain alias service to the new product

The email service specification offerings can be determined using the Hostway [Product Catalog API](#) for the core.plan.email.business product. Then add a new email service to the order by using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the email domain product URL.

114.6.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "name": "test-email-domain-alias.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.email.domainalias.mfg2",
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"],
  "billingCycle": 1
}
```

114.6.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

114.7 Add the domain alias service attributes

Use the [PUT /orders/{order_id}/account/products/{product_id}/services/{service_id}/attributes](#) call to add the domain alias name for the email service.

114.7.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services/00000143d407bea7e2b8
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "domain": "test-email-domain.com",
  "domain_alias": "test-email-domain-alias.com"
}
```

114.7.2 Response

```
204 No content
```

114.8 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and invoke the email domain provisioning.

114.8.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/action
Content-Type: application/json; charset=UTF-8

{
  "action": "submit"
}
```


114.8.2 Response

202 Accepted

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

115 Order-Exchange

115.1 Order a new Exchange domain

This example provides the steps for ordering a new Exchange domain

115.2 Create a new order

Use [POST /orders](#) to create a new order

115.2.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

115.2.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001
Set-Cookie : OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "orderId": "00000143d407b34742ee26ae007f000000010001",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001", "rel": "item" }
  ]
}
```

115.3 Create a new account for the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

115.3.1 Request

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

115.3.2 Response

```
204 No Content
```

115.4 Add an Exchange product to the order

The Exchange product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add a new websplanet product to the order by using [POST /orders/{order_id}/account/products](#).

115.4.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.email.exchange2010/offerings/USD-1"
}
```

115.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001
```

115.5 Add an Exchange service to the new product

115.5.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{"name": "myexchangedomain.com",
 "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.email.exchange2010",
 "billingCycle": 1,
 "attributes": {
```

```
    "domain": "myexchangedomain.com"
  }
}
```

115.5.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

115.6 Obtain a quote

115.6.1 Request

```
GET /orders/00000143d407b34742ee26ae007f000000010001/quote
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
```

115.6.2 Response

```
200 OK
Content-Type: application/json; charset=UTF-8
{
  "quote" : {
    "Hash" : "b6a714a2ba76b6f15df9e46964df21ca726594a0",
    "Currency" : "USD",
    "Total" : "0.00",
    "SubTotal" : "0.00",
    "OneTimeFeeAmount" : "0",
    "TaxTotal" : "0"
  },
  "links" : {
    "self" : {
      "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000143d407b34742ee26ae007f000000010001/quote/",
      "rel" : "self"
    }
  }
}
```

115.7 Submit the order

115.7.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/action
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{"action": "submit"}
```

115.7.2 Response

```
202 Accepted
no-body
```

115.8 Check for status

115.8.1 Request

```
GET /orders/00000143d407b34742ee26ae007f000000010001
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
Authorization: Basic cXd1QHhBcnRuZXJfYXBpX2RldmVsb3Blcl91c19tYWluOml1MzR0OGhm      <- credentials that have access to the account
```

115.8.2 Response

```
200 OK
{
  "order" : {
    "Status" : "Processing",
    "Account" : "http://coreapi01.ote.chicago.hostway:8092/accounts/acct999999"      <- "Completed" means that everything has p
  },
  "links" : [ {
    "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000143d407b34742ee26ae007f000000010001/",
    "rel" : "self"
  } ]
}
```

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

116 Order-Exchange-mailbox-free

116.1 Order a new, free Exchange mailbox

This example provides the steps for ordering a new Exchange mailbox in the case where it's offered without charge

116.2 Create the mailbox

116.2.1 Request

```
POST /accounts/acct999999/exchange/myexchangedomain.com/mailboxes
Content-Type: application/json; charset=UTF-8
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c19tYWluOml1MzR0OGhm
```

```
{
  "owner": {
    "username": "a.a",
    "password": "tester1234"
  },
  "admin": 0,
  "notes": "some text",
  "recipientLimit": 10,
  "deliverRedirect": "zsds",
  "forwardTo": "asdasd",
  "name": {
    "name": "John Smith",
    "company": "My Company",
    "department": "Sales",
    "title": "President"
  },
  "address": {
    "address": "100 Main St.",
    "city": "Chicago",
    "state": "IL",
    "zip": "60001",
    "country": "US"
  },
  "phones": {
    "businessPhone": "555-555-5501",
    "homePhone": "555-555-5502",
    "fax": "555-555-5503",
    "mobile": "555-555-5504"
  }
}
```

116.2.2 Response

```
202 Accepted
Location      http://coreapi01.ote.chicago.hostway:8092/orders/00000145ff9ba7e58e7c2c51007f000000010001
Set-Cookie    OwnerId=f9cafb10-2e85-4b1a-bd69-1b1a91437d50; Path=/
no-body
```

Note: order has already been submitted at this point!

116.3 Check for status

116.3.1 Request

```
GET /orders/00000145ff9ba7e58e7c2c51007f000000010001
Cookie: OwnerId=f9cafb10-2e85-4b1a-bd69-1b1a91437d50; Path=/
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c19tYWluOml1MzR0OGhm
```

116.3.2 Response

```
200 OK
{
  "order": {
    "Status": "Processing",
    "Account": "http://coreapi01.ote.chicago.hostway:8092/accounts/acct999999"
  },
  "links": [ {
    "href": "http://coreapi01.ote.chicago.hostway:8092/orders/00000145ff9ba7e58e7c2c51007f000000010001/",
    "rel": "self"
  } ]
}
```

<- "Completed" means that everything provisioned

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

117 Order-Exchange-mailbox-paid

117.1 Order a new, paid Exchange mailbox

This example provides the steps for ordering a new Exchange mailbox in the case where a charge applies

117.2 Create the mailbox

117.2.1 Request

```
POST /accounts/acct999999/exchange/myexchangedomain.com/mailboxes
Content-Type: application/json; charset=UTF-8
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c191c19tYWluOml1MzR0OGhm
```

```
{
  "owner": {
    "username": "a.a",
    "password": "tester1234"
  },
  "admin": 0,
  "notes": "some text",
  "recipientLimit": 10,
  "deliverRedirect": "zsds",
  "forwardTo": "asdasd",
  "name": {
    "name": "John Smith",
    "company": "My Company",
    "department": "Sales",
    "title": "President"
  },
  "address": {
    "address": "100 Main St.",
    "city": "Chicago",
    "state": "IL",
    "zip": "60001",
    "country": "US"
  },
  "phones": {
    "businessPhone": "555-555-5501",
    "homePhone": "555-555-5502",
    "fax": "555-555-5503",
    "mobile": "555-555-5504"
  }
}
```

117.2.2 Response

```
202 Accepted
Set-Cookie: OwnerId=bd048fa5-8714-462f-86f6-1feffd04023b; Path=/
{
  "total" : [ "5.18", "USD" ],
  "subtotal" : [ "5.18", "USD" ],
  "deferredTotal": [],
  "deferredSubtotal": [],
  "quotehash" : "0dd6b20d1ce3ae0e44882f3db11124d03f60ba53",
  "links" : [ {
    "href" : "http://coreapi01.ote.chicago.hostway:8092/accounts/acct999999/exchange/myexchangedomain.com/mailboxes/",
    "rel" : "self"
  }, {
    "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000145ff82ec6bf27d6421007f000000010001/action",
    "rel" : "related"
  } ]
}
```

117.3 Submit the order

117.3.1 Request

```
POST /orders/00000145ff82ec6bf27d6421007f000000010001/action
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=bd048fa5-8714-462f-86f6-1feffd04023b; Path=/
{"action": "submit"}
</nowiki>
```

```
=== Response ===
<nowiki>
202 Accepted
no-body
```

117.4 Check for status

117.4.1 Request

```
GET /orders/00000145ff82ec6bf27d6421007f000000010001
Cookie: OwnerId=bd048fa5-8714-462f-86f6-1feffd04023b; Path=/
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c191c19tYWluOml1MzR0OGhm
```

117.4.2 Response

200 OK

```
{
  "order" : {
    "Status" : "Processing",
    "Account" : "http://coreapi01.ote.chicago.hostway:8092/accounts/acct999999"
  },
  "links" : [ {
    "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000145ff82ec6bf27d6421007f000000010001/",
    "rel" : "self"
  } ]
}
```

<- "Completed" means that everything provisioned

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

118 Order-Exchange-otherproduct

118.1 Ordering Other Exchange Products

This order flow applies to encryption, archiving, mailing list and blackberry products. The example illustrates ordering encryption.

118.2 Create Encryption for a domain

118.2.1 Request

```
PUT /accounts/acct999999/exchange/myexchangedomain.com/emailEncryption
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c191c19tYWluOml1MzR0OGhm
{
  "adminEmail": "someone@somewhere.com"
}
```

118.2.2 Response

```
202 Accepted
Set-Cookie: OwnerId=73adb746-2443-4cc8-879e-886348385b9a; Path=/
Location: http://coreapi01.ote.chicago.hostway:8092/orders/00000145ffa79d31de17529f007f000000010001
no-body
```

Note: specified order has not yet been submitted.

118.3 Obtain a quote

118.3.1 Request

```
GET /orders/00000145ffa79d31de17529f007f000000010001/quote
Cookie: OwnerId=73adb746-2443-4cc8-879e-886348385b9a; Path=/
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c191c19tYWluOml1MzR0OGhm
```

118.3.2 Response

```
200 OK
Content-Type: application/json; charset=UTF-8
{
  "quote" : {
    "Hash" : "b6a714a2ba76b6f15df9e46964df21ca726594a0",
    "Currency" : "USD",
    "Total" : "0.00",
    "SubTotal" : "0.00",
    "OneTimeFeeAmount" : "0",
    "TaxTotal" : "0",
    "DeferredSubTotals": [],
    "DeferredTaxes": [],
    "DeferredTotals": []
  },
  "links" : {
    "self" : {
      "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000145ffa79d31de17529f007f000000010001/quote/",
      "rel" : "self"
    }
  }
}
```

118.4 Submit the order

118.4.1 Request

```
POST /orders/00000145ffa79d31de17529f007f000000010001/action
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=73adb746-2443-4cc8-879e-886348385b9a; Path=/
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c191c19tYWluOml1MzR0OGhm
{"action": "submit"}
</nowiki>
```

```
=== Response ===
<nowiki>
202 Accepted
no-body
```

118.5 Check for status

118.5.1 Request

```
GET /orders/00000145ffa79d31de17529f007f000000010001
Cookie: OwnerId=73adb746-2443-4cc8-879e-886348385b9a; Path=/
Authorization: Basic cXdlQHBhcnRuZXJfYXBpX2RldmVsb3B1c191c19tYWluOml1MzR0OGhm
```


118.5.2 Response

200 OK

```
{
  "order" : {
    "Status" : "Processing",
    "Account" : "http://coreapi01.ote.chicago.hostway:8092/accounts/acct999999"
  },
  "links" : [ {
    "href" : "http://coreapi01.ote.chicago.hostway:8092/orders/00000145ffa79d31de17529f007f000000010001/",
    "rel" : "self"
  } ]
}
```

<- "Completed" means that everything has p

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

119 Order-cloud-drive

120 Order a new cloud drive

This example provides the steps to order cloud drive through the Hostway [Ordering API](#). == Create a new order == Use [POST /orders](#) to create a new order

120.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

120.1.1 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf
Set-Cookie : OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "orderId": "0000013ad6dd95746a399f90000a71384bf242cf",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf", "rel": "item" }
  ]
}
```

120.2 Create a new account for the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

120.2.1 Request

```
PUT /orders/0000013ad6dd95746a399f90000a71384bf242cf/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

120.2.2 Response

```
204 No Content
```

120.3 Add "Linux Web Start" product to the order

The product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add the new product to the order by using [POST /orders/{order_id}/account/products](#).

120.3.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.linux.webstart/offerings/USD-12"
}
```

120.3.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf
```

120.4 Add the cloud drive service to the new product

The service specification offerings can be determined using the Hostway [Product Catalog API](#) for the core.plan.linux.webstart product. Then add the new cloud drive service to the order by using [POST /orders/{order_id}/account/products/{product_id}/services](#).

120.4.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "name": "test-domain.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.clouddrive.hs2.1gb",
  "billingCycle": 12,
  "attributes": { "displayName": "test-domain.com" }
}
```

120.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/
```

120.5 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and invoke the cloud drive provisioning.

120.5.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/action
Content-Type: application/json; charset=UTF-8

{
  "action": "submit"
}
```

120.5.2 Response

```
202 Accepted
```

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

121 Order-cloud-backup

122 Order a new cloud backup

This example provides the steps to order cloud backup through the Hostway [Ordering API](#). == Create a new order == Use [POST /orders](#) to create a new order

122.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

122.1.1 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf
Set-Cookie : OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "orderId": "0000013ad6dd95746a399f90000a71384bf242cf",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf", "rel": "item" }
  ]
}
```

122.2 Create a new account for the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

122.2.1 Request

```
PUT /orders/0000013ad6dd95746a399f90000a71384bf242cf/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

122.2.2 Response

```
204 No Content
```

122.3 Add "Linux Web Start" product to the order

The product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add the new product to the order by using [POST /orders/{order_id}/account/products](#).

122.3.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.linux.webstart/offerings/USD-12"
}
```

122.3.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf
```

122.4 Add the cloud backup service to the new product

The service specification offerings can be determined using the Hostway [Product Catalog API](#) for the core.plan.linux.webstart product. Then add the new cloud backup service to the order by using [POST /orders/{order_id}/account/products/{product_id}/services](#).

122.4.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=b0d6352a-f66a-476d-8e1d-2f3f9dea5c49; Path=/

{
  "name": "test-domain.com",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.cloudbackup.hs2.2gb",
  "billingCycle": 12,
  "attributes": { "displayName": "test-domain.com" }
}
```

122.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/0000013ad6dd95746a399f90000a71384bf242cf/account/products/0000013fd6dd95726c399e90000a71384bf242cf/
```

122.5 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and invoke the cloud backup provisioning.

122.5.1 Request

```
POST /orders/0000013ad6dd95746a399f90000a71384bf242cf/action
Content-Type: application/json; charset=UTF-8

{
  "action": "submit"
}
```

122.5.2 Response

```
202 Accepted
```

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

123 Order-webs-planet

123.1 Order a new WebsPlanet

This example provides the steps to order a new webs planet product through the Hostway Ordering API.

123.2 Create a new order

Use **POST** `/orders` to create a new order

123.2.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

123.2.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001
Set-Cookie : OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "orderId": "00000143d407b34742ee26ae007f000000010001",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001", "rel": "item" }
  ]
}
```

123.3 Create a new acout for the order

Use **PUT** `/orders/{order_id}/account` to create an account or add an existing one to the order.

123.3.1 Request

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

123.3.2 Response

```
204 No Content
```

123.4 Add a Websplanet product to the order

The websplanet product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add a new websplanet product to the order by using **POST** `/orders/{order_id}/account/products`.

123.4.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.linux.webstart/offerings/USD-1"
}
```

123.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001
```

123.5 Add a Webhosting service to the new product

A Websplanet service needs to be related to either a Windows or a Linux webhosting service. To do that, the webhosting service needs to be created first.

123.5.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{"name": "Websplanet",
```



```
"serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.webhosting.linux.5GB",
"billingCycle": 1}
```

123.5.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

123.6 Add the Webhosting service attributes

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services/00000143d407b34742ed9
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
```

```
{"domain": "ng-test-fitness-websplanet-20140505-0505.us"}
```

123.7 Add a Websplanet service to the new product

Please note that WebsPlanet can be added only as a child service to the webhosting service. You have to specify webhosting service you want websplanet to be added to.

Assuming you have a webhosting service in your order, you can add websplanet using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the webhosting service's URL.

123.7.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{"name": "Websplanet",
 "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.websplanet.1",
 "billingCycle": 1,
 "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]}
```

123.7.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

123.8 Add the WebsPlanet service attributes

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services/00000143d407bea7e2b84
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
```

```
{"domain": "ng-test-fitness-websplanet-20140505-0505.us",
 "email": "test@example.com"}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

124 Order-vps-virtuozzo

124.1 Order VPS Virtuozzo products and services

This example provides the steps to order a new VPS Virtuozzo product and services through the Hostway OrderAPI.

124.2 Create a new order

Use [POST /orders](#) to create a new order

124.2.1 Request

```
POST /orders
Content-Type: application/json; charset=UTF-8

{}
```

124.2.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001
Set-Cookie : OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "orderId": "00000143d407b34742ee26ae007f000000010001",
  "links": [
    { "href": "https://api.hostway.com/orders/", "rel": "self" },
    { "href": "https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001", "rel": "item" }
  ]
}
```

124.3 Create a new account or add an existing one to the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

124.3.1 Request for creating a new account

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "currency": "USD",
  "language": "en-US"
}
```

124.3.2 Request for adding an existing account

```
PUT /orders/00000143d407b34742ee26ae007f000000010001/account
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "accountNumber": "acct123456"
}
```

124.3.3 Response

```
204 No Content
```

124.4 Add a VPS Virtuozzo product to the order

The VPS Virtuozzo product specification offerings can be determined using the Hostway [Product Catalog API](#). Then add a new VPS Virtuozzo product to the order by using [POST /orders/{order_id}/account/products](#).

124.4.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/

{
  "offering": "https://api.hostway.com/productSpecifications/core.plan.vps.virtuozzo.ul01/offerings/USD-1"
}
```

124.4.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001
```

124.5 Add a Virtuozzo Server service to the new product

Virtuozzo Server Windows/Linux service needs to be created first before any other VPS Virtuozzo services(IP, Memory, ControlPanel, Disk, Bandwidth, PowerPack) are added.

124.5.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.server.u100",
  "billingCycle": 1
}
```

124.5.2 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.6 Add VPS Virtuozzo services to the new product

Please note that VPS Virtuozzo services(IP, Memory, ControlPanel, Disk, Bandwidth) can be added only as a child service to the Virtuozzo Server Windows/Linux service. You have to specify Virtuozzo Server Windows/Linux service you want your VPS Virtuozzo services(IP, Memory, ControlPanel, Disk, Bandwidth) to be added to.

124.6.1 Add VPS Virtuozzo Controlpanel service

Assuming you have already a Virtuozzo Server Windows/Linux service in your order, you can add Virtuozzo Controlpanel service using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the Virtuozzo Server Windows/Linux service's URL.

124.6.2 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.controlpanel.plesk9-10domain",
  "billingCycle": 1,
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]
}
```

124.6.3 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.6.4 Add VPS Virtuozzo Additional Memory service

Assuming you have already a Virtuozzo Server Windows/Linux service in your order, you can add VPS Virtuozzo Additional Memory service using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the Virtuozzo Server Windows/Linux service's URL.

124.6.5 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.additional_memory.256mb",
  "billingCycle": 1,
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]
}
```

124.6.6 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.6.7 Add VPS Virtuozzo Additional Disk Space service

Assuming you have already a Virtuozzo Server Windows/Linux service in your order, you can add VPS Virtuozzo Additional Disk Space service using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the Virtuozzo Server Windows/Linux service's URL.

124.6.8 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.additional_disk.10gb",
  "billingCycle": 1,
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]
}
```

124.6.9 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.6.10 Add VPS Virtuozzo Additional Bandwidth service

Assuming you have already a Virtuozzo Server Windows/Linux service in your order, you can add Virtuozzo Additional Bandwidth service using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the Virtuozzo Server Windows/Linux service's URL.

124.6.11 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.additional_bandwidth.1000gb",
  "billingCycle": 1,
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]
}
```

124.6.12 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.6.13 Add VPS Virtuozzo IP service

Assuming you have already a Virtuozzo Server Windows/Linux service in your order, you can add Virtuozzo IP service using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the Virtuozzo Server Windows/Linux service's URL.

124.6.14 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.ip",
  "billingCycle": 1,
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]
}
```

124.6.15 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.6.16 Add VPS Virtuozzo PowerPack service

Assuming you have already a Virtuozzo Server Windows/Linux service in your order, you can add VPS Virtuozzo PowerPack service using [POST /orders/{order_id}/account/products/{product_id}/services](#). The "relatedTo" attribute should contain the Virtuozzo Server Windows/Linux service's URL.

124.6.17 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/services
Content-Type: application/json; charset=UTF-8
Cookie: OwnerId=09185e9b-2ea0-4bef-950e-fc9f8b89861f; Path=/
{
  "name": "VPS Virtuozzo Test",
  "serviceSpecification": "https://api.hostway.com/serviceSpecifications/core.vps.virtuozzo.powerpack",
  "billingCycle": 1,
  "relatedTo": ["https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/"]
}
```

124.6.18 Response

```
201 Created
Content-Type: application/json; charset=UTF-8
Location : https://api.hostway.com/orders/00000143d407b34742ee26ae007f000000010001/account/products/00000143d407b725d9eb9a41007f000000010001/
```

124.7 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order and invoke the cloud drive provisioning.

124.7.1 Request

```
POST /orders/00000143d407b34742ee26ae007f000000010001/action
Content-Type: application/json; charset=UTF-8
{
  "action": "submit"
}
```

124.7.2 Response

202 Accepted

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

125 Order-Domain

126 Order a new domain

This is a step by step example of ordering a domain through the Hostway [Ordering API](#).

126.1 Create a new order

Use [POST /orders](#) to create a new order

126.1.1 Request

```
POST /orders
Content-Type: application/json

{ }
```

126.1.2 Response

```
201 Created

{
  "orderId":"00000149334635c2a163f194007f000000010001",
  "ownerId":"e497c8e7-8cf3-44ff-88d8-0c86521060da",
  "links":[
    {
      "href":"http://coreapi01.ote.chicago.hostway:8100/orders/",
      "rel":"self"
    },
    {
      "href":"http://coreapi01.ote.chicago.hostway:8100/orders/00000149334635c2a163f194007f000000010001",
      "rel":"item"
    }
  ]
}
```

126.2 Add product to the order

The domain registration product specification offerings can be determined using the Hostway [Product Catalog API](#). Add a new domain product to the order by using [POST /orders/{order_id}/account/products](#).

126.2.1 Request

```
POST /orders/00000149334635c2a163f194007f000000010001/account/products
Content-Type: application/json

{ "offering": "http://coreapi01.ote.chicago.hostway:8100/productSpecifications/core.plan.dnr.only/offerings/USD-12" }
```

126.2.2 Response

```
201 Created
Content-Type : application/json; charset=UTF-8
Connection : close
Location : http://coreapi01.ote.chicago.hostway:8100/orders/00000149334635c2a163f194007f000000010001/account/products/0000014933463b7219be46f0007f0000000010001

{
  "url":"http://coreapi01.ote.chicago.hostway:8100/orders/00000149334635c2a163f194007f000000010001/account/products/0000014933463b7219be46f0007f0000000010001",
  "productId":"0000014933463b7219be46f0007f0000000010001"
}
```

126.3 Add a service to the product

The domain registration service specification offerings can be determined using the Hostway [Product Catalog API](#) for the corresponding core.dnr.{tld} product. Then add a new email service to the order by using [POST /orders/{order_id}/account/products/{product_id}/services](#).

126.3.1 Request

```
POST /orders/00000149334635c2a163f194007f000000010001/account/products/0000014933463b7219be46f0007f0000000010001/services
Content-Type: application/json

{
  "name":"ng-test-fitness-20141021-1014.us",
  "serviceSpecification":"http://coreapi01.ote.chicago.hostway:8100/serviceSpecifications/core.dnr.us",
  "billingCycle":12
}
```

126.3.2 Response

```
201 Created
Content-Type : application/json; charset=UTF-8
Location : http://coreapi01.ote.chicago.hostway:8100/orders/00000149334635c2a163f194007f000000010001/account/products/0000014933463b7219be46f0007f0000000010001

{
  "url":"http://coreapi01.ote.chicago.hostway:8100/orders/00000149334635c2a163f194007f000000010001/account/products/0000014933463b7219be46f0007f0000000010001",
  "serviceId":"0000014933463eead40ac7ba007f0000000010001"
}
```

126.4 Add attributes to the service

Use the [PUT /orders/{order_id}/account/products/{product_id}/services/{service_id}/attributes](#) call to add the attributes for the domain service. Note that the example below is using "extraParams" attribute which is only required for some TLDs (.us in this case).

126.4.1 Request

PUT /orders/0000014933612cf9fb1c626a007f000000010001/account/products/0000014933613211db39d7c4007f0000000010001/services/0000014933613528f83d7
Content-Type: application/json

```
{
  "domainName": "ng-test-fitness-20141021-1044.us",
  "operation": "register",
  "term": 1,
  "authInfo": "mysecret",
  "nameservers": [
    "ns1.test.com",
    "ns2.test.com"
  ],
  "extraParams": [
    {
      "name": "us_nexus",
      "value": "C11"
    },
    {
      "name": "us_purpose",
      "value": "P1"
    }
  ],
  "contactInfo": {
    "registrant": {
      "type": "registrant",
      "firstName": "John",
      "lastName": "Doe",
      "company": "ACME Inc.",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "john.doe@test.com",
      "phone1": "+1.312.456789098"
    },
    "administrative": {
      "type": "administrative",
      "firstName": "Jane",
      "lastName": "Smith",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "jane.smith@test.com",
      "phone1": "+1.312.456789111",
      "fax1": "+1.312.456789112"
    },
    "billing": {
      "type": "billing",
      "firstName": "James",
      "lastName": "Johnson",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "james.johnson@test.com",
      "phone1": "+1.312.456789111"
    },
    "technical": {
      "type": "technical",
      "firstName": "Paul",
      "lastName": "Stevenson",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "paul.stevenson@test.com",
      "phone1": "+1.312.456789111"
    }
  }
}
```

126.4.2 Response

204 No content

126.5 Create a new account for the order

Use [PUT /orders/{order_id}/account](#) to create an account or add an existing one to the order.

126.5.1 Request

PUT /orders/0000014933612cf9fb1c626a007f000000010001/account
Content-Type: application/json

```
{ "currency": "USD", "language": "en-US" }
```

126.5.2 Response

204 No content

126.6 Add user info

126.6.1 Request

```
PUT /orders/0000014933612cf9fb1c626a007f000000010001/account/user
Content-Type: application/json
```

```
{ "userName": "quah@141021-104405.com", "password": "t0pSekr1t" }
```

126.6.2 Response

```
204 No content
```

126.7 Add billing contact

126.7.1 Request

```
PUT /orders/0000014933612cf9fb1c626a007f000000010001/account/contactInfo/billing
Content-Type: application/json
```

```
{
  "name":{
    "firstName":"Billing",
    "middleName":"X",
    "lastName":"Customer",
    "company":"Hostway"
  },
  "address":{
    "street1":"100 n riverside",
    "street2":"ste 800",
    "city":"Chicago",
    "stateOrProvince":"IL",
    "postalCode":"60606",
    "countryCode":"US"
  },
  "contactMedia":{
    "phone1":"312-555-2222",
    "phone2":"312-555-3333",
    "fax":"312-555-1111",
    "email1":"james.johnson@test.com",
    "email1Format":"html",
    "email2":"gah@wev.com",
    "email2Format":"text"
  }
}
```

126.7.2 Response

```
204 No Content
```

126.8 Add regular contact

126.8.1 Request

```
PUT /orders/0000014933612cf9fb1c626a007f000000010001/account/contactInfo/regular
Content-Type: application/json
```

```
{
  "name":{
    "firstName":"Billing",
    "middleName":"X",
    "lastName":"Customer",
    "company":"Hostway"
  },
  "address":{
    "street1":"100 n riverside",
    "street2":"ste 800",
    "city":"Chicago",
    "stateOrProvince":"IL",
    "postalCode":"60606",
    "countryCode":"US"
  },
  "contactMedia":{
    "phone1":"312-555-2222",
    "phone2":"312-555-3333",
    "fax":"312-555-1111",
    "email1":"james.johnson@test.com",
    "email1Format":"html",
    "email2":"gah@wev.com",
    "email2Format":"text"
  }
}
```

126.8.2 Response

```
204 No Content
```

126.9 Add payment info to the order

126.9.1 Request

PUT /orders/0000014933612cf9fb1c626a007f000000010001/account/paymentInfo
Content-Type: application/json

```
{
  "paymentInfoType": "credit_card",
  "creditCardType": "visa",
  "accountNumber": "4111111111111111",
  "cardHolderName": "John Jello",
  "expirationDate": "2015-06",
  "verificationNumber": "521",
  "billingAddress": {
    "street1": "100 n riverside",
    "street2": "ste 800",
    "city": "Chicago",
    "stateOrProvince": "IL",
    "postalCode": "60606",
    "countryCode": "US"
  }
}
```

126.9.2 Response

204 No Content

126.10 Validate the order

126.10.1 Request

POST /orders/0000014933612cf9fb1c626a007f000000010001/action
Content-Type: application/json

```
{ "action": "validate" }
```

126.10.2 Response

204 No Content

126.11 Get a quote

126.11.1 Request

GET /orders/0000014933612cf9fb1c626a007f000000010001/quote

126.11.2 Response

200 OK
Content-Type : application/json; charset=UTF-8

```
{
  "quote": {
    "PurchasedPlan": [
      {
        "Product": [
          {
            "ChildProduct": [
              ],
            "Name": "ng-test-fitness-20141021-1044.us",
            "MonthlyCycle": 12,
            "ConfigType": "core.dnr.us",
            "Fees": [
              {
                "ProrationAllowed": "0",
                "StartDate": "2014-10-21",
                "NumCharged": "0",
                "EndDate": "2015-10-20",
                "Description": "Domain registration fee ng-test-fitness-20141021-1044.us",
                "Discounts": [
                  ],
                "BaseAmount": "7.95",
                "UnitAmount": "7.95",
                "Prorated": "0",
                "MonthlyCycle": "12",
                "Currency": "USD",
                "Amount": "7.95",
                "NumCharges": "1",
                "ProratedUnitAmount": "7.95",
                "Type": "domain_registration_fee",
                "Quantity": "1",
                "Deferred": "0"
              }
            ],
            "Data": {
              "Register": {
                "ContactList": {
                  "Contact": [
                    {
                      "@city": "Chicago",
                      "@province": "IL",
                      "@first_name": "Paul",
                      "@fax": "",
                      "@address1": "123 First Str.",
                      "@address2": "",

```

```

        "@phone":"+1.312.456789111",
        "@country_code":"US",
        "@last_name":"Stevenson",
        "@postal":"34567",
        "@type":"technical",
        "@email":"paul.stevenson@test.com",
        "@company":""
    },
    {
        "@city":"Chicago",
        "@province":"IL",
        "@first_name":"Jane",
        "@fax":"",
        "@address1":"123 First Str.",
        "@address2":"",
        "@phone":"+1.312.456789111",
        "@country_code":"US",
        "@last_name":"Smith",
        "@postal":"34567",
        "@type":"admin",
        "@email":"jane.smith@test.com",
        "@company":""
    },
    {
        "@city":"Chicago",
        "@province":"IL",
        "@first_name":"John",
        "@fax":"",
        "@address1":"123 First Str.",
        "@address2":"",
        "@phone":"+1.312.456789098",
        "@country_code":"US",
        "@last_name":"Doe",
        "@postal":"34567",
        "@type":"company",
        "@email":"john.doe@test.com",
        "@company":"ACME Inc."
    }
],
    "@term":"1",
    "@lock":"",
    "@domain_name":"ng-test-fitness-20141021-1044.us",
    "@agreed":"",
    "@nameservers":"ns1.test.com,ns2.test.com",
    "@authInfo":"mysecret",
    "@reason":"",
    "@legal_type":"",
    "@agreement_version":"",
    "@operation":"register",
    "ExtraParams":[
        {
            "Name":"us_nexus",
            "Value":"C11"
        },
        {
            "Name":"us_purpose",
            "Value":"P1"
        }
    ]
},
    "PromotionCode":null,
    "ProductGUID":"0000014933613528f83d7290007f000000010001"
}
],
    "DisplayName":"",
    "Name":"DNR Only Plan",
    "ReferralKey":null,
    "MonthlyCycle":12,
    "PartnerId":"",
    "Plan":"core.plan.dnr.only",
    "Fees":[
        {
            "ProrationAllowed":"0",
            "StartDate":"2014-10-21",
            "NumCharged":"0",
            "EndDate":"2015-10-20",
            "Description":"Recurring fee DNR Only Plan, ng-test-fitness-20141021-1044.us 10/21/2014 through 10/20/2015",
            "Discounts":[]
        },
        {
            "BaseAmount":"0.00",
            "UnitAmount":"0.00",
            "Prorated":"0",
            "MonthlyCycle":"12",
            "Currency":"USD",
            "Amount":"0.00",
            "NumCharges":"-1",
            "ProratedUnitAmount":"0.00",
            "Type":"recurring",
            "Quantity":"1",

```

```

        "Deferred": "0"
    }
},
"PlanNumber": "0000014933613211db39d7c4007f000000010001",
"PromotionCode": null,
"PurchasedPlanNumber": "acct258192-0000014933615c88d6149e83007f00000001000"
}
},
"Hash": "b2f4dba3062c44084d3339561781d3bbc7bb9f70",
"Currency": "USD",
"Total": "7.95",
"SubTotal": "7.95",
"OneTimeFeeAmount": "7.95",
"TaxTotal": "0",
"DeferredSubTotals": [],
"DeferredTaxes": [],
"DeferredTotals": []
},
"links": {
    "self": {
        "href": "http://coreapi01.ote.chicago.hostway:8100/orders/0000014933612cf9fb1c626a007f000000010001/quote/",
        "rel": "self"
    }
}
}
}

```

126.12 Submit the order

Use [POST /orders/{order_id}/action](#) to submit the order.

126.12.1 Request

POST /orders/0000014933612cf9fb1c626a007f000000010001/action
Content-Type: application/json

```

{
    "action": "submit",
    "quoteHash": "b2f4dba3062c44084d3339561781d3bbc7bb9f70"
}

```

126.12.2 Response

202 Accepted

See also

- [Product Catalog API](#)
- [Ordering API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

127 Order-Domain-Shortcut

128 Order a new domain

This is an example of ordering a domain with the [Domain Order Shortcut](#). It is the same as the [Order Domain](#) process, using an existing account in the URL.

128.1 Create a new domain registration order

Use [PUT /accounts/{accountId}/domains/{domainName}](#) to create a new domain registration order for an existing account.

128.1.1 Request

PUT /accounts/acct839326/domains/ng-test-Fitness-shortcut-20141022-1033.com
Content-Type: application/json

```
{
  "domainName": "ng-test-Fitness-shortcut-20141022-1033.com",
  "operation": "register",
  "term": 1,
  "authInfo": "mysecret",
  "nameservers": [
    "ns1.test.com",
    "ns2.test.com"
  ],
  "contactInfo": {
    "registrant": {
      "type": "registrant",
      "firstName": "John",
      "lastName": "Doe",
      "company": "ACME Inc.",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "john.doe@test.com",
      "phone1": "+1.9494567890"
    },
    "administrative": {
      "type": "administrative",
      "firstName": "Jane",
      "lastName": "Smith",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "jane.smith@test.com",
      "phone1": "+1.9494567891",
      "fax1": "+1.9494567891"
    },
    "billing": {
      "type": "billing",
      "firstName": "James",
      "lastName": "Johnson",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "james.johnson@test.com",
      "phone1": "+1.9494567891"
    },
    "technical": {
      "type": "technical",
      "firstName": "Paul",
      "lastName": "Stevenson",
      "street1": "123 First Str.",
      "city": "Chicago",
      "zipOrPostal": "34567",
      "stateOrProvince": "IL",
      "countryCode": "US",
      "email1": "paul.stevenson@test.com",
      "phone1": "+1.9494567891"
    }
  }
}
```

128.1.2 Response

202 Accepted
Content-Type : application/json

```
{
  "orderId": "00000149387d9e73153111a9007f000000010001",
  "links": [
    {
      "href": "http://coreapi01.ote.chicago.hostway:8100/orders/00000149387d9e73153111a9007f000000010001",
      "rel": "self"
    }
  ]
}
```

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)