

# Table of Contents

<b>1 Dns-zone:GET</b>	<b>1</b>
<b>2 GET /dns/{zone}</b>	<b>2</b>
2.1 Contents	2
2.2 Request	2
2.3 Response	2
2.4 Examples	2
2.5 See also	3
<b>3 Dns-zone-records:GET</b>	<b>4</b>
<b>4 GET /dns/{zone}/records</b>	<b>5</b>
4.1 Contents	5
4.2 Request	5
4.3 Response	6
4.4 Examples	8
4.5 See also	9
<b>5 Dns-zone-records:POST</b>	<b>10</b>
<b>6 POST /dns/{zone}/records</b>	<b>11</b>
6.1 Contents	11
6.2 Request	11
6.3 Response	13
6.4 Examples	13
6.5 See also	14
<b>7 Dns-zone-records-recordId:PUT</b>	<b>15</b>
<b>8 PUT /dns/{zone}/records/{recordId}</b>	<b>16</b>
8.1 Contents	16
8.2 Request	16
8.3 Response	17
8.4 Examples	17
8.5 See also	18
<b>9 Dns-zone-records-recordId:DELETE</b>	<b>19</b>
<b>10 DELETE /dns/{zone}/records/{recordId}</b>	<b>20</b>
10.1 Contents	20
10.2 Request	20
10.3 Request Headers	20
10.4 Response	20
10.5 Examples	20
10.6 See also	20
<b>11 Dns-heartbeat:GET</b>	<b>21</b>
<b>12 GET /dns/heartbeat</b>	<b>22</b>
12.1 Contents	22
12.2 Request	22
12.3 Response	22
12.4 See also	22
<b>13 Dns-healthcheck:GET</b>	<b>23</b>
<b>14 GET /dns/healthcheck</b>	<b>24</b>
14.1 Contents	24
14.2 Request	24
14.3 Response	24
14.4 See also	24
<b>15 Common Features</b>	<b>25</b>

## 1 Dns-zone:GET

## 2 GET /dns/{zone}

Returns the details of a DNS zone.

### 2.1 Contents

- 1 GET /dns/{zone}
  - ◆ 1.1 Request
    - ◇ 1.1.1 Parameters
    - ◇ 1.1.2 Request Headers
  - ◆ 1.2 Response
    - ◇ 1.2.1 Status Code
    - ◇ 1.2.2 Response Body
  - ◆ 1.3 Examples
  - ◆ 1.4 See also

### 2.2 Request

GET /dns/{zone}

#### 2.2.1 Parameters

zone - *string*  
The name of the DNS zone.

#### 2.2.2 Request Headers

Authorization  
Base64-encoded username:password string

### 2.3 Response

#### 2.3.1 Status Code

- 200 OK  
Success
- 401 Unauthorized  
The server could not verify the credentials from the authorization header.
- 403 Forbidden  
The server denies the access to the resource.
- 404 Not Found  
The specified zone does not exist.

#### 2.3.2 Response Body

```
{
  "minimumTTL": {minimumTTL},
  "retry": {retry},
  "name": "{zone}",
  "primaryNS": "{primaryNS}",
  "refresh": {refresh},
  "expire": {expire},
  "emailAddress": "{emailAddress}",
  "ttl": {ttl},
  "serial": {serial},
  "links": [
    {"href": "https://api.hostway.com/dns/{zone}", "rel": "self"},
    {"href": "https://api.hostway.com/dns/{zone}/records", "rel": "related"}
  ]
}
```

### 2.4 Examples

*Request:*

GET /dns/test.com

*Response:*

401 Unauthorized

### *Request:*

```
GET /dns/unknown-zone.com
Authorization: Basic {base64_encoded(username:password)}
```

### *Response:*

403 Forbidden

```
{
  "forbidden": {"message": "Unauthorized: Dns failed permission check", "code": 403, "details": ""}
}
```

### *Request:*

```
GET /dns/test.com
Authorization: Basic {base64_encoded(username:password)}
```

### *Response:*

200 OK

```
{
  "minimumTTL": 300,
  "retry": 7200,
  "name": "test.com.",
  "links": [
    {"href": "http://127.0.0.1/dns/test.com/", "rel": "self"},
    {"href": "http://127.0.0.1/dns/test.com/records", "rel": "related"}
  ],
  "primaryNS": "a.dns.hostway.net.",
  "refresh": 28800,
  "expire": 604800,
  "emailAddress": "hostmaster.siteprotect.com.",
  "ttl": 14400,
  "serial": 1359151749
}
```

## 2.5 See also

- [DNS API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

### 3 Dns-zone-records:GET

## 4 GET /dns/{zone}/records

Returns the DNS zone records.

### 4.1 Contents

- 1 GET /dns/{zone}/records
  - ◆ 1.1 Request
    - ◇ 1.1.1 Parameters
    - ◇ 1.1.2 URI Parameters
    - ◇ 1.1.3 Request Headers
  - ◆ 1.2 Response
    - ◇ 1.2.1 Status Code
    - ◇ 1.2.2 Response Body
      - 1.2.2.1 Parameters
      - 1.2.2.2 Record Structures
        - 1.2.2.2.1 A record
        - 1.2.2.2.2 AAAA record
        - 1.2.2.2.3 NS record
        - 1.2.2.2.4 TXT and SPF records
        - 1.2.2.2.5 SRV record
        - 1.2.2.2.6 MX record
        - 1.2.2.2.7 CNAME record
  - ◆ 1.3 Examples
    - ◇ 1.3.1 Get a list of DNS records
    - ◇ 1.3.2 Get a paginated list of DNS records
    - ◇ 1.3.3 Get a filtered list of DNS records
  - ◆ 1.4 See also

### 4.2 Request

GET /dns/{zone}/records

#### 4.2.1 Parameters

zone - *string*  
The name of the DNS zone.

##### 4.2.1.1 URI Parameters

filterType  
Optional. Specifies the type of records to return: *A*, *AAAA*, *NS*, *TXT*, *SRV*, *MX*, *CNAME*

page - *number*  
Optional. Specifies the page to return in paginated response. Default is 1.

pageSize - *number*  
Optional. Specifies the number of records per page. Default 10, Max 100.

#### 4.2.2 Request Headers

Authorization  
Base64-encoded username:password string

## 4.3 Response

### 4.3.1 Status Code

200 OK  
Success

401 Unauthorized  
The server could not verify the credentials from the authorization header.

404 Not Found  
The specified zone does not exist.

### 4.3.2 Response Body

```
{
  "list": [
    {
      "id": {id},
      "name": "{domain}",
      "type": "AAAA",
      "ttl": {ttl},
      "address": "{ipv6_address}",
      "links": [
        { "href": "https://api.hostway.com/dns/{zone}/records/{id}/", "rel": "self" }
      ]
    },
    {
      "id": {id},
      "name": "{domain}",
      "type": "A",
      "ttl": {ttl},
      "address": "{ipv4_address}",
      "links": [
        { "href": "https://api.hostway.com/dns/{zone}/records/{id}/", "rel": "self" }
      ]
    }
  ],
  "links": [
    { "href": "https://api.hostway.com/dns/{zone}/records/", "rel": "self" }
  ]
}
```

#### 4.3.2.1 Parameters

list - list  
list of DNS records

id - integer  
The record's ID

id - string  
The record's type. Possible values are *A*, *AAA*, *NS*, *CNAME*, *MX*, *SVR* or *TXT*. Both SPF and TXT records will appear as *TXT* and share the same record structure.

ttl - integer  
DNS record's TTL in seconds

links - list  
[Hypermedia](#) to a particular DNS record

other type-specific parameters (optional)  
contains type-specific data. See [Record Structures](#) for more information.

links - list  
[Hypermedia](#) for the current DNS records list resource. May include links with information for the pagination.

#### 4.3.2.2 Record Structures

The goal of this section is to show the presentation of each DNS record in the response body based on the the record's type. The structure of each DNS record depends only on the record's type i.e. **A**, **AAA**, **NS**, **CNAME**, **MX**, **SVR** or **TXT**.

##### 4.3.2.2.1 A record

```
{
  "id": {record_id},
  "name": "{domain}",
  "type": "A",
  "address": "{ip_address}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```

#### 4.3.2.2.2 AAAA record

```
{
  "id": {record_id},
  "name": "{domain}",
  "type": "AAAA",
  "address": "{ipv6_address}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```

#### 4.3.2.2.3 NS record

```
{
  "id": {record_id},
  "name": "{domain}",
  "type": "NS",
  "nsdname": "{ns_domain}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```

#### 4.3.2.2.4 TXT and SPF records

```
{
  "id": {record_id},
  "name": "{domain}",
  "type": "TXT",
  "data": "{data}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```

**Note:** SPF records also appear as TXT records.

#### 4.3.2.2.5 SRV record

```
{
  "id": {record_id},
  "name": "{domain}",
  "type": "SRV",
  "priority": {priority},
  "weight": {weight},
  "port": {port},
  "target": "{target}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```

#### 4.3.2.2.6 MX record

```
{
  "id": {record_id},
  "name": "{domain}",
  "type": "MX",
  "preference": {preference},
  "exchange": "{mx_domain}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```

#### 4.3.2.2.7 CNAME record

```
{
  "id": {record_id},
  "name": "{name}",
  "type": "CNAME",
  "cname": "{domain}",
  "ttl": 3600,
  "links": [
    {
      "href": "{server_name}/dns/{zone}/records/{record_id}",
      "rel": "self"
    }
  ]
}
```



## 4.4 Examples

### 4.4.1 Get a list of DNS records

By default, the DNS records list is paginated to 10 records per page. If the page is not specified, first page will be returned.

GET <http://servername/dns/ng-test-hwus-petre-101202.com/records>

```
{
  "list" : [ {
    "name" : "ftp.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/10865/",
      "rel" : "self"
    } ],
    "ttl" : 14400,
    "address" : "10.10.100.60",
    "type" : "A",
    "id" : 10865
  }, {
    "name" : "ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/10866/",
      "rel" : "self"
    } ],
    "ttl" : 14400,
    "address" : "10.10.100.60",
    "type" : "A",
    "id" : 10866
  }, {
    "name" : "www.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/10864/",
      "rel" : "self"
    } ],
    "ttl" : 14400,
    "address" : "10.10.100.60",
    "type" : "A",
    "id" : 10864
  }, {
    "name" : "test-ipv6.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179100/",
      "rel" : "self"
    } ],
    "ttl" : 3000,
    "address" : "2001:0db8:85a3:0042:1000:8a2e:0370:7334",
    "type" : "AAAA",
    "id" : 179100
  }, {
    "name" : "sourcename.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179042/",
      "rel" : "self"
    } ],
    "cname" : "destinationdomain.com",
    "ttl" : 14400,
    "type" : "CNAME",
    "id" : 179042
  }, {
    "name" : "mail.ng-test-hwus-petre-101202.com.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179043/",
      "rel" : "self"
    } ],
    "exchange" : "mail.destination.com.ng-test-hwus-petre-101202.com",
    "preference" : 3,
    "ttl" : 14400,
    "type" : "MX",
    "id" : 179043
  }, {
    "name" : "ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/10860/",
      "rel" : "self"
    } ],
    "nsdname" : "vpdns.debian.hps.hostway",
    "ttl" : 14400,
    "type" : "NS",
    "id" : 10860
  }, {
    "name" : "ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/10861/",
      "rel" : "self"
    } ],
    "nsdname" : "vpdns2.debian.hps.hostway",
    "ttl" : 14400,
    "type" : "NS",
    "id" : 10861
  }, {
    "name" : "_service1._tcp.ng-test-hwus-petre-101202.com",
    "weight" : 3,
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179041/",
      "rel" : "self"
    } ],
    "port" : 80,
    "priority" : 2,
    "ttl" : 14400,
    "type" : "SRV",
    "id" : 179041,
    "target" : "svc-dest.ng-test-hwus-petre-101202.com"
  }, {
```

```

"name" : "spf-test.ng-test-hwus-petre-101202.com",
"links" : [ {
  "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179065/",
  "rel" : "self"
} ],
"data" : "v=spf1 exists:example.com -all",
"ttl" : 14400,
"type" : "TXT",
"id" : 179065
} ],
"links" : [ {
  "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/",
  "rel" : "self"
}, {
  "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records?page=2",
  "rel" : "next"
}, {
  "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records?page=2",
  "rel" : "last"
} ]
} ]
}

```

#### 4.4.2 Get a paginated list of DNS records

By default, the DNS records list is paginated to 10 records per page, if the **pageSize** parameter is not specified.

GET <http://servername/dns/ng-test-hwus-petre-101202.com/records?page=2>

```

{
  "list" : [ {
    "name" : "test-text.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179044/",
      "rel" : "self"
    } ],
    "data" : "test text",
    "ttl" : 14400,
    "type" : "TXT",
    "id" : 179044
  } ],
  "links" : [ {
    "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records?page=2",
    "rel" : "self"
  }, {
    "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records?page=1",
    "rel" : "first"
  }, {
    "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records?page=1",
    "rel" : "previous"
  } ]
}

```

#### 4.4.3 Get a filtered list of DNS records

Filtered by type.

GET <http://servername/dns/ng-test-hwus-petre-101202.com/records?filterType=TXT>

```

{
  "list" : [ {
    "name" : "spf-test.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179065/",
      "rel" : "self"
    } ],
    "data" : "v=spf1 exists:example.com -all",
    "ttl" : 14400,
    "type" : "TXT",
    "id" : 179065
  }, {
    "name" : "test-text.ng-test-hwus-petre-101202.com",
    "links" : [ {
      "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records/179044/",
      "rel" : "self"
    } ],
    "data" : "test text",
    "ttl" : 14400,
    "type" : "TXT",
    "id" : 179044
  } ],
  "links" : [ {
    "href" : "http://servername/dns/ng-test-hwus-petre-101202.com/records?filterType=TXT",
    "rel" : "self"
  } ]
}

```

### 4.5 See also

- [DNS API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

## 5 Dns-zone-records:POST

## 6 POST /dns/{zone}/records

Creates new DNS zone records.

### 6.1 Contents

- 1 POST /dns/{zone}/records
  - ◆ 1.1 Request
    - ◇ 1.1.1 Parameters
    - ◇ 1.1.2 URI Parameters
    - ◇ 1.1.3 Request Headers
    - ◇ 1.1.4 Request Body
      - 1.1.4.1 A record
      - 1.1.4.2 AAAA record
      - 1.1.4.3 NS record
      - 1.1.4.4 TXT record
      - 1.1.4.5 SRV record
      - 1.1.4.6 MX record
      - 1.1.4.7 CNAME record
  - ◆ 1.2 Response
    - ◇ 1.2.1 Status Code
    - ◇ 1.2.2 Response Header
  - ◆ 1.3 Examples
    - ◇ 1.3.1 Successful Request
    - ◇ 1.3.2 Unauthorized Request
    - ◇ 1.3.3 Attempt to create duplicate record
  - ◆ 1.4 See also

### 6.2 Request

POST /dns/{zone}/records

#### 6.2.1 Parameters

zone - *string*  
The name of the DNS zone.

##### 6.2.1.1 URI Parameters

None.

#### 6.2.2 Request Headers

Authorization  
Base64-encoded username:password string

Content-Type  
application/json

#### 6.2.3 Request Body

Added support for wildcard domain names.  
Ex:  
\*  
\*.somedomain.com  
The wildcard record name is stored in the database as it is supplied.  
If it's missing the zone origin(i.e. '') the API will return it with the zone

appended, i.e. '\*.domain.com'.

Added support for @ records, which represent the origin itself.

Ex:

@

The API will return the record with the zone origin appended to the name, i.e. '@.domain.com'

#### 6.2.3.1 A record

```
{
  "name": "{domain}",
  "type": "A",
  "address": "{ip_address}",
  "ttl": 3600
}
```

**name**  
Fully qualified domain name (FQDN) of the record

**address**  
IPv4 address

**ttl**  
Time to live (TTL) for the record in seconds

#### 6.2.3.2 AAAA record

```
{
  "name": "{domain}",
  "type": "AAAA",
  "address": "{ipv6_address}",
  "ttl": 3600
}
```

**name**  
Fully qualified domain name (FQDN) of the record

**address**  
IPv6 address

**ttl**  
Time to live (TTL) for the record in seconds

#### 6.2.3.3 NS record

```
{
  "name": "{domain}",
  "type": "NS",
  "nsdname": "{ns_domain}",
  "ttl": 3600
}
```

**name**  
Fully qualified domain name (FQDN) of the record

**nsdname**  
FQDN of the host which should be authoritative for the domain

**ttl**  
Time to live (TTL) for the record in seconds

#### 6.2.3.4 TXT record

```
{
  "name": "{domain}",
  "type": "TXT",
  "data": "{data}",
  "ttl": 3600
}
```

**name**  
Fully qualified domain name (FQDN) of the record

**data**  
TXT record data

**ttl**  
Time to live (TTL) for the record in seconds

#### 6.2.3.5 SRV record

```
{
  "name": "{domain}",
  "type": "SRV",
  "priority": {priority},
  "weight": {weight},
  "port": {port},
  "target": "{target}",
  "ttl": 3600
}
```

**name**  
Fully qualified domain name (FQDN) of the record

**priority**

	The priority of this target host
weight	Server selection mechanism
port	The port on this target host of this service
target	The domain name of the target host
ttd	Time to live (TTL) for the record in seconds

#### 6.2.3.6 MX record

```
{
  "name": "{domain}",
  "type": "MX",
  "preference": {preference},
  "exchange": "{mx_domain}",
  "ttl": 3600
}
```

name	Fully qualified domain name (FQDN) of the record
preference	Integer which specifies the preference given to this record among others at the same owner
exchange	FQDN which specifies a host willing to act as a mail exchange for the owner name
ttd	Time to live (TTL) for the record in seconds

#### 6.2.3.7 CNAME record

```
{
  "name": "{name}",
  "type": "CNAME",
  "cname": "{domain}",
  "ttl": 3600
}
```

name	Fully qualified domain name (FQDN) of the record
cname	FQDN which specifies the canonical or primary name for the owner
ttd	Time to live (TTL) for the record in seconds

## 6.3 Response

### 6.3.1 Status Code

201 OK	Success
400 Bad Request	TTL is below allowed minimum
401 Unauthorized	The server could not verify the credentials from the authorization header.
404 Not Found	The specified zone does not exist.
409 Conflict	Requested record conflicts with existing one.

### 6.3.2 Response Header

Location	The URI of the new DNS record.
----------	--------------------------------

## 6.4 Examples

### 6.4.1 Successful Request

#### Request

```
POST /dns/test.com/records
Authorization: Basic {base64_encoded(username:password)}
```

```
{
  "name": "alt.test.com",
  "type": "CNAME",
  "cname": "altdomain.com"
}
```

### *Response*

201 Created  
Location: <https://api.hostway.com/dns/test.com/records/447>

## 6.4.2 Unauthorized Request

### *Request*

POST /dns/test.com/records

```
{
  "name": "alt.test.com",
  "type": "CNAME",
  "cname": "altdomain.com"
}
```

### *Response*

401 Unauthorized

## 6.4.3 Attempt to create duplicate record

### *Request*

POST /dns/test.com/records  
Authorization: Basic {base64\_encoded(username:password)}

```
{
  "name": "alt.test.com",
  "type": "CNAME",
  "cname": "altdomain.com"
}
```

### *Response*

409 Conflict

```
{
  "conflict": {"message": "Data conflict", "code": 409, "details": ""}
}
```

## 6.5 See also

- [DNS API](#)
- [Common Features](#)
- [RFC 1035](#)
- [RFC 2782](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

## 7 Dns-zone-records-recordId:PUT



## 8 PUT /dns/{zone}/records/{recordId}

Update an existing zone record.

### 8.1 Contents

- 1 PUT /dns/{zone}/records/{recordId}
  - ◆ 1.1 Request
    - ◇ 1.1.1 Request Parameters
    - ◇ 1.1.2 URI Parameters
    - ◇ 1.1.3 Request Headers
    - ◇ 1.1.4 Request Body
      - 1.1.4.1 A record
      - 1.1.4.2 AAAA record
      - 1.1.4.3 NS record
      - 1.1.4.4 TXT record
      - 1.1.4.5 SRV record
      - 1.1.4.6 MX record
      - 1.1.4.7 CNAME record
  - ◆ 1.2 Response
    - ◇ 1.2.1 Status Code
    - ◇ 1.2.2 Response Body
  - ◆ 1.3 Examples
    - ◇ 1.3.1 Unauthorized Request
    - ◇ 1.3.2 Successful Update
  - ◆ 1.4 See also

### 8.2 Request

PUT /dns/{zone}/records/{recordId}

#### 8.2.1 Request Parameters

zone - *string*  
The DNS zone of the record.

recordId - *string*  
The unique Id of the record.

#### 8.2.2 URI Parameters

None.

#### 8.2.3 Request Headers

Content-Type  
application/json

Authorization  
Base64-encoded username & password string

#### 8.2.4 Request Body

Added support for wildcard domain names.  
Ex:

```
*
*.somedomain.com
The wildcard record name is stored in the database as it is supplied.
If it's missing the zone origin(i.e. '') the API will return it with the zone
appended, i.e. '*.domain.com'.
```

Added support for @ records, which represent the origin itself.  
Ex:

```
@
The API will return the record with the zone origin appended to the name, i.e. '@.domain.com'
```

#### 8.2.4.1 A record

```
{
  "name": {domain},
  "address": {ip_address},
  "ttl": 3600
}
```

#### 8.2.4.2 AAAA record

```
{
  "name": {domain},
  "address": {ipv6_address},
  "ttl": 3600
}
```

#### 8.2.4.3 NS record

```
{
  "name": {domain},
  "nsdname": {ns_domain},
  "ttl": 3600
}
```

#### 8.2.4.4 TXT record

```
{
  "name": {domain},
  "data": {data},
  "ttl": 3600
}
```

#### 8.2.4.5 SRV record

```
{
  "name": {domain},
  "priority": {priority},
  "weight": {weight},
  "port": {port},
  "target": {target},
  "ttl": 3600
}
```

#### 8.2.4.6 MX record

```
{
  "name": {domain},
  "preference": {preference},
  "exchange": {mx_domain},
  "ttl": 3600
}
```

#### 8.2.4.7 CNAME record

```
{
  "name": {name},
  "cname": {domain},
  "ttl": 3600
}
```

## 8.3 Response

### 8.3.1 Status Code

200 OK  
    Success

400 Bad Request  
    TTL is below allowed minimum

401 Unauthorized

403 Forbidden

409 Conflict

### 8.3.2 Response Body

None.

## 8.4 Examples

## 8.4.1 Unauthorized Request

### *Request*

```
PUT /dns/test.com/records/1234
{
  "name": "test",
  "cname": "otherdomain.com."
}
```

### *Response*

```
401 Unauthorized
```

## 8.4.2 Successful Update

### *Request*

```
PUT /dns/test.com/records/1234
Authorization: Basic {base64_encoded(username:password)}
{
  "name": "test1",
  "cname": "otherdomain1.com."
}
```

### *Response*

```
200 OK
{
  "name": "test1",
  "type": "CNAME",
  "cname": "otherdomain1.com."
}
```

## 8.5 See also

- [DNS API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

## 9 Dns-zone-records-recordId:DELETE

## 10 DELETE /dns/{zone}/records/{recordId}

Delete zone record.

### 10.1 Contents

- 1 DELETE /dns/{zone}/records/{recordId}
  - ◆ 1.1 Request
    - ◇ 1.1.1 Request Parameters
    - ◇ 1.1.2 URI Parameters
  - ◆ 1.2 Request Headers
    - ◇ 1.2.1 Request Body
  - ◆ 1.3 Response
    - ◇ 1.3.1 Status Code
  - ◆ 1.4 Examples
  - ◆ 1.5 See also

### 10.2 Request

DELETE /dns/{zone}/records/{recordId}

#### 10.2.1 Request Parameters

zone - *string*  
The DNS zone name.

recordId - *string*  
The unique record Id.

#### 10.2.2 URI Parameters

None.

### 10.3 Request Headers

Authorization  
Base64-encoded username & password string

#### 10.3.1 Request Body

None.

### 10.4 Response

#### 10.4.1 Status Code

204 No Content  
Success

401 Unauthorized

403 Forbidden

404 Not Found  
The specified zone or record Id don't exist.

### 10.5 Examples

*Request*

```
DELETE /dns/test.com/records/447
Authorization: Basic {base64_encoded(username:password)}
```

*Response:*

204 No Content

### 10.6 See also

- [DNS API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

## 11 Dns-heartbeat:GET

## 12 GET /dns/heartbeat

### 12.1 Contents

- 1 GET /dns/heartbeat
  - ◆ 1.1 Request
  - ◆ 1.2 Response
    - ◇ 1.2.1 Status Codes
  - ◆ 1.3 See also

### 12.2 Request

GET /dns/heartbeat

### 12.3 Response

#### 12.3.1 Status Codes

200 OK  
Success

500 Internal Server Error  
Internal error occurred.

### 12.4 See also

- [DNS API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

## 13 Dns-healthcheck:GET



## 14 GET /dns/healthcheck

### 14.1 Contents

- 1 GET /dns/healthcheck
  - ◆ 1.1 Request
  - ◆ 1.2 Response
    - ◇ 1.2.1 Status Codes
  - ◆ 1.3 See also

### 14.2 Request

GET /dns/healthcheck

### 14.3 Response

#### 14.3.1 Status Codes

200 OK  
Success

400 Bad Request  
If any of the database connections is down.

500 Internal Server Error  
If something is wrong with the DNS API.

### 14.4 See also

- [DNS API](#)
- [Common Features](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)

## 15 Common Features

All Hostway APIs support common features for authentication and authorization, pagination, references to related resources, etc.

- [Authentication](#)
- [Hypermedia](#)
- [Pagination](#)
- [Server Response Codes](#)
- [Filtering](#)

[download this selection of articles as a PDF book](#)

Please enable JavaScript to view the [comments powered by Disqus](#). [blog comments powered by Disqus](#)